



SPORTON International Inc.

No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
Ph: 886-3-327-3456 / FAX: 886-3-327-0973 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Adtran
Applicant Address	901 Explorer Boulevard Huntsville Alabama United States 35806-2807
FCC ID	HDCWLAN194XF2
Manufacturer's company	Senao Networks, Inc.
Manufacturer Address	3F, No. 529, Chung Cheng Rd., Hsintien, Taipei, Taiwan

Product Name	802.11 an PCIe Module
Brand Name	Adtran
Model Name	WLAN194XF2
Test Rule Part(s)	47 CFR FCC Part 15 Subpart E § 15.407
Test Freq. Range	5150 ~ 5250MHz
Received Date	Sep. 12, 2012
Final Test Date	Nov. 22, 2012
Submission Type	Original Equipment
Operating Mode	Master



Statement

Test result included is for the IEEE 802.11n and IEEE 802.11a (5150 ~ 5250MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009**,

47 CFR FCC Part 15 Subpart E and **KDB 789033 D01 v01r02**.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details	3
3.2. Accessories	6
3.3. Table for Filed Antenna	7
3.4. Table for Carrier Frequencies	8
3.5. Table for Test Modes	8
3.6. Table for Testing Locations.....	9
3.7. Table for Supporting Units	9
3.8. Table for Parameters of Test Software Setting	9
3.9. Test Configurations.....	10
4. TEST RESULT	13
4.1. AC Power Line Conducted Emissions Measurement	13
4.2. 99% Occupied Bandwidth Measurement.....	17
4.3. Maximum Conducted Average Output Power Measurement	24
4.4. Power Spectral Density Measurement.....	26
4.5. Peak Excursion Measurement	31
4.6. Radiated Emissions Measurement.....	35
4.7. Band Edge Emissions Measurement.....	49
4.8. Frequency Stability Measurement.....	53
4.9. Antenna Requirements	55
5. LIST OF MEASURING EQUIPMENTS	56
6. TEST LOCATION	58
7. TAF CERTIFICATE OF ACCREDITATION	59
APPENDIX A. TEST PHOTOS	A1 ~ A6
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3

History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR291831AA	Rev. 01	Initial issue of report	Jan. 08, 2013



1. CERTIFICATE OF COMPLIANCE

Product Name : 802.11 an PCIe Module
Brand Name : Adtran
Model Name : WLAN194XF2
Applicant : Adtran
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart E § 15.407

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Sep. 12, 2012 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Jordan Hsiao'. The signature is written in a cursive style and is positioned above a horizontal line.

Jordan Hsiao

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart E				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	14.83 dB
4.2	15.407(a)	26dB Spectrum Bandwidth	Complies	-
4.3	15.407(a)	Conducted Average Output Power	Complies	0.03 dB
4.4	15.407(a)	Power Spectral Density	Complies	0.01 dB
4.5	15.407(a)	Peak Excursion	Complies	3.2 dB
4.6	15.407(b)	Radiated Emissions	Complies	6.59 dB
4.7	15.407(b)	Band Edge Emissions	Complies	1.06 dB
4.8	15.407(g)	Frequency Stability	Complies	-
4.9	15.203	Antenna Requirements	Complies	-

Test Items	Uncertainty	Remark
AC Power Line Conducted Emissions	±2.3dB	Confidence levels of 95%
Conducted Average Output Power	±0.5dB	Confidence levels of 95%
Power Spectral Density	±0.5dB	Confidence levels of 95%
Peak Excursion	±0.5dB	Confidence levels of 95%
26dB Spectrum Bandwidth / Frequency Stability	±8.5×10 ⁻⁸	Confidence levels of 95%
Radiated Emissions (9kHz~30MHz)	±0.8dB	Confidence levels of 95%
Radiated Emissions (30MHz~1000MHz)	±1.9dB	Confidence levels of 95%
Radiated / Band Edge Emissions (1GHz~18GHz)	±1.9dB	Confidence levels of 95%
Radiated Emissions (18GHz~40GHz)	±1.9dB	Confidence levels of 95%
Temperature	±0.7°C	Confidence levels of 95%
Humidity	±3.2%	Confidence levels of 95%
DC / AC Power Source	±1.4%	Confidence levels of 95%

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM) For 802.11n
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	5150 ~ 5250MHz
Channel Number	4 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	11n MCS0 (HT 20MHz): 18.08 MHz ; 11n MCS0 (HT40 MHz): 36.48 MHz;
Maximum Conducted Average Output Power	11n MCS0 (HT20 MHz): 15.10 dBm ; 11n MCS0 (HT40 MHz): 15.97 dBm;
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

IEEE 802.11a

Items	Description
Product Type	WLAN (3TX, 3RX)
Radio Type	Intentional Transceiver
Power Type	From Host System
Modulation	OFDM for IEEE 802.11a
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5150 ~ 5250MHz
Channel Number	11a: 4
Channel Band Width (99%)	11a: 16.96 MHz
Maximum Conducted Average Output Power	11a: 14.95 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna & Band width

Antenna	Single (TX)		Two (TX)		Three (TX)	
	20 MHz	40 MHz	20 MHz	40 MHz	20 MHz	40 MHz
IEEE 802.11a	X	X	X	X	V	X
IEEE 802.11n	X	X	X	X	V	V

IEEE 802.11n spec

MCS	Spatial	Modulation	Coding	Data rate (Mbit/s)			
index	streams	type	rate	20 MHz channel		40 MHz channel	
				800 ns GI	400 ns GI	800 ns GI	400 ns GI
0	1	BPSK	1/2	6.5	7.2	13.5	15
1	1	QPSK	1/2	13	14.4	27	30
2	1	QPSK	3/4	19.5	21.7	40.5	45
3	1	16-QAM	1/2	26	28.9	54	60
4	1	16-QAM	3/4	39	43.3	81	90
5	1	64-QAM	2/3	52	57.8	108	120
6	1	64-QAM	3/4	58.5	65	121.5	135
7	1	64-QAM	5/6	65	72.2	135	150
8	2	BPSK	1/2	13	14.4	27	30
9	2	QPSK	1/2	26	28.9	54	60
10	2	QPSK	3/4	39	43.3	81	90
11	2	16-QAM	1/2	52	57.8	108	120
12	2	16-QAM	3/4	78	86.7	162	180
13	2	64-QAM	2/3	104	115.6	216	240
14	2	64-QAM	3/4	117	130	243	270
15	2	64-QAM	5/6	130	144.4	270	300
16	3	BPSK	1/2	19.5	21.7	40.5	45
17	3	QPSK	1/2	39	43.3	81	90
18	3	QPSK	3/4	58.5	65	121.5	135
19	3	16-QAM	1/2	78	86.7	162	180
20	3	16-QAM	3/4	117	130	243	270
21	3	64-QAM	2/3	156	173.3	324	360
22	3	64-QAM	3/4	175.5	195	364.5	405
23	3	64-QAM	5/6	195	216.7	405	450

Symbol	Explanation
NSS	Number of spatial streams
R	Code rate
NBPSC	Number of coded bits per single carrier
NCBPS	Number of coded bits per symbol
NDBPS	Number of data bits per symbol
GI	guard interval

IEEE 802. 11a, 11n Spec.

Worst Modulation Used for Conformance Testing				
IEEE 802.11 Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS	Worst Data Rate / MCS	Worst Modulation Mode
a	3	6-54 Mbps	6Mbps	11A5.2G-20M
n (HT20)	3	MCS 0-15	MCS 0	11N5.2G-20M
n (HT40)	3	MCS 0-15	MCS 0	11N5.2G-40M
Note 1: IEEE Std. 802.11-2007 modulation consists of IEEE Std. 802.11a-1999.				
Note 2: IEEE Std. 802.11n-2009 modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Worst modulation mode of Guard Interval (GI) is 400ns.				

3.2. Accessories

N/A


3.3. Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	Master Wave Technology CO., LTD	98618UNXX000	Dipole Antenna	MMCX	7
2	Master Wave Technology CO., LTD	98618UNXX000	Dipole Antenna	MMCX	7
3	Master Wave Technology CO., LTD	98618UNXX000	Dipole Antenna	MMCX	7

Note: The EUT has three antennas. (3TX/3RX)

For IEEE 802.11a/n mode (3TX/3RX):

Antenna 1 & Antenna 2 and Antenna 3 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

The EUT has three bandwidth system.

For 20MHz bandwidth systems, use Channel 36, 40, 44, 48.

For 40MHz bandwidth systems, use Channel 38, 46.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5150~5250 MHz Band 1	36	5180 MHz	44	5220 MHz
	38	5190 MHz	46	5230 MHz
	40	5200 MHz	48	5240 MHz
	42	5210 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode		Data Rate	Channel	Antenna
AC Power Conducted Emission	CTX		Auto	-	-
Conducted Average Output Power	11n 20MHz	Band 1	7.2Mbps	36/40/48	1/2/3/1+2+3
	11n 40MHz	Band 1	14.4Mbps	38/46	1/2/3/1+2+3
	11a	Band 1	6Mbps	36/40/48	1/2/3/1+2+3
Power Spectral Density	11n 20MHz	Band 1	7.2Mbps	36/40/48	1+2+3
	11n 40MHz	Band 1	14.4Mbps	38/46	1+2+3
	11a	Band 1	6Mbps	36/40/48	1+2+3
26dB Spectrum Bandwidth 99% Occupied Bandwidth Measurement Peak Excursion	11n 20MHz	Band 1	7.2Mbps	36/40/48	1+2+3
	11n 40MHz	Band 1	14.4Mbps	38/46	1+2+3
	11a	Band 1	6Mbps	36/40/48	1+2+3
Radiated Emission Below 1GHz	CTX		Auto	-	-
Radiated Emission Above 1GHz	11n 20MHz	Band 1	7.2Mbps	36/40/48	1+2+3
	11n 40MHz	Band 1	14.4Mbps	38/46	1+2+3
	11a	Band 1	6Mbps	36/40/48	1+2+3
Band Edge Emission	11n 20MHz	Band 1	7.2Mbps	36/40/48	1+2+3
	11n 40MHz	Band 1	14.4Mbps	38/46	1+2+3
	11a	Band 1	6Mbps	36/40/48	1+2+3
Frequency Stability	Un-modulation		-	40	N/A

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6220	E2KWM3945ABG

3.8. Table for Parameters of Test Software Setting

During testing, Channel & Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n MCS0 HT20MHz

Test Software Version	ART2-GUI Version:2.3 Build		
Frequency	5180 MHz	5200 MHz	5240 MHz
MCS0 20MHz	10	10	10

Power Parameters of IEEE 802.11n MCS0 HT40MHz

Test Software Version	ART2-GUI Version:2.3 Build	
Frequency	5190 MHz	5230 MHz
MCS0 40MHz	10.5	11.5

Power Parameters of IEEE 802.11a


Test Software Version	ART2-GUI Version:2.3 Build		
Frequency	5180 MHz	5200 MHz	5240 MHz
11a	10	9.5	10

During the test, "ART2-GUI Version:2.3 Build" under WIN XP was executed the test program to control the EUT continuously transmit RF signal.

3.9. Test Configurations


3.9.1. Radiation Emissions Test Configuration

Test Configuration: 30MHz~1GHz




Item	Connection	Shield	Length
1	Power cable	No	3.4M
2	Power cable	No	2.6M
3	ANT cable	No	0.2M
4	ANT cable	No	0.2M
5	ANT cable	No	0.2M

Test Configuration: above 1GHz



Item	Connection	Shield	Length
1	Power cable	No	1.8M
2	Power cable	No	1.8M
3	ANT cable	Yes	0.105M
4	ANT cable	No	0.175M
5	ANT cable	Yes	0.175M

3.9.2. AC Power Line Conduction Emissions Test Configuration



Item	Connection	Shield	Length
1	Power cable	No	3.4M
2	Power cable	No	2.6M
3	ANT cable	No	0.2M
4	ANT cable	No	0.2M
5	ANT cable	No	0.2M

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product that is designed to connect to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.


Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 KHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	24°C	Humidity	58%
Test Engineer	Sollo Lo	Phase	Line
Configuration	CTX		



	Freq	Level	Over	Limit	Read	LISN	Cable		
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Pol/Phase	Remark
			dB	dBuV	dBuV	dB	dB		
1	0.16155	25.95	-39.43	65.38	25.59	0.16	0.20	LINE	QP
2	0.16155	10.93	-44.45	55.38	10.57	0.16	0.20	LINE	AVERAGE
3	0.18346	23.41	-40.92	64.33	23.06	0.15	0.20	LINE	QP
4	0.18346	10.04	-44.29	54.33	9.69	0.15	0.20	LINE	AVERAGE
5	0.34830	11.51	-37.49	49.00	11.16	0.15	0.20	LINE	AVERAGE
6	0.34830	16.81	-42.19	59.00	16.46	0.15	0.20	LINE	QP
7	3.347	9.30	-36.70	46.00	8.82	0.21	0.27	LINE	AVERAGE
8	3.347	14.32	-41.68	56.00	13.84	0.21	0.27	LINE	QP
9	17.109	36.63	-23.37	60.00	35.69	0.44	0.50	LINE	QP
10	17.109	35.17	-14.83	50.00	34.23	0.44	0.50	LINE	AVERAGE
11	20.377	18.45	-41.55	60.00	17.46	0.49	0.50	LINE	QP
12	20.377	16.04	-33.96	50.00	15.05	0.49	0.50	LINE	AVERAGE

Temperature	24°C	Humidity	58%
Test Engineer	Sollo Lo	Phase	Neutral
Configuration	CTX		



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Pol/Phase	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	0.16241	25.70	-39.64	65.34	25.42	0.08	0.20	NEUTRAL	QP
2	0.16241	6.50	-48.84	55.34	6.22	0.08	0.20	NEUTRAL	AVERAGE
3	0.18152	23.08	-41.34	64.42	22.80	0.08	0.20	NEUTRAL	QP
4	0.18152	4.29	-50.13	54.42	4.01	0.08	0.20	NEUTRAL	AVERAGE
5	0.34646	16.90	-42.15	59.05	16.62	0.08	0.20	NEUTRAL	QP
6	0.34646	8.33	-40.72	49.05	8.05	0.08	0.20	NEUTRAL	AVERAGE
7	1.585	9.59	-46.41	56.00	9.37	0.10	0.12	NEUTRAL	QP
8	1.585	3.87	-42.13	46.00	3.65	0.10	0.12	NEUTRAL	AVERAGE
9	3.374	9.10	-36.90	46.00	8.70	0.12	0.28	NEUTRAL	AVERAGE
10	3.374	21.82	-34.18	56.00	21.42	0.12	0.28	NEUTRAL	QP
11	17.201	26.05	-33.95	60.00	25.20	0.35	0.50	NEUTRAL	QP
12	17.201	21.20	-28.80	50.00	20.35	0.35	0.50	NEUTRAL	AVERAGE

Note:

Level = Read Level + LISN Factor + Cable Loss.

4.2. 99% Occupied Bandwidth Measurement

4.2.1. Limit

No restriction limits. But resolution bandwidth within band edge measurement is 1% of the 99% occupied bandwidth.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 26dB Bandwidth
RB	300 kHz
VB	3000 kHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.2.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. The resolution bandwidth of 300 kHz and the video bandwidth of 1000 kHz were used.
3. Measured the spectrum width with power higher than 26dB below carrier.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of 99% Occupied Bandwidth

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT 20MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	21.12	18.08
40	5200 MHz	21.60	18.08
48	5240 MHz	21.44	18.08

Configuration IEEE 802.11n MCS0 HT 40MHz / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
38	5190 MHz	41.28	34.88
46	5230 MHz	42.24	36.48

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	26dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
36	5180 MHz	20.80	16.80
40	5200 MHz	21.12	16.64
48	5240 MHz	20.48	16.96

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20MHz / Ant. 1 + Ant. 2+ Ant. 3 / 5180 MHz




Date: 16.NOV.2012 22:49:04

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20MHz / Ant. 1 + Ant. 2+ Ant. 3 / 5200 MHz




Date: 16.NOV.2012 22:47:32

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT20MHz / Ant. 1 + Ant. 2+ Ant. 3 / 5240 MHz




Date: 16.NOV.2012 22:45:44

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40MHz / Ant. 1 + Ant. 2+ Ant. 3 / 5190 MHz




Date: 16.NOV.2012 22:59:16

26 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 HT40MHz / Ant. 1 + Ant. 2+ Ant. 3 / 5230 MHz




Date: 16.NOV.2012 22:56:35

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2+ Ant. 3 / 5180 MHz




Date: 16.NOV.2012 22:39:46

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2+ Ant. 3 / 5200 MHz



Date: 16.NOV.2012 22:42:28

26 dB Bandwidth Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2+ Ant. 3 / 5240 MHz



Date: 16.NOV.2012 22:44:16

4.3. Maximum Conducted Average Output Power Measurement

4.3.1. Limit

For the band 5.15–5.25 GHz, the maximum Conducted Average Output Power over the frequency band of operation shall not exceed the lesser of 50 mW (17dBm) or $4 \text{ dBm} + 10\log B$, where B is the 26 dB emissions bandwidth in MHz. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted Average output power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the peak power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Peak

4.3.3. Test Procedures

1. The transmitter output (antenna port) was connected to the power meter.
2. Test was performed in accordance with KDB 789033 Guidelines for Compliance Testing of Unlicensed National Information Infrastructure (U-NII) Devices - Part 15, Subpart E, section (C) Maximum conducted output power =>(4) Method PM (Measurement using an RF average power meter) Multiple antenna systems was performed in accordance with KDB 662911 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
3. When measuring maximum conducted output power with multiple antenna systems, add every result of the values by mathematic formula.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Maximum Conducted Average Output Power

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n
Test Date	Nov. 16, 2012		

Configuration IEEE 802.11n MCS0 HT20MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Average Power (dBm)			Total Conducted Average Output Power (dBm)	Max. Limit (dBm)	Result
		Ant.1	Ant.2	Ant.3			
36	5180 MHz	9.84	10.03	10.76	15.00	16.00	Complies
40	5200 MHz	9.56	10.15	11.12	15.10	16.00	Complies
48	5240 MHz	9.79	10.21	10.71	15.02	16.00	Complies

Configuration IEEE 802.11n MCS0 HT40MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Average Power (dBm)			Total Conducted Average Output Power (dBm)	Max. Limit (dBm)	Result
		Ant.1	Ant.2	Ant.3			
38	5190 MHz	10.54	11.25	11.33	15.83	16.00	Complies
46	5230 MHz	10.78	11.32	11.48	15.97	16.00	Complies

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a
Test Date	Nov. 16, 2012		

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Conducted Average Power (dBm)			Total Conducted Average Output Power (dBm)	Max. Limit (dBm)	Result
		Ant.1	Ant.2	Ant.3			
36	5180 MHz	9.52	9.75	10.89	14.87	16.00	Complies
40	5200 MHz	9.17	9.34	10.68	14.56	16.00	Complies
48	5240 MHz	9.55	9.86	10.98	14.95	16.00	Complies

4.4. Power Spectral Density Measurement

4.4.1. Limit

The power spectral density is defined as the highest level of power in dBm per MHz generated by the transmitter within the power envelope. The following table is power spectral density limits and decrease power density limit rule refer to section 4.3.1.

Frequency Range	Power Spectral Density limit (dBm/MHz)
5.15–5.25 GHz	4

4.4.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.


Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz
VB	3000 kHz
Detector	RMS
Trace	AVERAGE
Sweep Time	Auto
Trace Average	100 times

4.4.3. Test Procedures

1. The test procedure is the same as section 4.6.3.
2. Trace A, Set RBW =1MHz, VBW = 3MHz, Span >26dB bandwidth, Max. hold.
3. Delta Mark trace A Maximum frequency and trace B same frequency.
4. Repeat the above procedure until measurements for all frequencies were complete.
5. Procedures refer KDB 662911: Measure and sum the spectra across the outputs.

The first spectral bin of output 1 is summed with that in the first spectral bin of output 2 and that from the first spectral bin of output 3, and so on up to the Nth output to obtain the value for the first frequency bin of the summed spectrum. The summed spectrum value for each of the other frequency bins is computed in the same way. This will likely require transferring the measured spectra to a computer, where the bin-by-bin summing can be performed.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of Power Spectral Density

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n
Test Date	Nov. 16, 2012		

Configuration IEEE 802.11n MCS0 HT20MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	-2.13	-1.77	Complies
40	5200 MHz	-2.04	-1.77	Complies
48	5240 MHz	-1.96	-1.77	Complies

Note: Directional gain = $G_{ANT} + 10 \log(N)$ dBi = 11.77dBi > 6dBi, So Band1 Limit = $4 - (11.77 - 6) = -1.77$ dBm / MHz

Configuration IEEE 802.11n MCS0 HT40MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
38	5190 MHz	-3.73	-1.77	Complies
46	5230 MHz	-3.06	-1.77	Complies

Note: Directional gain = $G_{ANT} + 10 \log(N)$ dBi = 11.77dBi > 6dBi, So Band1 Limit = $4 - (11.77 - 6) = -1.77$ dBm / MHz

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a
Test Date	Nov. 16, 2012		

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	Total Power Density (dBm/MHz)	Max. Limit (dBm/MHz)	Result
36	5180 MHz	-2.11	-1.77	Complies
40	5200 MHz	-2.36	-1.77	Complies
48	5240 MHz	-1.78	-1.77	Complies

Note: Directional gain = $G_{ANT} + 10 \log(N)$ dBi = 11.77dBi > 6dBi, So Band1 Limit = $4 - (11.77 - 6) = -1.77$ dBm / MHz


Note: All the test values were listed in the report.

For plots, only the channel with maximum results was shown.


Power Density Plot on Configuration IEEE 802.11n MCS0 HT20MHz // Ant. 1 + Ant. 2 + Ant. 3 / 5240 MHz



Power Density Plot on Configuration IEEE 802.11n MCS0 HT40MHz // Ant. 1 + Ant. 2 + Ant. 3 / 5230 MHz



Power Density Plot on Configuration IEEE 802.11a // Ant. 1 + Ant. 2 + Ant. 3 / 5240 MHz



4.5. Peak Excursion Measurement

4.5.1. Limit

The ratio of the peak excursion of the modulation envelope (measured using a peak hold function) to the maximum Conducted Average Output Power (measured as specified above) shall not exceed 13 dB across any 1 MHz bandwidth or the emissions bandwidth whichever is less.

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Encompass the entire emissions bandwidth (EBW) of the signal
RB	1000 kHz (Peak Trace) / 1000 kHz (Average Trace)
VB	3000 kHz (Peak Trace) / 300 kHz (Average Trace)
Detector	Peak (Peak Trace) / PMS (Average Trace)
Trace	Max Hold
Sweep Time	60s

4.5.3. Test Procedures

1. The test procedure is the same as section 4.6.3.
2. Trace A, Set RBW = 1MHz, VBW = 3MHz, Span >26dB bandwidth, Max. hold.
3. Delta Mark trace A Maximum frequency and trace B same frequency.
4. Repeat the above procedure until measurements for all frequencies were complete.
5. Testing each modulation mode on a single channel is sufficient to demonstrate compliance with the peak excursion requirement.

4.5.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Test Result of Peak Excursion

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n

Configuration IEEE 802.11n MCS0 HT20MHz / Ant. 1 + Ant. 2 + Ant. 3

Channel	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
40	5200 MHz	9.79	13	Complies

Configuration IEEE 802.11n MCS0 HT40MHz / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
46	5230 MHz	9.72	13	Complies

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a

Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3


Channel	Frequency	Peak Excursion (dB)	Max. Limit (dB)	Result
48	5240 MHz	9.80	13	Complies

Peak Excursion Plot on Configuration IEEE 802.11n MCS0 HT20MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5200 MHz




Date: 16.NOV.2012 23:21:34

Peak Excursion Plot on Configuration IEEE 802.11n MCS0 HT40MHz / Ant. 1 + Ant. 2 + Ant. 3 / 5230 MHz



Date: 16.NOV.2012 23:17:45

Peak Excursion Plot on Configuration IEEE 802.11a / Ant. 1 + Ant. 2 + Ant. 3 / 5240 MHz



Date: 16.NOV.2012 23:23:36

4.6. Radiated Emissions Measurement

4.6.1. Limit

For transmitters operating in the 5.15-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). For transmitters operating in the In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.


Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	40 GHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1MHz / 3MHz for peak

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

4.6.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.6.4. Test Setup Layout



4.6.5. Test Deviation

There is no deviation with the original standard.

4.6.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.6.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	CTX
Test Date	Nov. 22, 2012		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log (\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.6.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	CTX

Horizontal



	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	144.46	35.83	43.50	-7.67	49.92	1.75	27.53	11.69	Peak	0	400	HORIZONTAL
2	172.59	36.89	43.50	-6.61	52.14	1.96	27.40	10.19	Peak	0	400	HORIZONTAL
3	298.69	36.41	46.00	-9.59	46.93	2.51	26.83	13.80	Peak	0	400	HORIZONTAL
4	499.48	37.69	46.00	-8.31	44.46	3.38	27.93	17.78	Peak	0	400	HORIZONTAL
5	865.17	37.67	46.00	-8.33	38.78	4.48	26.88	21.29	Peak	0	400	HORIZONTAL
6	901.06	38.28	46.00	-7.72	38.99	4.60	26.82	21.51	Peak	0	400	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	299.66	36.19	46.00	-9.81	46.71	2.51	26.83	13.80	Peak	0	100	VERTICAL
2	416.06	36.01	46.00	-9.99	43.90	3.07	27.62	16.66	Peak	0	100	VERTICAL
3	497.54	37.51	46.00	-8.49	44.32	3.37	27.93	17.75	Peak	0	100	VERTICAL
4	649.83	38.58	46.00	-7.42	42.64	3.90	27.56	19.60	Peak	0	100	VERTICAL
5	916.58	37.63	46.00	-8.37	38.04	4.68	26.72	21.63	Peak	0	100	VERTICAL
6 p	957.32	39.41	46.00	-6.59	39.07	4.86	26.47	21.95	Peak	0	100	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6.9. Results for Radiated Emissions (1GHz~40GHz)

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT20MHz Ch 36 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	15541.90	56.30	74.00	-17.70	43.18	10.59	35.59	38.12	175	100	Peak	HORIZONTAL
2 a	15542.84	43.01	54.00	-10.99	29.89	10.59	35.59	38.12	175	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15535.26	42.41	54.00	-11.59	29.27	10.58	35.59	38.15	42	100	Average	VERTICAL
2 p	15543.12	56.11	74.00	-17.89	42.99	10.59	35.59	38.12	42	100	Peak	VERTICAL

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT20MHz Ch 40 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15597.44	42.04	54.00	-11.96	28.98	10.60	35.58	38.04	298	100	Average	HORIZONTAL
2 p	15598.74	55.49	74.00	-18.51	42.43	10.60	35.58	38.04	298	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15595.98	41.98	54.00	-12.02	28.92	10.60	35.58	38.04	139	100	Average	VERTICAL
2 p	15597.56	55.76	74.00	-18.24	42.70	10.60	35.58	38.04	139	100	Peak	VERTICAL

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT20MHz Ch 48 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15716.88	41.70	54.00	-12.30	28.77	10.64	35.56	37.85	214	100	Average	HORIZONTAL
2 p	15719.42	55.22	74.00	-18.78	42.29	10.64	35.56	37.85	214	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15718.50	41.84	54.00	-12.16	28.91	10.64	35.56	37.85	38	100	Average	VERTICAL
2 p	15722.02	55.55	74.00	-18.45	42.62	10.64	35.56	37.85	38	100	Peak	VERTICAL

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT40MHz Ch 38 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15565.90	42.06	54.00	-11.94	28.95	10.60	35.58	38.09	58	100	Average	HORIZONTAL
2 p	15574.22	56.97	74.00	-17.03	43.88	10.60	35.58	38.07	58	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15569.16	42.06	54.00	-11.94	28.95	10.60	35.58	38.09	202	100	Average	VERTICAL
2 p	15570.60	55.35	74.00	-18.65	42.24	10.60	35.58	38.09	202	100	Peak	VERTICAL

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 HT40MHz Ch 46 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	15691.14	56.32	74.00	-17.68	43.37	10.63	35.56	37.88	285	100	Peak	HORIZONTAL
2 a	15692.72	41.67	54.00	-12.33	28.72	10.63	35.56	37.88	285	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15687.51	41.67	54.00	-12.33	28.69	10.63	35.56	37.91	129	100	Average	VERTICAL
2 p	15692.00	55.60	74.00	-18.40	42.65	10.63	35.56	37.88	129	100	Peak	VERTICAL

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11a Ch 36 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	15536.66	55.97	74.00	-18.03	42.83	10.58	35.59	38.15	326	100	Peak	HORIZONTAL
2 a	15539.46	42.47	54.00	-11.53	29.35	10.59	35.59	38.12	326	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15535.00	42.45	54.00	-11.55	29.31	10.58	35.59	38.15	161	100	Average	VERTICAL
2 p	15536.80	55.95	74.00	-18.05	42.81	10.58	35.59	38.15	161	100	Peak	VERTICAL

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11a Ch 40 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	15596.62	56.09	74.00	-17.91	43.03	10.60	35.58	38.04	250	100	Peak	HORIZONTAL
2 a	15598.56	42.01	54.00	-11.99	28.95	10.60	35.58	38.04	250	100	Average	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 p	15599.98	56.01	74.00	-17.99	42.95	10.60	35.58	38.04	49	100	Peak	VERTICAL
2 a	15600.96	42.04	54.00	-11.96	28.98	10.60	35.58	38.04	49	100	Average	VERTICAL

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11a Ch 48 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15716.44	41.70	54.00	-12.30	28.77	10.64	35.56	37.85	318	100	Average	HORIZONTAL
2 p	15723.88	55.74	74.00	-18.26	42.81	10.64	35.56	37.85	318	100	Peak	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 a	15718.32	41.73	54.00	-12.27	28.80	10.64	35.56	37.85	182	100	Average	VERTICAL
2 p	15724.62	56.14	74.00	-17.86	43.21	10.64	35.56	37.85	182	100	Peak	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.7. Band Edge Emissions Measurement

4.7.1. Limit

For transmitters operating in the 5.15-5.35 GHz band: all emissions outside of the 5.15-5.35 GHz band shall not exceed an EIRP of -27 dBm/MHz (68.3dBuV/m at 3m). In addition, In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.7.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RB / VB (Emission in restricted band)	1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average
RB / VB (Emission in non-restricted band)	1 MHz / 3MHz for Peak

4.7.3. Test Procedures

1. The test procedure is the same as section 4.6.3, only the frequency range investigated is limited to 100MHz around bandedges.
2. In case the emission is fail due to the used RB/VB is too wide, marker-delta method of FCC Public Notice DA00-705 will be followed.

4.7.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.6.4.

4.7.5. Test Deviation

There is no deviation with the original standard.

4.7.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.7.7. Test Result of Band Edge and Fundamental Emissions

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 20MHz Ch 36, 40, 48 /Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Channel 36

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	5150.00	72.70	74.00	-1.30	32.20	6.49	0.00	34.01	267	123	Peak	VERTICAL
2 !	5150.00	52.10	54.00	-1.90	11.60	6.49	0.00	34.01	267	123	Average	VERTICAL
3 a	5187.60	102.19				6.52	0.00	34.08	267	123	Average	VERTICAL
4 p	5188.20	119.50				6.52	0.00	34.08	267	123	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	5150.00	72.42	74.00	-1.58	31.92	6.49	0.00	34.01	268	113	Peak	VERTICAL
2 !	5150.00	52.51	54.00	-1.49	12.01	6.49	0.00	34.01	268	113	Average	VERTICAL
3 p	5200.80	123.54				6.52	0.00	34.11	268	113	Peak	VERTICAL
4 a	5200.80	108.49				6.52	0.00	34.11	268	113	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	5150.00	56.87	74.00	-17.13	16.37	6.49	0.00	34.01	266	110	Peak	VERTICAL
2	5150.00	46.10	54.00	-7.90	5.60	6.49	0.00	34.01	266	110	Average	VERTICAL
3 a	5234.40	107.29				6.54	0.00	34.18	266	110	Average	VERTICAL
4 p	5237.60	115.82				6.56	0.00	34.18	266	110	Peak	VERTICAL
5 !	5359.60	52.25	54.00	-1.75	11.21	6.62	0.00	34.42	266	110	Average	VERTICAL
6	5360.40	60.49	74.00	-13.51	19.45	6.62	0.00	34.42	266	110	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 40MHz Ch 38, 46 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Channel 38

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	5149.60	70.96	74.00	-3.04	30.46	6.49	0.00	34.01	258	119	Peak	VERTICAL
2 !	5150.00	52.35	54.00	-1.65	11.85	6.49	0.00	34.01	258	119	Average	VERTICAL
3 p	5194.00	112.69				6.52	0.00	34.08	258	119	Peak	VERTICAL
4 a	5194.40	92.02				6.52	0.00	34.08	258	119	Average	VERTICAL

Item 3, 4 are the fundamental frequency at 5190 MHz.

Channel 46

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	5150.00	69.90	74.00	-4.10	29.40	6.49	0.00	34.01	92	111	Peak	VERTICAL
2 !	5150.00	52.39	54.00	-1.61	11.89	6.49	0.00	34.01	92	111	Average	VERTICAL
3 a	5234.00	98.85				6.54	0.00	34.18	92	111	Average	VERTICAL
4 p	5235.20	118.79				6.54	0.00	34.18	92	111	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5230 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

Temperature	20°C	Humidity	60%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11a Ch 36, 40, 48 / Ant. 1 + Ant. 2 + Ant. 3
Test Date	Nov. 22, 2012		

Channel 36

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	5148.60	72.88	74.00	-1.12	32.38	6.49	34.01	0.00	Peak	100	82	VERTICAL
2	5149.40	50.09	54.00	-3.91	9.59	6.49	34.01	0.00	Average	100	82	VERTICAL
3	5183.80	101.84				6.51	34.08	0.00	Average	100	82	VERTICAL
4	5183.80	119.31				6.51	34.08	0.00	Peak	100	82	VERTICAL

Item 3, 4 are the fundamental frequency at 5180 MHz.

Channel 40

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1 !	5147.60	51.43	54.00	-2.57	10.93	6.49	0.00	34.01	275	113	Average	VERTICAL
2 !	5148.40	72.94	74.00	-1.06	32.44	6.49	0.00	34.01	275	113	Peak	VERTICAL
3 a	5197.20	105.74				6.52	0.00	34.11	275	113	Average	VERTICAL
4 p	5197.60	122.76				6.52	0.00	34.11	275	113	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5200 MHz.

Channel 48

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	T/Pos	A/Pos	Remark	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m	deg	cm		
1	5078.00	59.72	74.00	-14.28	19.40	6.45	0.00	33.87	257	115	Peak	VERTICAL
2	5078.80	47.74	54.00	-6.26	7.42	6.45	0.00	33.87	257	115	Average	VERTICAL
3 p	5246.40	122.70				6.56	0.00	34.22	257	115	Peak	VERTICAL
4 a	5246.40	107.05				6.56	0.00	34.22	257	115	Average	VERTICAL
5 !	5359.60	52.26	54.00	-1.74	11.22	6.62	0.00	34.42	257	115	Average	VERTICAL
6	5360.40	65.11	74.00	-8.89	24.07	6.62	0.00	34.42	257	115	Peak	VERTICAL

Item 3, 4 are the fundamental frequency at 5240 MHz.

Note:

Emission level (dBuV/m) = 20 log Emission level (uV/m)

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

4.8. Frequency Stability Measurement

4.8.1. Limit

Manufacturers of U-NII devices are responsible for ensuring frequency stability such that an emissions is maintained within the band of operation under all conditions of normal operation as specified in the user’s manual or $\pm 20\text{ppm}$ (IEEE 802.11nspecification).

4.8.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Entire absence of modulation emissions bandwidth
RB	10 kHz
VB	10 kHz
Sweep Time	Auto

4.8.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer.
2. EUT have transmitted absence of modulation signal and fixed channelize.
3. Set the spectrum analyzer span to view the entire absence of modulation emissions bandwidth.
4. Set RBW = 10 kHz, VBW = 10 kHz with peak detector and maxhold settings.
5. f_c is declaring of channel frequency. Then the frequency error formula is $(f_c - f) / f_c \times 10^6$ ppm and the limit is less than $\pm 20\text{ppm}$ (IEEE 802.11nspecification).
6. The test extreme voltage is to change the primary supply voltage from 85 to 115 percent of the nominal value
7. Extreme temperature rule is $-30^\circ\text{C} \sim 50^\circ\text{C}$.

4.8.4. Test Setup Layout



4.8.5. Test Deviation

There is no deviation with the original standard.

4.8.6. EUT Operation during Test

The EUT was programmed to be in continuously un-modulation transmitting mode.

4.8.7. Test Result of Frequency Stability

Voltage vs. Frequency Stability

Voltage	Measurement Frequency (MHz)
(V)	5200
126.50	5200.0098
110.00	5200.0096
93.50	5200.0086
Max. Deviation (MHz)	0.009800
Max. Deviation (ppm)	1.88

Temperature vs. Frequency Stability

Temperature	Measurement Frequency (MHz)
(°C)	5200
-30	5199.9785
-20	5199.9612
-10	5199.9688
0	5199.9726
10	5199.9876
20	5199.9842
30	5199.9843
40	5199.9536
50	5199.9548
Max. Deviation (MHz)	0.046400
Max. Deviation (ppm)	8.92

4.9. Antenna Requirements

4.9.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.9.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Jan. 11, 2012	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz~18GHz	Nov. 25, 2011	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 22, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 17, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 29, 2011	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9KHz~40GHz	Nov. 03, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9KHz ~ 2.75GHz	Mar. 20, 2012	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Sep. 09, 2011*	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N/A	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N/A	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz ~ 26.5 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz ~ 26.5 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 17, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 14, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127-478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz~30MHz	Feb. 03, 2012	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz~30MHz	Dec. 4, 2011	Conduction (CO01-CB)
Signal analyzer	R&S	FSV40	100979	9KHz~40GHz	Oct. 08, 2012	Conducted (TH01-CB)
Temp. and Humidity Chamber	Ten Billion	TTH-D3SP	TBN-931011	-30~100 degree	Jun. 05, 2012	Conducted (TH01-CB)
Thermo-Hygro Meter	N/A	HC 520	#1	15~70 degree	Nov. 02, 2012	Conducted (TH01-CB)
Signal Generator	R&S	SMR40	100302	10MHz-40GHz	Nov. 22, 2011	Conducted (TH01-CB)
RF Power Divider	HP	11636A	00306	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Power Splitter	Anaren	44100	1839	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
RF Power Splitter	Anaren	42100	17930	2GHz ~ 18GHz	N/A	Conducted (TH01-CB)
Signal generator	R&S	SMU200A	102782	10MHz-40GHz	Sep. 26, 2012	Conducted (TH01-CB)
Horn Antenna	COM-POWER	AH-118	071187	1GHz – 18GHz	May 09, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-12	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-13	-	1 GHz – 26.5 GHz	Nov. 17, 2011	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz~40GHz	Nov. 01, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz~40GHz	Nov. 01, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

“*” Calibration Interval of instruments listed above is two years.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. TAF CERTIFICATE OF ACCREDITATION



Certificate No. : L1190-110702

財團法人全國認證基金會
Taiwan Accreditation Foundation

Certificate of Accreditation

This is to certify that

Sporton International Inc.
EMC & Wireless Communications Laboratory
No.52, Hwa Ya 1st Road, Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien,
Taiwan, R.O.C.

is accredited in respect of laboratory

Accreditation Criteria	: ISO/IEC 17025:2005
Accreditation Number	: 1190
Originally Accredited	: December 15, 2003
Effective Period	: January 10, 2010 to January 09, 2013
Accredited Scope	: Testing Field, see described in the Appendix
Specific Accreditation Program	: Accreditation Program for Designated Testing Laboratory for Commodities Inspection Accreditation Program for Telecommunication Equipment Testing Laboratory Accreditation Program for BSMI Mutual Recognition Arrangement with Foreign Authorities


Jay-San Chen
President, Taiwan Accreditation Foundation
Date : July 02, 2011

P1, total 22 pages

The Appendix forms an integral part of this Certificate, which shall be invalid when use without the Appendix