



TEST REPORT

Report No. : AD002849-2 Date : 2003 March 28

Applicant : Kin Yat Industrial Co., Ltd.
7/F., Galaxy Factory Building,
25-27 Luk Hop Street, San Po Kong,
Kowloon, Hong Kong.

Sample Description : One(1) submitted sample stated to be Dump Truck of Model No. 90659.
Rating : 4 x 1.5 V size batteries
No. of sample(s) : Two(2) pieces ***

Date Received : 2003 February 25.

Test Period : 2003 February 25 – 2003 March 03.

Test Requested : FCC Part 15 Certification

Test Method : FCC Rules and Regulations Part 15 – May 2002
ANSI C63.4 – 1992

Test Result : See attached sheet(s) from page 2 to 10.

Conclusion : The submitted sample was found to comply with requirement of FCC
Part 15 Subpart B.

For and on behalf of
CMA Testing and Certification Laboratories

Authorized Signature : _____

Danny Chui
EMC Engineer - EL. Division

Page 1 of 10

FCC ID : HDT90659RX

This document shall not be reproduced either in full or in part except with written approval by the Authorized Representative of CMA Testing.

Room 1401-3, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmactl.com Web Site: <http://www.cmactl.com>



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

Table of Contents

1	General Information.....	3
1.1	General Description.....	3
1.2	Related Submittal Grants	3
1.3	Location of the test site.....	4
1.4	List of measuring equipment	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result.....	6
2.3	Radiated Emission Measurement Data.....	7
3	Description of the Line-conducted Test	8
3.1	Test Procedure	8
3.2	Test Result.....	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission	9
4.2	Photographs of the External and Internal Configurations of the EUT	9
5	Supplementary document	9
5.1	Bandwidth	9
6	Appendices.....	10



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

1 General Information

1.1 General Description

The equipment under test (EUT) is a superregenerative receiver for Dump Truck operating at 49.860 MHz which is controlled by a crystal. The EUT is powered by four “C” size batteries. The EUT receive the signal from transmitter for moving forward, backward, left, right direction and for dumping up and down operation.

The brief circuit description is listed as follows :

- Q1 and associated circuit act as superregeneration
- IC and associated circuit act as decoding
- Q7, Q8, Q9, Q10 and associated circuit act as motor (M1) control
- Q11, Q12, Q13, Q14 and associated circuit act as motor (M2) control
- Q20, Q21, Q24, Q25 and associated circuit act as motor (M3) control

1.2 Related Submittal Grants

This is a single application for certification of a transmitter. The transmitter for this receiver is authorized by Certification procedure.



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

1.3 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992. An Open Area Testing Site is set up for investigation and located at :

Top of the Roof, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. A double shielded room is located at :

Roof Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

1.4 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Certification No.	Calibration Date	Calibration Due Date
EMI Test Receiver	R&S	ESCS30	100001	S21141	Dec. 19, 2002	Dec. 18, 2003
Broadband Antenna	Schaffner	CBL6113B	2718	AC1753	Dec. 15, 2000	Jun. 14, 2003
Signal Generator	IFR	2023B	202302/938	Nil	Oct. 23, 2000	Apr. 22, 2003
LISN	R&S	ESH3-Z5	100038	S21142	Dec. 19, 2002	Dec. 18, 2003
Pulse Limiter	R&S	ESH3-Z2	100001	20-73194	May 2, 2001	May 1, 2003
Biconical Antenna	R&S	HK116	837414/004	4000.7752.02	Oct. 23, 2000	Apr. 22, 2003



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 1992.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

A signal generator was used to radiate an unmodulated continuous wave (CW) signal to the EUT (superregenerative receiver) at its operating frequency in order to “cohere” the characteristic broadband emissions from the receiver.

2.2 Test Result

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector.

It was found that the EUT meet the FCC requirement.



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

2.3 Radiated Emission Measurement Data

**Radiated emission
pursuant to
the requirement of FCC Part 15 subpart B**

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV/m)	Antenna and Cable factor (dB)	Field Strength (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
47.735	V	21.4	11.4	32.8	40.0	-7.2
49.738	V	19.8	11.4	31.2	40.0	-8.8
50.774	V	21.3	8.9	30.2	40.0	-9.8
51.656	V	17.6	8.9	26.5	40.0	-13.5
94.571	V	13.4	10.0	23.4	43.5	-20.1
95.430	V	14.2	10.0	24.2	43.5	-19.3
141.532	V	11.4	12.2	23.6	43.5	-19.9

Page 7 of 10

FCC ID : HDT90659RX



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 1992. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

For electronic filing, the photos are saved with filename TSup1.jpg to TSup2.jpg

4.2 Photographs of the External and Internal Configurations of the EUT

For electronic filing, the photos are saved with filename ExtPho1.jpg to ExtPho2.jpg and IntPho1.jpg to IntPho2.jpg.

5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmpl.pdf
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

5.1 Bandwidth

N.A.



TEST REPORT

Report No. : AD002849-2

Date : 2003 March 28

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1 page
A2.	Photos of External Configurations	1 page
A3.	Photos of Internal Configurations	1 page
A4.	ID Label/Location	2 pages
A5.	Block Diagram	1 page
A6.	Schematics	1 page
A7.	User Manual	4 pages
A8.	Operation Description	1 page

***** End of Report *****