

October 7, 2003

RE: Accton Technology Corporation

FCC ID: HED3CRWE554G72

After a review of the submitted information, I have a few comments on the above referenced Application.

- 1) Please provide an additional photograph underneath the shield/copper tape located on the bottom of the board.
- 2) The users manual page 123 mentions that the device must utilize shielded interface cables. However, page 101 states the device may uses shielded or unshielded cables. Additionally, the testing configuration given in the test report page 9 does not clearly label the UTP cable as shielded or unshielded. Given the prevalence of unshielded UTP, please confirm if the device was tested with a shielded or unshielded UTP cable. If the device was tested and meets the requirements with an unshielded UTP cable, it would be best to remove the phrase "(for example, use only shielded interface cables when connecting to computer or peripheral devices)" from the manual. However if a shielded cable is required, please have the manufacturer confirm that the unit ships with a shielded cable and remove the reference to unshielded cables on page 79.
- 3) The calculation on note 1 on page 53 of the test report appears incorrect. 103.7 57.53 = 46.17. Please correct.

Timothy R. Johnson Examining Engineer

mailto: tjohnson@AmericanTCB.com

The items indicated above must be submitted before processing can continue on the above referenced application. Failure to provide the requested information may result in application termination. Correspondence should be considered part of the permanent submission and may be viewed from the Internet after a Grant of Equipment Authorization is issued.

Please do not respond to this correspondence using the email reply button. In order for your response to be processed expeditiously, you must submit your documents through the AmericanTCB.com website. Also, please note that partial responses increase processing time and should not be submitted.

Any questions about the content of this correspondence should be directed to the sender.