



Test Report No:
23B0423R-RFUSV17S-A

RF EXPOSURE EVALUATION DECLARATION

Product Name	Wi-Fi 6 Access Point
Brand Name	E d g e - c o r e
Model No.	EAP111 (XXXXX), EAP111e (XXXXX) (Please refer to the section 1.1 for detail.)
FCC ID	HEDEAP111
Applicant's Name / Address	Accton Technology Corporation No. 1, Creation Rd. III, Science-based Industrial Park, Hsinchu 300, Taiwan, R.O.C.
Manufacturer's Name / Address (1)	Accton Technology Corporation Zhunan Factory 1F & 4F & 5F, No. 1, Keyi St., Zhunan Townshp, Miaoli County 350, Taiwan, R.O.C.
Manufacturer's Name / Address (2)	Accton Technology Corporation No. 1, Creation Rd. III, Science-based Industrial Park, Hsinchu 300, Taiwan, R.O.C.
Manufacturer's Name / Address (3)	VIETNAM ACCTON TECHNOLOGY COMPANY LIMITED Lot F1-2-3 Thang Long Industrial Park (Vinh Phuc), Tam Hop Commune Binh Xuyen District, Vinh Phuc Province, Vietnam
Test Method Requested, Standard	FCC CFR Title 47 Part 2.1091 Radiofrequency radiation exposure evaluation: mobile devices.
Verdict Summary	IN COMPLIANCE
Documented By	<i>Amelia Wu</i> Amelia Wu
Approved By	<i>Rueyyan Lin</i> Rueyyan Lin
Date of Receipt	Nov. 14, 2023
Date of Issue	Mar. 12, 2024
Report Version	V1.0

INDEX

page

Competences and Guarantees.....	3
General Conditions.....	3
Revision History.....	4
1. General Information.....	5
1.1. EUT Description.....	5
1.2. Testing Location Information.....	5
2. RF Exposure Evaluation.....	6
2.1. Test Limit.....	6
2.2. Test Result of RF Exposure Evaluation.....	7

Competences and Guarantees

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

IMPORTANT: No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

General Conditions

1. The test results relate only to the samples tested.
2. The test results shown in the test report are traceable to the national/international standard through the calibration report of the equipment and evaluated measurement uncertainty herein.
3. This report must not be used to claim product endorsement by TAF or any agency of the government.
4. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification Co., Ltd.
5. Measurement uncertainties evaluated for each testing system and associated connections are given here to provide the system information for reference. Compliance determinations do not take into account measurement uncertainties for each testing system, but are based on the results of the compliance measurement.

Revision History

Version	Description	Issued Date
V1.0	Initial issue of report	Mar. 12, 2024

1. General Information

1.1. EUT Description

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
WiFi 2.4 GHz	2400 ~ 2483.5	2412 ~ 2462	802.11b: DSSS 802.11g/n/ac: OFDM 802.11ax: OFDMA
WiFi 5 GHz	5150 ~ 5250 5250 ~ 5350 5470 ~ 5725 5725 ~ 5850	5180 ~ 5240 5260 ~ 5320 5500 ~ 5700 5745 ~ 5825	802.11a/n/ac: OFDM 802.11ax: OFDMA
Bluetooth	2400 ~ 2483.5	2402 ~ 2480	LE: GFSK

The difference for each model is shown as below:

EUT	Model No.	Antenna		
		Ant.	Model No.	Remark
1	EAP111 (XXXXX)	1	KG568-T4-175B17U7S	Internal Antenna
		2	KG568-T4-105W17U7S	Internal Antenna
		3	KG568-T4-175G17U7S	Internal Antenna
2	EAP111e (XXXXX)	1	98623PRSX001	External Antenna
		2	98623PRSX001	External Antenna
		3	KG568-T4-175G17U7S	Internal Antenna

The difference of "XXXXX" would be marketing strategy X can be symbol "A~Z, a~z, 1~9 or blank.

Note:

- The above EUT information is declared by the manufacturer.
- Antenna gain of EUT 1 (model: EAP111) is higher than that of EUT 2 (model: EAP111e), only EUT 1 (model: EAP111) was selected as representative model for the test and its data was recorded in this report.

1.2. Testing Location Information

Testing Location Information		
Test Laboratory : DEKRA Testing and Certification Co., Ltd.		
1 (TAF: 3024)	ADD: No.372-2, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. TEL: +886-3-582-8001 FAX: +886-3-582-8958	
2 (TAF: 3024)	ADD: No.372, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County 31061, Taiwan, R.O.C. TEL: +886-3-582-8001 FAX: +886-3-582-8958	
Test site number for address 1 includes HC-SR02. Test site number for address 2 includes HC-CB02, HC-CB03, HC-CB04, HC-SR10 and HC-SR12.		

2. RF Exposure Evaluation

2.1. Test Limit

(A) Test Limit for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	*(100)	<6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1500	-	-	f/300	<6
1500-100,000	-	-	5	<6

(B) Test Limit for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1500	-	-	f/1500	<30
1500-100,000	-	-	1.0	<30

Note: f = frequency in MHz; *Plane-wave equivalent power density

Power Density (S) is calculated by the following formula:

$$S=(P*G)/4\pi R^2$$

where:

S = power density (in appropriate units, e.g. mW/ cm²)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

π = 3.1416

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

2.2. Test Result of RF Exposure Evaluation

Exposure Environment: General Population / Uncontrolled Exposure

Evaluation Mode	E.I.R.P (dBm)	E.I.R.P (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Test Result (PASS/FAIL)
WiFi 2.4 GHz	28.935	782.528	0.156	1.000	PASS
WiFi 5 GHz Band 1	29.298	850.749	0.169	1.000	PASS
WiFi 5 GHz Band 2	25.259	335.629	0.067	1.000	PASS
WiFi 5 GHz Band 3	29.191	829.952	0.165	1.000	PASS
WiFi 5 GHz Band 4	32.664	1846.705	0.367	1.000	PASS
Bluetooth LE	8.490	7.063	0.001	1.000	PASS

Distance (cm): 20 for Maximum Permissible Exposure.

Co-location
<p>Conclusion:</p> <p>The formula of calculated the MPE is:</p> <p>CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1</p> <p>CPD = Calculation power density</p> <p>LPD = Limit of power density</p> <p>WiFi 2.4 GHz + WiFi 5 GHz + Buletooth LE function = 0.155 + 0.367 + 0.001 = 0.523, therefore the maximum calculations of above situations are less than the "1" limit.</p>

Note:

1. The above EUT information is declared by the manufacturer.
2. The results are based on the maximum power.