

Appendix C. Maximum Permissible Exposure



1. Maximum Permissible Exposure

1.1. Applicable Standard

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device. (A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm ²) | Averaging Time E ² , H ² or S (minutes) | |
|--------------------------|--------------------------------------|--------------------------------------|---|--|--|
| 0.3-3.0 | 614 | 1.63 | (100)* | 6 | |
| 3.0-30 | 1842 / f | 4.89 / f | (900 / f)* | 6 | |
| 30-300 | 61.4 | 0.163 | 1.0 | 6 | |
| 300-1500 | | | F/300 | 6 | |
| 1500-100,000 | | | 5 | 6 | |

(B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm²) | Averaging Time E ² , H ² or S (minutes) |
|--------------------------|--------------------------------------|--------------------------------------|--------------------------------|---|
| 0.3-1.34 | 614 | 1.63 | (100)* | 30 |
| 1.34-30 | 824/f | 2.19/f | (180/f)* | 30 |
| 30-300 | 27.5 | 0.073 | 0.2 | 30 |
| 300-1500 | | | F/1500 | 30 |
| 1500-100,000 | | | 1.0 | 30 |

Note: f = frequency in MHz; *Plane-wave equivalent power density

1.2. MPE Calculation Method

E (V/m) =
$$\frac{\sqrt{30 \times P \times G}}{d}$$
 Power Density: Pd (W/m²) = $\frac{E^2}{377}$

 $\mathbf{E} = \text{Electric field (V/m)}$

 $\mathbf{P} = \mathbf{Peak} \ \mathbf{RF} \ \mathbf{output} \ \mathbf{power} \ \mathbf{(W)}$

- $\mathbf{G} = \mathbf{E} \mathbf{U} \mathbf{T}$ Antenna numeric gain (numeric)
- d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.



1.3. Calculated Result and Limit

Antenna Type : Patch Antenna

Max Conducted Power for IEEE 802.11a : 10.90dBm

| Antenna Gain (dBi) | Antenna Gain (numeric) | Peak Output Power (dBm) | Peak Output Power (mW) | Power Density (S) (mW/cm ²) | Limit of Power Density (S) (mW/cm ²) | Test Result |
|-----------------------|---------------------------|-------------------------------|-----------------------------|---|--|-------------|
| 17 | 50.1187 | 10.9000 | 12.3027 | 0.122730 | 1 | Complies |