



11Mbps CHANNEL 6 Processing Gain				
Freq.	Gp	(S/N) °	Mj = J/S	Lsys
(GHz)	(dB)	(dB)	(dB)	(dB)
2.43890	11.45	16.4	-5.95	1
2.43895	11.20	16.4	-6.20	1
2.43900	11.30	16.4	-6.10	1
2.43905	11.28	16.4	-6.12	1
2.43910	11.15	16.4	-6.25	1
2.43915	11.11	16.4	-6.29	1
2.43920	11.10	16.4	-6.30	1
2.43925	11.08	16.4	-6.32	1
2.43930	11.08	16.4	-6.32	1
2.43935	11.09	16.4	-6.31	1
2.43940	11.09	16.4	-6.31	1
2.43945	10.80	16.4	-6.60	1
2.43950	10.97	16.4	-6.43	1
2.43955	11.00	16.4	-6.40	1
2.43960	11.04	16.4	-6.36	1
2.43965	11.06	16.4	-6.34	1
2.43970	11.08	16.4	-6.32	1
2.43975	11.18	16.4	-6.22	1
2.43980	11.23	16.4	-6.17	1
2.43985	11.30	16.4	-6.10	1
2.43990	11.32	16.4	-6.08	1
2.43995	11.38	16.4	-6.02	1
2.44000	11.40	16.4	-6.00	1
2.44005	11.45	16.4	-5.95	1
2.44010	11.46	16.4	-5.94	1
2.44015	11.48	16.4	-5.92	1
2.44020	11.49	16.4	-5.91	1
2.44025	11.50	16.4	-5.90	1
2.44030	11.61	16.4	-5.79	1
2.44035	11.66	16.4	-5.74	1
2.44040	11.67	16.4	-5.73	1
2.44045	11.78	16.4	-5.62	1
2.44050	11.83	16.4	-5.57	1
2.44055	12.00	16.4	-5.40	1



11Mbps CHANNEL 6 Processing Gain				
Freq. (GHz)	Gp (dB)	(S/N) • (dB)	Mj = J/S (dB)	Lsys (dB)
2.44060	12.20	16.4	-5.20	1
2.44065	12.21	16.4	-5.19	1
2.44070	12.21	16.4	-5.19	1
2.44075	12.22	16.4	-5.18	1
2.44080	12.23	16.4	-5.17	1
2.44085	12.23	16.4	-5.17	1
2.44090	12.23	16.4	-5.17	1
2.44095	12.24	16.4	-5.16	1
2.44100	12.24	16.4	-5.16	1
2.44105	12.36	16.4	-5.04	1
2.44110	12.40	16.4	-5.00	1
2.44115	12.45	16.4	-4.95	1
2.44120	12.48	16.4	-4.92	1
2.44125	12.70	16.4	-4.70	1
2.44130	12.81	16.4	-4.59	1
2.44135	12.88	16.4	-4.52	1
2.44140	12.90	16.4	-4.50	1
2.44145	12.89	16.4	-4.51	1
2.44150	12.88	16.4	-4.52	1
2.44155	12.90	16.4	-4.50	1
2.44160	12.90	16.4	-4.50	1
2.44165	12.85	16.4	-4.55	1
2.44170	12.76	16.4	-4.64	1
2.44175	12.79	16.4	-4.61	1
2.44180	12.81	16.4	-4.59	1
2.44185	13.19	16.4	-4.21	1
2.44190	13.14	16.4	-4.26	1
2.44195	13.35	16.4	-4.05	1
2.44200	13.41	16.4	-3.99	1
Processing Gain : 11.7 dB				



11Mbps CHANNEL 11 Processing Gain				
Freq. (GHz)	Gp (dB)	(S/N) ° (dB)	Mj = J/S (dB)	Lsys (dB)
2.45700	13.20	16.4	-4.20	1
2.45705	13.15	16.4	-4.25	1
2.45710	13.01	16.4	-4.39	1
2.45715	12.90	16.4	-4.50	1
2.45720	12.73	16.4	-4.67	1
2.45725	12.75	16.4	-4.65	1
2.45730	12.80	16.4	-4.60	1
2.45735	12.85	16.4	-4.55	1
2.45740	12.89	16.4	-4.51	1
2.45745	12.89	16.4	-4.51	1
2.45750	12.89	16.4	-4.51	1
2.45755	12.89	16.4	-4.51	1
2.45760	12.89	16.4	-4.51	1
2.45765	12.60	16.4	-4.80	1
2.45770	12.41	16.4	-4.99	1
2.45775	12.35	16.4	-5.05	1
2.45780	12.15	16.4	-5.25	1
2.45785	12.12	16.4	-5.28	1
2.45790	12.04	16.4	-5.36	1
2.45795	11.80	16.4	-5.60	1
2.45800	11.93	16.4	-5.47	1
2.45805	11.85	16.4	-5.55	1
2.45810	11.88	16.4	-5.52	1
2.45815	11.84	16.4	-5.56	1
2.45820	11.83	16.4	-5.57	1
2.45825	11.80	16.4	-5.60	1
2.45830	11.75	16.4	-5.65	1
2.45835	11.63	16.4	-5.77	1
2.45840	11.43	16.4	-5.97	1
2.45845	11.39	16.4	-6.01	1
2.45850	11.37	16.4	-6.03	1
2.45855	11.36	16.4	-6.04	1
2.45860	11.34	16.4	-6.06	1
2.45865	11.30	16.4	-6.10	1



11Mbps CHANNEL 11 Processing Gain				
Freq.	Gp	(S/N) °	Mj = J/S	Lsys
(GHz)	(dB)	(dB)	(dB)	(dB)
2.45870	11.17	16.4	-6.23	1
2.45875	11.15	16.4	-6.25	1
2.45880	11.10	16.4	-6.30	1
2.45885	11.10	16.4	-6.30	1
2.45890	11.11	16.4	-6.29	1
2.45895	11.08	16.4	-6.32	1
2.45900	11.05	16.4	-6.35	1
2.45905	11.03	16.4	-6.37	1
2.45910	11.03	16.4	-6.37	1
2.45915	10.70	16.4	-6.70	1
2.45920	10.72	16.4	-6.68	1
2.45925	10.60	16.4	-6.80	1
2.45930	10.69	16.4	-6.71	1
2.45935	10.68	16.4	-6.72	1
2.45940	10.67	16.4	-6.73	1
2.45945	10.66	16.4	-6.74	1
2.45950	10.65	16.4	-6.75	1
2.45955	10.68	16.4	-6.72	1
5.45960	10.77	16.4	-6.63	1
2.45965	10.77	16.4	-6.63	1
2.45970	10.76	16.4	-6.64	1
2.45975	10.75	16.4	-6.65	1
2.45980	10.74	16.4	-6.66	1
2.45985	10.75	16.4	-6.65	1
2.45990	10.85	16.4	-6.55	1
2.45995	10.95	16.4	-6.45	1
2.46000	10.96	16.4	-6.44	1
2.46005	10.97	16.4	-6.43	1
2.46010	10.96	16.4	-6.44	1
2.46015	10.96	16.4	-6.44	1
2.46020	10.95	16.4	-6.45	1
2.46025	10.95	16.4	-6.45	1
2.46030	10.95	16.4	-6.45	1
2.46035	10.94	16.4	-6.46	1
2.46040	10.90	16.4	-6.50	1
2.46045	10.96	16.4	-6.44	1



11Mbps CHANNEL 11 Processing Gain				
Freq.	Gp	(S/N) •	Mj = J/S	Lsys
(GHz)	(dB)	(dB)	(dB)	(dB)
2.46050	10.96	16.4	-6.44	1
2.46055	11.00	16.4	-6.40	1
2.46060	11.06	16.4	-6.34	1
2.46065	11.15	16.4	-6.25	1
2.46070	11.26	16.4	-6.14	1
2.46075	11.36	16.4	-6.04	1
2.46080	11.46	16.4	-5.94	1
2.46085	11.46	16.4	-5.94	1
2.46090	11.46	16.4	-5.94	1
2.46095	11.48	16.4	-5.92	1
2.46100	11.51	16.4	-5.89	1
2.46105	11.51	16.4	-5.89	1
2.46110	11.50	16.4	-5.90	1
2.46115	11.55	16.4	-5.85	1
2.46120	11.57	16.4	-5.83	1
2.46125	11.60	16.4	-5.80	1
2.46130	11.67	16.4	-5.73	1
2.46135	11.85	16.4	-5.55	1
2.46140	11.91	16.4	-5.49	1
2.46145	11.90	16.4	-5.50	1
2.46150	12.20	16.4	-5.20	1
2.46155	12.10	16.4	-5.30	1
2.46160	12.30	16.4	-5.10	1
2.46165	12.34	16.4	-5.06	1
2.46170	12.25	16.4	-5.15	1
2.46175	12.20	16.4	-5.20	1
2.46180	12.16	16.4	-5.24	1
2.46185	12.14	16.4	-5.26	1
2.46190	12.10	16.4	-5.30	1
2.46195	12.08	16.4	-5.32	1
2.46200	12.08	16.4	-5.32	1
2.46205	12.08	16.4	-5.32	1
2.46210	12.06	16.4	-5.34	1
2.46215	12.08	16.4	-5.32	1



11Mbps CHANNEL 11 Processing Gain				
Freq.	Gp	(S/N) °	Mj = J/S	Lsys
(GHz)	(dB)	(dB)	(dB)	(dB)
2.46220	12.29	16.4	-5.11	1
2.46225	12.33	16.4	-5.07	1
2.46230	12.43	16.4	-4.97	1
2.46235	12.43	16.4	-4.97	1
2.46240	12.44	16.4	-4.96	1
2.46245	12.40	16.4	-5.00	1
2.46250	12.12	16.4	-5.28	1
2.46255	11.80	16.4	-5.60	1
2.46260	11.87	16.4	-5.53	1
2.46265	11.70	16.4	-5.70	1
2.46270	11.78	16.4	-5.62	1
2.46275	11.70	16.4	-5.70	1
2.46280	11.68	16.4	-5.72	1
2.46285	11.68	16.4	-5.72	1
2.46290	11.68	16.4	-5.72	1
2.46295	11.68	16.4	-5.72	1
2.46300	11.69	16.4	-5.71	1
2.46305	11.69	16.4	-5.71	1
2.46310	11.69	16.4	-5.71	1
2.46315	11.68	16.4	-5.72	1
2.46320	11.66	16.4	-5.74	1
2.46325	11.40	16.4	-6.00	1
2.46330	11.35	16.4	-6.05	1
2.46335	11.30	16.4	-6.10	1
2.46340	11.27	16.4	-6.13	1
2.46345	11.15	16.4	-6.25	1
2.46350	11.08	16.4	-6.32	1
2.46355	11.10	16.4	-6.30	1
2.46360	11.11	16.4	-6.29	1
2.46365	11.11	16.4	-6.29	1
2.46370	11.12	16.4	-6.28	1
2.46375	11.15	16.4	-6.25	1
2.46380	11.18	16.4	-6.22	1
2.46385	11.20	16.4	-6.20	1



11Mbps CHANNEL 11 Processing Gain				
Freq. (GHz)	Gp (dB)	(S/N) • (dB)	Mj = J/S (dB)	Lsys (dB)
2.46390	11.22	16.4	-6.18	1
2.46395	11.20	16.4	-6.20	1
2.46400	11.19	16.4	-6.21	1
2.46405	11.15	16.4	-6.25	1
2.46410	11.11	16.4	-6.29	1
2.46415	11.08	16.4	-6.32	1
2.46420	11.04	16.4	-6.36	1
2.46425	10.80	16.4	-6.60	1
2.46430	10.97	16.4	-6.43	1
2.46435	10.95	16.4	-6.45	1
2.46440	10.91	16.4	-6.49	1
2.46445	10.80	16.4	-6.60	1
2.46450	10.87	16.4	-6.53	1
2.46455	10.87	16.4	-6.53	1
2.46460	10.87	16.4	-6.53	1
2.46465	10.90	16.4	-6.50	1
2.46470	10.90	16.4	-6.50	1
2.46475	10.95	16.4	-6.45	1
2.46480	10.99	16.4	-6.41	1
2.46485	11.10	16.4	-6.30	1
2.46490	11.12	16.4	-6.28	1
2.46495	11.20	16.4	-6.20	1
2.46500	11.25	16.4	-6.15	1
2.46505	11.30	16.4	-6.10	1
2.46510	11.32	16.4	-6.08	1
2.46515	11.31	16.4	-6.09	1
2.46520	11.31	16.4	-6.09	1
2.46525	11.30	16.4	-6.10	1
2.46530	11.46	16.4	-5.94	1
2.46535	11.50	16.4	-5.90	1
2.46540	11.54	16.4	-5.86	1
2.46545	11.68	16.4	-5.72	1
2.46550	11.69	16.4	-5.71	1



11Mbps CHANNEL 11 Processing Gain				
Freq. (GHz)	Gp (dB)	(S/N) ° (dB)	Mj = J/S (dB)	Lsys (dB)
2.46555	12.00	16.4	-5.40	1
2.46560	12.01	16.4	-5.39	1
2.46565	12.04	16.4	-5.36	1
2.46570	12.06	16.4	-5.34	1
2.46575	12.06	16.4	-5.34	1
2.46580	12.07	16.4	-5.33	1
2.46585	12.06	16.4	-5.34	1
2.46590	12.06	16.4	-5.34	1
2.46595	12.04	16.4	-5.36	1
2.46600	12.04	16.4	-5.36	1
2.46605	12.06	16.4	-5.34	1
2.46610	12.10	16.4	-5.30	1
2.46615	12.20	16.4	-5.20	1
2.46620	12.22	16.4	-5.18	1
2.46625	12.40	16.4	-5.00	1
2.46630	12.66	16.4	-4.74	1
2.46635	12.77	16.4	-4.63	1
2.46640	12.87	16.4	-4.53	1
2.46645	12.80	16.4	-4.60	1
2.46650	12.77	16.4	-4.63	1
2.46655	12.80	16.4	-4.60	1
2.46660	12.89	16.4	-4.51	1
2.46665	12.60	16.4	-4.80	1
2.46670	12.77	16.4	-4.63	1
2.46675	12.77	16.4	-4.63	1
2.46680	12.77	16.4	-4.63	1
2.46685	13.04	16.4	-4.36	1
2.46690	13.06	16.4	-4.34	1
2.46695	13.15	16.4	-4.25	1
2.46700	13.27	16.4	-4.13	1
Processing Gain : 11.65 dB				



5 INFORMATION ON THE TESTING LABORATORIES

We, ADT Corp., were founded in 1988 to provide our best service in EMC and Safety consultation. Our laboratories are accredited by the following approval agencies according to ISO/IEC Guide 25 or EN 45001:

USA	FCC, NVLAP
Germany	TUV Rheinland
Japan	VCCI
New Zealand	RFS
Norway	NEMKO, DNV
U.K.	INCHCAPE
R.O.C.	BSMI

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC Lab:
Tel: 886-2-26052180
Fax: 886-2-26052943

Hsin Chu EMC Lab:
Tel: 886-35-935343
Fax: 886-35-935342

Lin Kou Safety Lab:
Tel: 886-2-26093195
Fax: 886-2-26093184

Design Center:
Tel: 886-2-26093195
Fax: 886-2-26093184

Email: service@mail.adt.com.tw
Web Site: www.adt.com.tw