

# **Maximum Permissible Exposure Report**

Product	:	Server
Model Name	:	A5TS
FCC ID	:	HFS-A5TS
Test Regulation	:	47 CFR FCC Part 2.1091
<b>Received Date</b>	:	2021/7/8
Test Date	:	2021/7/7 ~ 2021/7/16
Issued Date	:	2021/9/29
Applicant	:	Quanta Computer Inc. No. 188, Wenhua 2nd Road, Guishan District, Taoyuan City 33377, Taiwan
Issued By	:	Underwriters Laboratories Taiwan Co., Ltd. Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.

Underwriters Laboratories Taiwan Co., Ltd. Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan Telephone :+886-2-7737-3000 Facsimile (FAX) :+886-3-583-7948 Doc No: 17-EM-F0864 / 5.0



## **REVISION HISTORY**

## Original Test Report No.: 4790036263-US-R1-V0

Rev.	Test report No. 4790036263-US-R1-V0	Date	Page revised	Contents
Original	4790036263-US-R1-V0	2021/9/29	-	Initial issue
0				



## **Table of Contents**

1.	Att	estation of Test Results	4
2.	Tes	st Methodology and Reference Procedures	5
3.	Fac	cilities and Accreditation	5
4.	Equ	uipment Under Test	6
		Description of EUT Description of Available Antennas	
5.	Rec	quirement	8
6.	Rac	dio Frequency Radiation Exposure Evaluation	9



#### 1. Attestation of Test Results

APPLICANT:	Quanta Computer Inc. No. 188, Wenhua 2nd Road, Guishan District, Taoyuan City 33377, Taiwan
MANUFACTURER:	Quanta Computer Inc. No. 188, Wenhua 2nd Road, Guishan District, Taoyuan City 33377, Taiwan
EUT DESCRIPTION:	Server
BRAND:	Quanta Computer Inc.
MODEL:	A5TS
SAMPLE STAGE:	Identical Prototype

APPLICABLE STANDARDS		
STANDARD	Test Results	
47 CFR FCC PART 2.1091	PASS	

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

**Note:** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:

ally In

Sally Lu Project Handler Date : 2021/9/29

Approved and Authorized By:

Mike

Mike Cai Date : 2021/9/29 Engineer Project Associate

Underwriters Laboratories Taiwan Co., Ltd.



## 2. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

#### **3.** Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.		
Address	ress Building B and Building E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan		
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.		



### 4. Equipment Under Test

#### 4.1. Description of EUT

Product Name	Server		
Brand Name	Quanta Computer Inc.		
Model Name	A5TS		
<b>Operating Frequency</b>	13.56 MHz		
Modulation	ASK		
Number of Channel	1		
Normal Voltage	240Vac		
Sample ID	4106585		
Software Version	N/A		

Note:

1. The EUT contains following accessory devices:

Product Brand		Model	Description	
K2 card	Annapurna	K2T-QB	-	
K2 card	Annapurna	K2X-N	-	

2. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual.



Test report No.	: 4790036263-US-R1-V0
Page	: 7 of 9
Issued date	: 2021/9/29
FCC ID	: HFS-A5TS

#### 4.2. Description of Available Antennas

Ant. No.	Transmitter Circuit	Brand Name	Model Name	Ant. Type	Maximum Gain (dBi)
1	Chain (0)	Smart Approach	SM-MFAD4-C02	FR4 Loop Coil	-

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual.



### 5. Requirement

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E 2,  H 2 or S (minutes)
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Power Density (S) is calculated by the following formula:

 $S = (P*G) / 4\pi R^2$ 

where: S = power density (in appropriate units, e.g. mW/ cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator R =distance to the center of radiation of the antenna (appropriate units, e.g., cm)



## 6. Radio Frequency Radiation Exposure Evaluation

Evaluation Frequency	Max. EIRP	Max. EIRP	Power density @ 20 cm	Limit
(MHz)	(dBm)	( <b>mW</b> )	(mW/cm <sup>2</sup> )	(mW/cm <sup>2</sup> )
13.56	-43.36	0.00005	0	0.98

Note:

- 1. Max. EIRP (dBm) = field strength of the emission (dB $\mu$ V/m) + 20log (measurement distance(m)) 104.7.
- 2. Max. EIRP (mW) =  $10^{(Max. EIRP (dBm) / 10)}$
- 3. Power density  $(mW/cm^2) = Max$ . EIRP  $(mW) / [4 \times \pi \times (calculated distance)^2]$ , the calculated distance is 20 cm.

#### **Conclusion:**

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

#### **END OF REPORT**