



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Notebook Computer

Model:

4067XXXX (X= 0~9, A~Z or blank), 4068XXXX (X= 0~9, A~Z or blank),
4187XXXX (X= 0~9, A~Z or blank), 4231XXXX (X= 0~9, A~Z or blank),
20013XXXX (X= 0~9, A~Z or blank), 20014XXXX (X= 0~9, A~Z or blank),
20015XXXX (X= 0~9, A~Z or blank)

Trade Name: Lenovo

Issued to

Quanta Computer Inc
No.188 Wen Hwa 2nd Rd., Kuei Shan Hsiang ,
Tao Yuan Shien 333, Taiwan

Issued by

Compliance Certification Services Inc.
No. 11, Wu-Gong 6th Rd., Wugu Industrial Park,
Taipei Hsien 248, Taiwan (R.O.C.)
<http://www.ccsemc.com.tw>
service@tw.ccsemc.com



Note: This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.



TABLE OF CONTENTS

- 1. TEST RESULT CERTIFICATION.....3**
- 2. EUT DESCRIPTION4**
- 3. TEST METHODOLOGY5**
 - 3.1 EUT CONFIGURATION5
 - 3.2 EUT EXERCISE.....5
 - 3.3 GENERAL TEST PROCEDURES.....5
 - 3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....6
 - 3.5 DESCRIPTION OF TEST MODES7
- 4. INSTRUMENT CALIBRATION.....8**
 - 4.1 MEASURING INSTRUMENT CALIBRATION.....8
 - 4.2 MEASUREMENT EQUIPMENT USED.....8
- 5. FACILITIES AND ACCREDITATIONS9**
 - 5.1 FACILITIES9
 - 5.2 EQUIPMENT.....9
 - 5.3 TABLE OF ACCREDITATIONS AND LISTINGS.....10
- 6. SETUP OF EQUIPMENT UNDER TEST11**
 - 6.1 SETUP CONFIGURATION OF EUT.....11
 - 6.2 SUPPORT EQUIPMENT.....11
- 7. FCC PART 15.247 REQUIREMENTS.....12**
 - 7.1 6DB BANDWIDTH.....12
 - 7.2 PEAK POWER.....17
 - 7.3 AVERAGE POWER.....21
 - 7.4 BAND EDGES MEASUREMENT.....25
 - 7.5 PEAK POWER SPECTRAL DENSITY.....34
 - 7.6 SPURIOUS EMISSIONS39
 - 7.7 POWERLINE CONDUCTED EMISSIONS.....53
- APPENDIX I RADIO FREQUENCY EXPOSURE56**
- APPENDIX II PHOTOGRAPHS OF TEST SETUP57**



1. TEST RESULT CERTIFICATION

Applicant: Quanta Computer Inc
No.188 Wen Hwa 2nd Rd., Kuei Shan Hsiang ,
Tao Yuan Shien 333, Taiwan

Equipment Under Test: Notebook Computer

Trade Name: Lenovo

Model: 4067XXXX (X= 0~9, A~Z or blank),
4068XXXX (X= 0~9, A~Z or blank),
4187XXXX (X= 0~9, A~Z or blank),
4231XXXX (X= 0~9, A~Z or blank),
20013XXXX (X= 0~9, A~Z or blank),
20014XXXX (X= 0~9, A~Z or blank),
20015XXXX (X= 0~9, A~Z or blank)

Date of Test: July 13 ~ 15, 2008

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted
Deviation from Applicable Standard	
None	

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in **ANSI C63.4: 2003** and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Rex Lai
Section Manager
Compliance Certification Services Inc.

Amanda Wu
Section Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	Notebook Computer
Trade Name	Lenovo
Model Number	4067XXXX (X= 0~9, A~Z or blank), 4068XXXX (X= 0~9, A~Z or blank), 4187XXXX (X= 0~9, A~Z or blank), 4231XXXX (X= 0~9, A~Z or blank), 20013XXXX (X= 0~9, A~Z or blank), 20014XXXX (X= 0~9, A~Z or blank), 20015XXXX (X= 0~9, A~Z or blank)
Model Discrepancy	The suffix of 4067XXXX (X= 0~9, A~Z or blank), 4068XXXX (X= 0~9, A~Z or blank), 4187XXXX (X= 0~9, A~Z or blank), 4231XXXX (X= 0~9, A~Z or blank), 20013XXXX (X= 0~9, A~Z or blank), 20014XXXX (X= 0~9, A~Z or blank), 20015XXXX (X= 0~9, A~Z or blank) on model number is just for marketing purpose only.
Power Supply	<ol style="list-style-type: none"> 1. Power Adapter: Model: 0225A2040 I/P: AC 100-240V, 50-60Hz, 1.7A O/P: DC 20V, 2.0A 2. Power Adapter: Model: PA-1650-02 I/P: AC 100-240V, 50-60Hz, 1.6A O/P: DC 19V, 3.42A 3. Power Adapter: Model: SADP-65KB D I/P: AC 100-240V, 50-60Hz O/P: DC 19V, 3.42A 4. Rechargeable Lithium Battery: Model: L08C6C21 Rating: 11.1VDC, 53Wh 5. Rechargeable Lithium Battery: Model: L08S3B21 Rating: 11.1VDC, 2.5Ah, 28Wh
Frequency Range	2412 ~ 2462 MHz
Transmit Power	IEEE 802.11b: 19.56 dBm IEEE 802.11g: 18.65 dBm
Modulation Technique	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: DSSS (CCK, DQPSK, DBPSK) + OFDM (QPSK, BPSK, 16-QAM, 64-QAM)
Transmit Data Rate	IEEE 802.11b Mode: 11, 5.5, 2, 1 Mbps IEEE 802.11g Mode: 54, 48, 36, 24, 18, 12, 11, 9, 6, 5.5, 2, 1Mbps
Number of Channels	11 Channels
Antenna Specification	Gain: 2.7 dBi
Antenna Designation	PIFA Antenna

Remark:

1. The sample selected for test was production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **HFS-FL** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4 and FCC CFR 47 2.1046, 2.1047, 2.1049, 2.1051, 2.1053, 2.1055, 2.1057, 15.207, 15.209 and 15.247.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: 4067XXXX (X= 0~9, A~Z or blank)) comes with three different adapters (0225A2040, PA-1650-02, SADP-65KB D) for sale. After the preliminary test, the adapter with model PA-1650-02 was found to emit the worst emissions and therefore had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

IEEE 802.11b mode:

Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 11Mbps data rate were chosen for the final testing.

IEEE 802.11g mode:

Channel 1(2412MHz), Channel 6(2437MHz) and Channel 11(2462MHz) with 54Mbps data rate were chosen for the final testing.



4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	MY43360131	02/24/2009

3M Semi Anechoic Chamber				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	09/10/2009
Test Receiver	Rohde&Schwarz	ESCI	100064	11/30/2009
Switch Controller	TRC	Switch Controller	SC94050010	05/03/2009
4 Port Switch	TRC	4 Port Switch	SC94050020	05/03/2009
Horn-Antenna	TRC	HA-0502	06	06/04/2009
Horn-Antenna	TRC	HA-0801	04	06/18/2009
Horn-Antenna	TRC	HA-1201A	01	08/11/2008
Horn-Antenna	TRC	HA-1301A	01	08/11/2009
Bilog- Antenna	Sunol Sciences	JB3	A030205	03/28/2009
Turn Table	Max-Full	MFT-120S	T120S940302	N.C.R.
Antenna Tower	Max-Full	MFA-430	A440940302	N.C.R.
Controller	Max-Full	MF-CM886	CC-C-1F-13	N.C.R.
Site NSA	CCS	N/A	FCC: 965860 IC: IC 6106	09/25/2008
Test S/W	LABVIEW (V 6.1)			

Remark: The measurement uncertainty is less than +/-3.7046dB (30MHz ~ 1GHz), +/-3.0958dB (Above 1GHz) which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.

Powerline Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI TEST RECEIVER 9kHz-30MHz	ROHDE & SCHWARZ	ESHS30	828144/003	11/18/2009
TWO-LINE V-NETWORK 9kHz-30MHz	SCHAFFNER	NNB41	03/10013	06/11/2009
LISN 10kHz-100MHz	EMCO	3825/2	9106-1809	04/09/2009
Test S/W	LABVIEW (V 6.1)			

Remark: The measurement uncertainty is less than +/- 2.81dB, which is evaluated as per the NAMAS NIS 81 and CISPR/A/291/CDV.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

No.11, Wugong 6th Rd., Wugu Industrial Park, Taipei Hsien 248, Taiwan

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT





Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."

5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	A2LA	EN 55011, EN 55014-1/2, CISPR 11, CISPR 14-1/2, EN 55022, EN 55015, CISPR 22, CISPR 15, AS/NZS 3548, VCCI V3 (2001), CFR 47, FCC Part 15/18, CNS 13783-1, CNS 13439, CNS 13438, CNS 13803, CNS 14115, EN 55024, IEC 801-2, IEC 801-3, IEC 801-4, IEC/EN 61000-3-2, EIC/EN 61000-3-3, IEC/EN 61000-4-2/3/4/5/6/8/11, EN 50081-1/ EN 61000-6-3, EN 50081-2/EN 61000-6-4, EN 50081-2/EN 61000-6-1: 2001	
USA	FCC	3M Semi Anechoic Chamber (965860 and 898658) to perform FCC Part 15/18 measurements	
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12.2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 6106 & IC 6106A-2) to perform RSS 212 Issue 1	

** No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.*



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	LCD Monitor	Samsung	173P	DII7H4JXB04968Y	FCC DoC	Shielded, 1.8m with 2 cores	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core
2.	USB Mouse	HP	MO19UCA	20440964	FCC DoC	Shielded, 1.8m	N/A
3.	USB 2.0 & 1394 External HDD	TeraSyS	F12-UF(COMBO)	A0100215-420014	FCC DoC	Shielded, 1.8m	N/A
4.	Multimedia Earphone	Labtec	Axis-301	N/A	FCC DoC	Unshielded, 1.8m*2	N/A

Remark:

1. *All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
2. *Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*




7. FCC PART 15.247 REQUIREMENTS

7.1 6DB BANDWIDTH

LIMIT

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW = 100kHz, VBW = RBW, Span = 50MHz, Sweep = auto.
4. Mark the peak frequency and -6dB (upper and lower) frequency.
5. Repeat until all the rest channels are investigated.

TEST RESULTS

No non-compliance noted.



Test mode: IEEE 802.11b

Channel	Frequency (MHz)	6Db Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	10.00	>500	PASS
Mid	2437	10.00		PASS
High	2462	9.33		PASS

Test mode: IEEE 802.11g


Channel	Frequency (MHz)	6Db Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.33	>500	PASS
Mid	2437	16.33		PASS
High	2462	16.17		PASS




Test Plot

IEEE 802.11b

6dB Bandwidth (CH Low)



6dB Bandwidth (CH Mid)





6dB Bandwidth (CH High)

Agilent 18:15:29 Jul 13, 2008

R T


6dB BW, g Mode High Ch.

Δ Mkr1 9.33 MHz

Ref 20 dBm

Atten 20 dB

0.88 dB



Center 2.462 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)

IEEE 802.11g

6dB Bandwidth (CH Low)

Agilent 17:37:32 Jul 13, 2008

R T


6dB BW, g Mode Low Ch.

Δ Mkr1 16.33 MHz

Ref 20 dBm

Atten 20 dB

-0.45 dB



Center 2.412 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)



6dB Bandwidth (CH Mid)

Agilent 17:31:14 Jul 13, 2008

R T


6dB BW, g Mode Mid Ch.

Δ Mkr1 16.33 MHz

Ref 20 dBm

Atten 20 dB

-1.47 dB



Center 2.437 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)

6dB Bandwidth (CH High)

Agilent 17:46:44 Jul 13, 2008

R T


6dB BW, g Mode High Ch.

Δ Mkr1 16.17 MHz

Ref 20 dBm

Atten 20 dB

0.89 dB



Center 2.462 00 GHz

Span 50 MHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 6.04 ms (601 pts)




7.2 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

1. Peak power is measured using the spectrum analyzer's internal channel power integration function.
2. Power is integrated over a bandwidth greater than or equal to the 99% bandwidth.

TEST RESULTS

No non-compliance noted.

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	19.44	0.0879	1.00	PASS
Mid	2437	19.56	0.0904		PASS
High	2462	19.54	0.0899		PASS

Test mode: IEEE 802.11g

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	18.15	0.0653	1.00	PASS
Mid	2437	18.06	0.0640		PASS
High	2462	18.65	0.0733		PASS



Test Plot

IEEE 802.11b

Peak Power (CH Low)


Agilent 14:39:58 Jul 15, 2008

R T

Peak Output Power , b Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Center 2.412 00 GHz

Span 16.81 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

19.44 dBm / 11.2040 MHz

-49.76 dBm/Hz

Peak Power (CH Mid)


Agilent 14:47:04 Jul 15, 2008

R T

Peak Output Power , b Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Center 2.437 00 GHz

Span 17.01 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

19.56 dBm / 11.3430 MHz

-50.49 dBm/Hz



Peak Power (CH High)


Agilent 14:52:07 Jul 15, 2008

R T

Peak Output Power , b Mode High Ch.

Ref 20 dBm

Atten 20 dB



Channel Power

19.54 dBm / 11.2445 MHz

Power Spectral Density

-49.57 dBm/Hz

IEEE 802.11g

Peak Power (CH Low)


Agilent 17:38:19 Jul 13, 2008

R T

Peak Output Power , g Mode Low Ch.

Ref 20 dBm

Atten 20 dB



Channel Power

18.15 dBm / 16.2720 MHz

Power Spectral Density

-53.97 dBm/Hz



Peak Power (CH Mid)


Agilent 19:55:19 Jul 15, 2008

R T

Peak Output Power , g Mode Mid Ch.

Ref 20 dBm

Atten 20 dB



Center 2.437 00 GHz

Span 24.43 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

18.06 dBm / 16.2900 MHz

-54.06 dBm/Hz

Peak Power (CH High)


Agilent 17:47:31 Jul 13, 2008

R T

Peak Output Power , g Mode High Ch.

Ref 20 dBm

Atten 20 dB



Center 2.462 00 GHz

Span 24.43 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

18.65 dBm / 16.2860 MHz

-53.47 dBm/Hz




7.3 AVERAGE POWER

LIMIT

None; for reporting purposes only.

Test Configuration



TEST PROCEDURE

1. Average power is measured using the spectrum analyzer's internal channel power integration function.
2. Power is integrated over a bandwidth greater than or equal to the 99% bandwidth.

TEST RESULTS

No non-compliance noted.

Test Data

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Output Power (dBm)
Low	2412	18.28
Mid	2437	18.04
High	2462	18.40

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Output Power (dBm)
Low	2412	15.04
Mid	2437	15.19
High	2462	15.12




Test Plot

IEEE 802.11b

Average Power (CH Low)

Agilent 14:56:08 Jul 15, 2008
AVG Output Power , b Mode Low Ch.

R T



Channel Power

Power Spectral Density


18.28 dBm / 11.2040 MHz

-52.21 dBm/Hz

Average Power (CH Mid)

Agilent 14:48:48 Jul 15, 2008

R T



Channel Power

Power Spectral Density

18.04 dBm / 11.3430 MHz

-52.50 dBm/Hz



Average Power (CH High)


Agilent 14:54:04 Jul 15, 2008

R T

AVG Output Power , b Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 2.462 00 GHz

Span 16.87 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

18.40 dBm / 11.2445 MHz

-52.11 dBm/Hz

IEEE 802.11g

Average Power (CH Low)


Agilent 17:39:21 Jul 13, 2008

R T

AVG Output Power , g Mode Low Ch.

Ref 30 dBm

Atten 30 dB



Center 2.412 00 GHz

Span 24.41 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

15.04 dBm / 16.2720 MHz

-57.07 dBm/Hz



Average Power (CH Mid)


Agilent 17:32:55 Jul 13, 2008

R T

AVG Output Power , g Mode Mid Ch.

Ref 30 dBm

Atten 30 dB



Center 2.437 00 GHz

Span 24.43 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

15.19 dBm / 16.2900 MHz

-56.93 dBm/Hz

Average Power (CH High)


Agilent 17:48:34 Jul 13, 2008

R T

AVG Output Power , g Mode High Ch.

Ref 30 dBm

Atten 30 dB



Center 2.462 00 GHz

Span 24.43 MHz

#Res BW 1 MHz

#VBW 3 MHz

Sweep 1 ms (601 pts)

Channel Power

Power Spectral Density

15.12 dBm / 16.2860 MHz


-57.00 dBm/Hz

7.4 BAND EDGES MEASUREMENT

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

TEST RESULTS

Refer to attach spectrum analyzer data chart.




Band Edges (IEEE 802.11b / CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent

R T




Detector mode: Average

Polarity: Vertical

Agilent

R T





Detector mode: Peak

Polarity: Horizontal


Agilent

R T

Mkr1 2.390 0 GHz
64.98 dBμV

Ref 123 dBμV

#Atten 16 dB



Start 2.310 0 GHz

Stop 2.420 0 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Horizontal


Agilent

R T

Mkr1 2.390 0 GHz
49.98 dBμV

Ref 123 dBμV

#Atten 16 dB



Start 2.310 0 GHz

Stop 2.420 0 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 8.577 s (601 pts)



Band Edges (IEEE 802.11b / CH High)

Detector mode: Peak

Polarity: Vertical


Agilent

R T

Mkr1 2.483 50 GHz
60.96 dBμV

Ref 123 dBμV

#Atten 16 dB



Start 2.460 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 1 MHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Vertical

Agilent

R T

Mkr1 2.483 50 GHz
46.62 dBμV

Ref 123 dBμV

#Atten 16 dB



Start 2.460 00 GHz

Stop 2.500 00 GHz

#Res BW 1 MHz

#VBW 10 Hz

Sweep 11.03 s (601 pts)




Detector mode: Peak

Polarity: Horizontal

Agilent

R T

Mkr1 2.483 50 GHz
60.32 dBμV




Detector mode: Average

Polarity: Horizontal

Agilent

R T

Mkr1 2.483 50 GHz
47.28 dBμV






Band Edges (IEEE 802.11g / CH Low)

Detector mode: Peak

Polarity: Vertical

Agilent

R T




Detector mode: Average

Polarity: Vertical

Agilent

R T





Detector mode: Peak

Polarity: Horizontal


Agilent

R T

Mkr1 2.390 0 GHz
69.62 dBμV

Ref 123 dBμV

#Atten 16 dB



Start 2.310 0 GHz

Res BW 1 MHz

#VBW 1 MHz

Stop 2.420 0 GHz

#Sweep 100 ms (601 pts)

Detector mode: Average

Polarity: Horizontal


Agilent

R T

Mkr1 2.390 0 GHz
48.32 dBμV

Ref 123 dBμV

#Atten 16 dB



Start 2.310 0 GHz

Res BW 1 MHz

#VBW 10 Hz

Stop 2.420 0 GHz

Sweep 8.577 s (601 pts)



Band Edges (IEEE 802.11g / CH High)


Detector mode: Peak

Polarity: Vertical

Agilent

R T

Mkr1 2.483 50 GHz
64.72 dB μ V




Detector mode: Average

Polarity: Vertical

Agilent

R T

Mkr1 2.483 50 GHz
46.50 dB μ V






Detector mode: Peak

Polarity: Horizontal

Agilent

R T

Mkr1 2.483 50 GHz
67.35 dBμV




Detector mode: Average

Polarity: Horizontal

Agilent

R T

Mkr1 2.483 50 GHz
47.15 dBμV




7.5 PEAK POWER SPECTRAL DENSITY

LIMIT

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

1. Place the EUT on the table and set it in transmitting mode.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
2. Set the spectrum analyzer as RBW = 3kHz, VBW = 10kHz, Span = 300kHz, Sweep=100s
3. Record the max. reading.
4. Repeat the above procedure until the measurements for all frequencies are completed.

TEST RESULTS

No non-compliance noted.



Test Data

Test mode: IEEE 802.11b

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-4.89	8.00	PASS
Mid	2437	-4.78		PASS
High	2462	-4.82		PASS

Test mode: IEEE 802.11g


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-9.93	8.00	PASS
Mid	2437	-11.26		PASS
High	2462	-9.61		PASS




Test Plot

IEEE 802.11b

PPSD (CH Low)



PPSD (CH Mid)





PPSD (CH High)

Agilent 18:19:39 Jul 13, 2008

R T

Peak Power Spectral Density, g Mode High Ch.

Mkr1 2.459 206 4 GHz

Ref 20 dBm

Atten 20 dB

-4.82 dBm



Center 2.459 250 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)

IEEE 802.11g

PPSD (CH Low)

Agilent 17:41:59 Jul 13, 2008

R T


Peak Power Spectral Density, g Mode Low Ch.

Mkr1 2.412 640 5 GHz

Ref 20 dBm

Atten 20 dB

-9.93 dBm



Center 2.412 650 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)



PPSD (CH Mid)

Agilent 17:35:09 Jul 13, 2008

R T

Peak Power Spectral Density, g Mode Mid Ch.

Mkr1 2.435 735 4 GHz

Ref 20 dBm

Atten 20 dB

-11.26 dBm

#Peak

Log

10

dB/

Offst

11.5

dB

DI

8.0

dBm

LgAv


W1 S2

S3 FS

□(f):

f>50k

Swp



Center 2.435 750 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)

PPSD (CH High)

Agilent 17:51:51 Jul 13, 2008

R T

Peak Power Spectral Density, g Mode High Ch.

Mkr1 2.462 890 5 GHz

Ref 20 dBm

Atten 20 dB

-9.61 dBm

#Peak

Log

10

dB/

Offst

11.5

dB

DI

8.0

dBm

LgAv


W1 S2

S3 FS

□(f):

f>50k

Swp



Center 2.462 900 0 GHz

Span 300 kHz

#Res BW 3 kHz

#VBW 10 kHz

#Sweep 100 s (601 pts)




7.6 SPURIOUS EMISSIONS

7.6.1 Conducted Measurement

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS

No non-compliance noted.




Test Plot

IEEE 802.11b

CH Low

Agilent 18:06:05 Jul 13, 2008


R T



CH Mid

Agilent 18:12:04 Jul 13, 2008

R T






CH High

Agilent 18:20:40 Jul 13, 2008

R T

Mkr1 2.47 GHz
5.84 dBm



Center 13.02 GHz Span 25.97 GHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.131 s (1001 pts)


IEEE 802.11g

CH Low

Agilent 17:43:33 Jul 13, 2008

R T

Mkr1 2.42 GHz
-0.01 dBm



Center 13.02 GHz Span 25.97 GHz
#Res BW 100 kHz #VBW 100 kHz Sweep 3.131 s (1001 pts)



CH Mid

Agilent 17:36:00 Jul 13, 2008

R T


Spurious, g Mode Mid Ch.

Mkr1 2.45 GHz

Ref 20 dBm

Atten 20 dB

0.65 dBm



Center 13.02 GHz

Span 25.97 GHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 3.131 s (1001 pts)

CH High

Agilent 17:53:08 Jul 13, 2008

R T


Spurious, g Mode High Ch.

Mkr1 2.47 GHz

Ref 20 dBm

Atten 20 dB

0.47 dBm



Center 13.02 GHz

Span 25.97 GHz

#Res BW 100 kHz

#VBW 100 kHz

Sweep 3.131 s (1001 pts)



7.6.2 Radiated Emissions

LIMIT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V/m}$)	Measurement Distance (m)
30-88	100*	3
88-216	150*	3
216-960	200*	3
Above 960	500	3


Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

2. In the emission table above, the tighter limit applies at the band edges.


Frequency (MHz)	Field Strength ($\mu\text{V/m}$ at 3-meter)	Field Strength (dB $\mu\text{V/m}$ at 3-meter)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

Test Configuration

Below 1 GHz



Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK: RBW=VBW=1MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

TEST RESULTS

No non-compliance noted.

**Below 1 GHz****Operation Mode:** Normal Link**Test Date:** July 13, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
38.08	V	41.60	-7.17	34.43	40.00	-5.57	QP
84.97	V	51.19	-15.21	35.97	40.00	-4.03	Peak
110.83	V	46.07	-10.15	35.92	43.50	-7.58	Peak
143.17	V	47.08	-8.21	38.86	43.50	-4.64	Peak
455.18	V	40.44	-2.41	38.03	46.00	-7.97	Peak
595.83	V	33.96	1.06	35.03	46.00	-10.97	Peak
72.03	H	48.30	-14.70	33.60	40.00	-6.40	QP
110.83	H	44.74	-10.15	34.59	43.50	-8.91	Peak
149.63	H	44.10	-8.59	35.51	43.50	-7.99	Peak
207.83	H	43.97	-7.95	36.02	43.50	-7.48	Peak
240.17	H	47.79	-8.09	39.70	46.00	-6.30	Peak
319.38	H	42.55	-6.05	36.50	46.00	-9.50	Peak

Remark:

1. Measuring frequencies from 30 MHz to the 1GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. Margin (dB) = Remark result (dBuV/m) – Quasi-peak limit (dBuV/m).



Above 1 GHz

Operation Mode: IEEE 802.11b / TX / CH Low

Test Date: July 13, 2008

Temperature: 25°C

Tested by: Jerry Lin

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
2250.00	V	63.14	53.67	-3.40	59.74	50.27	74.00	54.00	-3.73	AVG
2496.67	V	65.76	48.30	-2.64	63.12	45.66	74.00	54.00	-8.34	AVG
4825.00	V	53.85	49.02	0.35	54.20	49.37	74.00	54.00	-4.63	AVG
5716.67	V	50.90	---	0.72	51.63	---	74.00	54.00	-2.37	Peak
N/A										
2250.00	H	66.44	53.69	-3.40	63.04	50.29	74.00	54.00	-3.71	AVG
2496.67	H	65.73	47.98	-2.64	63.09	45.34	74.00	54.00	-8.66	AVG
4825.00	H	49.61	---	0.35	49.96	---	74.00	54.00	-4.04	Peak
7208.33	H	49.76	---	2.97	52.73	---	74.00	54.00	-1.27	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: IEEE 802.11b / TX / CH Mid

Test Date: July 13, 2008

Temperature: 25°C

Tested by: Jerry Lin

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
2273.33	V	65.11	54.11	-3.33	61.78	50.78	74.00	54.00	-3.22	AVG
2496.67	V	65.94	47.90	-2.64	63.30	45.26	74.00	54.00	-8.74	AVG
4875.00	V	53.78	48.98	0.24	54.01	49.22	74.00	54.00	-4.78	AVG
7308.33	V	50.52	---	2.95	53.47	---	74.00	54.00	-0.53	Peak
N/A										
2273.33	H	67.80	53.50	-3.33	64.46	50.17	74.00	54.00	-3.83	AVG
2493.33	H	65.97	48.20	-2.65	63.32	45.55	74.00	54.00	-8.45	AVG
4875.00	H	50.84	---	0.24	51.08	---	74.00	54.00	-2.92	Peak
7175.00	H	50.21	---	2.98	53.19	---	74.00	54.00	-0.81	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: IEEE 802.11b / TX / CH High

Test Date: July 13, 2008

Temperature: 25°C

Tested by: Jerry Lin

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
2280.00	V	65.30	52.10	-3.31	61.99	48.79	74.00	54.00	-5.21	AVG
2496.67	V	66.11	48.34	-2.64	63.47	45.70	74.00	54.00	-8.30	AVG
4925.00	V	55.68	52.88	0.13	55.81	53.01	74.00	54.00	-0.99	AVG
5708.33	V	51.22	---	0.71	51.93	---	74.00	54.00	-2.07	Peak
N/A										
2283.33	H	68.07	54.21	-3.30	64.77	50.91	74.00	54.00	-3.09	AVG
2496.67	H	67.66	48.55	-2.64	65.02	45.91	74.00	54.00	-8.09	AVG
3283.33	H	52.38	---	-0.78	51.60	---	74.00	54.00	-2.40	Peak
4925.00	H	53.78	---	0.13	53.91	---	74.00	54.00	-0.09	Peak
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: IEEE 802.11g / TX / CH Low

Test Date: July 13, 2008

Temperature: 25°C

Tested by: Jerry Lin

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
1063.33	V	66.71	47.54	-9.39	57.32	38.15	74.00	54.00	-15.85	AVG
2236.67	V	63.14	53.10	-3.44	59.69	49.66	74.00	54.00	-4.34	AVG
2496.67	V	65.75	47.52	-2.64	63.11	44.88	74.00	54.00	-9.12	AVG
4650.00	V	50.34	---	0.74	51.07	---	74.00	54.00	-2.93	Peak
4983.33	V	50.61	---	-0.00	50.61	---	74.00	54.00	-3.39	Peak
7241.67	V	51.57	39.63	2.96	54.53	42.59	74.00	54.00	-11.41	AVG
2256.67	H	66.21	53.10	-3.38	62.83	49.72	74.00	54.00	-4.28	AVG
2490.00	H	68.15	47.52	-2.66	65.49	44.86	74.00	54.00	-9.14	AVG
3216.67	H	52.48	---	-0.91	51.57	---	74.00	54.00	-2.43	Peak
7233.33	H	51.53	38.60	2.96	54.50	41.56	74.00	54.00	-12.44	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** IEEE 802.11g / TX / CH Mid**Test Date:** July 13, 2008**Temperature:** 25°C**Tested by:** Jerry Lin**Humidity:** 50 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
2273.33	V	64.15	54.30	-3.33	60.81	50.97	74.00	54.00	-3.03	AVG
2490.00	V	65.15	46.87	-2.66	62.49	44.21	74.00	54.00	-9.79	AVG
4875.00	V	50.75	---	0.24	50.98	---	74.00	54.00	-3.02	Peak
7308.33	V	53.29	37.69	2.95	56.23	40.64	74.00	54.00	-13.36	AVG
N/A										
2266.67	H	67.41	53.63	-3.35	64.06	50.28	74.00	54.00	-3.72	AVG
2493.33	H	67.84	45.85	-2.65	65.19	43.20	74.00	54.00	-10.80	AVG
3250.00	H	51.32	---	-0.85	50.48	---	74.00	54.00	-3.52	Peak
4891.67	H	49.65	---	0.20	49.85	---	74.00	54.00	-4.15	Peak
7316.67	H	53.46	38.36	2.95	56.40	41.31	74.00	54.00	-12.69	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



Operation Mode: IEEE 802.11g / TX / CH High

Test Date: July 13, 2008

Temperature: 25°C

Tested by: Jerry Lin

Humidity: 50 % RH

Polarity: Ver. / Hor.

Frequency (MHz)	Ant.Pol. (H/V)	Reading (Peak) (dBuV)	Reading (Average) (dBuV)	Correction Factor (dB/m)	Result (Peak) (dBuV/m)	Result (Average) (dBuV/m)	Limit (Peak) (dBuV/m)	Limit (Average) (dBuV/m)	Margin (dB)	Remark
2266.67	V	65.76	51.90	-3.35	62.40	48.55	74.00	54.00	-5.45	AVG
4916.67	V	51.51	---	0.15	51.66	---	74.00	54.00	-2.34	Peak
7383.33	V	50.25	---	2.93	53.19	---	74.00	54.00	-0.81	Peak
N/A										
2300.00	H	69.18	52.55	-3.25	65.93	49.30	74.00	54.00	-4.70	AVG
3283.33	H	53.05	---	-0.78	52.27	---	74.00	54.00	-1.73	Peak
4108.33	H	51.00	---	0.85	51.85	---	74.00	54.00	-2.15	Peak
4916.67	H	51.17	---	0.15	51.31	---	74.00	54.00	-2.69	Peak
7383.33	H	53.15	40.23	2.93	56.08	43.16	74.00	54.00	-10.84	AVG
N/A										

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Margin (dB) = Remark result (dBuV/m) – Average limit (dBuV/m).



7.7 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μH/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dBμV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

Test Configuration

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: Normal Link **Test Date:** July 13, 2008
Temperature: 22°C **Tested by:** Eddy Cheng
Humidity: 45% RH

Frequency (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB)	QP Result (dBuV)	AV Result (dBuV)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.1800	50.82	38.42	0.18	51.00	38.60	64.49	54.49	-13.49	-15.89	L1
0.2450	43.56	29.66	0.14	43.70	29.80	61.92	51.92	-18.22	-22.12	L1
0.2950	36.28	18.98	0.12	36.40	19.10	60.38	50.38	-23.98	-31.28	L1
4.4850	26.40	11.50	0.20	26.60	11.70	56.00	46.00	-29.40	-34.30	L1
15.9500	24.05	16.05	0.65	24.70	16.70	60.00	50.00	-35.30	-33.30	L1
19.1350	29.70	21.90	0.70	30.40	22.60	60.00	50.00	-29.60	-27.40	L1
0.1850	47.93	35.63	0.17	48.10	35.80	64.26	54.26	-16.16	-18.46	L2
0.2450	39.36	28.16	0.14	39.50	28.30	61.92	51.92	-22.42	-23.62	L2
0.3003	34.68	22.28	0.12	34.80	22.40	60.23	50.23	-25.43	-27.83	L2
0.3650	32.41	21.31	0.09	32.50	21.40	58.61	48.61	-26.11	-27.21	L2
4.5250	30.20	13.40	0.20	30.40	13.60	56.00	46.00	-25.60	-32.40	L2
10.5100	31.82	21.42	0.58	32.40	22.00	60.00	50.00	-27.60	-28.00	L2


Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz to 30MHz was 10kHz; the IF bandwidth of Test Receiver between 0.15MHz to 30MHz was 9kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)




Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)





APPENDIX I RADIO FREQUENCY EXPOSURE

LIMIT

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the Commission's guidelines. See §15.247(i) and §1.1307(b)(1) of this chapter.

EUT Specification

EUT	Notebook Computer
Frequency band (Operating)	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Bluetooth: <u>2.402GHz ~ 2.480 GHz</u>
Device category	<input checked="" type="checkbox"/> Portable (<20cm separation) <input type="checkbox"/> Mobile (>20cm separation)
Exposure classification	<input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²)
Antenna diversity	<input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input checked="" type="checkbox"/> Tx/Rx diversity
Max. output power	IEEE 802.11b: 19.56 dBm (90.36mW) IEEE 802.11g: 18.65 dBm (73.28mW)
Antenna gain (Max)	2.7 dBi (Numeric gain: 1.86)
Evaluation applied	<input type="checkbox"/> MPE Evaluation <input checked="" type="checkbox"/> SAR Evaluation* <input type="checkbox"/> N/A

Remark:

1. The maximum output power is 19.56dBm (90.36mW) at 2437MHz (with 1.86 numeric antenna gain.)
2. DTS device is not subject to routine RF evaluation; MPE estimate is used to justify the compliance.
3. For mobile or fixed location transmitters, no SAR consideration applied. The maximum power density is 1.0 mW/cm² even if the calculation indicates that the power density would be larger.

TEST RESULTS

No non-compliance noted.

Remark: Please refer to the separated SAR report.