


RF EXPOSURE EVALUATION REPORT

FCC ID : HFS-IRONRAN-RU5PI
Equipment : Remote Radio Unit
Brand Name : Quanta Computer Inc.
Model Name : IronRAN-RU5 PI GenA
Applicant : Quanta Computer Inc.
188, WEN HUA 2ND RD., GUISHAN
DIST., TAO YUAN CITY 33377, TAIWAN
Manufacturer : Quanta Computer Inc.
188, WEN HUA 2ND RD., GUISHAN
DIST., TAO YUAN CITY 33377, TAIWAN
Standard : 47 CFR Part 2.1091

We, SPORTON INTERNATIONAL INC has been evaluated this product in accordance with 47 CFR Part2.1091 and it complies with applicable limit.

Sporton Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190) and the FCC designation No. TW1190 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC evaluation.

The results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Laboratory, the test report shall not be reproduced except in full



Approved by: Cona Huang / Deputy Manager



SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

1. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	4
2. MAXIMUM RF AVERAGE OUTPUT POWER AMONG PRODUCTION UNITS	4
3. RF EXPOSURE LIMIT INTRODUCTION	5
4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	5
4.1. RF Exposure evaluation	5



1. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Remote Radio Unit
Brand Name	Quanta Computer Inc.
Model Name	IronRAN-RU5 PI GenA
FCC ID	HFS-IRONRAN-RU5PI
Wireless Technology and Frequency Range	5G NR n48/n77/n78 : 3550 MHz ~ 3700 MHz
Mode	5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

Reviewed by: Jason Wang

Report Producer: Carlie Tsai

2. Maximum RF average output power among production units

Radio Tech	Band Number	Maximum Transmit Power Level (dBm)	
		Per antenna	Total
FR1	n48	18.00	24.00
FR1	n77	18.00	24.00
FR1	n78	18.00	24.00

3. RF Exposure Limit Introduction

According to Part1.1307b, Or the available maximum time-averaged power or effective radiated power (ERP), whichever is greater, is less than or equal to the threshold Pth (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 centimeters to 40 centimeters and at frequencies from 0.3 GHz to 6 GHz (inclusive). Pth is given by:

$$P_{th} \text{ (mW)} = ERP_{20cm} (d / 20)^x \text{ for distance } d \leq 20cm$$

$$P_{th} \text{ (mW)} = ERP_{20cm} \text{ for distance } 20cm < d \leq 40cm$$

$$x = -\log_{10} \left(\frac{60}{ERP_{20cm} \sqrt{f}} \right)$$

$$ERP_{20cm} \text{ (mW)} \begin{array}{ll} 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz:} & 2040 f \\ 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz:} & 3060 \end{array}$$

4. Radio Frequency Radiation Exposure Evaluation

4.1. RF Exposure evaluation

Band	Antenna Gain (dBi)	Maximum Conducted Power (dBm)	Maximum EIRP (dBm)	Maximum ERP (dBm)	Maximum EIRP (mW)	Maximum ERP (mW)	P _{th}	P _{th} (mW)	Part1.1307 option(b) Threshold (mW)
5G NR n48	7.00	24.00	31.0	28.85	1258.93	767.36	28.85	767.36	3060.000
5G NR n77	7.00	24.00	31.0	28.85	1258.93	767.36	28.85	767.36	3060.000
5G NR n78	7.00	24.00	31.0	28.85	1258.93	767.36	28.85	767.36	3060.000

Conclusion:

According to 47 CFR §1.1307, the RF exposure analysis concludes that the RF Exposure is FCC compliant.