

## MAXIMUM PERMISSIBLE EXPOSURE (MPE)

### STANDARD APPLICABLE:

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

This is a Mobile device, the MPE is required.

According to §1.1310 and §2.1093 RF exposure is calculated.

### Limits for Maximum Permissive Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	F/1500	30
1500-15000	/	/	1.0	30

F = frequency in MHz

= Plane-wave equipment power density

**MAXIMUM PERMISSIBLE EXPOSURE (MPE) EVALUATION**

**802.11b Power Table**

<b>Frequency (MHz)</b>	<b>Reading Power (dBm)</b>	<b>Cable Loss</b>	<b>Output Power (dBm)</b>	<b>Output Power (W)</b>	<b>Limit (W)</b>
2412.00	22.47	0.00	22.47	0.17660	1
2437.00	22.70	0.00	22.70	0.18621	1
2462.00	<b>22.79</b>	0.00	<b>22.79</b>	0.19011	1

**MPE Prediction (802.11b)**

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	<b>22.79</b>	(dBm)
Maximum peak output power at antenna input terminal:	190.107828	(mW)
Duty cycle:	<b>100</b>	(%)
Maximum Pav :	190.107828	(mW)
Antenna gain (typical):	<b>3.05</b>	(dBi)
Maximum antenna gain:	2.018366364	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	<b>2462</b>	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.076375	(mW/cm <sup>2</sup> )

**Measurement Result**

The predicted power density level at 20 cm is 0.076375 mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1 mW/cm<sup>2</sup> at 2462MHz.

### 802.11g Power Table

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2412.00	22.79	0.00	22.79	0.19011	1
2437.00	23.02	0.00	23.02	0.20045	1
2462.00	<b>23.05</b>	0.00	<b>23.05</b>	0.20184	1

### MPE Prediction (802.11g)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	23.05	(dBm)
Maximum peak output power at antenna input terminal:	201.8366364	(mW)
Duty cycle:	100	(%)
Maximum Pav :	201.8366364	(mW)
Antenna gain (typical):	3.05	(dBi)
Maximum antenna gain:	2.018366364	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2462	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.081087	(mW/cm <sup>2</sup> )

### Measurement Result

The predicted power density level at 20 cm is 0.081087 mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1 mW/cm<sup>2</sup> at 2462.

### 802.11n\_20M (2.4G) Power Table

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
2412.00	22.71	0.00	22.71	0.18664	1
2437.00	22.85	0.00	22.85	0.19275	1
2462.00	<b>22.93</b>	0.00	<b>22.93</b>	0.19634	1

### MPE Prediction (802.11n\_20M (2.4G))

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	22.93	(dBm)
Maximum peak output power at antenna input terminal:	196.3360277	(mW)
Duty cycle:	100	(%)
Maximum Pav :	196.3360277	(mW)
Antenna gain (typical):	3.05	(dBi)
Maximum antenna gain:	2.018366364	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	2462	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.078877	(mW/cm <sup>2</sup> )

### Measurement Result

The predicted power density level at 20 cm is 0.078877 mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1 mW/cm<sup>2</sup> at 2462.

### 802.11a Power Table

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
5745.00	19.73	0.00	19.73	0.09397	1
5785.00	<b>19.85</b>	0.00	<b>19.85</b>	0.09661	1
5825.00	19.39	0.00	19.39	0.08690	1

### MPE Prediction (802.11a)

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	19.85	(dBm)
Maximum peak output power at antenna input terminal:	96.6050879	(mW)
Duty cycle:	100	(%)
Maximum Pav :	96.6050879	(mW)
Antenna gain (typical):	3.33	(dBi)
Maximum antenna gain:	2.152781735	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5785	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.041395	(mW/cm <sup>2</sup> )

### Measurement Result

The predicted power density level at 20 cm is 0.041395 mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1 mW/cm<sup>2</sup> at 5785.

### 802.11n\_20M (5GHz) Power Table

Frequency (MHz)	Reading Power (dBm)	Cable Loss	Output Power (dBm)	Output Power (W)	Limit (W)
5745.00	19.61	0.00	19.61	0.09141	1
5785.00	<b>19.69</b>	0.00	<b>19.69</b>	0.09311	1
5825.00	19.19	0.00	19.19	0.08299	1

### MPE Prediction (802.11n\_20M (5GHz))

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG / 4 \pi R^2$$

Where: S = Power density

P = Power input to antenna

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna

Maximum peak output power at antenna input terminal:	19.69	(dBm)
Maximum peak output power at antenna input terminal:	93.11078755	(mW)
Duty cycle:	100	(%)
Maximum Pav :	93.11078755	(mW)
Antenna gain (typical):	3.33	(dBi)
Maximum antenna gain:	2.152781735	(numeric)
Prediction distance:	20	(cm)
Prediction frequency:	5785	(MHz)
MPE limit for uncontrolled exposure at prediction	1	(mW/cm <sup>2</sup> )
Power density at predication frequency at 20 (cm)	0.039898	(mW/cm <sup>2</sup> )

### Measurement Result

The predicted power density level at 20 cm is 0.039898 mW/cm<sup>2</sup>. This is below the uncontrolled exposure limit of 1 mW/cm<sup>2</sup> at 5785.