

**47 CFR PART 15 SUBPART C TEST REPORT**

**for**

**1-Port UHF RFID Reader Module**

**Model No.: RM100**

**FCC ID: HLERM100U**

**of**

Applicant: unitech Electronics Co., Ltd.

Address: 5F., No. 136, Ln. 235, Baoqiao Rd. , Xindian Dist., New Taipei City ,  
Taiwan

Tested and Prepared

by

**Worldwide Testing Services (Taiwan) Co., Ltd.**

**FCC Registration No.: TW1477, TW1072**

**Industry Canada filed test laboratory Reg. No.: 20037, 5107A**



**Report No.: W6M22206-21923-C-1**

6F, NO. 58, LANE 188, RUEY-KUANG RD., NEIHU TAIPEI 114, TAIWAN, R.O.C.  
TEL: 886-2-66068877 FAX: 886-2-66068879 E-mail: [wts@wts-lab.com](mailto:wts@wts-lab.com)



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## **TABLE OF CONTENTS**

<b>CERTIFICATION OF TEST REPORT</b> .....	<b>2</b>
<b>1 GENERAL INFORMATION</b> .....	<b>2</b>
1.1 NOTES .....	2
1.2 TESTING LABORATORY.....	3
1.2.1 Location .....	3
1.2.2 Details of accreditation status .....	3
1.3 DETAILS OF APPROVAL HOLDER .....	3
1.4 APPLICATION DETAILS.....	4
1.5 GENERAL INFORMATION OF TEST ITEM .....	4
1.6 TEST STANDARDS .....	5
<b>2 TECHNICAL TEST</b> .....	<b>6</b>
2.1 SUMMARY OF TEST RESULTS .....	6
2.2 TEST ENVIRONMENT .....	6
2.3 TEST EQUIPMENT LIST .....	7
2.4 GENERAL TEST PROCEDURE.....	10
<b>3 TEST RESULTS (ENCLOSURE)</b> .....	<b>12</b>
3.1 PEAK OUTPUT POWER (TRANSMITTER) .....	13
3.2 EQUIVALENT ISOTROPIC RADIATED POWER (EIRP).....	16
3.3 EXEMPTION LIMITS FOR ROUTINE EVALUATION .....	16
3.4 TRANSMITTER RADIATED EMISSIONS IN RESTRICTED BANDS .....	18
3.5 SPURIOUS EMISSIONS (TX).....	19
3.6 CARRIER FREQUENCY SEPARATION .....	21
3.7 NUMBER OF HOPPING FREQUENCIES .....	24
3.7.1 Pseudorandom Frequency Hopping Sequence .....	25
3.7.2 Coordination of hopping sequences to other transmitters .....	25
3.7.3 System Receiver Hopping Capability.....	25
3.8 TIME OF OCCUPANCY (DWELL TIME).....	26
3.9 20dB BANDWIDTH .....	30
3.9.1 System Receiver Input Bandwidth .....	32
3.10 EMISSION BAND OF NON-RESTRICTED .....	33
3.11 RADIATED EMISSIONS FROM DIGITAL PART .....	36
3.12 POWER LINE CONDUCTED EMISSION.....	37



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## 1 General Information

### 1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems. The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

### Tester:

September 23, 2022

Rick Chen

*Rick Chen*

Date

WTS-Lab.

Name

Signature

### Technical responsibility for area of testing:

September 23, 2022

Kevin Wang

*Kevin Wang*

Date

WTS

Name

Signature



# **Worldwide Testing Services(Taiwan) Co., Ltd.**

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## **1.2 Testing laboratory**

### **1.2.1 Location**

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,  
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber

No.35, Aly. 21, Ln. 228, Ankang Rd., Neihu Dist.,  
Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6613-0228

Worldwide Testing Services (Taiwan) Co., Ltd.

6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,  
Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6606-8877

### **1.2.2 Details of accreditation status**

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1477, TW1072

Industry Canada filed test laboratory Reg. No.: 20037, 5107A

### **Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :**

Name: ./.

Accredited number: ./.

Street: ./.

Town: ./.

Country: ./.

## **1.3 Details of approval holder**

Name: unitech Electronics Co., Ltd.

Street: 5F., No. 136, Ln. 235, Baoqiao Rd. , Xindian Dist.,

Town: New Taipei City ,

Country: Taiwan



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

### 1.4 Application details

Date of receipt of test item: June 20, 2022  
Date of test: from June 21, 2022 to August 22, 2022

### 1.5 General information of Test item

Type of test item: 1-Port UHF RFID Reader Module  
Model number: RM100  
Multi-listing model number: ./.  
Sample no.: #01

#### Technical data

Frequency band: 902.75-927.25 MHz  
Frequency ( ch A): 902.75 MHz  
Frequency ( ch B): 915.25 MHz  
Frequency ( ch C): 927.25 MHz

#### Transmitter

#### Unom

Power ( ch A): Conducted: 29.38 dBm  
Power ( ch B): Conducted: 29.25 dBm  
Power ( ch C): Conducted: 29.29 dBm

Power supply: 4.4Vd.c.  
Operation modes: Duplex  
Modulation type: DSB-ASK,PR-ASK  
Antenna type: UHF RFID antenna  
Antenna gain: 4 dBi  
Host device: none

Classification:

Fixed Device	<input type="checkbox"/>
Mobile Device (Human Body distance > 20cm)	<input type="checkbox"/>
Portable Device (Human Body distance < 20cm)	<input type="checkbox"/>
Modular Radio Device	<input checked="" type="checkbox"/>



# ***Worldwide Testing Services(Taiwan) Co., Ltd.***

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

**Manufacturer: (if applicable)**

Name: ./.

Street: ./.

Town: ./.

Country: ./.

## **1.6 Test standards**

47 CFR PART 15 SUBPART C § 15.247 (2020-10)



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## **2 Technical test**

### **2.1 Summary of test results**

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

**or**

The deviations were ascertained in the course of the tests performed.

### **2.2 Test environment**

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Details of power supply: 4.4Vd.c.

Extreme conditions parameters: test voltage : -- extreme  
min : -- V  
max : -- V

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Emission (Power Line Conducted Emission)	Expanded Uncertainty : AMN : 1.03 dB Voltage probe : 1.05 dB
Estimation Result of Uncertainty of Radiated Emission(3M) (Transmitter Radiated Emissions in restricted Bands, Spurious emissions (tx), Radiated Emissions from Digital Part)	Expanded Uncertainty : 0.009-30 MHz : 3.48 dB 30-1000 MHz : 4.48 dB 1-18 GHz : 4.15 dB 18-40 GHz : 3.78 dB
Estimation Result of Uncertainty of Bandwidth Measurement (20 dB Bandwidth)	Expanded Uncertainty : 0.45 kHz
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 3.07 dB
Estimation Result of Uncertainty of Band Edge Measurement (Band-edge Compliance of RF Emissions)	Expanded Uncertainty : 0.67 dBc
Estimation Result of Uncertainty of Frequency Separation Measurement (Carrier Frequency Separation, Number of Hopping Frequencies)	Expanded Uncertainty : 554.14 Hz
Estimation Result of Uncertainty of Duty Cycle Measurement (Time of Occupancy (Dwell Time))	Expanded Uncertainty : 0.1 ms

The decision rule is: Measurement uncertainty is not included in the calculation of test results.



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## 2.3 Test Equipment List

No.	Test equipment	Type	Serial No.	Manufacturer	Cal. Date	Next Cal. Date
ETSTW-CE 001	EMI TEST RECEIVER	ESHS10	842121/013	R&S	2022/6/22	2023/6/21
ETSTW-CE 003	AC POWER SOURCE	APS-9102	D161137	GW	Function Test	
ETSTW-CE 004	ZWEILEITER-V-NETZNACHBILDUNG TWO-LINE V-NETWORK	ESH3-Z5	840731/011	R&S	2021/11/9	2022/11/8
ETSTW-CE 006	IMPULSBEGRENZER PULSE LIMITER	ESH3-Z2	100226	R&S	2021/9/22	2022/9/21
ETSTW-CE 008	HF-EICHLITUNG RF STEP ATTENUATOR 139dB DPSP	334.6010.02	844581/024	R&S	Function Test	
ETSTW-CE 009	TEMP.&HUMIDITY CHAMBER	GTH-225-40-1P-U	MAA0305-009	GIANT FORCE	2022/7/18	2023/7/17
ETSTW-CE 016	TWO-LINE V-NETWORK	ENV216	100050	R&S	2021/11/8	2022/11/7
ETSTW-CE 028	MXE EMI Receiver	N9038A	MY53220110	Agilent	2022/7/18	2023/7/17
ETSTW-RE 003	EMI TEST RECEIVER	ESI 26	831438/001	R&S	2022/6/21	2023/6/20
ETSTW-RE 004	EMI TEST RECEIVER	ESI 40	832427/004	R&S	2021/9/28	2022/9/27
ETSTW-RE 012	TUNABLE BANDREJECT FILTER	D.C 0309	146	K&L	Function Test	
ETSTW-RE 013	TUNABLE BANDREJECT FILTER	D.C 0336	397	K&L	Function Test	
ETSTW-RE 018	MICROWAVE HORN ANTENNA	AT4560	27212	AR	2022/8/3	2023/8/2
ETSTW-RE 019	MICROWAVE HORN ANTENNA	22240-25	121074	FM	2022/6/13	2023/6/12
ETSTW-RE 027	Passive Loop Antenna	6512	00034563	ETS-Lindgren	2022/6/22	2023/6/21
ETSTW-RE 030	Double-Ridged Guide Horn Antenna	3117	00035224	ETS-Lindgren	2022/5/23	2023/5/22
ETSTW-RE 042	Biconical Antenna	HK116	100172	R&S	2022/3/4	2023/3/3
ETSTW-RE 043	Log-Periodic Dipole Antenna	HL223	100166	R&S	2022/6/28	2023/6/27
ETSTW-RE 044	Log-Periodic Antenna	HL050	100094	R&S	2022/7/1	2023/6/30
ETSTW-RE 045	ESA-E SERIES SPECTRUM ANALYZER	E4404B	MY45111242	Agilent	Pre-test Use	
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 051	Attenuator 6dB	50HF-006-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 053	Attenuator 3dB	50HF-003-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2022/3/28	2023/3/27
ETSTW-RE 060	Attenuator 30dB	5015-30	F651012z-01	ATM	2022/2/18	2023/2/17
ETSTW-RE 062	Amplifier Module	CHC 2	None	KMIC	2022/5/13	2023/5/12
ETSTW-RE 064	Bluetooth Test Set	MT8852B-042	6K00005709	Anritsu	Function Test	
ETSTW-RE 069	Double-Ridged Guide Horn Antenna	3117	00069377	ETS-Lindgren	Function Test	
ETSTW-RE 072	CELL SITE TEST SET	8921A	3339A00375	HP	2021/10/27	2022/10/26
ETSTW-RE 088	SOLID STATE AMPLIFIER	KMA180265A01	99057	KMIC	2021/9/17	2022/9/16
ETSTW-RE 091	Match Pad	MDCS1500	None	WOKEN	2022/6/9	2023/6/8
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2022/2/18	2023/2/17
ETSTW-RE 112	AC POWER SOURCE	TFC-1005	T-0A023536	T-Power	Function test	





# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U

ETSTW-RE 115	2.4GHz Notch Filter	N0124411	473874	MICROWAVE CIRCUITS	2022/1/5	2023/1/4
ETSTW-RE 120	RF Player	MP9200	MP9210-111022	ADIVIC	2021/10/29	2022/10/28
ETSTW-RE 122	SIGNAL GENERATOR	SMF100A	102149	R&S	2022/6/20	2023/6/19
ETSTW-RE 125	5GHz Notch filter	5NSL11-5200/E221.3-O/O	1	K&L Microwave	2022/8/3	2023/8/2
ETSTW-RE 126	5GHz Notch filter	5NSL12-5800/E221.3-O/O	1	K&L Microwave	2022/8/3	2023/8/2
ETSTW-RE 127	RF Switch Box	RFS-01	None	WTS	2022/2/18	2023/2/17
ETSTW-RE 128	5.3GHz Notch filter	N0153001	SN487233	Microwave Circuits	2022/8/3	2023/8/2
ETSTW-RE 129	5.5GHz Notch filter	N0555984	SN487234	Microwave Circuits	2022/8/3	2023/8/2
ETSTW-RE 130	Handheld RF Spectrum Analyzer	N9340A	CN0147000204	Agilent	Pre-test Use	
ETSTW-RE 142	Amplifier	8447D	2805A03378	Agilent	2022/5/13	2023/5/12
ETSTW-RE 146	Preamplifier	JPA-10MIG	15090004	JPT	2022/5/27	2023/5/26
ETSTW-RE 152	Bi-log Hybrid Antenna	MCTD 2786B	BLB20J04029	ETC	2021/10/5	2022/10/4
ETSTW-RE 153	Signal Analyzer	FSV40	101929	R&S	2021/10/6	2022/10/5
ETSTW-RE 159	Bi-log Hybrid Antenna (30M~1000 MHz)	MCTD 2786B	BLB21N04035	ETC	2021/12/06	2022/12/05
ETSTW-RF 002	Electromagnetic field probe	LF-30	K-0007	STT	2022/6/15	2023/6/14
ETSTW-EMI 011	USB Compact Modulator	SFC-U	101689	R&S	2022/6/10	2023/6/9
ETSTW-GSM 002	Universal Radio Communication Tester	CMU 200	109439	R&S	2022/3/28	2023/3/27
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2022/5/9	2023/5/8
ETSTW-GSM 004	Wideband Radio Communication Tester	CMW500	128092	R&S	2021/10/29	2022/10/28
ETSTW-GSM 019	Band Reject Filter	WRCTF824/849-822/851-40 /12+9SS	3	WI	2022/1/5	2023/1/4
ETSTW-GSM 020	Band Reject Filter	WRCD1747/1748-1743/1752-32/5SS	1	WI	2022/1/5	2023/1/4
ETSTW-GSM 021	Band Reject Filter	WRCD1879.5/1880.5-1875.5/1884.5-32/5SS	3	WI	2022/1/5	2023/1/4
ETSTW-GSM 022	Band Reject Filter	WRCT901.9/903.1-904.25-50/8SS	1	WI	2022/1/5	2023/1/4
ETSTW-GSM 023	Power Divider	4901.19.A	None	SUHNER	2021/9/7	2022/9/6
ETSTW-GSM 024	Radio Communication Analyzer	MT8821C	None	Anritsu	2022/5/3	2023/5/2
ETSTW-GSM 025	Band Reject Filter	BRM19835	001	Micro-Tronics	2022/8/3	2023/8/2
ETSTW-Cable 011	SMA to N type Cable	RGU-400	None	THERMAX	Pre-test Use NCR	
ETSTW-Cable 016	BNC Cable	Switch Box	B Cable 1	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 017	BNC Cable	X Cable	B Cable 2	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 018	BNC Cable	Y Cable	B Cable 3	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 019	BNC Cable	Z Cable	B Cable 4	Schwarz beck	2022/2/18	2023/2/17
ETSTW-Cable 020	N TYPE Cable	OATS Cable 1	N30N30-L335-15M	JYE BAO CO.,LTD.	2022/6/15	2023/6/14
ETSTW-Cable 027	Microwave Cable	SUCOFLEX 104	279083	HUBER+SUHNER	2022/5/6	2023/5/5
ETSTW-Cable 028	Microwave Cable	FA147A0015M2020	30064-2	UTIFLEX	2021/9/17	2022/9/16
ETSTW-Cable 029	Microwave Cable	FA147A0015M2020	30064-3	UTIFLEX	2021/9/17	2022/9/16
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2022/2/18	2023/2/17



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

ETSTW-Cable 043	Microwave Cable	SUCOFLEX 104	317576	HUBER+SUHNER	2022/5/13	2023/5/12
ETSTW-Cable 047	Microwave Cable	SUCOFLEX 104	325518	HUBER+SUHNER	2022/7/1	2023/6/30
ETSTW-Cable 058	Microwave Cable	SUCOFLEX 104	none	HUBER+SUHNER	2022/5/27	2023/5/26
ETSTW-Cable 064	Microwave Cable	SUCOFLEX 104	MY28891	HUBER+SUHNER	2022/5/13	2023/5/12
ETSTW-Cable 071	N TYPE CABLE	EMCCFD400-NM-NM-25000	170239	EMCI	2022/5/27	2023/5/26
ETSTW-Cable 072	SMA type cable (8m)	SUCOFLEX 104	805800/4	HUBER+SUHNER	2022/5/13	2023/5/12
ETSTW-Cable 074	SMA type cable (2m)	SUCOFLEX 104	802563/4	HUBER+SUHNER	2022/5/13	2023/5/12
WTSTW-SW 002	EMI TEST SOFTWARE	EZ EMC	None	Farad	Version ETS-03A1 Version EMEC-3A1+	
WTSTW-SW 006	EMI TEST SOFTWARE	e3	None	AUDIX	Version 9.161014	
WTSTW-SW 008	Signal studio	Agilent	None	AUDIX	Version 2.0.0.1	
ETSTW-TH 002	Thermohygrometer	608-H1	45204317	Testo	2021/10/18	2022/10/17
ETSTW-TH 003	Wireless weather station	GAIA	N/A	TFA	2021/10/18	2022/10/17



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## **2.4 General Test Procedure**

**POWER LINE CONDUCTED INTERFERENCE:** The procedure used was ANSI STANDARD C63.10-2013 6.2 using a LISN (if necessary). Both lines were observed. The bandwidth of the spectrum analyzer was 10 kHz with an appropriate sweep speed.

**RADIATION INTERFERENCE:** The test procedure used was according to ANSI STANDARD C63.10-2013 6.3 employing a spectrum analyzer. For investigated frequency is equal to or below 1GHz, the RBW and VBW of the spectrum analyzer was 100 kHz and 100kHz respectively with an appropriate sweep speed. For investigated frequency is above 1GHz, both of RBW and VBW of the spectrum analyzer were 1 MHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The ambient temperature of the UUT was 23°C with a humidity of 40 %.

**FORMULA OF CONVERSION FACTORS:** The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dB $\mu$ V) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB.

Example:

Freq (MHz)      METER READING + ACF + CABLE LOSS (to the receiver) = FS  
33                      20 dB $\mu$ V + 10.36 dB + 6 dB = 36.36 dB $\mu$ V/m @3m

The EUT was placed on a table 80 cm high and with dimensions of 1m by 1.5m (non metallic table) and arranged according to ANSI C63.10-2013 6.2.2. The table used for radiated measurements is capable of continuous rotation. The spectrum was scanned from 30 MHz to the frequency specified as follows:

- (1) If the intentional radiator operates below 10 GHz: to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.
- (2) If the intentional radiator operates at or above 10 GHz and below 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 100 GHz, whichever is lower.
- (3) If the intentional radiator operates at or above 30 GHz: to the fifth harmonic of the highest fundamental frequency or to 200 GHz, whichever is lower, unless specified otherwise elsewhere in the rules.
- (4) If the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to the range specified in paragraphs (a)(1)-(a)(3) of this section or the range applicable to the digital device, as shown in paragraph (b)(1) of this Section, whichever is the higher frequency range of investigation.

For hand-held devices, a exploratory test was performed with three (3) orthogonal planes to determine the highest emissions.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.



## **Worldwide Testing Services(Taiwan) Co., Ltd.**

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

When the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.

The formula is as follows:

Average = Peak + Duty Factor

Duty Factor =  $20 \log (\text{dwell time}/T)$

T = 100ms when the pulse train period is over 100 ms or the period of the pulse train.

Modified Limits for peak according to 15.35 (b) = Max Permitted average Limits + 20dB

ANSI STANDARD C63.10-2013 B.2.7: Any measurements that utilize special test software shall be indicated and referenced in the test report. During testing, test software 'EZ EMC' was used for setting up different operation modes.



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## **3 Test results (enclosure)**

TEST CASE	Para. Number	Required	Test passed	Test failed
Peak Output Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Equivalent radiated Power	15.247(b)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions radiated – Transmitter operating	15.247(d):15.209	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Spurious Emissions conducted – Transmitter operating	15.247	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
Carrier Frequency Separation	15.247(a) (1)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Number of Hopping Frequencies	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Time of Occupancy (Dwell Time)	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20 dB Bandwidth	15.247(a) (1)(i)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Emission Band of Non-Restricted	15.247(d)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Radiated Emission from Receiver Part	15.109	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>
Power Line Conducted Emission	15.207(a)	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>

The follows is intended to leave blank.



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

### 3.1 Peak Output Power (transmitter)

FCC Rule: 15.247

This measurement applies to equipment with an integral antenna and to equipment with an antenna connector and equipped with an antenna as declared by the applicant.


The power was measured with modulation (declared by the applicant).

Test date: August 18, 2022

Temperature: 24.8 °C

Humidity: 51.6 %

Tester: Rick




MAX OUTPUT POWER 902.75MHz  
Date: 18.AUG.2022 15:42:51




# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U



MAX OUTPUT POWER 915.25MHz  
Date: 18.AUG.2022 15:41:45



MAX OUTPUT POWER 927.25MHz  
Date: 18.AUG.2022 15:44:17



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

Limits:

Frequency MHz	Number of hopping channels			
	$\geq 75$	$\geq 50$	$49 \geq 25$	$74 \geq 15$
902-928	--	30 dBm	24 dBm	--
2400-2483.5 MHz	30 dBm	--	--	21 dBm
5725-5850 MHz	30 dBm	--	--	--

In case of employing transmitter antennas having antenna gain >dBi and using fixed point-to point operation consider §15.247 (b)(4).

Test equipment used: ETSTW-RE 055, ETSTW-RE 050, ETSTW-RE 064





# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

## 3.2 Equivalent Isotropic Radiated Power (EIRP)

FCC Rule: 15.247(b)(3)

EIRP = max. conducted output power + antenna gain

EIRP = 29.38 dBm + 0.61 dB [tolerance] +(4 dBi [antenna gain claimed by manufacturer] = 33.99 dBm  
= 2506.11 mW

## 3.3 Exemption Limits for Routine Evaluation

according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

### MPE Calculation Method

#### (A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

#### (B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz

\*Plane-wave equivalent power density



## Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

mW/cm<sup>2</sup>.

Established separation distance is 20 cm.

Operating frequency band: 902.75-927.25 MHz

The product meets RF exposure requirement.

Because the power density of 0.4986 mW/cm<sup>2</sup> at 902.75 MHz is below the power density limit of 0.6018 mW/cm<sup>2</sup>.



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

### **3.4 Transmitter Radiated Emissions in restricted Bands**

FCC Rules: 15.247 (d), 15.205, 15.209, 15.35

9 kHz to 30 MHz spurious emissions relative to the limit. Emission more than 20 dB below the limit do not need to be reported.

Radiated emission measurements were performed from 30 MHz to 26000 MHz.

For radiated emission tests, the analyzer setting was as followings:

RES BW VID BW

Frequency <1 GHz 100 kHz 100 kHz (Peak measurements)

Frequency >1 GHz 1 MHz 1 MHz (Peak measurements)

1 MHz 1 MHz (Average measurements)

Limits:

For frequencies below 1GHz :

Frequency of Emission (MHz)	Field strength (microvolts/meter)	Field Strength (dB microvolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

For frequencies above 1GHz (Average measurements).

Guidance on Measurement of FHSS Systems:

“If the emission is pulsed, modify the unit for continues operation , use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation.” Here the correction was added to the limit instead subtracted from the reading.

Duty cycle correction =  $20 \log(\text{dwell time}/100\text{ms})$

For frequencies above 1GHz (Average measurements).

Limit – duty cycle correction

No duty cycle correction was added to the reading.

54.0dB $\mu$ V/m

For frequencies above 1GHz (Peak measurements).

Limit + 20dB

54.0dB $\mu$ V/m + 20 dB= 74 dB $\mu$ V/m

Test equipment used: ETSTW-RE 004, ETSTW-RE 030, ETSTW-RE 062, ETSTW-RE 142, ETSTW-RE 152, ETSTW-RE 064

Explanation: See attached diagrams in appendix.



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U

### 3.5 Spurious emissions (tx)

Spurious emission was measured with modulation (declared by manufacturer).

In any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c))

SAMPLE CALCULATION OF LIMIT. All results will be updated by an automatic measuring system in accordance to point 2.3.

Calculation of test results:

Such factors like antenna correction, cable loss, external attenuation etc. are already included in the provided measurement results. This is done by using validated test software and calibrated test system according the accreditation requirements.

The peak and average spurious emission plots was measured with the average limits.

In the Table being listed the critical peak and average value an exhibit the compliance with the above calculated Limits.

If in the column's correction factor states a value then the max. Field strength in the same row is corrected by a value gained from the "Marker-Delta-Method" or the „Duty-Cycle Correction Factor“.

### Summary table with radiated data of the test plots

Model: RM100 Date: --  
 Mode: -- Temperature: -- °C Engineer: --  
 Polarization: Horizontal Humidity: -- %

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U

Polarization: Vertical

Frequency (MHz)	Reading (dBuV)	Detector	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--

Frequency (MHz)	Reading (dBuV)		Factor (dB) Corr.	Result (dBuV/m)		Limit (dBuV/m)		Margin (dB)	Table Degree (Deg.)	Ant. High (cm)
	Peak	Ave.		Peak	Ave.	Peak	Ave.			
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--
--	--	--	--	--	--	--	--	--	--	--

- Note**
1. Correction Factor = Antenna factor + Cable loss - Pre-amplifier
  2. The formula of measured value as: Test Result = Reading + Correction Factor
  3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
  4. All not in the table noted test results are more than 20 dB below the relevant limits.
  5. After evaluated, the test result in this report adopt the worst case to measure, please see attached diagrams in appendix.

All other not noted test plots do not contain significant test results in relation to the limits.

**TEST RESULT (Transmitter):** The unit DOES meet the FCC requirements.

Test equipment used: ETSTW-RE 030, ETSTW-RE 111, ETSTW-RE 088, ETSTW-RE 018, ETSTW-RE 064




Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U

### 3.6 Carrier Frequency Separation

Carrier Frequency Separation was measured with modulation (declared by manufacturer).

According to FCC rules part 15 subpart C §15.247 frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or 20 dB bandwidth of the hopping channel, whichever is greater.

Test date: August 17, 2022  
Temperature: 24.4 °C  
Humidity: 58.0 %  
Tester: Rick




FREQUENCY SEPARATION 902.75MHz  
Date: 17.AUG.2022 20:56:06




# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U



FREQUENCY SEPARATION 915.25MHz  
Date: 17.AUG.2022 20:57:07



FREQUENCY SEPARATION 927.25MHz  
Date: 17.AUG.2022 20:57:56



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

**Limits:**

Frequency Range MHz	Limits	
	20 dB bandwidth < 25 kHz	20 dB bandwidth > 25 kHz
902-928	25 kHz	20 dB bandwidth
2400-2483.5 5725-5850.0	25 kHz	20 dB bandwidth

Test equipment used: ETSTW-RE 055, ETSTW-RE 064





Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U

### 3.7 Number of Hopping Frequencies

According to FCC rules part 15 subpart C §15.247 frequency hopping systems operating in the 2400-2483.5 MHz band shall use at least 15 hopping frequencies. Frequency hopping systems in 5725-5850 MHz bands shall use least 75 hopping frequencies.


For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the system shall use at least 50 hopping frequencies; if the 20dB bandwidth of the hopping channel 250 kHz or greater, the system shall use at least 25 hopping frequencies.

Test date: August 17, 2022

Temperature: 24.4 °C

Humidity: 58.0 %

Tester: Rick



NUMBER OF HOPPING  
 Date: 17.AUG.2022 20:52:22

#### Limits:

Frequency Range MHz	Limit	
	20dB Bandwidth	Number of Channels
902-928 MHz	Bandwidth < 250 kHz	≥ 50
	Bandwidth ≥ 250 kHz	≥ 25
2400-2483.5	not defined	15
5725-5850.0 MHz	1 MHz	75

Test equipment used: ETSTW-RE 055, ETSTW-RE 064



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

### **3.7.1 Pseudorandom Frequency Hopping Sequence**

The generation of the hopping sequence is determined by the Bluetooth core specification and complies with the FCC requirements.

### **3.7.2 Coordination of hopping sequences to other transmitters**

According to the Bluetooth core specification such a coordination is not possible. During scatternet function only one of the two hopping sequences will be used at a definite moment.

### **3.7.3 System Receiver Hopping Capability**

According to the Bluetooth core specification. The system receivers shift frequencies in synchronization with the transmitted signals.



Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U


### 3.8 Time of Occupancy (Dwell Time)

Frequency hopping systems operating in the 5725-5850 MHz band shall use an average time of occupancy on any frequency not greater than 0.4 seconds within a 30 second period.


In 2400-2483.5 MHz band the average time of occupancy on any channel shall not be greater than 0.4 seconds multiplied by the number of hopping channels employed.

For frequency hopping systems operating in the 902-928 MHz band: if the 20dB bandwidth of the hopping channel is less than 250 kHz, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 20 second period; if the 20dB bandwidth of the hopping channel is 250 kHz or greater, the average time of occupancy on any frequency shall not be greater than 0.4 seconds within a 10 second period.

Test date: August 17, 2022  
Temperature: 24.4 °C  
Humidity: 58.0 %  
Tester: Rick




DWELL TIME 902.75MHz  
Date: 17.AUG.2022 20:03:15




# Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U



DWELL TIME 902.75MHz(396.63ms \* levent =396.63ms)  
 Date: 17.AUG.2022 19:57:49




DWELL TIME 915.25MHz  
 Date: 17.AUG.2022 20:01:16




# Worldwide Testing Services(Taiwan) Co., Ltd.


Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U




DWELL TIME 915.25MHz(396.63ms \* levent =396.63ms)  
Date: 17.AUG.2022 19:58:28



DWELL TIME 927.25MHz  
Date: 17.AUG.2022 20:02:19



Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U




DWELL TIME 927.25MHz(396.63ms \* 1event =396.63ms)  
 Date: 17.AUG.2022 19:59:00

### Limits and measurement periods:

Frequency MHz	Number of channels	Measurement Periode	Limit
902 – 928	≥50	20 s	0.4 s
	49 ≥ 25	10 s	0.4 s
2400 – 2483.5	≥ 15	0.4 s * number of used channels	0.4 s
5725- 5850	≥ 75	30 s	0.4s

Test equipment used: ETSTW-RE 055, ETSTW-RE 064



Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U

## 3.9 20dB Bandwidth

Frequency hopping systems operating in the 5725-5850 MHz bands shall use a maximum 20dB bandwidth of 1 MHz.

The 20dB bandwidth is measured on the lowest, middle and highest hopping channel.


For frequency hopping systems operating in the 902-928 MHz band the maximum 20dB bandwidth of the hopping channel is 500 kHz.

Test date: August 17, 2022


Temperature: 24.4 °C

Humidity: 58.0 %

Tester: Rick




20DB BANDWIDTH 902.75MHz  
Date: 17.AUG.2022 18:53:24




# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U




20DB BANDWIDTH 915.25MHz  
 Date: 17.AUG.2022 18:51:35



20DB BANDWIDTH 927.25MHz  
 Date: 17.AUG.2022 20:42:40





Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U

**Limits:**

Frequency Range / MHz	Limit
902-928	$\leq 500$ kHz
2400-2483.5	not defined
5725-5850	$\leq 1$ MHz

Test equipment used: ETSTW-RE 055, ETSTW-RE 064

**3.9.1 System Receiver Input Bandwidth**

It is determined in the Bluetooth core specification. The value matches to the bandwidth of transmitter signal.



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

### 3.10 Emission band of non-restricted

According to FCC rules part 15 subpart C §15.247(d) in any 100 kHz bandwidth outside the frequency band in which the intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in § 15.209(a) is not required.


In addition radiated emission which fall in the restricted bands, as defined in section 15.205(a), must also with the radiated emission limits.

Test date: August 17, 2022

Temperature: 24.4 °C

Humidity: 58.0 %

Tester: Rick




BANDEDGE 902.75MHz  
Date: 17.AUG.2022 20:46:54




# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
FCC ID: HLERM100U



BANDEDGE 927.25MHz

Date: 17.AUG.2022 20:45:21




BANDEDGE HOPPING MODE 902.75MHz

Date: 17.AUG.2022 20:49:07



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U



BANDEDGE HOPPING MODE 927.25MHz  
 Date: 17.AUG.2022 20:50:13

**Limits:**

Frequency Range / MHz	Limit
902 – 928 2400 – 2483.5 5725 - 5850	- 20 dB

Test equipment used: ETSTW-RE 055, ETSTW-RE 050, ETSTW-RE 064



Registration number: W6M22206-21923-C-1

FCC ID: HLERM100U

**3.11 Radiated Emissions from Receiver Part**

FCC Rule: 15.109

**Summary table with radiated data of the test plots**

Except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

Frequency of Emission (MHz)	Field Strength (microvolts/meter)	Field Strength (dBmicrovolts/meter)
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

Test equipment used: ETSTW-RE 030, ETSTW-RE 055, ETSTW-RE 064, ETSTW-RE 111

Explanation: Please see attached diagrams in appendix.




Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U

## 3.12 Power Line Conducted Emission

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the table bellows with this provision shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminals.

This measurement was transact first with instrumentation using an average and peak detector and a 10 kHz bandwidth. If the peak detector achieves a calculated level, the measurement is repeated by an instrumentation using a quasi-peak detector.




Site : Chamber\_03  
 Condition : FCC Part 15 Class B Conduction (QP)      Phase : N  
 EUT : W6M22204-21923      Power : 120Va.c.  
 M/N:  
 Test Mode :  
 Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1561	32.69	QP	9.61	42.30	65.67	-23.37	
	0.1561	20.43	AVG	9.61	30.04	55.67	-25.63	
	0.1822	29.96	QP	9.61	39.57	64.38	-24.81	
	0.1822	16.76	AVG	9.61	26.37	54.38	-28.01	
	0.2284	24.77	QP	9.59	34.36	62.51	-28.15	
	0.2284	1.89	AVG	9.59	11.48	52.51	-41.03	
	0.4671	19.11	QP	9.47	28.58	56.57	-27.99	
	0.4671	3.19	AVG	9.47	12.66	46.57	-33.91	
	6.6250	13.21	QP	9.93	23.14	60.00	-36.86	
	6.6250	0.26	AVG	9.93	10.19	50.00	-39.81	
	25.8750	23.28	QP	10.43	33.71	60.00	-26.29	
*	25.8750	22.76	AVG	10.43	33.19	50.00	-16.81	



# Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22206-21923-C-1  
 FCC ID: HLERM100U



Site : Chamber\_03  
 Condition : FCC Part 15 Class B Conduction (QP)      Phase : L1  
 EUT : W6M22204-21923      Power : 120Va.c.  
 M/N:  
 Test Mode :  
 Note :


Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corrected factor(dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Comment
	0.1568	32.27	QP	9.62	41.89	65.63	-23.74	
	0.1568	19.84	AVG	9.62	29.46	55.63	-26.17	
	0.1705	30.96	QP	9.62	40.58	64.94	-24.36	
	0.1705	2.60	AVG	9.62	12.22	54.94	-42.72	
	0.2338	23.41	QP	9.59	33.00	62.31	-29.31	
	0.2338	0.96	AVG	9.59	10.55	52.31	-41.76	
	0.4720	21.38	QP	9.48	30.86	56.48	-25.62	
	0.4720	4.60	AVG	9.48	14.08	46.48	-32.40	
	15.2625	14.77	QP	10.06	24.83	60.00	-35.17	
	15.2625	0.56	AVG	10.06	10.62	50.00	-39.38	
	25.8750	22.78	QP	10.17	32.95	60.00	-27.05	
*	25.8750	22.18	AVG	10.17	32.35	50.00	-17.65	

### Limits:

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	Quasi Peak	Average
0.15-0.5	66 to 56	56 to 46
0.5-5	56	46
5-30	60	50

- Note:**
1. The formula of measured value as: Test Result = Reading + Correction Factor
  2. The Correction Factor = Cable Loss + LISN Insertion Loss + Pulse Limit Loss
  3. Detector function in the form : PK = Peak, QP = Quasi Peak, AV = Average
  4. All not in the table noted test results are more than 20 dB below the relevant limits.
  5. Up Line: QP Limit Line, Down Line: Ave Limit Line.

Test equipment used: ETSTW-CE 001, ETSTW-CE 016, ETSTW-RE 045.



## **Appendix**

### **A Photos**

1. External Photos
2. Internal Photos
3. Set Up Photo of Radiated Emission
4. Set Up Photo of Conducted Emission

### **B Measurement diagrams**

Radiated Emission





Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

**Radiated Emission Measurement**

Operator: Sky

File :1

Data :#1


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 09:37:31

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22206-21923

M/N:

Test Mode : TX 902.75MHz

Note :

Polarization: **Horizontal**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	141.4627	30.15	peak	-6.82	23.33	74.00	102	81	-50.67	
*	252.3848	34.94	peak	-7.42	27.52	46.00	100	199	-18.48	

\*:Maximum data    x:Over limit    !:over margin



Radiated Emission Measurement

Operator: Sky

File :1

Data :#2


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 09:39:29

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22206-21923

M/N:

Test Mode : TX 902.75MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	97.6352	38.74	peak	-10.32	28.42	74.00	102	3	-45.58	
*	167.9760	31.86	peak	-10.33	21.53	43.50	110	106	-21.97	



Radiated Emission Measurement

Operator: Sky

File :2

Data :#1


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 09:43:10

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 300-1000

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	806.4126	40.38	peak	1.53	41.91	74.00	102	113	-32.09	
*	1000.0000	44.00	peak	6.00	50.00	54.00	100	8	-4.00	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :2

Data :#2


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 09:44:52

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 300-1000

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	806.4126	33.29	peak	1.53	34.82	74.00	103	17	-39.18	
*	1000.0000	38.57	peak	6.00	44.57	54.00	100	244	-9.43	

\*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#1


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:42:45

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1805.611	56.79	peak	-5.43	51.36	74.00	150	211	-22.64	

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Sky

File :3

Data :#5


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:43:51

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1805.611	65.29	peak	-5.43	59.86	74.00	150	307	-14.14	nonrestricted

\*:Maximum data    x:Over limit    !:over margin



Radiated Emission Measurement

Operator: Sky

File :3

Data :#2


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:45:05

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2709.419	45.85	peak	-3.70	42.15	74.00	150	332	-31.85	
*	3611.222	44.23	peak	-1.38	42.85	74.00	150	24	-31.15	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#6


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:46:12

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 902.75MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2709.419	44.61	peak	-3.70	40.91	74.00	150	17	-33.09	
*	3611.222	45.97	peak	-1.38	44.59	74.00	150	288	-29.41	

\*:Maximum data    x:Over limit    !:over margin





Radiated Emission Measurement

Operator: Sky

File :3

Data :#3


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:47:36

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 902.75MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	5418.838	47.95	peak	1.43	49.38	74.00	150	32	-24.62	
*	6316.633	55.76	peak	3.54	59.30	74.00	150	110	-14.70	nonrestricted
	7222.445	47.19	peak	5.24	52.43	74.00	150	102	-21.57	

\*:Maximum data    x:Over limit    !:over margin



Radiated Emission Measurement

Operator: Sky

File :3

Data :#7


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:48:52

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 902.75MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4513.026	48.89	peak	-1.01	47.88	74.00	150	47	-26.12	
	5418.838	49.64	peak	1.43	51.07	74.00	150	110	-22.93	
*	5418.838	47.21	AVG	1.43	48.64	54.00	150	110	-5.36	
	6316.633	59.79	peak	3.54	63.33	74.00	150	62	-10.67	nonrestricted
	7222.445	51.02	peak	5.24	56.26	74.00	150	159	-17.74	nonrestricted

\*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#4


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:51:13

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 902.75MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#8


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 05:52:24

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Sky

File :1

Data :#1


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 10:41:52

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22206-21923

M/N:

Test Mode : TX 915.25MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	167.9760	31.64	peak	-10.33	21.31	43.50	102	6	-22.19	
*	252.3848	33.66	peak	-7.42	26.24	46.00	117	210	-19.76	



Radiated Emission Measurement

Operator: Sky

File :1

Data :#2


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 10:43:19

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22206-21923

M/N:

Test Mode : TX 915.25MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	91.6834	37.98	peak	-12.39	25.59	74.00	105	93	-48.41	
*	167.9760	34.77	peak	-10.33	24.44	43.50	112	62	-19.06	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :2

Data :#1


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 10:35:42

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 300-1000

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	311.2223	46.90	peak	-5.67	41.23	74.00	114	109	-32.77	
*	819.0380	42.07	peak	1.91	43.98	74.00	101	27	-30.02	

\*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

**Radiated Emission Measurement**

Operator: Sky

File :2

Data :#2


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 10:37:34

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 300-1000

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	671.7435	36.73	peak	0.50	37.23	74.00	111	13	-36.77	
*	819.0380	36.54	peak	1.91	38.45	74.00	104	225	-35.55	

\*:Maximum data    x:Over limit    !:over margin





Radiated Emission Measurement

Operator: Sky

File :3

Data :#1


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:13:55

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1831.663	53.33	peak	-5.47	47.86	74.00	150	330	-26.14	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8875

Radiated Emission Measurement

Operator: Sky

File :3

Data :#5


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:15:05

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1831.663	61.45	peak	-5.47	55.98	74.00	150	13	-18.02	nonrestricted

\*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Sky

File :3

Data :#2


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:19:25

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3663.327	53.21	peak	-1.41	51.80	74.00	150	2	-22.20	
*	3663.327	52.18	AVG	-1.41	50.77	54.00	150	2	-3.23	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#6


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:20:32

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3663.327	51.13	peak	-1.41	49.72	74.00	150	174	-24.28	
*	3663.327	50.16	AVG	-1.41	48.75	54.00	150	174	-5.25	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#3


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:22:08

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 915.25MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	5490.982	47.03	peak	1.38	48.41	74.00	150	109	-25.59	
	6404.810	49.07	peak	3.81	52.88	74.00	150	111	-21.12	
	7326.653	46.82	peak	5.19	52.01	74.00	150	247	-21.99	
*	7326.653	45.32	AVG	5.19	50.51	54.00	150	247	-3.49	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#7


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:25:17

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 915.25MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4577.154	45.71	peak	-1.17	44.54	74.00	150	47	-29.46	
	5490.982	46.63	peak	1.38	48.01	74.00	150	120	-25.99	
	6404.810	54.41	peak	3.81	58.22	74.00	150	331	-15.78	nonrestricted
	7322.091	53.84	peak	5.21	59.05	74.00	150	175	-14.95	
*	7322.091	47.73	AVG	5.21	52.94	54.00	150	175	-1.06	

\*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#4


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:31:09

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#8


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:32:14

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin





Radiated Emission Measurement

Operator: Sky

File :1

Data :#1


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 10:47:37

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22206-21923

M/N:

Test Mode : TX 927.25MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	142.0040	30.03	peak	-6.88	23.15	74.00	100	47	-50.85	
*	216.1322	33.80	peak	-10.04	23.76	74.00	100	110	-50.24	



Radiated Emission Measurement

Operator: Sky

File :1

Data :#2


Date: 2022/6/29

Temperature:28.3 °C

90.0 dBuV/m

Time: 下午 10:49:50

Humidity:57.3 %



Site : Chamber

Condition : FCC Restriction Band 30-300

EUT : W6M22206-21923

M/N:

Test Mode : TX 927.25MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	91.6834	39.15	peak	-12.39	26.76	74.00	100	31	-47.24	
*	167.9760	34.04	peak	-10.33	23.71	43.50	100	207	-19.79	



Radiated Emission Measurement

Operator: Sky

File :2

Data :#1


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 下午 01:27:54

Humidity:50.1 %



Site : Chamber

Condition : FCC Restriction Band 300-1000

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	468.3367	35.67	peak	-3.24	32.43	74.00	100	4	-41.57	
	706.8134	31.53	peak	0.23	31.76	74.00	100	311	-42.24	



Radiated Emission Measurement

Operator: Sky

File :2

Data :#2


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 下午 01:29:05

Humidity:50.1 %



Site : Chamber

Condition : FCC Restriction Band 300-1000

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	468.3367	33.42	peak	-3.24	30.18	74.00	100	185	-43.82	
	698.3967	29.05	peak	0.18	29.23	74.00	100	207	-44.77	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#1


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:37:46

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1855.711	54.52	peak	-5.50	49.02	74.00	150	114	-24.98	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#5


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:39:39

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	1855.711	61.12	peak	-5.50	55.62	74.00	150	10	-18.38	nonrestricted

\*:Maximum data x:Over limit !:over margin



Radiated Emission Measurement

Operator: Sky

File :3

Data :#2


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:40:54

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 927.25MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3711.423	54.21	peak	-1.36	52.85	74.00	150	26	-21.15	
*	3711.423	53.27	AVG	-1.36	51.91	54.00	150	26	-2.09	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#6


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:42:09

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	2476.954	44.40	peak	-3.36	41.04	74.00	150	14	-32.96	
	3262.525	42.86	peak	-1.80	41.06	74.00	150	71	-32.94	
	3711.423	50.68	peak	-1.36	49.32	74.00	150	110	-24.68	
*	3711.423	49.35	AVG	-1.36	47.99	54.00	150	110	-6.01	





Radiated Emission Measurement

Operator: Sky

File :3

Data :#3


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:44:09

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	5563.126	52.20	peak	1.10	53.30	74.00	150	184	-20.70	
	6492.986	47.73	peak	2.99	50.72	74.00	150	301	-23.28	
	7422.846	44.66	peak	4.85	49.51	74.00	150	220	-24.49	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#7


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 07:45:23

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : TX 927.25MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	4633.266	46.90	peak	-1.22	45.68	74.00	150	70	-28.32	
	5563.126	49.27	peak	1.10	50.37	74.00	150	114	-23.63	
	6492.986	54.00	peak	2.99	56.99	74.00	150	32	-17.01	nonrestricted
	7417.869	55.16	peak	4.86	60.02	74.00	155	185	-13.98	
*	7417.869	47.35	AVG	4.86	52.21	54.00	155	185	-1.79	

\*:Maximum data x:Over limit !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#4


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 08:03:41

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#8


Date: 2022/7/1

Temperature:28.8 °C

90.0 dBuV/m

Time: 下午 08:04:58

Humidity:57.4 %



Site : Chamber

Condition : FCC\_part 15 RE-Class C\_Above 1GHz\_PK

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : TX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Radiated Emission Measurement

Operator: Sky

File :1

Data :#1


Date: 2022/8/16

Temperature:29.6 °C

80.0 dBuV/m

Time: 下午 01:37:18

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_30-1000MHz

EUT : W6M22206-21923

M/N:

Test Mode : RX 902.75MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	150.5210	29.67	peak	-7.86	21.81	43.50	116	159	-21.69	
	272.9860	33.45	peak	-6.54	26.91	46.00	100	326	-19.09	
	480.9820	29.01	peak	-3.15	25.86	46.00	102	62	-20.14	
*	648.1563	30.00	peak	0.66	30.66	46.00	100	32	-15.34	



Radiated Emission Measurement

Operator: Sky

File :1

Data :#2


Date: 2022/8/16

Temperature:29.6 °C

80.0 dBuV/m

Time: 下午 01:38:50

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_30-1000MHz

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	57.2144	33.73	peak	-11.04	22.69	40.00	123	50	-17.31	
	150.5210	33.32	peak	-7.86	25.46	43.50	104	221	-18.04	
	245.7715	31.38	peak	-7.86	23.52	46.00	112	90	-22.48	
	271.0421	30.39	peak	-6.61	23.78	46.00	107	6	-22.22	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#1


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:11:20

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : RX 902.75MHz

Note :

Polarization: *Horizontal*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3595.190	40.38	peak	-1.42	38.96	74.00	150	110	-35.04	
*	5601.202	40.04	peak	0.96	41.00	74.00	150	130	-33.00	

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#5


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:12:12

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : RX 902.75MHz

Note :

Polarization: **Vertical**

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	5334.669	41.97	peak	1.01	42.98	74.00	150	40	-31.02	
*	7312.625	40.99	peak	5.25	46.24	74.00	150	330	-27.76	

\*:Maximum data    x:Over limit    !:over margin





Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#2


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:11:32

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#6


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:12:24

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#3


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:11:53

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#7


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:12:46

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

EUT : W6M22206-21923

M/N:

Test Mode : RX 902.75MHz

Note :

Polarization: *Vertical*

Power : 120 Va.c.

Distance: 3m

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#4


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:12:00

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#8


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:12:53

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 902.75MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Radiated Emission Measurement

Operator: Sky

File :1

Data :#1

Date: 2022/8/16

Temperature:29.6 °C

80.0 dBuV/m

Time: 下午 01:40:36

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	152.4648	29.86	peak	-8.12	21.74	43.50	132	6	-21.76	
	237.9960	31.44	peak	-8.34	23.10	46.00	104	41	-22.90	
*	271.0421	34.54	peak	-6.61	27.93	46.00	110	118	-18.07	
	480.9820	29.66	peak	-3.15	26.51	46.00	129	2	-19.49	



Radiated Emission Measurement

Operator: Sky

File :1

Data :#2


Date: 2022/8/16

Temperature:29.6 °C

80.0 dBuV/m

Time: 下午 01:42:04

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_30-1000MHz

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	150.5210	32.20	peak	-7.86	24.34	43.50	119	50	-19.16	
	243.8277	30.91	peak	-8.00	22.91	46.00	124	221	-23.09	
	416.8337	28.25	peak	-3.67	24.58	46.00	104	6	-21.42	
	480.9820	29.40	peak	-3.15	26.25	46.00	130	90	-19.75	





Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#1


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:16:37

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3482.966	41.25	peak	-2.40	38.85	74.00	150	18	-35.15	
*	5769.539	40.13	peak	1.67	41.80	74.00	150	304	-32.20	

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#5


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:17:28

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3735.471	42.11	peak	-1.21	40.90	74.00	150	20	-33.10	
*	6120.240	40.18	peak	2.68	42.86	74.00	150	130	-31.14	

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#2


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:16:49

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#6


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:17:41

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#3


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:17:10

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#7


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:18:03

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#4


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:17:17

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#8


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:18:10

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 915.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin





Radiated Emission Measurement

Operator: Sky

File :1

Data :#1


Date: 2022/8/16

Temperature:29.6 °C

80.0 dBuV/m

Time: 下午 01:43:55

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_30-1000MHz

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	272.9860	35.02	peak	-6.54	28.48	46.00	124	29	-17.52	
	298.2565	31.78	peak	-5.90	25.88	46.00	105	127	-20.12	
	480.9820	29.56	peak	-3.15	26.41	46.00	131	101	-19.59	
*	648.1563	29.64	peak	0.66	30.30	46.00	110	6	-15.70	



Radiated Emission Measurement

Operator: Sky

File :1

Data :#2


Date: 2022/8/16

Temperature:29.6 °C

80.0 dBuV/m

Time: 下午 01:45:30

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_30-1000MHz

Polarization: **Vertical**

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
*	148.5772	32.77	peak	-7.63	25.14	43.50	102	57	-18.36	
	272.9860	31.08	peak	-6.54	24.54	46.00	118	311	-21.46	
	480.9820	29.92	peak	-3.15	26.77	46.00	125	100	-19.23	
	547.0741	28.54	peak	-1.85	26.69	46.00	109	6	-19.31	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#1


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:20:21

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3805.611	41.14	peak	-0.78	40.36	74.00	150	103	-33.64	
*	6120.240	40.04	peak	2.68	42.72	74.00	150	64	-31.28	



Radiated Emission Measurement

Operator: Sky

File :3

Data :#5


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:21:13

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
	3707.415	41.98	peak	-1.38	40.60	74.00	150	39	-33.40	
*	6414.830	40.13	peak	3.71	43.84	74.00	150	112	-30.16	



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#2


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:20:33

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#6


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:21:25

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#3


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:20:55

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#7


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:21:47

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin





Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#4


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:21:01

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Horizontal*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin



Address:6F.,No.58,Ln 188,Ruey Kuang Rd,Neihu,Taipei  
 Tel:+886-2-6606-8877  
 Fax:+886-2-6606-8879

Radiated Emission Measurement

Operator: Sky

File :3

Data :#8


Date: 2022/8/16

Temperature:29.6 °C

90.0 dBuV/m

Time: 上午 10:21:54

Humidity:50.1 %



Site : Chamber

Condition : FCC\_part 15 RE-Class B\_Above 1GHz\_PK

Polarization: *Vertical*

EUT : W6M22206-21923

Power : 120 Va.c.

M/N:

Distance: 3m

Test Mode : RX 927.25MHz

Note :

Mk.	Frequency (MHz)	Reading (dBuV)	Detector	Corr. factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Ant.Pos (cm)	Tab.Pos (deg.)	Margin (dB)	Comment
-----	-----------------	----------------	----------	---------------------	-----------------	----------------	--------------	----------------	-------------	---------

\*:Maximum data    x:Over limit    !:over margin