



FCC RADIO TEST REPORT

FCC ID : HLZA24002
Equipment : Tablet PC
Brand Name : acer
Model Name : A24002
Marketing Name : Acer Iconia Tab A8 ,A8-11
Applicant : Acer Incorporated
8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist.,
New Taipei City 22181, Taiwan (R.O.C)
Manufacturer : Acer Incorporated
8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist.,
New Taipei City 22181, Taiwan (R.O.C)
Standard : FCC Part 15 Subpart C §15.247

The product was received on Mar. 27, 2024 and testing was performed from Apr. 19, 2024 to May 14, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report..... 3

Summary of Test Result..... 4

1 General Description..... 5

 1.1 Product Feature of Equipment Under Test..... 5

 1.2 Modification of EUT 5

 1.3 Testing Location 5

 1.4 Applicable Standards..... 5

2 Test Configuration of Equipment Under Test 6

 2.1 Carrier Frequency Channel 6

 2.2 Test Mode..... 7

 2.3 Connection Diagram of Test System..... 8

 2.4 Support Unit used in test configuration and system 8

 2.5 EUT Operation Test Setup 9

 2.6 Measurement Results Explanation Example..... 9

3 Test Result..... 10

 3.1 Number of Channel Measurement 10

 3.2 Hopping Channel Separation Measurement 11

 3.3 Dwell Time Measurement..... 12

 3.4 20dB and 99% Bandwidth Measurement 13

 3.5 Output Power Measurement..... 14

 3.6 Conducted Band Edges Measurement..... 15

 3.7 Conducted Spurious Emission Measurement 16

 3.8 Radiated Band Edges and Spurious Emission Measurement 17

 3.9 AC Conducted Emission Measurement..... 21

 3.10 Antenna Requirements..... 23

4 List of Measuring Equipment 24

5 Measurement Uncertainty 25

Appendix A. Conducted Test Results

Appendix B. AC Conducted Emission Test Result

Appendix C. Radiated Spurious Emission

Appendix D. Radiated Spurious Emission Plots

Appendix E. Duty Cycle Plots

Appendix F. Setup Photographs



History of this test report

Report No.	Version	Description	Issue Date
FR432784A	01	Initial issue of report	May 31, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1) 15.247(b)(4)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	9.99 dB under the limit at 185.79 MHz
3.9	15.207	AC Conducted Emission	Pass	9.94 dB under the limit at 0.59 MHz
3.10	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Lewis Ho

Report Producer: Clio Lo



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax, and Wi-Fi 5GHz 802.11a/n/ac/ax.	
Antenna Type WLAN: FPC Antenna Bluetooth: FPC Antenna	

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	2.37

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH22-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-




2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst plane, and the worst mode of radiated spurious emissions is Bluetooth 1Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
Conducted Test Cases	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth BR 1Mbps GFSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
	Mode 3: CH78_2480 MHz		
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN (2.4GHz) Link + MPEG4 + Earphone + USB Cable (Charging from AC Adapter)		
Remark: For Radiated Test Cases, the worst mode data rate 1Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 1Mbps, and no other significantly frequencies found in conducted spurious emission.			

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Earphone + Mic	Samsung	Ecouteur	N/A	Unshielded, 1.8 m	N/A
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A



2.5 EUT Operation Test Setup

The RF test items, utility “adb command 1.0.36” was installed in EUT which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300 kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

3.1.4 Test Setup



3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

3.2 Hopping Channel Separation Measurement

3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels;
RBW = 300 kHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.

3.3 Dwell Time Measurement

3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Dwell Time

Please refer to Appendix A.

3.4 20dB and 99% Bandwidth Measurement

3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Use the following spectrum analyzer settings for 20 dB Bandwidth measurement.
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;
RBW \geq 1-5% of the 99% bandwidth; VBW \geq 3 * RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
6. Measure and record the results in the test report.

3.4.4 Test Setup



3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.

3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.5 Output Power Measurement

3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.
If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

3.5.4 Test Setup



3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.

3.6 Conducted Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set the maximum power setting and enable the EUT to transmit continuously.
3. Set RBW = 100 kHz, VBW = 300 kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2 and 3.
5. Measure and record the results in the test report.

3.6.4 Test Setup



3.6.5 Test Result of Conducted Band Edges

Please refer to Appendix A.

3.6.6 Test Result of Conducted Hopping Mode Band Edges

Please refer to Appendix A.

3.7 Conducted Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.7.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, scan up through 10th harmonic. All harmonics / spurious must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.7.4 Test Setup



3.7.5 Test Result of Conducted Spurious Emission

Please refer to Appendix A.



3.8 Radiated Band Edges and Spurious Emission Measurement

3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics / spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.8.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.




3.8.3 Test Procedures

1. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
2. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT is arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz, RBW = 1 MHz for $f > 1$ GHz ; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
 - (3) For average measurement: use duty cycle correction factor method per 15.35(c).
Duty cycle = On time/100 milliseconds
On time = $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$
Where N_1 is number of type 1 pulses, L_1 is length of type 1 pulses, etc.
Average Emission Level = Peak Emission Level + $20 * \log$ (Duty cycle)
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.
8. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-“.


Note: The average levels are calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from $20 \log$ (dwell time/100ms). This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.

3.8.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.8.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.8.7 Duty Cycle

Please refer to Appendix E.

3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.9 AC Conducted Emission Measurement

3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.9.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.9.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.9.4 Test Setup



3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.10 Antenna Requirements

3.10.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.10.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9kHz~30MHz	Feb. 23, 2024	May 02, 2024~ May 14, 2024	Feb. 22, 2025	Radiation (03CH22-HY)
Bilog Antenna with 6dB	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Oct. 15, 2023	May 02, 2024~ May 14, 2024	Oct. 14, 2024	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 15, 2023	May 02, 2024~ May 14, 2024	Jul. 14, 2024	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18E N	1GHz~18GHz	Jul. 12, 2023	May 02, 2024~ May 14, 2024	Jul. 11, 2024	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1224	18GHz~40GHz	Jul. 10, 2023	May 02, 2024~ May 14, 2024	Jul. 09, 2024	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 28, 2023	May 02, 2024~ May 14, 2024	Sep. 27, 2024	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060801	18-40GHz	Jun. 27, 2023	May 02, 2024~ May 14, 2024	Jun. 26, 2024	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY60241058	10Hz~44GHz	Jul. 06, 2023	May 02, 2024~ May 14, 2024	Jul. 05, 2024	Radiation (03CH22-HY)
Hygrometer	TECPEL	DTM-303A	TP211469	N/A	Jan. 03, 2024	May 02, 2024~ May 14, 2024	Jan. 02, 2025	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
Software	Audix	E3 6.09824_2019122	RK-002347	N/A	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	May 02, 2024~ May 14, 2024	Mar. 05, 2025	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804390/2,804611/2,804615/2	N/A	Oct. 24, 2023	May 02, 2024~ May 14, 2024	Oct. 23, 2024	Radiation (03CH22-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Apr. 23, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Apr. 23, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz-200MHz	Oct. 20, 2023	Apr. 23, 2024	Oct. 19, 2024	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 14, 2024	Apr. 23, 2024	Mar. 13, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	Apr. 23, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	Apr. 23, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	Apr. 23, 2024	Sep. 19, 2024	Conduction (CO07-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	Apr. 19, 2024~ May 09, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Meter	Agilent	E4416A	GB41292344	N/A	Jul. 12, 2023	Apr. 19, 2024~ May 09, 2024	Jul. 11, 2024	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US40441548	50MHz~18GHz	Jul. 12, 2023	Apr. 19, 2024~ May 09, 2024	Jul. 11, 2024	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Jan. 24, 2024	Apr. 19, 2024~ May 09, 2024	Jan. 23, 2025	Conducted (TH05-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.44 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Shiming Liu/Junyu Zhou	Temperature:	21~25	°C
Test Date:	2024/4/19~2024/5/9	Relative Humidity:	51~54	%

TEST RESULTS DATA									
20dB and 99% Occupied Bandwidth and Hopping Channel Separation									
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.946	0.832	1.007	0.6307	Pass
DH	1Mbps	1	39	2441	0.947	0.833	0.990	0.6314	Pass
DH	1Mbps	1	78	2480	0.948	0.834	0.999	0.6320	Pass
2DH	2Mbps	1	0	2402	1.304	1.177	1.003	0.8694	Pass
2DH	2Mbps	1	39	2441	1.305	1.178	0.990	0.8702	Pass
2DH	2Mbps	1	78	2480	1.305	1.178	1.016	0.8700	Pass
3DH	3Mbps	1	0	2402	1.274	1.164	1.003	0.8494	Pass
3DH	3Mbps	1	39	2441	1.274	1.164	0.990	0.8492	Pass
3DH	3Mbps	1	78	2480	1.271	1.164	1.007	0.8472	Pass

TEST RESULTS DATA						
Dwell Time						
Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time (hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH5	79	106.670	2.88	0.31	0.4	Pass
DH5 (AFH)	20	53.330	2.88	0.15	0.4	Pass


TEST RESULTS DATA					
Peak Power Table					
DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result
DH1	0	1	6.22	20.97	Pass
	39	1	6.49	20.97	Pass
	78	1	6.48	20.97	Pass
2DH1	0	1	5.57	20.97	Pass
	39	1	5.71	20.97	Pass
	78	1	5.80	20.97	Pass
3DH1	0	1	5.86	20.97	Pass
	39	1	5.98	20.97	Pass
	78	1	6.06	20.97	Pass

TEST RESULTS DATA				
Average Power Table				
(Reporting Only)				
DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)
DH1	0	1	5.84	5.29
	39	1	6.09	5.29
	78	1	6.08	5.29
2DH1	0	1	2.50	5.19
	39	1	2.68	5.19
	78	1	2.87	5.19
3DH1	0	1	2.52	5.17
	39	1	2.69	5.17
	78	1	2.97	5.17

TEST RESULTS DATA			
Number of Hopping Frequency			
Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




Number of Hopping Frequency





Hopping Channel Separation


<1Mbps>






<2Mbps>


Channel Separation Plot on Channel 00 - 01



Channel Separation Plot on Channel 39 - 40




Channel Separation Plot on Channel 77 - 78






<3Mbps>


Channel Separation Plot on Channel 00 - 01



Channel Separation Plot on Channel 39 - 40




Channel Separation Plot on Channel 77 - 78






20dB Bandwidth

<1Mbps>






<2Mbps>






<3Mbps>






99% Occupied Bandwidth

<1Mbps>






<2Mbps>






<3Mbps>






Band Edges

<1Mbps>






<2Mbps>






<3Mbps>






Hopping Mode Band Edges

<1Mbps>






<2Mbps>






<3Mbps>






Conducted Spurious Emission

<1Mbps>






<2Mbps>





<3Mbps>






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	22.2~23.3°C
		Relative Humidity :	42.7~60.1%

EUT Information

Report NO : 432784
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	27.48	55.40	27.92	L1	OFF	19.9
0.161250	42.27	---	65.40	23.13	L1	OFF	19.9
0.171240	---	25.69	54.90	29.21	L1	OFF	19.9
0.171240	41.21	---	64.90	23.69	L1	OFF	19.9
0.185460	---	27.10	54.24	27.14	L1	OFF	19.9
0.185460	42.53	---	64.24	21.71	L1	OFF	19.9
0.229290	---	25.61	52.48	26.87	L1	OFF	19.9
0.229290	39.34	---	62.48	23.14	L1	OFF	19.9
0.278250	---	28.91	50.87	21.96	L1	OFF	19.9
0.278250	40.48	---	60.87	20.39	L1	OFF	19.9
0.296610	---	29.38	50.34	20.96	L1	OFF	19.9
0.296610	41.12	---	60.34	19.22	L1	OFF	19.9
0.316500	---	28.15	49.80	21.65	L1	OFF	19.9
0.316500	40.12	---	59.80	19.68	L1	OFF	19.9
0.415500	---	26.10	47.54	21.44	L1	OFF	19.9
0.415500	39.29	---	57.54	18.25	L1	OFF	19.9
0.446820	---	27.26	46.93	19.67	L1	OFF	19.9
0.446820	41.15	---	56.93	15.78	L1	OFF	19.9
0.476250	---	28.11	46.40	18.29	L1	OFF	19.9

0.476250	40.10	---	56.40	16.30	L1	OFF	19.9
0.510000	---	31.79	46.00	14.21	L1	OFF	19.9
0.510000	42.83	---	56.00	13.17	L1	OFF	19.9
0.530250	---	20.90	46.00	25.10	L1	OFF	19.9
0.530250	39.11	---	56.00	16.89	L1	OFF	19.9
0.586500	---	32.98	46.00	13.02	L1	OFF	19.9
0.586500	46.06	---	56.00	9.94	L1	OFF	19.9
0.639690	---	25.09	46.00	20.91	L1	OFF	19.9
0.639690	40.27	---	56.00	15.73	L1	OFF	19.9
0.735000	---	26.59	46.00	19.41	L1	OFF	19.9
0.735000	38.69	---	56.00	17.31	L1	OFF	19.9
0.878100	---	27.34	46.00	18.66	L1	OFF	19.9
0.878100	38.03	---	56.00	17.97	L1	OFF	19.9
0.996810	---	26.86	46.00	19.14	L1	OFF	19.9
0.996810	39.56	---	56.00	16.44	L1	OFF	19.9
1.056750	---	27.51	46.00	18.49	L1	OFF	19.9
1.056750	40.38	---	56.00	15.62	L1	OFF	19.9
1.115250	---	24.78	46.00	21.22	L1	OFF	19.9
1.115250	39.70	---	56.00	16.30	L1	OFF	19.9
1.191750	---	26.35	46.00	19.65	L1	OFF	19.9
1.191750	40.38	---	56.00	15.62	L1	OFF	19.9
1.243500	---	25.89	46.00	20.11	L1	OFF	19.9
1.243500	38.56	---	56.00	17.44	L1	OFF	19.9
1.310190	---	26.23	46.00	19.77	L1	OFF	19.9
1.310190	38.40	---	56.00	17.60	L1	OFF	19.9
1.363830	---	25.94	46.00	20.06	L1	OFF	19.9
1.363830	37.51	---	56.00	18.49	L1	OFF	19.9
2.139000	---	24.36	46.00	21.64	L1	OFF	20.0
2.139000	37.15	---	56.00	18.85	L1	OFF	20.0
2.728860	---	24.38	46.00	21.62	L1	OFF	20.0
2.728860	35.74	---	56.00	20.26	L1	OFF	20.0
3.605820	---	23.11	46.00	22.89	L1	OFF	20.0
3.605820	35.01	---	56.00	20.99	L1	OFF	20.0
4.884000	---	21.35	46.00	24.65	L1	OFF	20.0
4.884000	32.78	---	56.00	23.22	L1	OFF	20.0
11.893830	---	24.48	50.00	25.52	L1	OFF	20.1
11.893830	35.95	---	60.00	24.05	L1	OFF	20.1
12.741000	---	26.17	50.00	23.83	L1	OFF	20.1
12.741000	37.74	---	60.00	22.26	L1	OFF	20.1
13.564500	---	28.31	50.00	21.69	L1	OFF	20.1
13.564500	40.48	---	60.00	19.52	L1	OFF	20.1
14.954820	---	26.76	50.00	23.24	L1	OFF	20.1
14.954820	37.40	---	60.00	22.60	L1	OFF	20.1
16.701000	---	28.08	50.00	21.92	L1	OFF	20.1
16.701000	40.16	---	60.00	19.84	L1	OFF	20.1
17.636100	---	26.56	50.00	23.44	L1	OFF	20.1
17.636100	37.20	---	60.00	22.80	L1	OFF	20.1
18.426750	---	24.22	50.00	25.78	L1	OFF	20.1
18.426750	32.77	---	60.00	27.23	L1	OFF	20.1

EUT Information

Report NO : 432784
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150270	---	27.75	55.99	28.24	N	OFF	19.9
0.150270	40.18	---	65.99	25.81	N	OFF	19.9
0.188250	---	24.64	54.11	29.47	N	OFF	19.9
0.188250	39.89	---	64.11	24.22	N	OFF	19.9
0.213000	---	23.32	53.09	29.77	N	OFF	19.9
0.213000	39.23	---	63.09	23.86	N	OFF	19.9
0.230010	---	22.82	52.45	29.63	N	OFF	19.9
0.230010	36.85	---	62.45	25.60	N	OFF	19.9
0.372660	---	23.02	48.44	25.42	N	OFF	19.9
0.372660	34.82	---	58.44	23.62	N	OFF	19.9
0.467250	---	23.21	46.56	23.35	N	OFF	19.9
0.467250	36.15	---	56.56	20.41	N	OFF	19.9
0.519000	---	29.70	46.00	16.30	N	OFF	19.9
0.519000	36.90	---	56.00	19.10	N	OFF	19.9
0.555000	---	32.30	46.00	13.70	N	OFF	19.9
0.555000	41.25	---	56.00	14.75	N	OFF	19.9
0.582990	---	29.77	46.00	16.23	N	OFF	19.9
0.582990	41.76	---	56.00	14.24	N	OFF	19.9
0.937500	---	26.84	46.00	19.16	N	OFF	19.9

0.937500	37.83	---	56.00	18.17	N	OFF	19.9
1.041000	---	26.41	46.00	19.59	N	OFF	19.9
1.041000	39.65	---	56.00	16.35	N	OFF	19.9
1.115430	---	26.26	46.00	19.74	N	OFF	19.9
1.115430	41.12	---	56.00	14.88	N	OFF	19.9
1.183380	---	26.90	46.00	19.10	N	OFF	19.9
1.183380	40.42	---	56.00	15.58	N	OFF	19.9
1.284720	---	27.14	46.00	18.86	N	OFF	19.9
1.284720	39.50	---	56.00	16.50	N	OFF	19.9
1.409640	---	26.88	46.00	19.12	N	OFF	19.9
1.409640	37.96	---	56.00	18.04	N	OFF	19.9
1.531050	---	24.61	46.00	21.39	N	OFF	19.9
1.531050	36.71	---	56.00	19.29	N	OFF	19.9
2.222250	---	22.41	46.00	23.59	N	OFF	20.0
2.222250	32.87	---	56.00	23.13	N	OFF	20.0
2.780790	---	25.17	46.00	20.83	N	OFF	20.0
2.780790	35.21	---	56.00	20.79	N	OFF	20.0
3.466500	---	24.44	46.00	21.56	N	OFF	20.0
3.466500	33.33	---	56.00	22.67	N	OFF	20.0
4.830000	---	22.50	46.00	23.50	N	OFF	20.0
4.830000	29.91	---	56.00	26.09	N	OFF	20.0
12.642270	---	21.81	50.00	28.19	N	OFF	20.1
12.642270	34.66	---	60.00	25.34	N	OFF	20.1
13.561440	---	26.22	50.00	23.78	N	OFF	20.1
13.561440	38.95	---	60.00	21.05	N	OFF	20.1
14.919990	---	23.36	50.00	26.64	N	OFF	20.1
14.919990	36.30	---	60.00	23.70	N	OFF	20.1
16.071000	---	23.88	50.00	26.12	N	OFF	20.2
16.071000	36.89	---	60.00	23.11	N	OFF	20.2
17.359620	---	24.22	50.00	25.78	N	OFF	20.2
17.359620	36.43	---	60.00	23.57	N	OFF	20.2



Appendix C. Radiated Spurious Emission

Test Engineer :	BANK Lin, Ken Kuo and Karl Hou	Temperature :	21.3~23.5°C
		Relative Humidity :	51~58%

2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BT CH00 2402MHz		2388.54	47.38	-26.62	74	44.3	26.91	8.52	32.35	100	30	P	H	
		2388.54	22.59	-31.41	54	-	-	-	-	-	-	A	H	
	*	2402	104.86	-	-	101.68	27	8.54	32.36	100	30	P	H	
	*	2402	80.07	-	-	-	-	-	-	-	-	A	H	
													H	
														H
			2388.96	43.91	-30.09	74	40.83	26.91	8.52	32.35	296	16	P	V
			2388.96	19.12	-34.88	54	-	-	-	-	-	-	A	V
	*		2402	102.06	-	-	98.88	27	8.54	32.36	296	16	P	V
	*		2402	77.27	-	-	-	-	-	-	-	-	A	V
													V	
													V	
BT CH 39 2441MHz		2387	42.71	-31.29	74	39.61	26.93	8.52	32.35	119	27	P	H	
		2387	17.92	-36.08	54	-	-	-	-	-	-	A	H	
	*	2441	105.44	-	-	102.4	26.81	8.61	32.38	119	27	P	H	
	*	2441	80.65	-	-	-	-	-	-	-	-	A	H	
			2489.5	43.48	-30.52	74	40.29	26.9	8.7	32.41	119	27	P	H
			2489.5	18.69	-35.31	54	-	-	-	-	-	-	A	H
			2374.12	41.86	-32.14	74	38.71	27	8.49	32.34	286	14	P	V
			2374.12	17.07	-36.93	54	-	-	-	-	-	-	A	V
	*		2441	101.93	-	-	98.89	26.81	8.61	32.38	286	14	P	V
	*		2441	77.14	-	-	-	-	-	-	-	-	A	V
			2492.72	41.43	-32.57	74	38.21	26.93	8.71	32.42	286	14	P	V
			2492.72	16.64	-37.36	54	-	-	-	-	-	-	A	V



BT CH 78 2480MHz	*	2480	104.64	-	-	101.47	26.9	8.68	32.41	100	27	P	H
	*	2480	79.85	-	-	-	-	-	-	-	-	A	H
		2483.64	48.57	-25.43	74	45.39	26.9	8.69	32.41	100	27	P	H
		2483.64	23.78	-30.22	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	100.98	-	-	97.81	26.9	8.68	32.41	298	316	P	V
	*	2480	76.19	-	-	-	-	-	-	-	-	A	V
		2483.72	45.74	-28.26	74	42.56	26.9	8.69	32.41	298	316	P	V
		2483.72	20.95	-33.05	54	-	-	-	-	-	-	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz
BT (Harmonic @ 3m)

BT	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 00 2402MHz		4804	52.32	-21.68	74	40.47	32.32	13.03	33.5	109	108	P	H	
		4804	27.53	-26.47	54	-	-	-	-	-	-	A	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			4804	54.72	-19.28	74	42.87	32.32	13.03	33.5	298	249	P	V
			4804	29.93	-24.07	54	-	-	-	-	-	-	A	V
														V
														V
														V
														V
														V
														V
													V	
													V	



BT	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 39 2441MHz		4882	46.77	-27.23	74	34.63	32.56	13.07	33.49	100	24	P	H	
		4882	21.98	-32.02	54	-	-	-	-	-	-	A	H	
		7323	51.43	-22.57	74	33.76	37.5	16.02	35.85	100	63	P	H	
		7323	26.64	-27.36	54	-	-	-	-	-	-	A	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			4882	47.76	-26.24	74	35.62	32.56	13.07	33.49	291	257	P	V
			4882	22.97	-31.03	54	-	-	-	-	-	-	A	V
			7323	52.36	-21.64	74	34.69	37.5	16.02	35.85	100	128	P	V
			7323	27.57	-26.43	54	-	-	-	-	-	-	A	V
														V
														V
														V
													V	
													V	
													V	
													V	
													V	
													V	



BT	Note	Frequency (MHz)	Level (dB μ V/m)	Margin (dB)	Limit Line (dB μ V/m)	Read Level (dB μ V)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BT CH 78 2480MHz		4960	50.04	-23.96	74	37.7	32.7	13.11	33.47	100	121	P	H	
		4960	25.25	-28.75	54	-	-	-	-	-	-	A	H	
		7440	53.5	-20.5	74	35.96	37.32	16.15	35.93	100	64	P	H	
		7440	28.71	-25.29	54	-	-	-	-	-	-	A	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
BT CH 78 2480MHz		4960	51.98	-22.02	74	39.64	32.7	13.11	33.47	285	265	P	V	
		4960	27.19	-26.81	54	-	-	-	-	-	-	A	V	
		7440	52.05	-21.95	74	34.51	37.32	16.15	35.93	100	123	P	V	
		7440	27.26	-26.74	54	-	-	-	-	-	-	A	V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
	Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. 												



Emission above 18GHz

2.4GHz BT (SHF)

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BT SHF		24916	42.26	-31.74	74	42.7	39.5	19.73	59.67	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			23579	42.2	-31.8	74	44.28	39.02	18.97	60.07	-	-	P
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.												



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz BT LF		98.04	28.56	-14.94	43.5	43.66	15.84	1.78	32.72	-	-	P	H	
		185.79	33.51	-9.99	43.5	48.92	14.78	2.48	32.67	-	-	P	H	
		263.01	31.71	-14.29	46	41.35	20.15	2.89	32.68	-	-	P	H	
		300.7	31.21	-14.79	46	41.65	19.21	3.07	32.72	-	-	P	H	
		605.2	35.22	-10.78	46	37.81	25.81	4.41	32.81	-	-	P	H	
		995.1	34.98	-19.02	54	29.68	30.47	5.74	30.91	-	-	P	H	
														H
														H
														H
														H
														H
														H
			96.96	28.52	-14.98	43.5	43.79	15.7	1.76	32.73	-	-	P	V
			147.18	30.84	-12.66	43.5	44.17	17.24	2.14	32.71	-	-	P	V
			175.53	28.85	-14.65	43.5	43.8	15.31	2.42	32.68	-	-	P	V
			307	27.61	-18.39	46	37.94	19.29	3.1	32.72	-	-	P	V
			601	32.96	-13.04	46	35.62	25.76	4.39	32.81	-	-	P	V
			949.6	35.62	-10.38	46	30.61	30.88	5.54	31.41	-	-	P	V
														V
														V
													V	
													V	
													V	

Remark

- No other spurious found.
- All results are PASS against limit line.
- The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is Margin line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BT CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Margin (dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Margin (dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

Peak measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots



Test Engineer :	BANK Lin, Ken Kuo and Karl Hou	Temperature :	21.3~23.5°C
		Relative Humidity :	51~58%

2.4GHz 2400~2483.5MHz




BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
Peak	<p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE2004A18EN_230712 HORIZONTAL : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto</p>	<p>Site : 03CH22-HY Condition : PEAK_74 3m LE2004A18EN_230712 HORIZONTAL : RBW:3000.000kHz VBW:3000.000kHz SWT:Auto</p>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Vertical	Fundamental
Peak	 <p>Site : 09CH22-HY Condition : PEAK_SE_74 3m LEZC04A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Site : 09CH22-HY Condition : PEAK_74 3m LEZC04A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH39 2441MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZC04A1BEN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LEZC04A1BEN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZC04A1BEN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
Vertical		Fundamental
Peak	<p>Date: 2024-05-02</p> <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZC04A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	<p>Date: 2024-05-02</p> <p>Site : 03CH22-HY Condition : PEAK_74 3m LEZC04A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Peak	<p>Date: 2024-05-02</p> <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZC04A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Horizontal	Fundamental
Peak	 <p>Site : 09CH22-HY Condition : PEAK_BE_74 3m LEZC04A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 09CH22-HY Condition : PEAK_74 3m LEZC04A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH78 2480MHz	
	Vertical	Fundamental
Peak	 <p>Site : 09CH22-HY Condition : PEAK_BE_74 3m LEZC04A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 09CH22-HY Condition : PEAK_74 3m LEZC04A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





2.4GHz 2400~2483.5MHz



BT (Harmonic @ 3m)

BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH22-1HY Condition : PEAK_74 3m LEZC04A18EN_230712 HORIZONTAL</p>	 <p>Site : 03CH22-1HY Condition : PEAK_74 3m LEZC04A18EN_230712 VERTICAL</p>





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
<p>10.6G ~18G Avg.</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 VERTICAL</p>





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BT CH39 2441MHz		
Horizontal		Vertical
Peak Avg.	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2C04A1BEN_230712 HORIZONTAL</p>	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2C04A1BEN_230712 VERTICAL</p>





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH39 2441MHz	
	Horizontal	Vertical
<p>10.6G ~18G Avg.</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL :</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 VERTICAL :</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2C04A1BEN_230712 HORIZONTAL</p>	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2C04A1BEN_230712 VERTICAL</p>





BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH78 2480MHz	
	Horizontal	Vertical
<p>10.6G ~18G Avg.</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL :</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 VERTICAL :</p>



Emission above 18GHz



2.4GHz BT (SHF @ 1m)

BT	2.4GHz 2400~2483.5MHz	
	BT SHF	
	Horizontal	Vertical
<p>Peak Avg.</p>	<p>Level (dBuV/m) Date: 2024-05-03</p>  <p>Site : 03CH22-HY Condition : PEAK_74 1m SHF_1224_230710 HORIZONTAL</p>	<p>Level (dBuV/m) Date: 2024-05-03</p>  <p>Site : 03CH22-HY Condition : PEAK_74 1m SHF_1224_230710 VERTICAL</p>




Emission below 1GHz

2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
	BT LF	
	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH22-1HY Condition : QP 3m BIL0663304_Z31015_16 HORIZONTAL</p>	 <p>Site : 03CH22-1HY Condition : QP 3m BIL0663304_Z31015_16 VERTICAL</p>

Appendix E. Duty Cycle Plots



Note:

1. Worst case Duty cycle = on time/100 milliseconds = $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor = $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. DH5 has the highest duty cycle worst case and is reported.

Duty Cycle Correction Factor Consideration for AFH mode:

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the on time period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period. $[100 \text{ ms} / 57.6 \text{ ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100 \text{ ms}) = -24.79 \text{ dB}$$