



FCC RADIO TEST REPORT

FCC ID : HLZA24002
Equipment : Tablet PC
Brand Name : acer
Model Name : A24002
Marketing Name : Acer Iconia Tab A8 ,A8-11
Applicant : Acer Incorporated
8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist.,
New Taipei City 22181, Taiwan (R.O.C)
Manufacturer : Acer Incorporated
8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist.,
New Taipei City 22181, Taiwan (R.O.C)
Standard : FCC Part 15 Subpart C §15.247

The product was received on Mar. 27, 2024 and testing was performed from Apr. 19, 2024 to May 14, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report..... 3

Summary of Test Result..... 4

1 General Description..... 5

 1.1 Product Feature of Equipment Under Test..... 5

 1.2 Modification of EUT 5

 1.3 Testing Location 5

 1.4 Applicable Standards..... 5

2 Test Configuration of Equipment Under Test 6

 2.1 Carrier Frequency Channel 6

 2.2 Test Mode..... 7

 2.3 Connection Diagram of Test System..... 8

 2.4 Support Unit used in test configuration and system 8

 2.5 EUT Operation Test Setup 9

 2.6 Measurement Results Explanation Example..... 9

3 Test Result..... 10

 3.1 6dB and 99% Bandwidth Measurement 10

 3.2 Output Power Measurement..... 11

 3.3 Power Spectral Density Measurement 12

 3.4 Conducted Band Edges and Spurious Emission Measurement 13

 3.5 Radiated Band Edges and Spurious Emission Measurement 14

 3.6 AC Conducted Emission Measurement..... 18

 3.7 Antenna Requirements 20

4 List of Measuring Equipment 21

5 Measurement Uncertainty 22

Appendix A. Conducted Test Results

Appendix B. AC Conducted Emission Test Result

Appendix C. Radiated Spurious Emission

Appendix D. Radiated Spurious Emission Plots

Appendix E. Duty Cycle Plots

Appendix F. Setup Photographs



History of this test report

Report No.	Version	Description	Issue Date
FR432784B	01	Initial issue of report	May 31, 2024



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(2)	6dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.247(b)(3) 15.247(b)(4)	Output Power	Pass	-
3.3	15.247(e)	Power Spectral Density	Pass	-
3.4	15.247(d)	Conducted Band Edges and Spurious Emission	Pass	-
3.5	15.247(d)	Radiated Band Edges and Spurious Emission	Pass	3.95 dB under the limit at 4804.00 MHz
3.6	15.207	AC Conducted Emission	Pass	9.94 dB under the limit at 0.59 MHz
3.7	15.203	Antenna Requirement	Pass	-

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Lewis Ho**Report Producer: Ming Chen**



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature
General Specs Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n/ax, and Wi-Fi 5GHz 802.11a/n/ac/ax.
Antenna Type WLAN: FPC Antenna Bluetooth: FPC Antenna

Antenna information		
2400 MHz ~ 2483.5 MHz	Peak Gain (dBi)	2.37

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.2 Modification of EUT

No modifications made to the EUT during the testing.

1.3 Testing Location

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, CO07-HY, 03CH22-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.4 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	21	2444
	1	2404	22	2446
	2	2406	23	2448
	3	2408	24	2450
	4	2410	25	2452
	5	2412	26	2454
	6	2414	27	2456
	7	2416	28	2458
	8	2418	29	2460
	9	2420	30	2462
	10	2422	31	2464
	11	2424	32	2466
	12	2426	33	2468
	13	2428	34	2470
	14	2430	35	2472
	15	2432	36	2474
	16	2434	37	2476
	17	2436	38	2478
	18	2438	39	2480
	19	2440	-	-
20	2442	-	-	




2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases	
Test Item	Data Rate / Modulation
Conducted Test Cases	Bluetooth – LE / GFSK
	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps
	Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps
	Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
	Mode 4: Bluetooth Tx CH00_2402 MHz_2Mbps
	Mode 5: Bluetooth Tx CH19_2440 MHz_2Mbps
	Mode 6: Bluetooth Tx CH39_2480 MHz_2Mbps
Radiated Test Cases	Mode 1: Bluetooth Tx CH00_2402 MHz_1Mbps Mode 2: Bluetooth Tx CH19_2440 MHz_1Mbps Mode 3: Bluetooth Tx CH39_2480 MHz_1Mbps
AC Conducted Emission	Mode 1 :Bluetooth Link + WLAN (2.4GHz) Link + MPEG4 + Earphone + USB Cable (Charging from AC Adapter)
Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.	

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	WLAN AP	ASUS	RT-AC52	MSQ-RTAC4A00	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Earphone + Mic	Samsung	Ecouteur	N/A	Unshielded, 1.8 m	N/A
5.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A



2.5 EUT Operation Test Setup

The RF test items, utility “adb command 1.0.36” was installed in EUT which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * RBW$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB Bandwidth

Please refer to Appendix A.

3.1.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna of directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator.
3. The path loss is compensated to the results for each measurement.
4. Set the maximum power setting and enable the EUT to transmit continuously.
5. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth (VBW) = 10 kHz. In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6 dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.
7. The Measured power density (dBm)/ 100 kHz is a reference level and is used as 20 dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission

All harmonics/spurious must be at least 30 dB down from the highest emission level within the authorized band.

3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedure

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW = 300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges Plots

Please refer to Appendix A.

3.4.6 Test Result of Conducted Spurious Emission Plots

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.5.2 Measuring Instruments


Please refer to the measuring equipment list in this test report.

**3.5.3 Test Procedures**


1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-“.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW = 3 MHz for $f \geq 1$ GHz for peak measurement.
For average measurement:
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz



3.5.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix C and D.

3.5.7 Duty Cycle

Please refer to Appendix E.

3.5.8 Test Result of Radiated Spurious Emission (30 MHz ~ 10th Harmonic)

Please refer to Appendix C and D.



3.6 AC Conducted Emission Measurement

3.6.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.6.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.6.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9 kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.6.4 Test Setup



3.6.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



3.7 Antenna Requirements

3.7.1 Standard Applicable

The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

3.7.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	TECEPEL	DTM-303A	TP201996	N/A	Nov. 07, 2023	Apr. 19, 2024~ May 08, 2024	Nov. 06, 2024	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	17100015SNO 35 (NO:109)	10MHz~6GHz	Jan. 15, 2024	Apr. 19, 2024~ May 08, 2024	Jan. 14, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV3044	101466	10HZ~44GHZ	Jan. 24, 2024	Apr. 19, 2024~ May 08, 2024	Jan. 23, 2025	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 23, 2023	Apr. 19, 2024~ May 08, 2024	Aug. 22, 2024	Conducted (TH05-HY)
AC Power Source	ACPOWER	AFC-11003G	F317040033	N/A	N/A	Apr. 23, 2024	N/A	Conduction (CO07-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Apr. 23, 2024	N/A	Conduction (CO07-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-F N	9561-F N00373	9kHz~200MHz	Oct. 20, 2023	Apr. 23, 2024	Oct. 19, 2024	Conduction (CO07-HY)
RF Cable	HUBER + SUHNER	RG 214/U	1358175	9kHz~30MHz	Mar. 14, 2024	Apr. 23, 2024	Mar. 13, 2025	Conduction (CO07-HY)
Two-Line V-Network	TESEQ	NNB 51	45051	N/A	Mar. 10, 2024	Apr. 23, 2024	Mar. 09, 2025	Conduction (CO07-HY)
Four-Line V-Network	TESEQ	NNB 52	36122	N/A	Mar. 07, 2024	Apr. 23, 2024	Mar. 06, 2025	Conduction (CO07-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102317	9kHz~3.6GHz	Sep. 20, 2023	Apr. 23, 2024	Sep. 19, 2024	Conduction (CO07-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100315	9kHz~30MHz	Feb. 23, 2024	May 02, 2024~ May 14, 2024	Feb. 22, 2025	Radiation (03CH22-HY)
Bilog Antenna with 6dB	TESEQ & WOKEN	CBL 6111D & 00802N1D-06	63304 & 002	30MHz~1GHz	Oct. 15, 2023	May 02, 2024~ May 14, 2024	Oct. 14, 2024	Radiation (03CH22-HY)
Amplifier	SONOMA	310N	421581	N/A	Jul. 15, 2023	May 02, 2024~ May 14, 2024	Jul. 14, 2024	Radiation (03CH22-HY)
Double Ridged Guide Horn Antenna	RFSPIN	DRH18-E	LE2C04A18E N	1GHz~18GHz	Jul. 12, 2023	May 02, 2024~ May 14, 2024	Jul. 11, 2024	Radiation (03CH22-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1224	18GHz~40GHz	Jul. 10, 2023	May 02, 2024~ May 14, 2024	Jul. 09, 2024	Radiation (03CH22-HY)
Amplifier	EMEC	EM01G18GA	060877	N/A	Sep. 28, 2023	May 02, 2024~ May 14, 2024	Sep. 27, 2024	Radiation (03CH22-HY)
Preamplifier	EMEC	EM18G40G	060801	18-40GHz	Jun. 27, 2023	May 02, 2024~ May 14, 2024	Jun. 26, 2024	Radiation (03CH22-HY)
Signal Analyzer	Keysight	N9010B	MY60241058	10Hz~44GHz	Jul. 06, 2023	May 02, 2024~ May 14, 2024	Jul. 05, 2024	Radiation (03CH22-HY)
Hygrometer	TECEPEL	DTM-303A	TP211469	N/A	Jan. 03, 2024	May 02, 2024~ May 14, 2024	Jan. 02, 2025	Radiation (03CH22-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
Software	Audix	E3 6.09824_2019 122	RK-002347	N/A	N/A	May 02, 2024~ May 14, 2024	N/A	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	803951/2	9kHz~30MHz	Mar. 06, 2024	May 02, 2024~ May 14, 2024	Mar. 05, 2025	Radiation (03CH22-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	804390/2,804 611/2,804615/ 2	N/A	Oct. 24, 2023	May 02, 2024~ May 14, 2024	Oct. 23, 2024	Radiation (03CH22-HY)



5 Measurement Uncertainty

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.44 dB
---	---------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.5 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.4 dB
---	--------

Appendix A. Test Result of Conducted Test Items

Test Engineer:	Junyu Jhou and Wei Shun	Temperature:	21~25	°C
Test Date:	2024/4/19~2024/5/8	Relative Humidity:	51~54	%

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	1Mbps	1	0	2402	1.022	0.710	0.50	Pass
BLE	1Mbps	1	19	2440	1.021	0.710	0.50	Pass
BLE	1Mbps	1	39	2480	1.022	0.712	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	1Mbps	1	0	2402	5.00	30.00	2.37	7.37	36.00	Pass
BLE	1Mbps	1	19	2440	5.30	30.00	2.37	7.67	36.00	Pass
BLE	1Mbps	1	39	2480	5.20	30.00	2.37	7.57	36.00	Pass

TEST RESULTS DATA
Peak Power Density

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	1Mbps	1	0	2402	5.18	-9.77	2.37	8.00	Pass
BLE	1Mbps	1	19	2440	5.37	-9.55	2.37	8.00	Pass
BLE	1Mbps	1	39	2480	5.42	-9.51	2.37	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Occupied BW (MHz)	6dB BW (MHz)	6dB BW Limit (MHz)	Pass/Fail
BLE	2Mbps	1	0	2402	2.040	1.246	0.50	Pass
BLE	2Mbps	1	19	2440	2.041	1.246	0.50	Pass
BLE	2Mbps	1	39	2480	2.044	1.248	0.50	Pass

TEST RESULTS DATA
Average Power Table

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)	Conducted Power Limit (dBm)	DG (dBi)	EIRP Power (dBm)	EIRP Power Limit (dBm)	Pass /Fail
BLE	2Mbps	1	0	2402	5.00	30.00	2.37	7.37	36.00	Pass
BLE	2Mbps	1	19	2440	5.30	30.00	2.37	7.67	36.00	Pass
BLE	2Mbps	1	39	2480	5.20	30.00	2.37	7.57	36.00	Pass

TEST RESULTS DATA
Peak Power Density


Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Peak PSD (dBm /100kHz)	Peak PSD (dBm /3kHz)	DG (dBi)	Peak PSD Limit (dBm /3kHz)	Pass/Fail
BLE	2Mbps	1	0	2402	4.72	-12.44	2.37	8.00	Pass
BLE	2Mbps	1	19	2440	4.88	-12.30	2.37	8.00	Pass
BLE	2Mbps	1	39	2480	4.93	-12.26	2.37	8.00	Pass

Note: PSD (dBm/ 100kHz) is a reference level used for Conducted Band Edges and Conducted Spurious Emission 30dBc limit.




6dB Bandwidth

<1Mbps>






<2Mbps>





99% Occupied Bandwidth


<1Mbps>






<2Mbps>


99% Occupied Bandwidth Plot on Channel 00



99% Occupied Bandwidth Plot on Channel 19




99% Occupied Bandwidth Plot on Channel 39






Power Spectral Density (dBm/3kHz)

<1Mbps>





<2Mbps>






Band Edge and Conducted Spurious Emission


<1Mbps>

Channel 00


100kHz PSD reference Level Plot




Low Channel Plot



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 19

100kHz PSD reference Level Plot




Mid Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




High Channel Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot







<2Mbps>

Channel 00


100kHz PSD reference Level Plot




Low Channel Plot



Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 19

100kHz PSD reference Level Plot




Mid Channel Plot

Spurious Emission 30MHz~1GHz Plot




Spurious Emission 1GHz~26.5GHz Plot






Channel 39


100kHz PSD reference Level Plot




High Channel Plot



Spurious Emission 30MHz~1GHz Plot



Spurious Emission 1GHz~26.5GHz Plot






Appendix B. AC Conducted Emission Test Results

Test Engineer :	Louis Chung	Temperature :	22.2~23.3°C
		Relative Humidity :	42.7~60.1%

EUT Information

Report NO : 432784
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.161250	---	27.48	55.40	27.92	L1	OFF	19.9
0.161250	42.27	---	65.40	23.13	L1	OFF	19.9
0.171240	---	25.69	54.90	29.21	L1	OFF	19.9
0.171240	41.21	---	64.90	23.69	L1	OFF	19.9
0.185460	---	27.10	54.24	27.14	L1	OFF	19.9
0.185460	42.53	---	64.24	21.71	L1	OFF	19.9
0.229290	---	25.61	52.48	26.87	L1	OFF	19.9
0.229290	39.34	---	62.48	23.14	L1	OFF	19.9
0.278250	---	28.91	50.87	21.96	L1	OFF	19.9
0.278250	40.48	---	60.87	20.39	L1	OFF	19.9
0.296610	---	29.38	50.34	20.96	L1	OFF	19.9
0.296610	41.12	---	60.34	19.22	L1	OFF	19.9
0.316500	---	28.15	49.80	21.65	L1	OFF	19.9
0.316500	40.12	---	59.80	19.68	L1	OFF	19.9
0.415500	---	26.10	47.54	21.44	L1	OFF	19.9
0.415500	39.29	---	57.54	18.25	L1	OFF	19.9
0.446820	---	27.26	46.93	19.67	L1	OFF	19.9
0.446820	41.15	---	56.93	15.78	L1	OFF	19.9
0.476250	---	28.11	46.40	18.29	L1	OFF	19.9

0.476250	40.10	---	56.40	16.30	L1	OFF	19.9
0.510000	---	31.79	46.00	14.21	L1	OFF	19.9
0.510000	42.83	---	56.00	13.17	L1	OFF	19.9
0.530250	---	20.90	46.00	25.10	L1	OFF	19.9
0.530250	39.11	---	56.00	16.89	L1	OFF	19.9
0.586500	---	32.98	46.00	13.02	L1	OFF	19.9
0.586500	46.06	---	56.00	9.94	L1	OFF	19.9
0.639690	---	25.09	46.00	20.91	L1	OFF	19.9
0.639690	40.27	---	56.00	15.73	L1	OFF	19.9
0.735000	---	26.59	46.00	19.41	L1	OFF	19.9
0.735000	38.69	---	56.00	17.31	L1	OFF	19.9
0.878100	---	27.34	46.00	18.66	L1	OFF	19.9
0.878100	38.03	---	56.00	17.97	L1	OFF	19.9
0.996810	---	26.86	46.00	19.14	L1	OFF	19.9
0.996810	39.56	---	56.00	16.44	L1	OFF	19.9
1.056750	---	27.51	46.00	18.49	L1	OFF	19.9
1.056750	40.38	---	56.00	15.62	L1	OFF	19.9
1.115250	---	24.78	46.00	21.22	L1	OFF	19.9
1.115250	39.70	---	56.00	16.30	L1	OFF	19.9
1.191750	---	26.35	46.00	19.65	L1	OFF	19.9
1.191750	40.38	---	56.00	15.62	L1	OFF	19.9
1.243500	---	25.89	46.00	20.11	L1	OFF	19.9
1.243500	38.56	---	56.00	17.44	L1	OFF	19.9
1.310190	---	26.23	46.00	19.77	L1	OFF	19.9
1.310190	38.40	---	56.00	17.60	L1	OFF	19.9
1.363830	---	25.94	46.00	20.06	L1	OFF	19.9
1.363830	37.51	---	56.00	18.49	L1	OFF	19.9
2.139000	---	24.36	46.00	21.64	L1	OFF	20.0
2.139000	37.15	---	56.00	18.85	L1	OFF	20.0
2.728860	---	24.38	46.00	21.62	L1	OFF	20.0
2.728860	35.74	---	56.00	20.26	L1	OFF	20.0
3.605820	---	23.11	46.00	22.89	L1	OFF	20.0
3.605820	35.01	---	56.00	20.99	L1	OFF	20.0
4.884000	---	21.35	46.00	24.65	L1	OFF	20.0
4.884000	32.78	---	56.00	23.22	L1	OFF	20.0
11.893830	---	24.48	50.00	25.52	L1	OFF	20.1
11.893830	35.95	---	60.00	24.05	L1	OFF	20.1
12.741000	---	26.17	50.00	23.83	L1	OFF	20.1
12.741000	37.74	---	60.00	22.26	L1	OFF	20.1
13.564500	---	28.31	50.00	21.69	L1	OFF	20.1
13.564500	40.48	---	60.00	19.52	L1	OFF	20.1
14.954820	---	26.76	50.00	23.24	L1	OFF	20.1
14.954820	37.40	---	60.00	22.60	L1	OFF	20.1
16.701000	---	28.08	50.00	21.92	L1	OFF	20.1
16.701000	40.16	---	60.00	19.84	L1	OFF	20.1
17.636100	---	26.56	50.00	23.44	L1	OFF	20.1
17.636100	37.20	---	60.00	22.80	L1	OFF	20.1
18.426750	---	24.22	50.00	25.78	L1	OFF	20.1
18.426750	32.77	---	60.00	27.23	L1	OFF	20.1

EUT Information

Report NO : 432784
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150270	---	27.75	55.99	28.24	N	OFF	19.9
0.150270	40.18	---	65.99	25.81	N	OFF	19.9
0.188250	---	24.64	54.11	29.47	N	OFF	19.9
0.188250	39.89	---	64.11	24.22	N	OFF	19.9
0.213000	---	23.32	53.09	29.77	N	OFF	19.9
0.213000	39.23	---	63.09	23.86	N	OFF	19.9
0.230010	---	22.82	52.45	29.63	N	OFF	19.9
0.230010	36.85	---	62.45	25.60	N	OFF	19.9
0.372660	---	23.02	48.44	25.42	N	OFF	19.9
0.372660	34.82	---	58.44	23.62	N	OFF	19.9
0.467250	---	23.21	46.56	23.35	N	OFF	19.9
0.467250	36.15	---	56.56	20.41	N	OFF	19.9
0.519000	---	29.70	46.00	16.30	N	OFF	19.9
0.519000	36.90	---	56.00	19.10	N	OFF	19.9
0.555000	---	32.30	46.00	13.70	N	OFF	19.9
0.555000	41.25	---	56.00	14.75	N	OFF	19.9
0.582990	---	29.77	46.00	16.23	N	OFF	19.9
0.582990	41.76	---	56.00	14.24	N	OFF	19.9
0.937500	---	26.84	46.00	19.16	N	OFF	19.9

0.937500	37.83	---	56.00	18.17	N	OFF	19.9
1.041000	---	26.41	46.00	19.59	N	OFF	19.9
1.041000	39.65	---	56.00	16.35	N	OFF	19.9
1.115430	---	26.26	46.00	19.74	N	OFF	19.9
1.115430	41.12	---	56.00	14.88	N	OFF	19.9
1.183380	---	26.90	46.00	19.10	N	OFF	19.9
1.183380	40.42	---	56.00	15.58	N	OFF	19.9
1.284720	---	27.14	46.00	18.86	N	OFF	19.9
1.284720	39.50	---	56.00	16.50	N	OFF	19.9
1.409640	---	26.88	46.00	19.12	N	OFF	19.9
1.409640	37.96	---	56.00	18.04	N	OFF	19.9
1.531050	---	24.61	46.00	21.39	N	OFF	19.9
1.531050	36.71	---	56.00	19.29	N	OFF	19.9
2.222250	---	22.41	46.00	23.59	N	OFF	20.0
2.222250	32.87	---	56.00	23.13	N	OFF	20.0
2.780790	---	25.17	46.00	20.83	N	OFF	20.0
2.780790	35.21	---	56.00	20.79	N	OFF	20.0
3.466500	---	24.44	46.00	21.56	N	OFF	20.0
3.466500	33.33	---	56.00	22.67	N	OFF	20.0
4.830000	---	22.50	46.00	23.50	N	OFF	20.0
4.830000	29.91	---	56.00	26.09	N	OFF	20.0
12.642270	---	21.81	50.00	28.19	N	OFF	20.1
12.642270	34.66	---	60.00	25.34	N	OFF	20.1
13.561440	---	26.22	50.00	23.78	N	OFF	20.1
13.561440	38.95	---	60.00	21.05	N	OFF	20.1
14.919990	---	23.36	50.00	26.64	N	OFF	20.1
14.919990	36.30	---	60.00	23.70	N	OFF	20.1
16.071000	---	23.88	50.00	26.12	N	OFF	20.2
16.071000	36.89	---	60.00	23.11	N	OFF	20.2
17.359620	---	24.22	50.00	25.78	N	OFF	20.2
17.359620	36.43	---	60.00	23.57	N	OFF	20.2



Appendix C. Radiated Spurious Emission

Test Engineer :	BANK Lin, Ken Kuo and Karl Hou	Temperature :	21.3~23.5°C
		Relative Humidity :	51~58%

2.4GHz 2400~2483.5MHz

BLE (Band Edge @ 3m)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
BLE CH 00 2402MHz		2379.615	51.28	-22.72	74	38.29	27	18.34	32.35	117	37	P	H	
		2369.955	41.76	-12.24	54	28.78	27	18.32	32.34	117	37	A	H	
	*	2402	105.04	-	-	92.02	27	18.38	32.36	117	37	P	H	
	*	2402	104.45	-	-	91.43	27	18.38	32.36	117	37	A	H	
													H	
													H	
			2327.85	52.24	-21.76	74	39.21	27.1	18.25	32.32	353	321	P	V
			2383.605	41.34	-12.66	54	28.38	26.96	18.35	32.35	353	321	A	V
	*		2402	101.43	-	-	88.41	27	18.38	32.36	353	321	P	V
	*		2402	100.81	-	-	87.79	27	18.38	32.36	353	321	A	V
														V
													V	
BLE CH 19 2440MHz		2370	51.24	-22.76	74	38.26	27	18.32	32.34	113	33	P	H	
		2375.92	41.42	-12.58	54	28.43	27	18.34	32.35	113	33	A	H	
	*	2440	105.93	-	-	93.06	26.8	18.45	32.38	113	33	P	H	
	*	2440	105.37	-	-	92.5	26.8	18.45	32.38	113	33	A	H	
			2492.56	50.82	-23.18	74	37.76	26.93	18.55	32.42	113	33	P	H
			2487.92	41.43	-12.57	54	28.4	26.9	18.54	32.41	113	33	A	H
			2380.4	50.01	-23.99	74	37.02	27	18.34	32.35	397	297	P	V
			2379.44	40.86	-13.14	54	27.87	27	18.34	32.35	397	297	A	V
	*		2440	101.41	-	-	88.54	26.8	18.45	32.38	397	297	P	V
	*		2440	100.82	-	-	87.95	26.8	18.45	32.38	397	297	A	V
			2495.28	51.56	-22.44	74	38.48	26.95	18.55	32.42	397	297	P	V
		2486.64	41.26	-12.74	54	28.23	26.9	18.54	32.41	397	297	A	V	



BLE CH 39 2480MHz	*	2480	105.36	-	-	92.35	26.9	18.52	32.41	114	34	P	H
	*	2480	104.84	-	-	91.83	26.9	18.52	32.41	114	34	A	H
		2484.28	51.52	-22.48	74	38.5	26.9	18.53	32.41	114	34	P	H
		2483.52	43	-11	54	29.98	26.9	18.53	32.41	114	34	A	H
													H
													H
	*	2480	100.63	-	-	87.62	26.9	18.52	32.41	399	82	P	V
	*	2480	100.01	-	-	87	26.9	18.52	32.41	399	82	A	V
		2483.52	50.96	-23.04	74	37.94	26.9	18.53	32.41	399	82	P	V
		2483.64	42.14	-11.86	54	29.12	26.9	18.53	32.41	399	82	A	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz

BLE (Harmonic @ 3m)

BLE	Note	Frequency (MHz)	Level (dBμV/m)	Margin (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 00 2402MHz		4804	52.14	-21.86	74	40.29	32.32	13.03	33.5	110	108	P	H	
		4804	46.53	-7.47	54	34.68	32.32	13.03	33.5	110	108	A	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			4804	54.65	-19.35	74	42.8	32.32	13.03	33.5	295	255	P	V
			4804	50.05	-3.95	54	38.2	32.32	13.03	33.5	295	255	A	V
														V
														V
														V
														V
														V
														V
													V	



BLE	Note	Frequency (MHz)	Level (dBµV/m)	Margin (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 19 2440MHz		4880	47.31	-26.69	74	35.17	32.56	13.07	33.49	113	115	P	H	
		4880	37.74	-16.26	54	25.6	32.56	13.07	33.49	113	115	A	H	
		7320	52.57	-21.43	74	34.91	37.5	16.01	35.85	100	64	P	H	
		7320	42.55	-11.45	54	24.89	37.5	16.01	35.85	100	64	A	H	
													H	
													H	
													H	
														H
														H
														H
														H
														H
			4880	47.84	-26.16	74	35.7	32.56	13.07	33.49	300	251	P	V
			4880	40.05	-13.95	54	27.91	32.56	13.07	33.49	300	251	A	V
			7320	52.21	-21.79	74	34.55	37.5	16.01	35.85	100	123	P	V
			7320	42.35	-11.65	54	24.69	37.5	16.01	35.85	100	123	A	V
														V
														V
														V
														V
													V	
													V	
													V	



BLE	Note	Frequency (MHz)	Level (dBµV/m)	Margin (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
BLE CH 39 2480MHz		4960	51.45	-22.55	74	39.11	32.7	13.11	33.47	100	8	P	H	
		4960	45.46	-8.54	54	33.12	32.7	13.11	33.47	100	8	A	H	
		7440	53.21	-20.79	74	35.67	37.32	16.15	35.93	100	4	P	H	
		7440	45.12	-8.88	54	27.58	37.32	16.15	35.93	100	4	A	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			4960	52.94	-21.06	74	40.6	32.7	13.11	33.47	279	255	P	V
			4960	48.34	-5.66	54	36	32.7	13.11	33.47	279	255	A	V
			7440	52.27	-21.73	74	34.73	37.32	16.15	35.93	100	128	P	V
			7440	43.04	-10.96	54	25.5	37.32	16.15	35.93	100	128	A	V
														V
														V
														V
														V
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission above 18GHz

2.4GHz BLE (SHF)

BT	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
2.4GHz BLE SHF		24678	41.93	-32.07	74	42.93	39.51	19.63	60.14	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			18014	42.39	-31.61	74	53.76	37.72	15.12	64.21	-	-	P
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.												



Emission below 1GHz

2.4GHz BLE (LF)

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
2.4GHz BLE LF		98.58	27.77	-15.73	43.5	42.82	15.89	1.78	32.72	-	-	P	H	
		187.41	32.73	-10.77	43.5	48.16	14.76	2.48	32.67	-	-	P	H	
		252.48	30.95	-15.05	46	42	18.77	2.84	32.66	-	-	P	H	
		342	30.98	-15.02	46	40.32	20.13	3.28	32.75	-	-	P	H	
		601	34.78	-11.22	46	37.44	25.76	4.39	32.81	-	-	P	H	
		971.3	35.37	-18.63	54	30.07	30.85	5.63	31.18	-	-	P	H	
														H
														H
														H
														H
														H
														H
			96.96	28.18	-15.32	43.5	43.45	15.7	1.76	32.73	-	-	P	V
			146.37	30.92	-12.58	43.5	44.22	17.28	2.13	32.71	-	-	P	V
			176.88	28.59	-14.91	43.5	43.64	15.2	2.43	32.68	-	-	P	V
			308.4	27.41	-18.59	46	37.71	19.32	3.11	32.73	-	-	P	V
			605.2	32.77	-13.23	46	35.36	25.81	4.41	32.81	-	-	P	V
			967.1	35.2	-18.8	54	29.89	30.92	5.61	31.22	-	-	P	V
														V
														V
													V	
													V	
													V	

Remark

- No other spurious found.
- All results are PASS against limit line.
- The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is Margin line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

BLE	Note	Frequency	Level	Margin	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
BLE CH 00 2402MHz		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Margin (dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Margin (dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 74(dBμV/m)
= -18.55(dB)

For Average Limit @ 2390MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)
= 43.54 (dBμV/m)
2. Margin (dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 43.54(dBμV/m) – 54(dBμV/m)
= -10.46(dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix D. Radiated Spurious Emission Plots

Test Engineer :	BANK Lin, Ken Kuo and Karl Hou	Temperature :	21.3~23.5°C
		Relative Humidity :	51~58%





Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz





BLE (Band Edge @ 3m)

BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
Horizontal		Fundamental
Peak	 <p>Level (dBm/Vm) vs Frequency (MHz) plot showing a peak at approximately 2402 MHz. The y-axis ranges from 10 to 140 dBm/Vm, and the x-axis ranges from 2310 to 2415 MHz. A red horizontal line is drawn at approximately 75 dBm/Vm.</p> <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	 <p>Level (dBm/Vm) vs Frequency (MHz) plot showing a peak at approximately 2402 MHz. The y-axis ranges from 10 to 140 dBm/Vm, and the x-axis ranges from 1000 to 3000 MHz. A red horizontal line is drawn at approximately 75 dBm/Vm, labeled 'PEAK_74'.</p> <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>
Avg.	 <p>Level (dBm/Vm) vs Frequency (MHz) plot showing an average spectrum with a peak at approximately 2402 MHz. The y-axis ranges from 10 to 140 dBm/Vm, and the x-axis ranges from 2310 to 2415 MHz. A red horizontal line is drawn at approximately 55 dBm/Vm.</p> <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>	 <p>Level (dBm/Vm) vs Frequency (MHz) plot showing an average spectrum with a peak at approximately 2402 MHz. The y-axis ranges from 10 to 140 dBm/Vm, and the x-axis ranges from 1000 to 3000 MHz. A red horizontal line is drawn at approximately 55 dBm/Vm, labeled 'AVG_54'.</p> <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:2.700kHz SWT:Auto</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH00 2402MHz		
Vertical		Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	 <p>Site : 03CH22-HY Condition : AV6_BE_54 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:2700KHz SWT:Auto</p>	 <p>Site : 03CH22-HY Condition : AV6_54 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:2700KHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
	Horizontal	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	 <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:2.700KHz SWT:Auto</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:2.700KHz SWT:Auto</p>





BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Horizontal	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE2C04A18EN_230712 HORIZONTAL : RBW:1000.000kHz VBW:2700kHz SWT:Auto</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - L		
Vertical		Fundamental
Peak	<p>Date: 2024-05-03</p> <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Date: 2024-05-03</p> <p>Site : 03CH22-HY Condition : PEAK_74 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	<p>Date: 2024-05-03</p> <p>Site : 03CH22-HY Condition : AV6_BE_54 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:2700KHz SWT:Auto</p>	<p>Date: 2024-05-03</p> <p>Site : 03CH22-HY Condition : AV6_54 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:2700KHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH19 2440MHz - R		
	Vertical	Fundamental
Peak	 <p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LE2C04A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p>	Left blank
Avg.	 <p>Site : 03CH22-HY Condition : AVG_BE_54 3m LE2C04A18EN_230712 VERTICAL : RBW:1000.000kHz VBW:2700kHz SWT:Auto</p>	Left blank



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Fundamental
Peak	<p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZ004A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH22-HY Condition : PEAK_74 3m LEZ004A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	<p>Site : 03CH22-HY Condition : AVG_BE_54 3m LEZ004A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:2700KHz SWT:Auto</p>	<p>Site : 03CH22-HY Condition : AVG_54 3m LEZ004A18EN_230712 HORIZONTAL : RBW:1000.000KHz VBW:2700KHz SWT:Auto</p>



BLE	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BLE CH39 2480MHz		
Vertical		Fundamental
Peak	<p>Site : 03CH22-HY Condition : PEAK_BE_74 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH22-HY Condition : PEAK_74 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Avg.	<p>Site : 03CH22-HY Condition : AV6_BE_54 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:2.700KHz SWT:Auto</p>	<p>Site : 03CH22-HY Condition : AV6_54 3m LEZ004A18EN_230712 VERTICAL : RBW:1000.000KHz VBW:2.700KHz SWT:Auto</p>





2.4GHz 2400~2483.5MHz



BLE (Harmonic @ 3m)

BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH00 2402MHz	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH22-1HY Condition : PEAK_74 3m LE2C04A18EN_230712 HORIZONTAL</p>	<p>Site : 03CH22-1HY Condition : PEAK_74 3m LE2C04A18EN_230712 VERTICAL</p>





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BLE CH00 2402MHz		
	Horizontal	Vertical
<p>10.6G ~18G Avg.</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL :</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 VERTICAL :</p>





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH19 2440MHz	
	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2004A18EN_230712 HORIZONTAL</p>	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2004A18EN_230712 VERTICAL</p>





BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BLE CH19 2440MHz		
	Horizontal	Vertical
<p>10.6G ~18G Avg.</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL :</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 VERTICAL :</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BLE CH39 2480MHz		
	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2004A18EN_230712 HORIZONTAL</p>	 <p>Site : 03CH22-HY Condition : PEAK_74 3m LE2004A18EN_230712 VERTICAL</p>



BLE	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BLE CH39 2480MHz	
	Horizontal	Vertical
<p>10.6G ~18G Avg.</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 HORIZONTAL :</p>	 <p>Site : 03CH22-HY Condition : AVG_54 3m LE2C04A18EN_230712 VERTICAL :</p>



Emission above 18GHz



2.4GHz BLE (SHF @ 1m)

BLE	2.4GHz 2400~2483.5MHz	
	BLE SHF	
	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH22-1FY Condition : PEAK_74 1m SHF_1224_230710 HORIZONTAL</p>	<p>Site : 03CH22-1FY Condition : PEAK_74 1m SHF_1224_230710 VERTICAL</p>



Emission below 1GHz

2.4GHz BLE (LF)

BLE	2.4GHz 2400~2483.5MHz	
	BLE LF	
	Horizontal	Vertical
QP / Peak	 <p>Site : 03CH22-1HY Condition : QP 3m BIL0663304_231015_16 HORIZONTAL</p>	 <p>Site : 03CH22-1HY Condition : QP 3m BIL0663304_231015_16 VERTICAL</p>



Appendix E. Duty Cycle Plots

Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
Bluetooth - LE for 1Mbps	60.26	376	2.66	2.7KHz

