



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of raise you wish to raise. A failure to raise such insue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specification, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.



Table of Contents

Rele	ase Control Record	3
1	Certificate of Conformity	4
2	RF Exposure	5
	Limits For Maximum Permissible Exposure (MPE) Mpe Calculation Formula Classification	. 5
3	Calculation Result Of Maximum Conducted Power	. 6



Release Control Record					
Issue No.	Description			Date Issued	
SA150304E02A					
	Description Original release.			Date Issued Apr. 21, 2015	
Poport No : SA150204E		Page No. 2/6		rt Format Varsion: 6.1.1	



1 Certificate of C	Certificate of Conformity				
Product:	DLP Projector				
Brand:	Acer				
Test Model:	K138ST				
Series Model:	L224, CWX1428, LK-W16				
Sample Status:	ENGINEERING SAMPLE				
Applicant:	Acer Incorporated				
Test Date:	Mar. 27, 2015				
Standards:	FCC Part 2 (Section 2.1091)				
	KDB 447498 D03				
	IEEE C95.1				
The above equipme	nt has been tested by Bureau Veritas Consumer Products Services (H.K.) Ltd.,				
Taoyuan Branch, an	d found compliance with the requirement of the above standards. The test record, data				
evaluation & Equipme	ent Under Test (EUT) configurations represented herein are true and accurate accounts				

of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by :	<u> </u>	Date:	Apr. 21, 2015
	Claire Kuan / Specialist		
Approved by :	May Chen / Manager	Date:	Apr. 21, 2015
			s. V



2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

		Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)		
	Limits For General Population / Uncontrolled Exposure					
300-1500			F/1500	30		
1500-100,000			1.0	30		

F = Frequency in MHz

2.2 MPE Calculation Formula

 $Pd = (Pout^*G) / (4^*pi^*r^2)$

where

 $Pd = power density in mW/cm^{2}$

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



3 Calculation Result of Maximum Conducted Power

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2402-2480	5.395	0.03	20	0.00108	1

--- END ---