

5.1.4 Test Data:

Power Line Conducted Emissions (Hot) Channel 1, 6, 11


Operator:JerryChiou

Temperature(C):23

Humidity(%):56

04:10:26PM,Friday,July16,2004

Frequency MHz	LISNLoss (dB)	CableLoss (dB)	QPCorrt. Amp.(dBuV)	QPLimit (dBuV)	QPMargin (dB)	AVECorrt. Amp.(dBuV)	AVELimit (dBuV)	AVEMargin (dB)
0.2039	0.10	0.05	46.60	64.46	-17.86	33.55	54.46	-20.91
0.53583	0.12	0.07	46.30	56.00	-9.70	36.15	46.00	-9.85
0.60525	0.13	0.07	43.63	56.00	-12.37	36.43	46.00	-9.57
0.6463	0.14	0.07	42.27	56.00	-13.73	32.03	46.00	-13.97
0.70966	0.15	0.07	41.90	56.00	-14.10	34.99	46.00	-11.01
1.30463	0.27	0.08	36.51	56.00	-19.49	21.47	46.00	-24.53
1.69671	0.23	0.08	39.99	56.00	-16.01	25.85	46.00	-20.15
1.8005	0.22	0.09	34.98	56.00	-21.02	24.24	46.00	-21.76
2.35501	0.20	0.10	34.67	56.00	-21.33	19.48	46.00	-26.52
2.65881	0.20	0.11	34.90	56.00	-21.10	21.31	46.00	-24.69



Power Line Conducted Emissions (Neutral) Channel 1, 6, 11


Operator:JerryChiou

Temperature(C):23

04:02:12PM, Friday, July 16, 2004

Humidity(%):56

Frequency	LISN Loss	Cable Loss	QPCorrt.	QPLimit	QPMargin	AVECorrt.	AVELimit	AVEMargin
MHz	(dB)	(dB)	Amp.(dBuV)	(dBuV)	(dB)	Amp.(dBuV)	(dBuV)	(dB)
0.21191	0.10	0.05	51.65	64.23	-12.58	40.12	54.23	-14.11
0.50028	0.12	0.07	45.02	56.00	-10.98	35.24	46.00	-10.76
0.54693	0.12	0.07	43.49	56.00	-12.51	30.98	46.00	-15.02
0.60413	0.13	0.07	43.35	56.00	-12.65	35.65	46.00	-10.35
0.60831	0.13	0.07	42.46	56.00	-13.54	34.32	46.00	-11.68
1.72529	0.20	0.08	39.29	56.00	-16.71	24.37	46.00	-21.63
2.37353	0.20	0.10	35.51	56.00	-20.49	21.06	46.00	-24.94
2.51793	0.20	0.10	32.33	56.00	-23.67	22.81	46.00	-23.19
3.86286	0.20	0.14	33.99	56.00	-22.01	18.97	46.00	-27.03
4.061	0.20	0.14	32.81	56.00	-23.19	19.63	46.00	-26.37



* NOTE: During the test, the EMI receiver was set to Max. Hold then switch the EUT Channel between 1, 6, 11 to get the maximum reading of all these channels.
 Margin = Amplitude + Insertion Loss - Limit
 A margin of -8dB means that the emission is 8dB below the limit

5.2 Bandwidth for DSSS [Section 15.247 (a)(2)]

5.2.1 Test Procedure

The Transmitter output of EUT was connected to the spectrum analyzer. The 6 dB bandwidth of the fundamental frequency was measured. The setting of spectrum analyzer is as follows

Equipment mode	Spectrum analyzer
Detector function	Peak mode
RBW	100KHz
VBW	100KHz

5.2.2 Test Setup



5.2.3 Test Data:

6dB Bandwidth

Temp. (deg. C): 25


Test Engr: Mailes Hsieh Humidity (%): 50

Chennel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (MHz)	Pass/Fail
1	2412	16.6	0.5	Pass
6	2437	16.6	0.5	Pass
11	2462	16.6	0.5	Pass


Channel 1:



Channel 6:



Channel 11:



5.3 DSSS Maximum Peak Output Power [Section 15.247 (b)(1)]

5.3.1 Test Procedure

The Transmitter output of EUT was connected to the peak power analyzer.

5.3.2 Test Setup



5.3.3 Test Data

Maximum Peak Output Power

Temp. (deg. C): 25

Test Engr: Mailes Hsieh

Humidity (%): 50

Channel	Frequency (Mhz)	Analyzer Reading (dBm)	Cable Loss (dB)	Peak Power Output (mW)	Peak Power Output (dBm)	Limit (dBm)	Pass/Fail
1	2412	15.437	1.1	45.05	16.537	30	Pass
6	2437	14.874	1.1	39.57	15.974	30	Pass
11	2462	14.486	1.1	36.19	15.586	30	Pass

Note: Two RF output(MAIN & AUX) have been test,the worse data shown above.

5.4 Radiated Emission Measurement [Section [15.247(c)(4)]

5.4.1 EUT Configuration

The equipment under test was set up on the 10 meter chamber with measurement distance of 3 meters. The EUT was placed on a non-conductive table 80cm above ground.

Any changes made to the configuration, or modifications made to the EUT, during testing are noted in the following test record.

5.4.2 Test Procedure

The system was set up as described above, with the EMI diagnostic software running. We found the maximum readings by varying the height of antenna and then rotating the turntable. Both polarization of antenna, horizontal and vertical, are measured.

30M to 1GHz: The highest emissions between 30 MHz to 1000 MHz were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in quasi-peak mode to determine the precise amplitude of the emissions. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission.

1GHz – 25GHz: The highest emissions were also analyzed in details by operating the spectrum analyzer and/or EMI receiver in peak mode to determine the precise amplitude of the emission. While doing so, the interconnecting cables and major parts of the system were moved around, the antenna height was varied between one and four meters, its polarization was varied between vertical and horizontal, and the turntable was slowly rotated, to maximize the emission. During test the EMI receiver and spectrum was setup according to *EMI Receiver/Spectrum Analyzer Configuration*.

For the test of 2nd to 10th harmonics frequencies , the equipment setup was also refer to *EMI Receiver/Spectrum Analyzer Configuration*. The frequencies were tested using Peak mode first, if the test data is higher than the emissions limit, an additional measurement using Average mode will be performed and the average reading will be compared to the limit and record in test report.

5.4.3 EMI Receiver/Spectrum Analyzer Configuration (for the frequencies tested)

Frequency Range Tested:	30MHz~1000MHz
Detector Function:	Quasi-Peak Mode
Resolution Bandwidth (RBW):	120KHz
Video Bandwidth (VBW)	1MHz

Frequency Range Tested:	1GHz – 25 GHz
Detector Function:	Peak Mode
Resolution Bandwidth (RBW):	1MHz
Video Bandwidth (VBW)	1MHz

Frequency Range Tested:	1GHz – 25 GHz
Detector Function:	Average Mode
Resolution Bandwidth (RBW):	1MHz
Video Bandwidth (VBW)	10 Hz

5.4.4 Test Data (30MHz – 1GHz):

30M – 1GHz Open Field Radiated Emissions (Horizontal) Channel 1, 6, 11

Operator:JerryChiou

Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
95.96	20.63	9.49	1.83	0.00	31.96	43.50	-11.54	196.00	187.00
143.49	19.50	9.99	2.31	0.00	31.79	43.50	-11.71	196.00	122.00
299.66	16.84	13.59	3.72	0.00	34.15	46.00	-11.85	103.00	186.00
455.83	19.20	16.44	5.00	0.00	40.64	46.00	-5.36	103.00	7.00
520.82	12.20	18.04	5.40	0.00	35.64	46.00	-10.36	103.00	7.00
585.81	11.51	18.87	5.79	0.00	36.17	46.00	-9.83	103.00	7.00
650.8	7.95	19.00	6.23	0.00	33.17	46.00	-12.83	146.00	157.00
696.39	8.97	19.00	6.52	0.00	34.49	46.00	-11.51	103.00	170.00
716.76	8.67	19.37	6.72	0.00	34.76	46.00	-11.24	103.00	7.00
911.73	12.86	20.56	7.82	0.00	41.24	46.00	-4.76	103.00	284.00

30M – 1GHz Open Field Radiated Emissions (Vertical) Channel 1, 6, 11

Operator:JerryChiou

Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A.Tower	T.Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
324.88	15.48	13.95	4.08	0.00	33.51	46.00	-12.49	152.00	203.00
455.83	21.04	16.44	5.00	0.00	42.47	46.00	-3.53	103.00	190.00
520.82	13.33	18.04	5.40	0.00	36.77	46.00	-9.23	103.00	320.00
585.81	13.41	18.87	5.79	0.00	38.07	46.00	-7.93	103.00	238.00
629.46	9.79	18.96	6.14	0.00	34.89	46.00	-11.11	103.00	190.00
650.8	16.17	19.00	6.23	0.00	41.40	46.00	-4.60	152.00	235.00
695.42	9.52	19.00	6.51	0.00	35.04	46.00	-10.96	152.00	235.00
715.79	8.30	19.35	6.71	0.00	34.35	46.00	-11.65	152.00	24.00
761.38	6.11	20.10	6.95	0.00	33.16	46.00	-12.84	196.00	133.00
911.73	14.36	20.56	7.82	0.00	42.74	46.00	-3.26	196.00	314.00

NOTE: During the Pre-test, the EUT has been tested for Channel 1, 6, 11 transmit from Main and Aux antenna respectively to get all the critical emission frequencies. In the final test all the critical emission frequencies has been tested and the test data are listed above.

Margin = Corrected Amplitude – Limit

Corrected Amplitude = Radiated Amplitude + Antenna Correction Factor + Cable Loss - Pre-Amplifier Gain

A margin of -8dB means that the emission is 8dB below the limit

All frequencies from 30MHz to 1GHz have been tested

5.4.5 Test Data (1GHz – 25 GHz) .

1GHz~ 25 GHz (Horizontal), Channel 1: 2412 MHz

Operator:JerryChiou

RBW:1MHz
Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A. Tower	T. Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1367.13	53.60 pk	26.19	2.21	35.10	46.90 pk	54.00 av	-7.10	101	87
2311.19	52.41 pk	30.94	1.65	35.44	49.55 pk	54.00 av	-4.45	101	141
2693.31	47.32 pk	30.98	1.39	35.46	44.23 pk	54.00 av	-9.77	102	261
3212.79	48.28 pk	31.27	1.56	35.73	45.38 pk	54.00 av	-8.62	103	302
4258.74	40.45 pk	32.98	2.07	39.23	36.26 pk	54.00 av	-17.74	102	63
9721.28	32.59 pk	40.41	3.29	33.84	42.44 pk	54.00 av	-11.56	102	6

1GHz~ 25 GHz (Vertical), Channel 1: 2412 MHz

Operator:JerryChiou

RBW:1MHz
Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A. Tower	T. Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1367.13	53.76 pk	26.19	2.21	35.10	47.06 pk	54.00 av	-6.94	101	87
2311.19	54.48 pk	30.94	1.65	35.44	51.63 pk	54.00 av	-2.37	101	141
2366.13	52.96 pk	30.93	1.48	35.46	49.91 pk	54.00 av	-4.09	101	158
3212.79	54.49 pk	31.27	1.56	35.73	51.59 pk	54.00 av	-2.41	103	302
4258.74	41.91 pk	32.98	2.07	39.23	37.73 pk	54.00 av	-16.27	101	3
8618.38	34.39 pk	41.51	3.01	34.72	44.19 pk	54.00 av	-9.81	102	110

Note:

1. According to ANSI C63.4-2001 8.3.1.2 Notes(1): Where limits are specified by agencies for both average and peak (or quasi-peak) detection, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
2. “*” : Fundamental Frequency
3. “***”: Not in the restricted band, Limit level=Fundamental Emission-20dB
4. “pk”: peak mode
5. “av”: average mode
6. “---”: No meter reading data due to the emission level is smaller than spectrum noise level.
7. The Spectrum noise level+Correction Factor < Limit - 6 dB
8. Margin=Corrected Amplitude – Limit
9. Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss-Pre-Amplifier Gain
10. A margin of -8dB means that the emission is 8dB below the limit.

All frequencies from 1GHz to 25 GHz have been tested.

1GHz~ 25 GHz (Horizontal), Channel 6 : 2437 MHz

Operator:JerryChiou

RBW:1MHz
Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A. Tower	T. Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1367.13	53.27 pk	26.19	2.21	35.10	46.56 pk	54.00 av	-7.44	101	87
2231.27	51.24 pk	30.95	1.89	35.41	48.68 pk	54.00 av	-5.32	101	116
2333.67	51.18 pk	30.93	1.58	35.45	48.24 pk	54.00 av	-5.76	101	148
3247.75	49.02 pk	31.30	1.58	35.80	46.10 pk	54.00 av	-7.90	103	293
4258.74	40.31 pk	32.98	2.07	39.23	36.13 pk	54.00 av	-17.87	102	8
8708.29	34.40 pk	41.37	3.02	34.70	44.09 pk	54.00 av	-9.91	102	89

1GHz~ 25 GHz (Vertical), Channel 6 : 2437 MHz

Operator:JerryChiou

RBW:1MHz
Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A. Tower	T. Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1367.13	54.14 pk	26.19	2.21	35.10	47.44 pk	54.00 av	-6.56	101	87
2333.67	54.74 pk	30.93	1.58	35.45	51.81 pk	54.00 av	-2.19	101	148
2535.96	51.28 pk	30.91	1.37	35.51	48.05 pk	54.00 av	-5.95	102	211
3247.75	54.30 pk	31.30	1.58	35.80	51.39 pk	54.00 av	-2.61	103	293
4258.74	42.86 pk	32.98	2.07	39.23	38.68 pk	54.00 av	-15.32	100	247
8690.31	34.25 pk	41.40	3.02	34.70	43.96 pk	54.00 av	-10.04	102	93

Note:

1. According to ANSI C63.4-2001 8.3.1.2 Notes(1): Where limits are specified by agencies for both average and peak (or quasi-peak) detection, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
2. “*” : Fundamental Frequency
3. “***”: Not in the restricted band, Limit level=Fundamental Emission-20dB
4. “pk”: peak mode
5. “av”: average mode
6. “---”: No meter reading data due to the emission level is smaller than spectrum noise level.
7. The Spectrum noise level+Correction Factor < Limit - 6 dB
8. Margin=Corrected Amplitude – Limit
9. Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss-Pre-Amplifier Gain
10. A margin of -8dB means that the emission is 8dB below the limit.

All frequencies from 1GHz to 25 GHz have been tested.

1GHz~ 25 GHz (Horizontal), Channel 11: 2462 MHz

Operator:JerryChiou

RBW:1MHz
Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A. Tower	T. Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1367.13	53.70 pk	26.19	2.21	35.10	46.99 pk	54.00 av	-7.01	101	87
2286.21	53.09 pk	30.94	1.73	35.43	50.33 pk	54.00 av	-3.67	101	133
2358.64	49.77 pk	30.93	1.51	35.46	46.74 pk	54.00 av	-7.26	101	156
3280.22	49.85 pk	31.32	1.60	35.85	46.92 pk	54.00 av	-7.08	103	285
6912.59	31.24 pk	38.63	3.15	37.44	35.58 pk	54.00 av	-18.42	101	27
8678.32	34.77 pk	41.41	3.02	34.70	44.50 pk	54.00 av	-9.50	102	96

1GHz~ 25 GHz (Vertical), Channel 11 : 2462 MHz

Operator:JerryChiou

RBW:1MHz
Humidity(%):47
Temperature(C):29

Frequency	Rx_R.	Ant_F.	Cab_L.	PreAmpl	Emission	Limit	Margin	A. Tower	T. Table
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	cm	deg
1367.13	54.13 pk	26.19	2.21	35.10	47.42 pk	54.00 av	-6.58	101	87
2358.64	53.50 pk	30.93	1.51	35.46	50.47 pk	54.00 av	-3.53	101	156
2413.59	51.19 pk	30.92	1.54	35.48	48.16 pk	54.00 av	-5.84	101	173
3280.22	54.79 pk	31.32	1.60	35.85	51.86 pk	54.00 av	-2.14	103	285
4258.74	42.54 pk	32.98	2.07	39.23	38.36 pk	54.00 av	-15.64	100	192
8678.32	33.97 pk	41.41	3.02	34.70	43.70 pk	54.00 av	-10.30	102	96

Note:

1. According to ANSI C63.4-2001 8.3.1.2 Notes(1): Where limits are specified by agencies for both average and peak (or quasi-peak) detection, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.
2. “* ”: Fundamental Frequency
3. “***”: Not in the restricted band, Limit level=Fundamental Emission-20dB
4. “pk”: peak mode
5. “av”: average mode
6. “---”: No meter reading data due to the emission level is smaller than spectrum noise level.
7. The Spectrum noise level+Correction Factor < Limit - 6 dB
8. Margin=Corrected Amplitude – Limit
9. Corrected Amplitude=Radiated Amplitude+Antenna Correction Factor+Cable Loss-Pre-Amplifier Gain
10. A margin of -8dB means that the emission is 8dB below the limit.


All frequencies from 1GHz to 25 GHz have been tested.

5.5 Band Edge Measurement

5.5.1 Test Procedure (Conducted)

4. The transmitter output of EUT was connected to the spectrum analyzer.
 Equipment mode: Spectrum analyzer
 Detector function: Peak mode
 SPAN: 100MHz
 RBW: 100KHz
 VBW: 100KHz
 Center frequency: 2.4GHz, 2.4835GHz.
5. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed
6. Find the next peak frequency outside the operation frequency band

5.5.2 Test Setup (Conducted)



5.5.3 Test Data:

Table: Band Edge measurement (Conducted)


Test Engr: Mailes Hsieh		Temp. (deg. C):	25	
		Humidity (%):	50	
Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Carrier - Outsideband Limit: >20dB (dB)	Pass/Fail
1	2413.2	101.33	---	---
Outside band	1399.9	71.84	29.49	Pass
11	2463.2	100.84	---	---
Outside band	2477	66.46	34.38	Pass

Note: Two RF output(MAIN & AUX) have been test,the worse data shown above.

Band Edge Conducted measurement



Band Edge Conducted Measurement



5.5.4 Test Procedure (Radiated)

1. Antenna and Turntable test procedure same as Radiated Emission Measurement.
Equipment mode: Spectrum analyzer
Detector function: Peak mode
SPAN: 100MHz
RBW: 1MHz
VBW: 1MHz
Center frequency: 2.395GHz, 2.48GHz.
2. Using Peak Search to read the peak power of Carrier frequencies after Maximum Hold function is completed.
3. Find the next peak frequency outside the operation frequency band
4. For peak frequency emission level measurement in Restricted Band ,
Change RBW: 1MHz
VBW: 10Hz
Span: 100MHz.
5. Get the spectrum reading after Maximum Hold function is completed.

5.5.5 Test Setup (Radiated)

Same as *Radiated Emission Measurement*

5.5.6 Test Data

Table Band Edge measurement (Radiated)

Temp. (deg. C): 25

Test Engr: Mailes Hsieh

Humidity (%): 50

Channel	Frequency (MHz)	Spectrum Reading (dBuV)	Correction Factor (dB/m)	Emission Level (dBuV/m)	dBc (Limit: > 20dBc)	Limit (dBuV/m)	Equip. Setup VBW	Pass or Fail
1(peak mode)	2406.6	67.39	35.48	102.87	---	---	1MHz	---
Outside band	2400	46.57	35.48	82.05	20.82	---	1MHz	Pass
1(average mode)	2404.8	54.13	35.48	89.61	---	---	10Hz	---
Restricted band	2390	11.47	35.47	46.94	---	54	10Hz	Pass
11(peak mode)	2465	67.14	35.5	102.64	---	---	1MHz	---
Outside band	2478.6	33.82	35.51	69.33	33.31	---	1MHz	Pass
11(average mode)	2463.1	53.43	35.5	88.93	---	---	10Hz	---
Restricted band	2483.5	11.72	35.51	47.23	---	54	10Hz	Pass

Note:


The Spectrum plot of emission level measurement in Restricted band is attached.

Emission Level=Spectrum Reading+Correction Factor


Correction Factor=Antenna Factor+cable loss–amplifier gain

Both Horizontal and Vertical polarizaion have been tested and the worst data is listed above.


**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Peak Mode (Channel 1)**




**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Average Mode (Channel 1)**



**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Peak Mode (Channel 11)**



**Band Edge measurement for radiated emission in Restricted Band(Radiated)
Average Mode (Channel 11)**



5.6 RF Exposure Measurement [Section 15.247(b)(4) & 1.1307(b)]

See SAR report

5.7 DSSS Peak Power Spectral Density [Section 15.247(d)]

5.7.1 Test Procedure

1. The Transmitter output of EUT was connected to the spectrum analyzer.
 Equipment mode: Spectrum analyzer
 Detector function: Peak mode
 SPAN:1.5MHz
 RBW: 3KHz
 VBW: 30KHz
 Center frequency: fundamental frequency tested.
 Sweep time= 500 sec.
2. Using Peak Search to read the peak power after Maximum Hold function is completed.

5.7.2 Test Setup



5.7.3 Test Data

Maximum Peak Output Power Density

Temp. (deg. C): 25

Test Engr: Mailes Hsieh

Humidity (%): 50

Chennel	Frequency (MHz)	Spectrum Reading (dBm/3KHz)	Cable Loss (dB)	Peak Power Output (dBm/3KHz)	Limit (dBm/3KHz)	Pass/Fail
1	2412	-18.26	1.1	-17.16	8	Pass
6	2437	-17.86	1.1	-16.76	8	Pass
11	2462	-19.12	1.1	-18.02	8	Pass

Note: Two RF output(MAIN & AUX) have been test,the worse data shown above.

Channel 1



Channel 6



Channel 11



6. Appendix

6.1 Appendix A: Measurement Procedure for Power line Conducted Emissions

The measurements are performed in a 3.5m x 3.4m x 2.5m shielded room, which referred as Conduction 01 test site, or a 3m x 3m x 2.3m test site, which referred as Conduction 02 test site. The EUT was placed on non-conduction 1.0m x 1.5m table, which is 0.8 meters above an earth-grounded.

Power to the EUT was provided through the LISN which has the Impedance (50ohm/50uH) vs. Frequency Characteristic in accordance with the required standard. Power to the LISNs were filtered to eliminate ambient signal interference and these filters were bonded to the ground plane. Peripheral equipment required to provide a functional system (support equipment) for EUT testing was powered from the second LISN through a ganged, metal power outlet box which is bonded to the ground plane at the LISN.

If the EUT is supplied with a flexible power cord, the power cord length in excess of the distance separating the EUT from the LISN shall be folded back and forth at the center of the lead so as to form a bundle not exceeding 40cm in length. If the EUT is provided with a permanently coiled power cord, bundling of the cord is not required. If the EUT is supplied without a power cord, the EUT shall be connected to the LISN by a power cord of the type specified by the manufacturer which shall not be longer than 1 meter. The excess power cord shall be bundled as described above. If a non-flexible power cord is provided with the EUT, it shall be cut to the length necessary to attach the EUT to the LISN and shall not be bundled.

The interconnecting cables were arranged and moved to get the maximum emission. Both the line of power cord, hot and neutral, were measured.

The highest emissions were analyzed in details by operating the spectrum analyzer in fixed tuned mode to determine the nature of the emissions and to provide information which could be useful in reducing their amplitude.

6.2 Appendix B: Test Procedure for Radiated Emissions

Preliminary Measurements in the Anechoic Chamber

The radiated emissions are initially measured in the anechoic chamber at a measurement distance of 3 meters. Desktop EUT are placed on a wooden stand 0.8 meter in height. The measurement antenna is 3 meters from the EUT. The test setup in anechoic chamber is the same as open site. The turntable rotated 360°. The antenna height is varied from 1-2.5m. The primary objective of the radiated measurements in the anechoic chamber is to identify the frequency spectrum in the absence of the electromagnetic environment existing on the open test site. The frequencies can then be pre-selected on the open test site to obtain the corresponding amplitude. The initial scan is made with the spectrum analyzer in automatic sweep mode. The spectrum peaks are then measured manually to determine the exact frequencies.

Measurements on the Open Site or 10m EMC Chamber

The radiated emissions test will then be repeated on the open site or 10m EMC chamber to measure the amplitudes accurately and without the multiple reflections existing in the shielded room. The EUT and support equipment are set up on the turntable of one of the 3 or 10 meter open field sites. Desktop EUT are set up on a wooden stand 0.8 meter above the ground.

For the initial measurements, the receiving antenna is varied from 1-4 meter height and is changed in the vertical plane from vertical to horizontal polarization at each frequency. Both readings are recorded with the quasi-peak detector with 120KHz bandwidth. For frequency between 30 MHz and 1000MHz, the reading is recorded with peak detector or quasi-peak detector. For frequency above 1 GHz, the reading is recorded with peak detector or average detector with 1 MHz bandwidth.

At the highest amplitudes observed, the EUT is rotated in the horizontal plane while changing the antenna polarization in the vertical plane to maximize the reading. The interconnecting cables were arranged and moved to get the maximum emission. Once the maximum reading is obtained, the antenna elevation and polarization will be varied between specified limits to maximize the readings.

6.3 Appendix C: Test Equipment

6.3.1 Test Equipment List

Location	Equipment Name	Brand	Model	S/N	Last Cal. Date	Next Cal. Date
Conduction	Coaxial Cable 1F-C2	Harbourindustries	RG400	1F-C2	06/02/2004	06/02/2005
Conduction	Digital Hygro-Thermometer Conduct	MicroLife	HT-2126G	ISL-Conductio n02	12/04/2002	12/04/2004
Conduction	EMI Receiver 02	HP	85460A	3448A00183	10/02/2003	10/02/2004
Conduction	LISN 01	R&S	ESH2-Z5	890485/013	04/29/2004	04/29/2005
Conduction	LISN 04	EMCO	3810/2	9604-1429	12/18/2003	12/18/2004
Radiation	BILOG Antenna 07	Schaffner	CBL6112B	2755	12/19/2003	12/19/2004
Radiation	Coaxial Cable Chmb 02-10M	Belden	RG-8/U	Chmb 02-10M	09/09/2003	09/09/2004
Radiation	Microwave Cable Chmb 02 3M	HUBER+SUHNER AG.	Sucoflex 103	42731/3 & 42729/3	03/17/2004	03/17/2005
Radiation	Digital Hygro-Thermometer Chmb 02	MicroLife	HT-2126G	Chmb 02	12/04/2002	12/04/2004
Radiation	EMI Receiver 03	HP	85460A	3448A00209	01/08/2004	01/08/2005
Radiation	Spectrum Analyzer 13	Advantest	R3132	121200411	02/12/2004	02/12/2005
Rad. Above 1Ghz	Horn Antenna 02	Com-Power	AH-118	10088	02/17/2004	02/17/2005
Rad. Above 1Ghz	Horn Antenna 04	Com-Power	AH-826	081-001	01/07/2004	01/07/2005
Rad. Above 1Ghz	Horn Antenna 05	Com-Power	AH-640	100A	09/18/2003	09/18/2005
Rad. Above 1Ghz	Microwave Cable RF SK-01	HUBER+SUHNER AG.	Sucoflex 102	22139 /2	02/17/2004	02/17/2005
Rad. Above 1Ghz	Peak Power Analyzer	HP	8990A	3621A01269	01/02/2004	01/02/2005
Rad. Above 1Ghz	Power Sensor Radar	HP	84815A	3318A01828	01/02/2004	01/02/2006
Rad. Spurious Emission	Power Meter 01	HP	438A	3513U06187	01/07/2004	01/07/2005
Rad. Spurious Emission	Power Sensor RF 01	HP	8481H	MY41091048	06/17/2004	06/17/2005
Rad. Above 1Ghz	Preamplifier 02	MITEQ	AFS44-0010265 0-40-10P-44	728229	05/12/2004	05/12/2005
Rad. Above 1Ghz	Preamplifier 09	MITEQ	AFS44-0010265 0-40-10P-44	858687	05/12/2004	05/12/2005
Rad. Above 1Ghz	Preamplifier 10	MITEQ	JS-26004000-27 -5A	818471	N/A	N/A
Rad. Above 1Ghz	Spectrum Analyzer 07	Advantest	R3182	110600649	04/08/2004	04/08/2005


Note: Calibration is traceable to NIST or national or international standards.

6.3.2 Software for Controlling Spectrum/Receiver and Calculating Test Data



Radiation/Conduction	Filename	Version	Issued Date
Conduction	Tile.exe	1.12E	7/7/2000
Radiation	Tile.exe	1.12C	6/16/2000

6.4 Appendix D: Layout of EUT and Support Equipment

6.4.1 General Conducted Test Configuration



6.4.2 General Radiation Test Configuration



6.5 Appendix E: Description of Support Equipment

6.5.1 Description of Support Equipment

Support Unit 1.

Description:	DELL USB Mouse
Model Number:	M-UR69
Serial Number:	LNA24412741
Power Supply Type:	N/A
Power Cord:	N/A
FCC ID:	N/A (Comply with FCC DOC)

Support Unit 2.

Description:	Acer Monitor
Model:	G781
Serial Number:	999007101214400445T7AA31T
Power Cord:	Non-shielded, Detachable
FCC ID:	(Comply with FCC Standards)

6.5.2 Software for Controlling Support Unit

Test programs exercising various part of EUT were used. The programs were executed as follows:

- A. Send H pattern to the video port device (Monitor).
- B. The RF software makes the transmitter contiunely sending RF signals
- C. Repeat the above steps.

	Filename	Issued Date
CRTU2 Rev2.2.9.3000	CRTU-II.exe	2003/12/10
Monitor	HH.bat	8/20/1991

6.5.3 I/O Cable Condition of EUT and Support Units

Description	Path	Cable Length	Cable Type	Connector Type
AC Power Cord	110V (~240V) to AC Power Cord Inlet (3-pin)	1.8M	Nonshielded, Detachable	Plastic Head
Monitor Data Cable	Monitor to PC VGA port	1.6M	Shielded, Un-detachable	Metal Head
Mouse Data Cable	Mouse to PC Mouse port	1.8M	Shielded, Un-detachable	Metal Head

6.6 Appendix F: Accuracy of Measurement

Test Site: Conduction 02

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.104	k=1	0.052
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.330	k=1	0.165
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	LISN Factor Calibration	Normal	k=2	1.200	k=1	0.600
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty Uc(y)	Normal			k=1	0.850
7	Total Uncertainty @95% mim. Confidence Level	Normal	k=2	1.701		

Measurement Uncertainty Calculations:

$$Uc (y) = \text{square root} (u_1 (y)^2 + u_2 (y)^2 + \dots\dots\dots+u_n (y)^2)$$

$$U = 2 * Uc (y)$$

Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS : The treatment of Uncertainty in EMC Measurement.

Test Site: Chamber 02-3M

Item	Source of Uncertainty	Probability Distribution	Total Uncertainties (dB)		Standard Uncertainty (dB)	
			k	Value	k	Value
1	Systematic Effects: (Assessment from 20 repeat observation; 1 reading on EUT)	Normal	k=2	0.067	k=1	0.034
2	Random Effects: (Assessment from 20 random observations; 1 reading on EUT)	Normal	k=2	0.103	k=1	0.052
3	Receiver Calibration	Rectangular	k=1.73	1.000	k=1	0.577
4	Antenna Factor Calibration	Normal	k=2	1.700	k=1	0.850
5	Cable Loss Calibration	Normal	k=2	1.000	k=1	0.500
6	Combined Standard Uncertainty Uc(y)	Normal			k=1	1.029
7	Total Uncertainty @95% mim. Confidence Level	Normal	k=2	2.059		

Measurement Uncertainty Calculations:


$$U_c(y) = \text{square root} (u_1(y)^2 + u_2(y)^2 + \dots + u_n(y)^2)$$

$$U = 2 * U_c(y)$$


Note: The measurement Uncertainties mentioned above also refer to NIS 81-1994 of NAMAS : The treatment of Uncertainty in EMC Measurement.

6.7 Appendix G: Photographs of EUT Configuration Test Set Up


The Front View of Highest Conducted Set-up For EUT




The Back View of Highest Conducted Set-up For EUT



The Front View of Highest Radiated Set-up For EUT



The Back View of Highest Radiated Set-up For EUT



6.8 Appendix H: Antenna Spec.

Please refer to the attached file.