

Page: 1 of 190

ELECTROMAGNETIC EMISSIONS CLASS II PERMISSIVE CHANGE REPORT





FCC Applicant: Acer Incorporated

8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi, New Taipei Citv

22181, Taiwan (R.O.C)

FCC Manufacturer: Qunata Computer Inc.

211 Wen Hwa 2nd Rd., Kueishan, Taoyuan 33377, Taiwan

11ax RTL8852AE Combo Module **Product Name:**

Brand Name: acer

Model No.: RTL8852AE

Report Number: TERF2204000360E2

FCC ID HLZRTL8852AE

Issue Date: Jun. 17, 2022

Date of Test: Apr. 19, 2022~May. 03, 2022

Date of EUT Received: Apr. 06, 2022

Approved By

We hereby certify that:

The above equipment was tested by SGS Taiwan Ltd. Central RF Lab The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10:2013 and the energy emitted by the sample EUT comply with FCC rule part §15.407.

The results of this report relate only to the sample identified in this report.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 2 of 190

Revision History					
Report Number	Revision	Description	Issue Date	Revised By	Remark
TERF2204000360E2	00	Original.	Jun. 17, 2022	Yi-Shan Tsai	

Note:

1 . The remark "*" indicates modification of the report upon requests from certification body.



Page: 3 of 190

Contents

1	GENERAL INFORMATION	4
2	SYSTEM TEST CONFIGURATION	8
3	SUMMARY OF TEST RESULT	11
4	DESCRIPTION OF TEST MODES	12
5	MEASUREMENT UNCERTAINTY	16
6	MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT	17
7	LINDESIRABLE RADIATED EMISSION MEASUREMENT	24

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 4 of 190

GENERAL INFORMATION

1.1 **Product Description**

Product Name:	11ax RTL8852AE Combo Module	
Brand Name: acer		
Model No.: RTL8852AE		
EUT Series No.:	N8KA3WW0012080BCE27600A	
Power Supply:	11.61Vdc from Rechargeable Lithium Ion Battery Pack 5 / 9 / 12 / 15 / 20Vdc from AC/DC Adapter	

1.2 **Modulation & Data Rate**

Modulation type:	64QAM, 16QAM, QPSK, BPSK for OFDM
	256QAM for OFDM in 802.11ac
	256QAM,1024QAM for OFDMA in 802.11ax
	802.11 a: 6 - 54 Mbps
	802.11 ac_20MHz: up to 173.4 Mbps
	802.11 ac_40MHz: up to 400 Mbps
Transition Rate:	802.11 ac_80MHz: up to 866.6 Mbps
	802.11 ax_20MHz: up to 286.8 Mbps
	802.11 ax_40MHz: up to 573.6 Mbps
	802.11 ax_80MHz: up to 1201 Mbps

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 5 of 190

1.3 Antenna Designation

Antenna Type	Supplier	Main / Aux	Antenna Part No.	Freq. (MHz)	Peak Antenna Gain (dBi)	Direction Gain (dBi)
				5150~5250	2.84	5.57
		Main		5250~5350	2.91	5.67
		IVIAITI	5470~57	5470~5725	2.91	5.95
PIFA	WNC		81EABS15.G72	5725~5850	2.82	5.90
FIFA	VVINC		01EAB313.G72	5150~5250	2.26	5.57
	Δ.	Aux	5250~5350 2.40	2.40	5.67	
Aux	Aux		5470~5725	2.96	5.95	
		5725~5850	2.96	5.90		

Note:

- Pre-scanned was done on the above antennas, measurements were demonstrated by using the antenna with the highest gain as the worst case scenarios.
- 2. Antenna information is provided by the applicant.



Page: 6 of 190

Wi-Fi	Frequency Range	Channels	Rated Power(Avg) (dBm) (Worst Case)	Modulation Technology
a/	5180~5240	4	21.88 dBm	OFDM
n_HT/	5260~5320	4	21.79 dBm	OFDM
ac_VHT/ ax_HE	5500~5720	12	21.84 dBm	OFDM
20M	5745-5825	5	27.92 dBm	OFDMA
n UT	5190~5230	2	22.84 dBm	OFDMA
n_HT ac_VHT/	5270~5310	2	22.69 dBm	OFDMA
ax_HE 40M	5510~5710	6	23.43 dBm	OFDM
40101	5755-5795	2	24.12 dBm	OFDMA
	5210	1	17.60 dBm	OFDM
ac_VHT/	5290	1	17.74 dBm	OFDMA
ax_HE 80M	5530~5690	3	20.88 dBm	OFDMA
	5775	1	19.57 dBm	OFDM



Page: 7 of 190

1.5 Test Methodology of Applied Standards

FCC Part 15, Subpart E §15.407 FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 FCC KDB 662911 D01 Multiple Transmitter Output v02r01 ANSI C63.10:2013

1.6 Test Facility

Laboratory	Test Site Address	Test Site Name	FCC Designa- tion number	IC CAB identifier
		SAC 1		
		SAC 3		
		Conduction 1		
	No.134, Wu Kung Road, New Taipei	Conducted 1		
	Industrial Park, Wuku District, New	Conducted 2	TW0027	
	Taipei City, Taiwan.	Conducted 3		TW3702
		Conducted 4		
		Conducted 5		
SGS Taiwan Ltd.		Conducted 6		
Central RF Lab.		Conduction C		
(TAF code 3702)		SAC C		
(1741 COUC 37 02)		SAC D		
		SAC G		
	No 2 Koji 1et Pd. Gujehan Dietriet	.2, Keji 1st Rd., Guishan District, Tagunan City Taiwan 223 Conducted B TW0028		
	Taoyuan City, Taiwan 333		TW0028	
	ladydair City, Taiwair 555	Conducted C		
		Conducted D		
		Conducted E		
		Conducted F		
		Conducted G		

Note: Test site name is remarked on the equipment list in each section of this report as an indication where measurements occurred in specific test site and address.

1.7 Special Accessories

There are no special accessories used while test was conducted.

1.8 Equipment Modifications

There was no modification incorporated into the EUT.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號



Page: 8 of 190

2 SYSTEM TEST CONFIGURATION

2.1 EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

2.2 EUT Exercise

An engineering test mode (software/firmware) that applicant provided was utilized to manipulate the EUT into transmit, selection of the test channel, and modulation scheme.

2.3 Test Procedure

2.3.1 Conducted Test (RF)

The active antenna port of the unlicensed wireless device is connected to the spectrum analyzer with attenuator to protect the instrumentation. If a second antenna port is available, it is tested at one operating frequency, with other port(s) appropriately terminated, to verify it has similar output characteristics as the fully tested port.

2.3.2 Radiated Emissions

The EUT is a placed on a turn table. For emissions testing at or below 1 GHz, the table height shall be 0.8 m above the reference ground plane. For emission measurements above 1 GHz, the table height shall be 1.5 m. The turn table shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the max. emission, the relative positions of this transmitter (EUT) was rotated through three orthogonal axes and measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製



Page: 9 of 190

2.4 **Measurement Results Explanation Example**

Radiated Emission Test Sites For Measurements From 9 kHz To 30 MHz 2.4.1

Radiated emission below 30MHz is measured in a 9m*6m*6m semi-anechoic chamber, the measurements correspond to those obtained at an open-field test site.

There is a comparison data of both open-field test site and semi-Anechoic chamber, and the result came out very similar.


2.4.2 For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuation factor between EUT conducted port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly EUT RF output level.



Page: 10 of 190

2.5 **Test Configuration**



2.6 Control Unit(s)

Radiated Emission Test Site: SAC D					
EQUIPMENT TYPE	MFR	MODEL NUM- BER	SERIAL NUM- BER	LAST CAL.	CAL DUE.
Adapter	LITEON	PA-1650-58	N/A	N.C.R	N.C.R

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 www.sgs.com.tw



Page: 11 of 190

SUMMARY OF TEST RESULT

FCC Rules	Description Of Test	Result
§15.407(a)	Maximum Conducted Output Power	Compliant
§15.205 §15.209 §15.407(b)	Undesirable Radiated Emissions	Compliant

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 12 of 190

DESCRIPTION OF TEST MODES

4.1 **Operating Frequencies**

Operated band in 5150 MHz ~5250 MHz:

20 M		
СН	Freq (MHz)	
36	5180	
40	5200	
44	5220	
48	5240	

u	1111 3130 WILLE 3230 WILLE.				
	4	0 M	8	0 M	
	СН	Freq (MHz)	СН	Freq (MHz)	
	38	5190	42	5210	
	46	5230			

Operated band in 5250 MHz ~5350 MHz:

Operated by		
20 M		
СН	Freq (MHz)	
52	5260	
56	5280	
60	5300	
64	5320	

10 111 JZJU W							
	40 M						
	СН	Freq					
	5	(MHz)					
	54	5270					
	62	5310					

_							
	80 M						
	СН	Freq (MHz)					
	58	5290					

Operated bar z:

	20 M						
СН	Freq (MHz)						
100	5500						
104	5520						
108	5540						
112	5560						
116	5580						
120	5600						
124	5620						
128	5640						
132	5660						
136	5680						
140	5700						
144	5720						

1	nd in 5470 MHz ~5725 MH							
	4	0 M	80 M					
	СН	Freq (MHz)	СН	Freq (MHz)				
	102	5510	106	5530				
	110	5550	122	5610				
	118	5590	138	5690				
	126	5630						
	134	5670						
	142	5710						

Operated band in 5725 MHz ~5850 MHz:

4	20 M					
СН	Freq (MHz)					
149	5745					
153	5765					
157	5785					
161	5805					
165	5825					

M		4	0 M	80 M				
Freq		СН	Freq (MHz)	СН	Freq (MHz)			
MHz)		5	(MHz)	СП	(MHz)			
5745		151	5755	155	5775			
5765		159	5795					
5785								

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 13 of 190

4.2 The Worst Test Modes and Channel Details

- The EUT has been tested under operating condition.
- 2. Test program used to control the EUT for staying in continuous transmitting mode is programmed.
- 3. Investigation has been done on all the possible configurations for searching the worst case. The given UE is pre-scanned among below modes.

Modulation	Tı	ransmiss	sion Chair	า	Single Transmission Spatial	Multiple Transmission Spatial
⊠ 802.11 a	⊠ Ch0	⊠ Ch1	☐ Ch2	□ Ch3	☐ 1TX	⊠ 2TX
⊠ 802.11 ac	⊠ Ch0	⊠ Ch1	☐ Ch2	□ Ch3	☐ SISO	⊠ MIMO
⊠ 802.11 ax	⊠ Ch0	⊠ Ch1	☐ Ch2	□ Ch3	☐ SISO	⊠ MIMO

4. Therefore, below summary is the modes of test configuration that yield the highest reading and generate the highest emission chosen to carry out the relevantly mandatory test items.

items.								
		RADIATED	EMISSION TE	EST (BELOW	1 GHz)			
MODE	FREQUENCY BAND (MHz)	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION	DATA RATE (Mbps)	ANTENNA PORT		
	5180~5240	36 to 48	44		· · ·			
802.11a	5260~5320	52 to 64	60	OFDM	6	2TX		
002.11a	5500~5720	100 to 144	116	OFDIVI	0	217		
	5745~5825	149 to 165	157					
RADIATED EMISSION TEST (ABOVE 1 GHz)								
MODE	FREQUENCY	AVAILABLE	TESTED	MODULATION	DATA RATE	ANTENNA		
MODE	BAND (MHz)	CHANNEL	CHANNEL	MODULATION	(Mbps)	PORT		
802.11a	5180~5240	36 to 48	36,44,48					
	5260~5320	52 to 64	52,60,64	OFDM	6	2TX		
002.11a	5500~5720	100 to 144	100,116,140,144	OI DIVI		217		
	5745~5825	149 to 165	149,157,165					
	5180~5240	36 to 48	36,44,48					
802.11ac VHT20	5260~5320	52 to 64	52,60,64	OFDM	MCS0	MIMO		
002.11ac_V11120	5500~5700	100 to 140	100,116,140	OFDIVI	IVICOU	IVIIIVIO		
	5745~5825	149 to 165	149,157,165					
	5190~5230	38 to 46	38,46					
802.11ac VHT40	5270~5310	54 to 62	54,62	OFDM	MCS0	MIMO		
002.11ac_V11140	5510~5670	102 to 134	102,110,134	OI DIVI	MCSU	IVIIIVIO		
	5755~5795	151 to 159	151,159					
	5210	42	42					
802.11ac_VHT80	5290	58	58	OFDM	MCS0	MIMO		
002.11aC_V1110U	5530~5610	106 to 138	106,122,138	OFDIVI	IVICOU	IVIIIVIO		
	5775	155	155					

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 www.sgs.com.tw



Page: 14 of 190

		RADIATE	DEMISSION T	EST (ABOVE	1 GHz)		
MODE	FREQUENCY	AVAILABLE	TESTED	MODULATION	RU	DATA RATE	ANTENNA
MODE	BAND (MHz)	CHANNEL	CHANNEL	MODULATION	CONFIGURATI	(Mbps)	PORT
	5180~5240	36 to 48	36,44,48		FULL RU		
802.11ax_HE20	5260~5320	52 to 64	52,60,64	OFDMA	26/0,26/8	MCS0	MIMO
002.11ax_11E20	5500~5720	100 to 144	100,116,140,144	OFDIVIA	52/37,52/40	MOSU	IVIIIVIO
	5745~5825	149 to 165	149,157,165		106/53,106/54		
	5190~5230	38 to 46	38,46				
802.11ax_HE40	5270~5310	54 to 62	54,62	OFDMA	FULL	MCS0	MIMO
002.11ax_⊓⊑40	5510~5670	102 to 142	102,110,134,142	OFDIVIA	FULL	MCSU	IVIIIVIO
	5755~5795	151 to 159	151,159				
	5210	42	42				
000 11 11-00	5290	58	58	OEDMA	FULL	M000	MIMO
802.11ax_HE80	5530~5610	106 to 138	106,122,138	OFDMA		MCS0	MIMO
	5775	155	155				
			CONDUCTE	D TEST			
MODE	FREQUENCY	AVAILABLE	TESTED	MODULATION	DATA	DATA RATE	
WIODE	BAND (MHz)	CHANNEL	CHANNEL	MODULATION	(Mb	ps)	PORT
	5180~5240	36 to 48	36,44,48		6		
802.11a	5260~5320	52 to 64	52,60,64	OFDM			2TX
002.11a	5500~5720	100 to 144	100,116,140,144	OFDIVI			ZIX
	5745~5825	149 to 165	149,157,165				
	5180~5240	36 to 48	36,44,48				
900 11aa V/UT00	5260~5320	52 to 64	52,60,64	OFDM	MC	200	MIMO
802.11ac_VHT20	5500~5700	100 to 140	100,116,140	OFDIVI	IVIC	MCS0	
	5745~5825	149 to 165	149,157,165				
	5190~5230	38 to 46	38,46				
000 11aa \/UT10	5270~5310	54 to 62	54,62	OFDM	M	200	MIMO
802.11ac_VHT40	5510~5670	102 to 134	102,110,134	OFDM	IVIC	CS0	MIMO
	5755~5795	151 to 159	151,159				
	5210	42	42				
000 11 \/\\\	5290	58	58	OFDM		200	MIMO
802.11ac_VHT80	5530~5610	106 to 138	106,122,138	OFDM	IMIC	CS0	MIMO
	5775	155	155				

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 15 of 190

CONDUCTED TEST								
MODE	FREQUENCY	AVAILABLE	TESTED MODULATION		RU	DATA RATE	ANTENNA	
INIODE	BAND (MHz)	CHANNEL	CHANNEL	MODULATION	CONFIGURATI	(Mbps)	PORT	
	5180~5240	36 to 48	36,44,48		FULL RU			
802.11ax HE20	5260~5320	52 to 64	52,60,64	OFDMA	26/0,26/8	MCS0	MIMO	
002.11ax_11E20	5500~5720	100 to 144	100,116,140,144	OFDIVIA	52/37,52/40			
	5745~5825	149 to 165	149,157,165		106/53,106/54			
	5190~5230	38 to 46	38,46		FULL	MCS0		
802.11ax HE40	5270~5310	54 to 62	54,62	OFDMA			MIMO	
002.11ax_11L40	5510~5670	102 to 142	102,110,134,142	OI DIVIA			IVIIIVIO	
	5755~5795	151 to 159	151,159					
	5210	42	42					
000 11 11500	5290	58	58	OFDMA	FULL	MCS0	MIMO	
802.11ax_HE80	5530~5610	106 to 138	106,122,138	OFDIVIA	FULL		IVIIIVIO	
	5775	155	155					

Note:

The field strength of radiated emission was measured as the EUT positioned in different orthogonal planes (E1/E2/H) based on actual usage of the EUT to pre-scan the emissions for determining the worst case scenario.



Page: 16 of 190

MEASUREMENT UNCERTAINTY

Test Items	Un	certain	ty
Output Power measurement	+/-	1	dB
Undesignable radiated emission measurement	+/-	1.68	dB
Temperature	+/-	0.4	°C
Humidity	+/-	3.5	%
DC / AC Power Source	+/-	1	%

Radiated Spurious Emission Measurement Uncertainty					
	+/-	2.57	dB	9kHz~30MHz	
Polarization: Vertical	+/-	4.85	dB	30MHz - 1000MHz	
Polarization. Vertical	+/-	4.45	dB	1GHz - 18GHz	
	+/-	4.24	dB	18GHz - 40GHz	
	+/-	2.57	dB	9kHz~30MHz	
Polarization: Horizontal	+/-	4.37	dB	30MHz - 1000MHz	
Polarization: Horizontal	+/-	4.45	dB	1GHz - 18GHz	
	+/-	4.24	dB	18GHz - 40GHz	

Note:

- 1. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.
- 2. The conformity assessment statement in this report is based solely on the test results, measurement uncertainty is excluded.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnielectronic cornal occuments, subject to Terris and Conditions for Electronic Documents at https://www.sgs.com.tw/ lerms-and-Conditions.
Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 17 of 190

MAXIMUM CONDUCTED OUTPUT POWER MEASUREMENT

6.1 Standard Applicable

6.1.1 **Output Power**

				e-CRF Title	47 §15.407	
Band		EUT CATEGORY	Conducted Output Power	EIRP	TPC	Antenna Directional Gain Requirements
		Fixed point-to- point	1 Watt(30dBm)	Not required	Not required	23dBi
U-NII-1		Out door AP	1 Watt(30dBm)	Elevation angle above 30 degrees 125mW (21dBm)	Not required	6dBi
014111		Indoor AP	1 Watt(30dBm) Not required		Not required	6dBi
	٧	Other	250mW(23.98dBm)	Not required	Not required	6dBi
U-NII-2A	٧	Other	250mW(23.98dBm) or 11dBm+10 log B	Not required	When EIRP >500mW At least 6dB below EIRP	6dBi
U-NII-2C	٧	Other	250mW(23.98dBm) or 11dBm+10 log B	Not required	1W (30dBm)	6dBi
U-NII-3	٧	Other	1 Watt(30dBm)	Not required	Not required	6dBi
U-IVII-3		Fixed point-to-point	1 Watt(30dBm)	Not required	Not required	Not required
		Indoor AP (a channel spans 5725~5850 and 5850~5895MHz)	Not required	36dBm	Not required	Not required
U-NII-4		indoor client (a channel spans 5725~5850 and 5850~5895MHz)	Not required	30dBm	Not required	Not required
		subordinate device	Not required	36dBm	Not required	Not required

^{1.} If transmitting antennas of directional gain greater than the antenna requirements column, the Maximum transmit power shall be reduced by the amount in dB that the direction-al gain of the antenna.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

^{2.} For the 10 log B, B is the 26 dB emission bandwidth.



Page: 18 of 190


6.2 Measurement Equipment Used:

	Conducted Emission Test Site: Conducted D										
EQUIPMENT TYPE	MFR	MODEL NUM- BER	SERIAL NUM- BER	LAST CAL.	CAL DUE.						
Spectrum Ana- lyzer	KEYSIGHT	N9010B	MY59071574	06/25/2021	06/24/2022						
Power Meter	Anritsu	ML2496A	2138002	11/12/2021	11/11/2022						
Power Sensor	Anritsu	MA2411B	1911390	09/20/2021	09/19/2022						
Power Sensor	Anritsu	MA2411B	1911398	09/22/2021	09/21/2022						
Test Software	SGS Taiwan	Radio Test Soft- ware	Ver.21	N.C.R	N.C.R						
Attenuator	Marvelous	WATT-218FS-10	RF15	11/18/2021	11/17/2022						
Attenuator	Marvelous	WATT-218FS-10	RF16	11/18/2021	11/17/2022						
DC Block	PASTERNACK	PE8210	RF158	11/18/2021	11/17/2022						

NOTE: N.C.R refers to Not Calibrated Required.

6.3 **Test Setup**

6.3.1 **Output Power**



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 www.sgs.com.tw



Page: 19 of 190

6.4 Measurement Procedure

6.4.1 **Output Power Measurements**

- 1. Place the EUT on the table and set it in transmitting mode.
- The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules .
- Remove the antenna from the EUT and then connect a low loss RF cable from the an-3. tenna port to the power meter
- Power Meter is used as the auxiliary test equipment to conduct the output power meas-4. urement.
- Record the max. reading and add 10 log(1/duty cycle).
- Repeat above procedures until all frequency (low, middle, and high channel) measured were complete.
- 7. MIMO mode: offset is set with "measure and add 10 Log (N)" to measurement for MIMO mode. Offset = cable loss + 10 log (N), where N is number of transmitting antenna, cable loss is specified below.

Note:

As per section F. 2). e). (ii) of FCC KDB 662911 D01

If antenna gains are not equal and each transmit antenna is driven by only one spatial stream, directional gain may be calculated by either of the following formulas.

• Directional Gain =
$$10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^{2}}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

NSS = the number of independent spatial streams of data;

NANT = the total number of antennas

 $g_{i,k} = /20$ 10Gk if the kth antenna is being fed by spatial stream i, or zero if it is not;

 \hat{G}_k is the gain in dBi of the kth antenna.

The antenna gain is not greater than 6 dBi. Therefore, reduction of power is not required.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 20 of 190

6.5 Output Power Measurement Result

6.5.1 FCC Output power

802.11a 2TX

	Frequency	Data	Power	Avg. POV	VER (dBm)	TOTAL	TOTAL	REQUIRED	
СН	(MHz)	Rate	set	Ch0	Ch1	POWER (dBm)	POWER (mW)	LIMIT (dBm)	RESULT
36	5180	6	19.5	18.93	18.75	21.88	154.170	23.98	PASS
44	5220	6	19.5	18.87	18.69	21.82	152.055	23.98	PASS
48	5240	6	19.5	18.82	18.61	21.75	149.624	23.98	PASS
52	5260	6	19.5	18.85	18.65	21.79	151.008	23.98	PASS
60	5300	6	19.5	18.79	18.59	21.73	148.936	23.98	PASS
64	5320	6	19.5	18.75	18.53	21.68	147.231	23.98	PASS
100	5500	6	17	16.47	16.31	19.43	87.700	23.98	PASS
116	5580	6	19.5	18.9	18.7	21.84	152.757	23.98	PASS
140	5700	6	16.5	15.84	15.57	18.74	74.817	23.98	PASS
144	5720(U-NII 2C)	6	20	18.08	17.78	20.97	125.076	23.02	PASS
144	5720 (U-NII 3)	6	20	13.78	13.76	16.81	47.973	30	PASS
149	5745	6	23	22.35	22.08	25.25	334.965	30	PASS
157	5785	6	23	22.3	22.01	25.19	330.370	30	PASS
165	5825	6	23	22.24	21.96	25.14	326.588	30	PASS

802.11ac_VHT20_MIMO

СН	Frequency	Data	Power	Avg. POV	VER (dBm)	TOTAL POWER	TOTAL POWER	REQUIRED LIMIT	RESULT
CH	(MHz)	Rate	set	Ch0	Ch1	(dBm)	(mW)	(dBm)	KESULI
36	5180	MCS0	19	18.55	18.29	21.46	139.959	23.98	PASS
44	5220	MCS0	19	18.62	18.36	21.53	142.233	23.98	PASS
48	5240	MCS0	19	18.72	18.45	21.62	145.211	23.98	PASS
52	5260	MCS0	19	18.59	18.32	21.49	140.929	23.98	PASS
60	5300	MCS0	19	18.51	18.27	21.43	138.995	23.98	PASS
64	5320	MCS0	19	18.67	18.41	21.58	143.880	23.98	PASS
100	5500	MCS0	17	16.55	16.36	19.49	88.920	23.98	PASS
116	5580	MCS0	19	18.7	18.42	21.60	144.544	23.98	PASS
140	5700	MCS0	17	16.49	16.23	19.40	87.096	23.98	PASS
144	5720(U-NII 2C)	MCS0	20	17.81	17.53	20.71	117.824	23.98	PASS
144	5720 (U-NII 3)	MCS0	20	14.26	13.96	17.15	51.912	30	PASS
149	5745	MCS0	23	22.32	21.94	25.17	328.852	30	PASS
157	5785	MCS0	23	22.25	21.89	25.11	324.340	30	PASS
165	5825	MCS0	23	22.21	21.81	25.05	319.890	30	PASS

802.11ac_VHT40_MIMO

OI.	Frequency	Data	Power	Avg. POW	VER (dBm)	TOTAL	TOTAL	REQUIRED	DECLU T
СН	(MHz)	Rate	set	Ch0	Ch1	POWER (dBm)	POWER (mW)	LIMIT (dBm)	RESULT
38	5190	MCS0	16.5	15.85	15.72	18.85	76.736	23.98	PASS
46	5230	MCS0	20	19.42	19.19	22.37	172.584	23.98	PASS
54	5270	MCS0	20	19.35	19.12	22.30	169.824	23.98	PASS
62	5310	MCS0	15.5	14.67	14.52	17.66	58.345	23.98	PASS
102	5510	MCS0	16	15.29	15.13	18.28	67.298	23.98	PASS
110	5550	MCS0	21	20.46	20.27	23.43	220.293	23.98	PASS
134	5670	MCS0	17.5	16.94	16.75	19.91	97.949	23.98	PASS
142	5710(U-NII 2C)	MCS0	21	19.69	19.45	22.63	183.246	23.98	PASS
142	5710 (U-NII 3)	MCS0	21	12.28	12.26	15.33	34.096	30	PASS
151	5755	MCS0	20.5	19.92	19.8	22.92	195.884	30	PASS
159	5795	MCS0	21.5	21.06	20.82	24.01	251.768	30	PASS

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號



Page: 21 of 190

802.11ac_VHT80_MIMO

СН	Frequency	Data	Power	Avg. POW	VER (dBm)	TOTAL POWER	TOTAL POWER	REQUIRED LIMIT	RESULT
СП	(MHz)	z) Rate set Ch0 Ch1		Ch1	(dBm)	(mW)	(dBm)	KESOLI	
42	5210	MCS0	15.5	14.57	14.41	17.60	57.544	23.98	PASS
58	5290	MCS0	14.5	13.5	13.28	16.50	44.668	23.98	PASS
106	5530	MCS0	13.5	12.59	12.42	15.62	36.475	23.98	PASS
122	5610	MCS0	17	16.08	15.91	19.11	81.470	23.98	PASS
138	5690(U-NII 2C)	MCS0	18	16.75	16.56	19.77	94.799	23.98	PASS
138	5690 (U-NII 3)	MCS0	18	7.61	7.40	10.62	11.525	30	PASS
155	5775	MCS0	17.5	16.57	16.35	19.57	90.573	30	PASS

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 22 of 190

802.11ax HE20 MIMO

СН	Frequency	Data	RU config.	Power	Avg. POV	VER (dBm)	TOTAL POWER	TOTAL POWER	REQUIRED LIMIT	RESUL
	(MHz)	Rate	J 3	set	Ch0	Ch1	(dBm)	(mW)	(dBm)	
		MCS0	full	19.5	18.82	18.5	21.71	148.252	23.98	PASS
26	E400	MCS0	26/0	10.5	10.35	9.96	13.20	20.893	23.98	PASS
36	5180	MCS0	52/37	13.5	13.05	12.83	15.99	39.719	23.98	PASS
		MCS0	106/53	16.5	15.87	15.72	18.84	76.560	23.98	PASS
		MCS0	full	19.5	18.89	18.62	21.80	151.356	23.98	PASS
		MCS0	26/4	10.5	10.43	10.12	13.32	21.478	23.98	PASS
40	5200	MCS0	52/39	13.5	12.98	12.76	15.92	39.084	23.98	PASS
		MCS0	106/53	16.5	15.82	15.65	18.78	75.509	23.98	PASS
		MCS0	full	19.5	18.94	18.66	21.85	153.109	23.98	PAS
		MCS0	26/8	10.5	10.46	10.19	13.37	21.727	23.98	PAS
48	5240	MCS0	52/40	13.5	12.91	12.64	15.82	38.194	23.98	PAS
		MCS0	106/54	16.5	15.9	15.76	18.88	77.268	23.98	PAS
		MCS0	full	19.5	18.79	18.46	21.67	146.893	23.98	PAS
					1					
52	5260	MCS0	26/0	10.5	10.4	10.07	13.28	21.281	23.98	PAS
		MCS0	52/37	13.5	12.95	12.71	15.88	38.726	23.98	PAS
		MCS0	106/53	16.5	15.79	15.58	18.73	74.645	23.98	PAS
		MCS0	full	19.5	18.75	18.41	21.63	145.546	23.98	PAS
60	5300	MCS0	26/4	10.5	10.37	10.03	13.25	21.135	23.98	PAS
00	0000	MCS0	52/39	13.5	12.97	12.76	15.91	38.994	23.98	PAS
		MCS0	106/54	16.5	15.92	15.78	18.90	77.625	23.98	PAS
		MCS0	full	19.5	18.85	18.57	21.76	149.968	23.98	PAS
64	5220	MCS0	26/8	10.5	10.49	10.24	13.41	21.928	23.98	PAS
64	5320	MCS0	52/40	13.5	12.92	12.73	15.87	38.637	23.98	PAS
		MCS0	106/54	16.5	15.77	15.55	18.71	74.302	23.98	PAS
		MCS0	full	18.5	17.75	17.48	20.66	116.413	23.98	PAS
		MCS0	26/0	10.5	10.43	10.18	13.35	21.627	23.98	PAS
100	5500	MCS0	52/37	13.5	12.87	12.68	15.82	38.194	23.98	PAS
		MCS0	106/53	16.5	15.84	15.59	18.76	75.162	23.98	PAS
		MCS0	full	19.5	18.9	18.63	21.81	151.705	23.98	PAS
		MCS0	24/4	10.5	10.35	10.06	13.25	21.135	23.98	PAS
116	5580					1				
		MCS0	52/39	13.5	12.97	12.8	15.93	39.174	23.98	PAS
		MCS0	106/53	16.5	15.8	15.66	18.78	75.509	23.98	PAS
		MCS0	full	16	15.36	15.14	18.30	67.608	23.98	PAS
140	5700	MCS0	26/8	10.5	10.51	10.27	13.44	22.080	23.98	PAS
		MCS0	52/40	13.5	12.87	12.73	15.85	38.459	23.98	PAS
		MCS0	106/54	16.5	15.83	15.68	18.80	75.858	23.98	PAS
	5720(U-NII 2C)	MCS0	full	20.5	18.36	18.23	21.34	135.993	23.07	PAS
	5720 (U-NII 3)	MCS0	full	20.5	14.30	14.01	17.20	52.425	30	PAS
		MCS0	26/8	10	9.46	9.19	12.37	17.258	30	PAS
144		MCS0	26/0	9	8.24	8.06	11.20	13.183	30	PAS
144	F700	MCS0	52/40	13	13.49	13.3	16.44	44.055	30	PAS
	5720	MCS0	52/37	10.5	10.4	10.17	13.33	21.528	30	PAS
		MCS0	106/54	16.5	15.68	15.43	18.60	72.444	30	PAS
		MCS0	106/53	14	13.44	13.25	16.39	43.551	30	PAS
		MCS0	full	23.5	22.42	22.15	25.33	341.193	30	PAS
		MCS0	26/0	20	19.24	18.99	22.16	164.437	30	PAS
149	5745	MCS0	52/37	21	20.26	20.08	23.22	209.894	30	PAS
					1	1				
	+	MCS0	106/53	21.5	20.77	20.54	23.70	234.423	30	PAS
		MCS0	full	23.5	22.38	22.12	25.30	338.844	30	PAS
157	5785	MCS0	26/4	23.5	22.32	21.9	25.16	328.095	30	PAS
		MCS0	52/39	23.5	22.29	21.85	25.12	325.087	30	PAS
		MCS0	106/54	26	24.92	24.7	27.86	610.942	30	PAS
		MCS0	full	23.5	22.33	22.04	25.23	333.426	30	PAS
165	5825	MCS0	26/8	23.5	22.36	22.08	25.27	336.512	30	PAS
100	0020	MCS0	52/40	25.5	24.55	24.26	27.45	555.904	30	PAS
	•	MCS0	106/54	26	24.98	24.77	27.92	619.441	30	PAS

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號



Page: 23 of 190

802.11ax_HE40_MIMO

OUZ.TTAX_TTL40										
СН	Frequency	Data Rate	RU config.	Power set	Avg. POW	Avg. POWER (dBm)		TOTAL REQUIRED POWER LIMIT		RESULT
СП	(MHz)				Ch0	Ch1	POWER (dBm)	(mW)	(dBm)	RESOLI
38	5190	MCS0	full	15	14.25	14.04	17.22	52.723	23.98	PASS
46	5230	MCS0	full	20.5	19.86	19.66	22.84	192.309	23.98	PASS
54	5270	MCS0	full	20.5	19.7	19.53	22.69	185.780	23.98	PASS
62	5310	MCS0	full	15.5	14.84	14.56	17.78	59.979	23.98	PASS
102	5510	MCS0	full	13	12.32	12.14	15.31	33.963	23.98	PASS
110	5550	MCS0	full	21.5	20.88	20.67	23.85	33.963	23.98	PASS
134	5670	MCS0	full	17.5	16.67	16.47	19.65	92.257	23.98	PASS
142	5710(U-NII 2C)	MCS0	full	21.5	19.97	19.80	22.97	197.970	23.98	PASS
142	5710 (U-NII 3)	MCS0	full	21.5	12.47	12.55	15.59	36.225	30	PASS
151	5755	MCS0	full	20.5	19.59	19.36	22.55	179.887	30	PASS
159	5795	MCS0	full	22	21.13	20.96	24.12	258.226	30	PASS

802.11ax HE80 MIMO

СН	Frequency	Data	Dilloonfin	RU config. Power	Avg. POW	/ER (dBm)	TOTAL POWER	TOTAL POWER	REQUIRED LIMIT	RESULT
Сп	(MHz)	Rate	KO comig.	set	Ch0 Ch1		(dBm)	(mW)	(dBm)	RESULI
42	5210	MCS0	full	14	12.81	12.62	15.83	38.282	23.98	PASS
58	5290	MCS0	full	15.5	14.23	14.98	17.74	59.429	23.98	PASS
106	5530	MCS0	full	14.5	13.34	13.13	16.35	43.152	23.98	PASS
122	5610	MCS0	full	17.5	15.22	15.96	18.72	74.473	23.98	PASS
138	5690(U-NII 2C)	MCS0	full	19.5	17.90	17.61	20.88	122.415	23.98	PASS
138	5690 (U-NII 3)	MCS0	full	19.5	6.49	6.24	9.49	8.883	30	PASS
155	5775	MCS0	full	18.5	16.26	16.04	19.27	84.528	30	PASS

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 24 of 190

7 UNDESIRABLE RADIATED EMISSION MEASUREMENT

7.1 Standard Applicable

 $EIRP = ((E^*d)^2) / 30$, where E is the field strength in V/m, d is the measurement distance (3m), EIRP is the equivalent isotropically radiated power in Watts.

7.1.1 5150~5850 MHz

Applicable	Operation	EIRP		Field Strength
to	Freq. (MHz)	Freq. (MHz)	Limits (dBm/MHz)	@ 3m
15.407(b)(1) RSS-247 §6.2.1.2	5150~5250	f ≤ 5150		
15.407(b)(2) RSS-247 §6.2.2.2	5250~5350	f ≥ 5350	PK: -27	PK: 68.2
15.407(b)(3) RSS-247 §6.2.3.2	5475~5725	f ≤ 5470 f ≥ 5725		
		at 75 MHz or more above or be- low the band edge	PK:-27	PK: 68.2
15.407(b)(4)(i)	5725~5850	increasing linearly from 75~25MHz above or below the band edge		PK: 68.2~105.2
RSS-247 §6.2.4.2		increasing linearly from 25~5MHz above or below the band edge	PK:10~15.6	PK: 105.2~110.8
		increasing linearly from 5~0 MHz above or below the band edge	PK: 15.6~27	PK:110.8~122.2

7.1.2 Spurious Emission

Unwanted spurious emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table:

Frequency (MHz)	Field strength (microvolts/meter)	Distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號



Page: 25 of 190

7.2 Measurement Equipment Used:

	Ra	diated Emission Test	Site: SAC D		
EQUIPMENT TYPE	MFR	MODEL NUMBER	SERIAL NUM- BER	LAST CAL.	CAL DUE.
Broadband An- tenna	SCHWAZBECK	VULB 9168	9168-617	11/12/2021	11/11/2022
Horn Antenna	Schwarzbeck	BBHA9170	185	08/06/2021	08/05/2022
Horn Antenna	Schwarzbeck	BBHA9120D	1341	06/04/2021	06/03/2022
Loop Antenna	ETS.LINDGREN	6502	143303	05/07/2021	05/06/2022
3m Site NSA	SGS	966 chamber D	N/A	07/12/2021	07/11/2022
Test Software	audix	e3	E3 20923 SGS Ver.9 (C)	N.C.R	N.C.R
Spectrum Ana- lyzer	KEYSIGHT	N9010A	MY57120200	03/24/2022	03/23/2023
Pre-Amplifier	EMC Instru- ments	EMC184045B	980135	10/27/2021	10/26/2022
Pre-Amplifier	EMC Instru- ments	EMC9135	980234	11/18/2021	11/17/2022
Pre-Amplifier	EMC Instru- ments	EMC12630SE	980273	11/18/2021	11/17/2022
Coaxial Cable	Huber+Suhner	RG 214/U	W21.01	11/18/2021	11/17/2022
Coaxial Cable	Huber Suhner	EMC106-SM-SM- 7200	150703	11/18/2021	11/17/2022
Coaxial Cable	Huber Suhner	SUCOFLEX 104	MY17413/4	11/18/2021	11/17/2022
Attenuator	Marvelous	WATT-218FS-10	RF17	11/18/2021	11/17/2022
Lowpass Filter	Woken	EWT-56-0019	RF173	11/18/2021	11/17/2022
Notch Filter	Woken	EWT-14-0251	RF179	11/18/2021	11/17/2022
Notch Filter	Woken	EWT-14-0275	RF180	11/18/2021	11/17/2022
Notch Filter	Woken	EWT-14-0251	RF181	11/18/2021	11/17/2022
Band Reject Fil- ter	Titan Microwave Co. Ltd	T04N5725589550S01	210519-2-2	07/27/2021	07/26/2022

NOTE: N.C.R refers to Not Calibrated Required.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。




Page: 26 of 190




7.3 **Test Setup**

(A) Radiated Emission Test Set-Up, Frequency From 30MHz to 1000MHz



(B) Radiated Emission Test Set-Up, Frequency Above 1GHz



Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limita Attention is drawn to the limitation of liability, indemnirections formed accuments, subject to ferms and continuous in Certain and intermediate the friends and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

台灣檢驗科技股份有限公司

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 www.sgs.com.tw



Page: 27 of 190

7.4 **Measurement Procedure**

- 1. The testing follows FCC KDB 789033 D02.
- The EUT was placed on a turn table with 0.8m for frequency< 1GHz and 1.5m for frequency> 1GHz above ground plane.
- 3. The turn table shall rotate 360 degrees to determine the position of maximum emission
- EUT is set 3m away from the receiving antenna which varied from 1m to 4m to find out the highest emissions.
- Set the spectrum analyzer as RBW=100 kHz and VBW=300 kHz for Peak Detector (PK) at frequency between 30MHz and 1 GHz
- Use receiver mode as RBW=120 kHz for Quasi-peak (QP) at frequency between 30MHz and 1 GHz.
- Set the spectrum analyzer as RBW=1 MHz, VBW=3 MHz for Maximum Emission Measure-7. ments at frequency above 1 GHz.
- Set the spectrum analyzer as RBW=1 MHz, VBW=10 Hz (Duty cycle > 98%) or VBW ≥ 1/T 8. (Duty cycle < 98%) for Average Emission Measurements at frequency above 1 GHz.
- When measurement procedures for electric field radiated emissions above 1 GHz the EUT measurement is to be made "while keeping the antenna in the 'cone of radiation' from that area and pointed at the area both in azimuth and elevation, with polarization oriented for maximum response." is still within the 3dB illumination BW of the measurement antenna.
- 10. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
- 11. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- **12.** Repeat above procedures until all frequency measured were complete.



Page: 28 of 190

7.5 **Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor (if any) from the measured reading. The basic equation with a sample calculation is as follows:

FS = RA + AF + CL - AG

Where FS = Field Strength

CL = Cable Attenuation Factor (Cable Loss)

RA = Reading Amplitude

AG = Amplifier Gain

AF = Antenna Factor

The limit of the emission level is expressed in dBuV/m, which converts 20*log(uV/m)

Actual $FS(dB\mu V/m) = SPA$. Reading level(dB μV) + Factor(dB) $Factor(dB) = Antenna\ Factor(dB\mu V/m) + Cable\ Loss(dB) - Pre\ Amplifier\ Gain(dB)$

7.6 Test Results of Radiated Spurious Emissions from 9 kHz to 30 MHz

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit per 15.31(o) was not reported.

Pre-scan was done at frequency 5.47 GHz and 5.85 GHz for bandedge measurement of straddle channels 138, 142 and 144 which was 20dB lower than the limit per 15.31(o) was not reported.

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製





Page: 29 of 190

7.7 **Radiated Spurious Emission Measurement Result**

7.7.1 **Spurious Emission**


Report Number :TERF2204000360E2 Test Site :SAC D

Test Date :2022-04-19 **Operation Mode** :802.11a

Test Frequency Temp./Humi. :5200 MHz :19.2/66

Test Mode :TX CH MID Antenna Pol. :Vertical

:Andy Wang **EUT Pol** :NB Plane Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
72.680	Peak	51.13	-20.18	30.95	40.00	-9.05
198.780	Peak	44.37	-19.66	24.71	43.50	-18.79
256.010	Peak	47.37	-17.40	29.97	46.00	-16.03
415.090	Peak	46.06	-13.20	32.87	46.00	-13.13
769.140	Peak	35.98	-6.49	29.49	46.00	-16.51
916.580	Peak	36.87	-4.99	31.87	46.00	-14.13

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-19

Test Frequency :5200 MHz Temp./Humi. :19.2/66

Test Mode :TX CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
31.940	Peak	45.12	-19.32	25.81	40.00	-14.20
199.750	Peak	43.27	-19.73	23.54	43.50	-19.96
256.980	Peak	55.46	-17.35	38.10	46.00	-7.90
434.490	Peak	44.53	-12.67	31.86	46.00	-14.14
769.140	Peak	38.11	-6.49	31.62	46.00	-14.38
958.290	Peak	35.80	-4.24	31.56	46.00	-14.44

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 31 of 190

Report Number :TERF2204000360E2

:NB Plane

Test Site :SAC D

Operation Mode :802.11a

Test Date :2022-04-19

Test Frequency :5300 MHz

EUT Pol


Temp./Humi. :19.2/66

Antenna Pol.

Test Mode :TX CH MID

Engineer :Andy Wang

:Vertical



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
		•		•	•	
72.680	Peak	50.70	-20.18	30.52	40.00	-9.48
122.150	Peak	46.88	-19.26	27.62	43.50	-15.88
357.860	Peak	47.57	-14.50	33.07	46.00	-12.93
514.030	Peak	43.22	-11.42	31.80	46.00	-14.20
669.230	Peak	39.56	-8.07	31.50	46.00	-14.50
954.410	Peak	43.26	-4.28	38.98	46.00	-7.02

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-19

Test Frequency :5300 MHz Temp./Humi. :19.2/66

Test Mode :TX CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
31.940	Peak	44.63	-19.32	25.31	40.00	-14.69
199.750	Peak	45.16	-19.73	25.43	43.50	-18.07
352.040	Peak	49.79	-14.85	34.94	46.00	-11.06
418.970	Peak	47.32	-13.09	34.23	46.00	-11.77
770.110	Peak	36.03	-6.47	29.56	46.00	-16.44
973.810	Peak	38.11	-4.69	33.42	54.00	-20.58

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 33 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-19

Test Frequency :5580 MHz Temp./Humi. :19.2/66

Test Mode :TX CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
73.650	Peak	52.11	-20.53	31.58	40.00	-8.42
124.090	Peak	43.58	-19.15	24.43	43.50	-19.07
258.920	Peak	47.22	-17.25	29.97	46.00	-16.03
454.860	Peak	41.18	-11.67	29.51	46.00	-16.49
770.110	Peak	35.60	-6.47	29.13	46.00	-16.87
934.040	Peak	35.79	-4.56	31.23	46.00	-14.77

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



:SAC D

Test Site

Report No.: TERF2204000360E2

Page: 34 of 190

Report Number :TERF2204000360E2

Operation Mode :802.11a Test Date :2022-04-19

Test Frequency :5580 MHz Temp./Humi. :19.2/66

Test Mode :TX CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum	Factor	Actual FS	Limit @3m	Margin
		Reading Level		_	_	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
110.510	Peak	54.13	-20.14	33.99	43.50	-9.51
199.750	Peak	42.44	-19.73	22.71	43.50	-20.79
255.040	Peak	54.81	-17.46	37.35	46.00	-8.65
407.330	Peak	49.17	-13.45	35.72	46.00	-10.28
667.290	Peak	41.80	-8.00	33.79	46.00	-12.21
912.700	Peak	36.80	-5.13	31.67	46.00	-14.33

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



:SAC D

Report No.: TERF2204000360E2

Page: 35 of 190


Report Number :TERF2204000360E2 Test Site

Operation Mode :802.11a Test Date :2022-04-19

Test Frequency :5785 MHz Temp./Humi. :19.2/66

Test Mode :TX CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
72.680	Peak	53.52	-20.18	33.34	40.00	-6.66
122.150	Peak	49.49	-19.26	30.23	43.50	-13.27
357.860	Peak	49.82	-14.50	35.32	46.00	-10.68
597.450	Peak	46.37	-9.71	36.66	46.00	-9.34
709.000	Peak	47.81	-8.63	39.19	46.00	-6.81
951.500	Peak	38.86	-4.39	34.48	46.00	-11.52

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-19

Test Frequency :5785 MHz Temp./Humi. :19.2/66

Test Mode :TX CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
31.940	Peak	45.01	-19.32	25.69	40.00	-14.31
199.750	Peak	45.57	-19.73	25.84	43.50	-17.66
353.010	Peak	51.90	-14.79	37.11	46.00	-8.89
418.970	Peak	46.79	-13.09	33.70	46.00	-12.30
733.250	Peak	46.55	-7.80	38.75	46.00	-7.25
942.770	Peak	36.19	-4.55	31.64	46.00	-14.36

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 37 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5200 MHz Temp./Humi. :20.4/69

Test Mode :TX CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
10400.000	Peak	40.11	10.11	50.22	68.20	-17.98
15600.000	Average	28.40	9.32	37.72	54.00	-16.28
15600.000	Peak	39.30	9.32	48.62	74.00	-25.38

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 38 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5200 MHz Temp./Humi. :20.4/69

:Horizontal Test Mode :TX CH MID Antenna Pol.

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
10400.000	Peak	41.24	10.11	51.35	68.20	-16.85
15600.000	Average	28.37	9.32	37.69	54.00	-16.31
15600.000	Peak	38.41	9.32	47.73	74.00	-26.27

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 39 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5300 MHz Temp./Humi. :20.4/69

Test Mode :TX CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
10600.000	Average	29.33	9.48	38.81	54.00	-15.19
10600.000	Peak	39.11	9.48	48.60	74.00	-25.40
15900.000	Average	29.40	8.52	37.92	54.00	-16.08
15900.000	Peak	39.40	8.52	47.92	74.00	-26.08

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 40 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5300 MHz Temp./Humi. :20.4/69

:Horizontal Test Mode :TX CH MID Antenna Pol.

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
10600.000	Average	30.38	9.48	39.86	54.00	-14.14
10600.000	Peak	41.35	9.48	50.84	74.00	-23.16
15900.000	Average	26.69	8.52	35.21	54.00	-18.79
15900.000	Peak	36.04	8.52	44.56	74.00	-29.44

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 41 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5580 MHz Temp./Humi. :20.4/69

:TX CH MID Test Mode Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11160.000	Average	29.18	10.80	39.98	54.00	-14.02
11160.000	Peak	38.51	10.80	49.31	74.00	-24.69
16740.000	Peak	34.33	12.01	46.34	68.20	-21.86

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 42 of 190

Report Number :TERF2204000360E2

Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5580 MHz


Temp./Humi. :20.4/69

Antenna Pol.

Test Mode :TX CH MID

:Horizontal





Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11160.000	Average	28.07	10.80	38.86	54.00	-15.14
11160.000	Peak	38.31	10.80	49.10	74.00	-24.90
16740.000	Peak	33.17	12.01	45.17	68.20	-23.03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 43 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5785 MHz Temp./Humi. :20.4/69

Test Mode :TX CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11570.000	Average	29.46	10.16	39.62	54.00	-14.38
11570.000	Peak	40.39	10.16	50.55	74.00	-23.45
17355.000	Peak	37.61	15.06	52.68	68.20	-15.52

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Operation Mode :802.11a Test Date :2022-04-28

Test Frequency :5785 MHz Temp./Humi. :20.4/69

:Horizontal Test Mode :TX CH MID Antenna Pol.

EUT Pol :NB Plane Engineer :Jack Tseng



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
11570.000	Average	29.55	10.16	39.71	54.00	-14.29
11570.000	Peak	39.01	10.16	49.17	74.00	-24.83
17355.000	Peak	35.11	15.06	50.17	68.20	-18.03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。





Page: 45 of 190


7.7.2 Band edge falling to restricted band

Report Number Test Site :SAC D :TERF2204000360E2

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5180 MHz Temp./Humi. :21.6/62 Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane :Andy Wang Engineer



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5150.000	Average	44.02	1.24	45.26	54.00	-8.74
5150,000	Peak	67.71	1.24	68.95	74.00	-5.05

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5180 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW :Horizontal Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5150.000	Average	44.28	1.24	45.51	54.00	-8.49
5150.000	Peak	67.64	1.24	68.88	74.00	-5.12

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 47 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5320 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical Engineer :Andy Wang

EUT Pol :NB Plane



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	48.93	0.38	49.31	54.00	-4.69
5350.000	Peak	69.56	0.38	69.94	74.00	-4.06
5352.360	Average	49.33	0.39	49.72	54.00	-4.28
5352.360	Peak	71.38	0.39	71.78	74.00	-2.22

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Report No.: TERF2204000360E2 Page: 48 of 190




Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5320 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	48.86	0.38	49.23	54.00	-4.77
5350.000	Peak	70.34	0.38	70.71	74.00	-3.29
5353.680	Average	47.52	0.40	47.93	54.00	-6.07
5353.680	Peak	71.52	0.40	71.93	74.00	-2.07

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5500 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5449.640	Average	46.00	0.88	46.88	54.00	-7.12
5449.640	Peak	60.91	0.88	61.79	74.00	-12.21
5460.000	Average	46.19	0.92	47.11	54.00	-6.89
5460.000	Peak	60.08	0.92	61.00	74.00	-13.00
5470.000	Peak	63.18	0.95	64.14	68.20	-4.06






Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5500 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5407.280	Average	45.68	0.78	46.47	54.00	-7.53
5407.280	Peak	61.03	0.78	61.82	74.00	-12.18
5460.000	Average	46.30	0.92	47.22	54.00	-6.78
5460.000	Peak	59.82	0.92	60.74	74.00	-13.26
5469.680	Peak	65.20	0.95	66.16	68.20	-2.04
5470.000	Peak	64.98	0.95	65.93	68.20	-2.27



Page: 51 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5700 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5725.000	Peak	63.78	1.28	65.05	68.20	-3.15

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 52 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5700 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
_							
	5725,000	Peak	64.39	1.28	65.66	68.20	-2.54

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



:SAC D

:21.6/62

:Vertical

:2022-04-21

Test Site

Test Date

Temp./Humi.

Report No.: TERF2204000360E2

Page: 53 of 190


Report Number :TERF2204000360E2

Operation Mode :802.11a

Test Frequency :5720 MHz

Test Mode :BE CH MID Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
5456.600	Average	45.88	0.91	46.79	54.00	-7.21
5456.600	Peak	60.05	0.91	60.96	74.00	-13.04
5460.000	Average	45.88	0.92	46.80	54.00	-7.20
5460.000	Peak	58.83	0.92	59.75	74.00	-14.25
5470.000	Peak	58.56	0.95	59.51	68.20	-8.69
5480.000	Peak	58.82	0.99	59.80	68.20	-8.40
5850.000	Peak	59.16	1.51	60.67	68.20	-7.53
5929.800	Peak	61.49	2.32	63.81	68.20	-4.39

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

台灣檢驗科技股份有限公司

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Member of SGS Group



Page: 54 of 190




Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5720 MHz Temp./Humi. :21.6/62

Test Mode :BE CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5400.700	Average	45.54	0.77	46.31	54.00	-7.69
5400.700	Peak	60.05	0.77	60.82	74.00	-13.18
5460.000	Average	45.86	0.92	46.78	54.00	-7.22
5460.000	Peak	58.69	0.92	59.61	74.00	-14.39
5470.000	Peak	58.71	0.95	59.66	68.20	-8.54
5480.000	Peak	59.09	0.99	60.08	68.20	-8.12
5850.000	Peak	59.55	1.51	61.06	68.20	-7.14
5916.800	Peak	61.40	2.24	63.64	68.20	-4.56

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 55 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5745 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5648.050	Peak	63.08	0.98	64.07	68.20	-4.13
5650.000	Peak	61.91	0.98	62.88	68.20	-5.32
5700.000	Peak	77.01	1.01	78.02	105.20	-27.18
5720.000	Peak	83.97	1.22	85.19	110.80	-25.61
5725.000	Peak	86.17	1.28	87.45	122.20	-34.75



Page: 56 of 190

Report Number :TERF2204000360E2 Test Site :SAC D


Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5745 MHz

Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dΒμV/m	dBμV/m	dB
5648.515	Peak	62.45	0.98	63.43	68.20	-4.77
5650.000	Peak	61.52	0.98	62.49	68.20	-5.71
5700.000	Peak	80.44	1.01	81.44	105.20	-23.76
5720.000	Peak	83.25	1.22	84.47	110.80	-26.33
5725.000	Peak	86.94	1.28	88.22	122.20	-33.98

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 57 of 190

Report Number :TERF2204000360E2 Test Site :SAC D


Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5825 MHz

Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	80.73	1.51	82.24	122.20	-39.96
5855.000	Peak	75.07	1.58	76.65	110.80	-34.15
5875.000	Peak	71.08	1.83	72.91	105.20	-32.29
5925.000	Peak	59.14	2.29	61.43	68.20	-6.77
5931.990	Peak	61.11	2.33	63.44	68.20	-4.76

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。





Page: 58 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11a Test Date :2022-04-21

Test Frequency :5825 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
Peak	82.32	1.51	83.83	122.20	-38.37
Peak	77.21	1.58	78.78	110.80	-32.02
Peak	74.17	1.83	76.00	105.20	-29.20
Peak	59.10	2.29	61.39	68.20	-6.81
Peak	61.21	2.19	63.40	68.20	-4.80
	Mode PK/QP/AV Peak Peak Peak Peak	Mode Reading Level dBμV Peak 82.32 Peak 77.21 Peak 74.17 Peak 59.10	Mode PK/QP/AV Reading Level dBμV dB Peak 82.32 1.51 Peak 77.21 1.58 Peak 74.17 1.83 Peak 59.10 2.29	Mode PK/QP/AV Reading Level dBμV FS dBμV/m Peak 82.32 1.51 83.83 Peak 77.21 1.58 78.78 Peak 74.17 1.83 76.00 Peak 59.10 2.29 61.39	Mode PK/QP/AV Reading Level dBμV FS dBμV/m @3m dBμV/m Peak 82.32 1.51 83.83 122.20 Peak 77.21 1.58 78.78 110.80 Peak 74.17 1.83 76.00 105.20 Peak 59.10 2.29 61.39 68.20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

台灣檢驗科技股份有限公司

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Member of SGS Group



Page: 59 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5180 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5148.900	Average	47.42	1.22	48.64	54.00	-5.36
5148.900	Peak	66.80	1.22	68.02	74.00	-5.98
5150.000	Average	47.53	1.24	48.76	54.00	-5.24
5150.000	Peak	66.40	1.24	67.64	74.00	-6.36



Page: 60 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5180 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW :Horizontal Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5147.500	Average	47.44	1.20	48.64	54.00	-5.36
5147.500	Peak	68.13	1.20	69.33	74.00	-4.67
5150.000	Average	47.54	1.24	48.78	54.00	-5.22
5150.000	Peak	65.43	1.24	66.67	74.00	-7.33

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 61 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5320 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	45.89	0.38	46.27	54.00	-7.73
5350.000	Peak	66.81	0.38	67.18	74.00	-6.82
5350.800	Average	45.06	0.38	45.44	54.00	-8.56
5350.800	Peak	68.73	0.38	69.11	74.00	-4.89

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



:SAC D

Test Site

Report No.: TERF2204000360E2

Page: 62 of 190


Report Number :TERF2204000360E2

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5320 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	45.88	0.38	46.25	54.00	-7.75
5350.000	Peak	67.58	0.38	67.96	74.00	-6.04
5352.600	Average	45.80	0.40	46.20	54.00	-7.80
5352.600	Peak	67.85	0.40	68.24	74.00	-5.76

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5500 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5456.840	Average	45.81	0.91	46.72	54.00	-7.28
5456.840	Peak	61.07	0.91	61.98	74.00	-12.02
5460.000	Average	45.88	0.92	46.80	54.00	-7.20
5460.000	Peak	59.69	0.92	60.61	74.00	-13.39
5469.080	Peak	62.46	0.95	63.41	68.20	-4.79
5470.000	Peak	60.36	0.95	61.31	68.20	-6.89






Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5500 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
						·
5455.520	Average	45.91	0.90	46.81	54.00	-7.19
5455.520	Peak	60.80	0.90	61.70	74.00	-12.30
5460.000	Average	45.87	0.92	46.78	54.00	-7.22
5460.000	Peak	58.08	0.92	59.00	74.00	-15.00
5468.360	Peak	64.48	0.95	65.42	68.20	-2.78
5470.000	Peak	61.29	0.95	62.25	68.20	-5.95

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 65 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5700 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
	5725.000	Peak	62.27	1.28	63.55	68.20	-4.65
	5726.480	Peak	63.68	1.29	64.97	68.20	-3.23

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 66 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5700 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
	5725.000	Peak	63.38	1.28	64.65	68.20	-3.55
	5725.280	Peak	63.98	1.28	65.26	68.20	-2.94






Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5720 MHz Temp./Humi. :21.6/62

Test Mode :BE CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
5455.300	Average	45.84	0.90	46.74	54.00	-7.26
5455.300	Peak	59.75	0.90	60.65	74.00	-13.35
5460.000	Average	45.84	0.92	46.76	54.00	-7.24
5460.000	Peak	58.16	0.92	59.08	74.00	-14.92
5470.000	Peak	59.30	0.95	60.26	68.20	-7.94
5480.000	Peak	59.47	0.99	60.46	68.20	-7.74
5850.000	Peak	60.22	1.51	61.73	68.20	-6.47
5936.950	Peak	61.10	2.36	63.47	68.20	-4.73






Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5720 MHz Temp./Humi. :21.6/62

Test Mode :BE CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5452.050	Average	45.79	0.89	46.68	54.00	-7.32
5452.050	Peak	60.13	0.89	61.03	74.00	-12.97
5460.000	Average	45.82	0.92	46.74	54.00	-7.26
5460.000	Peak	59.39	0.92	60.31	74.00	-13.69
5470.000	Peak	58.73	0.95	59.68	68.20	-8.52
5480.000	Peak	59.84	0.99	60.83	68.20	-7.37
5850.000	Peak	59.55	1.51	61.06	68.20	-7.14
5986.350	Peak	62.66	2.01	64.67	68.20	-3.53

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5745 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5648.050	Peak	62.85	0.98	63.84	68.20	-4.36
5650.000	Peak	61.18	0.98	62.16	68.20	-6.04
5700.000	Peak	73.32	1.01	74.33	105.20	-30.87
5720.000	Peak	79.58	1.22	80.80	110.80	-30.00
5725.000	Peak	84.96	1.28	86.24	122.20	-35.96



Page: 70 of 190

Report Number :TERF2204000360E2

Test Site :SAC D

Operation Mode :802.11ac20

Test Date :2022-04-21


Test Frequency :5745 MHz Temp./Humi. :21.6/62

Antenna Pol.

Test Mode :BE CH LOW **EUT Pol** :NB Plane

Engineer :Andy Wang

:Horizontal



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5618.600	Peak	61.20	1.08	62.28	68.20	-5.92
5650.000	Peak	61.36	0.98	62.34	68.20	-5.86
5700.000	Peak	74.35	1.01	75.36	105.20	-29.84
5720.000	Peak	79.75	1.22	80.97	110.80	-29.83
5725.000	Peak	85.44	1.28	86.72	122.20	-35.48

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 71 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5825 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5850.000	Peak	74.67	1.51	76.18	122.20	-46.02
5855.000	Peak	75.11	1.58	76.69	110.80	-34.11
5875.000	Peak	64.34	1.83	66.17	105.20	-39.03
5925.000	Peak	59.67	2.29	61.96	68.20	-6.24
5963.270	Peak	61.49	2.28	63.77	68.20	-4.43

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



:SAC D

Report No.: TERF2204000360E2

Page: 72 of 190


Report Number :TERF2204000360E2 Test Site

Operation Mode :802.11ac20 Test Date :2022-04-21

Test Frequency :5825 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	77.21	1.51	78.73	122.20	-43.47
5855.000	Peak	74.82	1.58	76.40	110.80	-34.40
5875.000	Peak	66.48	1.83	68.31	105.20	-36.89
5925.000	Peak	60.04	2.29	62.33	68.20	-5.87
5947.290	Peak	61.08	2.42	63.50	68.20	-4.70



Page: 73 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-21

Test Frequency :5190 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5145.400	Average	47.60	1.17	48.77	54.00	-5.23
5145.400	Peak	70.62	1.17	71.80	74.00	-2.20
5150.000	Average	47.84	1.24	49.07	54.00	-4.93
5150.000	Peak	69.35	1.24	70.58	74.00	-3.42

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 74 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-21

Test Frequency :5190 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW :Horizontal Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5144.700	Average	47.46	1.16	48.62	54.00	-5.38
5144.700	Peak	67.94	1.16	69.10	74.00	-4.90
5150.000	Average	47.50	1.24	48.73	54.00	-5.27
5150.000	Peak	63.19	1.24	64.43	74.00	-9.57

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 75 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-21

Test Frequency :5310 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	50.12	0.38	50.50	54.00	-3.50
5350.000	Peak	70.31	0.38	70.68	74.00	-3.32
5351.000	Average	49.67	0.38	50.05	54.00	-3.95
5351.000	Peak	70.82	0.38	71.21	74.00	-2.79

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號



Page: 76 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-21

Test Frequency :5310 MHz Temp./Humi. :21.6/62

:Horizontal Test Mode :BE CH HIGH Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	45.66	0.38	46.04	54.00	-7.96
5350.000	Peak	68.59	0.38	68.97	74.00	-5.03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 77 of 190

Report Number :TERF2204000360E2

Test Site :SAC D


Operation Mode :802.11ac40 Test Date :2022-04-22

Test Frequency :5510 MHz

Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5454.120	Average	45.80	0.90	46.70	54.00	-7.30
5454.120	Peak	62.33	0.90	63.23	74.00	-10.77
5460.000	Average	45.93	0.92	46.85	54.00	-7.15
5460.000	Peak	60.59	0.92	61.51	74.00	-12.49
5469.840	Peak	64.74	0.95	65.70	68.20	-2.50
5470.000	Peak	62.92	0.95	63.88	68.20	-4.32

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。





Page: 78 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-22

Test Frequency :5510 MHz Temp./Humi. :21.6/62

Test Mode :BE CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
Average	46.80	0.89	47.69	54.00	-6.31
Peak	62.50	0.89	63.39	74.00	-10.61
Average	46.59	0.92	47.51	54.00	-6.49
Peak	59.66	0.92	60.58	74.00	-13.42
Peak	64.36	0.94	65.30	68.20	-2.90
Peak	63.04	0.95	63.99	68.20	-4.21
	Mode PK/QP/AV Average Peak Average Peak Peak	Mode PK/QP/AV Reading Level dBµV Average 46.80 Peak 62.50 Average 46.59 Peak 59.66 Peak 64.36	Mode PK/QP/AV Reading Level dBμV dB Average 46.80 0.89 Peak 62.50 0.89 Average 46.59 0.92 Peak 59.66 0.92 Peak 64.36 0.94	Mode PK/QP/AV Reading Level dB μV FS dB μV/m Average 46.80 0.89 47.69 Peak 62.50 0.89 63.39 Average 46.59 0.92 47.51 Peak 59.66 0.92 60.58 Peak 64.36 0.94 65.30	Mode PK/QP/AVReading Level dBμVFS dBμV/m@3m dBμV/mAverage46.800.8947.6954.00Peak62.500.8963.3974.00Average46.590.9247.5154.00Peak59.660.9260.5874.00Peak64.360.9465.3068.20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 79 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-25

Test Frequency :5670 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	63.27	1.28	64.54	68.20	-3.66
5726.480	Peak	64.33	1.29	65.62	68.20	-2.58

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 80 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-25

Test Frequency :5670 MHz Temp./Humi. :21.6/62

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
	5725.000	Peak	63.30	1.28	64.58	68.20	-3.62
	5731.040	Peak	63.87	1.34	65.21	68.20	-2.99

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 81 of 190



Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-25

Test Frequency :5710 MHz Temp./Humi. :21.6/62

Test Mode :BE CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5429.300	Average	46.55	0.84	47.38	54.00	-6.62
5429.300	Peak	60.48	0.84	61.32	74.00	-12.68
5460.000	Average	46.57	0.92	47.48	54.00	-6.52
5460.000	Peak	59.13	0.92	60.05	74.00	-13.95
5470.000	Peak	60.30	0.95	61.26	68.20	-6.94
5480.000	Peak	59.23	0.99	60.22	68.20	-7.98
5850.000	Peak	59.65	1.51	61.17	68.20	-7.03
5936.300	Peak	61.82	2.36	64.17	68.20	-4.03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號 t (886-2) 2299-3279 f (886-2) 2298-0488 www.sgs.com.tw






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-25

Test Frequency :5710 MHz Temp./Humi. :21.6/62

Test Mode :BE CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5400.050	Average	46.17	0.77	46.94	54.00	-7.06
5400.050	Peak	61.16	0.77	61.93	74.00	-12.07
5460.000	Average	46.50	0.92	47.42	54.00	-6.58
5460.000	Peak	59.48	0.92	60.40	74.00	-13.60
5470.000	Peak	59.77	0.95	60.72	68.20	-7.48
5480.000	Peak	60.45	0.99	61.44	68.20	-6.76
5850.000	Peak	60.27	1.51	61.78	68.20	-6.42
5929.800	Peak	61.52	2.32	63.84	68.20	-4.36



Page: 83 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-26

Test Frequency :5755 MHz Temp./Humi. :22.3/61

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5641.250	Peak	64.58	1.01	65.59	68.20	-2.61
5650.000	Peak	61.03	0.98	62.01	68.20	-6.19
5700.000	Peak	73.55	1.01	74.56	105.20	-30.64
5720.000	Peak	82.28	1.22	83.51	110.80	-27.29
5725.000	Peak	84.74	1.28	86.02	122.20	-36.18

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-26

Test Frequency :5755 MHz Temp./Humi. :22.3/61

Test Mode :BE CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5640.590	Peak	64.00	1.01	65.01	68.20	-3.19
5650.000	Peak	61.73	0.98	62.71	68.20	-5.49
5700.000	Peak	71.65	1.01	72.66	105.20	-32.54
5720.000	Peak	84.05	1.22	85.27	110.80	-25.53
5725.000	Peak	83.22	1.28	84.49	122.20	-37.71



Page: 85 of 190


Report Number :TERF2204000360E2

Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-26

Test Frequency :5795 MHz Test Mode :BE CH HIGH Temp./Humi. :22.3/61 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5850.000	Peak	74.59	1.51	76.11	122.20	-46.09
5855.000	Peak	72.85	1.58	74.43	110.80	-36.37
5875.000	Peak	66.50	1.83	68.33	105.20	-36.87
5925.000	Peak	60.46	2.29	62.75	68.20	-5.45
5948.720	Peak	61.79	2.43	64.22	68.20	-3.98

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac40 Test Date :2022-04-26

Test Frequency :5795 MHz Temp./Humi. :22.3/61

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμ̈V	dB	dBµV/m	dBμV/m	dB
5850.000	Peak	74.60	1.51	76.11	122.20	-46.09
5855.000	Peak	73.42	1.58	74.99	110.80	-35.81
5875.000	Peak	68.38	1.83	70.21	105.20	-34.99
5925.000	Peak	59.47	2.29	61.76	68.20	-6.44
5959.340	Peak	61.17	2.33	63.50	68.20	-4.70

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 87 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5210 MHz Temp./Humi. :22.3/61

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5117.120	Average	50.11	0.76	50.87	54.00	-3.13
5117.120	Peak	70.74	0.76	71.50	74.00	-2.50
5150.000	Average	50.74	1.24	51.97	54.00	-2.03
5150.000	Peak	68.15	1.24	69.39	74.00	-4.61



Page: 88 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5210 MHz Temp./Humi. :22.3/61

Test Mode :BE CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5120.920	Average	49.38	0.82	50.20	54.00	-3.80
5120.920	Peak	71.12	0.82	71.93	74.00	-2.07
5150.000	Average	50.58	1.24	51.82	54.00	-2.18
5150.000	Peak	69.18	1.24	70.42	74.00	-3.58

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 89 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5290 MHz Temp./Humi. :22.3/61

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
5350.000		50.17	0.38	50.55	54.00	-3.45
5350.000 5350.000 5379.500	Average Peak Average	65.29 50.42	0.38 0.61	65.66 51.02	74.00 54.00	-8.34 -2.98
5379.500	Peak	68.99	0.61	69.60	74.00	-2.98 -4.40

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 90 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5290 MHz Temp./Humi. :22.3/61

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5350.000	Average	50.19	0.38	50.56	54.00	-3.44
5350.000	Peak	66.64	0.38	67.02	74.00	-6.98
5377.500	Average	50.12	0.59	50.71	54.00	-3.29
5377.500	Peak	71.29	0.59	71.88	74.00	-2.12

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 91 of 190




Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5530 MHz Temp./Humi. :22.3/61

Test Mode :BE CH LOW Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5441.200	Average	50.98	0.86	51.84	54.00	-2.16
5441.200	Peak	63.43	0.86	64.29	74.00	-9.71
5460.000	Average	51.03	0.92	51.95	54.00	-2.05
5460.000	Peak	61.91	0.92	62.83	74.00	-11.17
5466.900	Peak	65.01	0.94	65.95	68.20	-2.25
5470.000	Peak	59.24	0.95	60.20	68.20	-8.00

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 92 of 190

Report Number :TERF2204000360E2

:NB Plane

Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5530 MHz

EUT Pol


Temp./Humi. :22.3/61

Antenna Pol.

Test Mode :BE CH LOW

> Engineer :Andy Wang

:Horizontal



Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
Average	47.73	0.86	48.59	54.00	-5.41
Peak	63.70	0.86	64.56	74.00	-9.44
Average	48.40	0.92	49.32	54.00	-4.68
Peak	62.46	0.92	63.38	74.00	-10.62
Peak	64.31	0.94	65.25	68.20	-2.95
Peak	62.30	0.95	63.26	68.20	-4.94
	Mode PK/QP/AV Average Peak Average Peak Peak	Mode PK/QP/AV Reading Level dBµV Average 47.73 Peak 63.70 Average 48.40 Peak 62.46 Peak 64.31	Mode PK/QP/AV Reading Level dBμV dB Average 47.73 0.86 Peak 63.70 0.86 Average 48.40 0.92 Peak 62.46 0.92 Peak 64.31 0.94	Mode PK/QP/AVReading Level dBμVFS dBμV/mAverage47.730.8648.59Peak63.700.8664.56Average48.400.9249.32Peak62.460.9263.38Peak64.310.9465.25	Mode PK/QP/AV Reading Level dBμV FS dBμV/m @3m dBμV/m Average 47.73 0.86 48.59 54.00 Peak 63.70 0.86 64.56 74.00 Average 48.40 0.92 49.32 54.00 Peak 62.46 0.92 63.38 74.00 Peak 64.31 0.94 65.25 68.20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 93 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5610 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
							_
	5725.000	Peak	61.65	1.28	62.92	68.20	-5.28

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 94 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5610 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	64.65	1.28	65.93	68.20	-2.27

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5690 MHz Temp./Humi. :22.3/68

Test Mode :BE CH MID Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5439.050	Average	39.10	0.86	39.96	54.00	-14.04
5439.050	Peak	55.89	0.86	56.75	74.00	-17.25
5460.000	Average	39.85	0.92	40.77	54.00	-13.23
5460.000	Peak	51.96	0.92	52.88	74.00	-21.12
5470.000	Peak	52.48	0.95	53.43	68.20	-14.77
5480.000	Peak	51.08	0.99	52.07	68.20	-16.13
5850.000	Peak	64.03	1.51	65.54	68.20	-2.66






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5690 MHz Temp./Humi. :22.3/68

Test Mode :BE CH MID Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5437.100	Average	39.98	0.86	40.84	54.00	-13.16
5437.100	Peak	53.28	0.86	54.14	74.00	-19.86
5460.000	Average	40.32	0.92	41.24	54.00	-12.76
5460.000	Peak	51.33	0.92	52.25	74.00	-21.75
5470.000	Peak	51.89	0.95	52.84	68.20	-15.36
5480.000	Peak	55.97	0.99	56.96	68.20	-11.24
5850.000	Peak	63.11	1.51	64.63	68.20	-3.57

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 97 of 190

Report Number :TERF2204000360E2


Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5775 MHz Test Mode :BE CH LOW Temp./Humi. :22.3/68

Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5649.665	Peak	63.81	0.98	64.79	68.20	-3.41
5650.000	Peak	62.18	0.98	63.15	68.20	-5.05
5700.000	Peak	73.57	1.01	74.58	105.20	-30.62
5720.000	Peak	73.36	1.22	74.58	110.80	-36.22
5725.000	Peak	74.12	1.28	75.39	122.20	-46.81

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。






Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5775 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5649.335	Peak	62.93	0.98	63.91	68.20	-4.29
5650.000	Peak	61.37	0.98	62.34	68.20	-5.86
5700.000	Peak	73.83	1.01	74.84	105.20	-30.36
5720.000	Peak	73.58	1.22	74.80	110.80	-36.00
5725.000	Peak	77.45	1.28	78.73	122.20	-43.47



Page: 99 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5775 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	74.90	1.51	76.41	122.20	-45.79
5855.000	Peak	74.86	1.58	76.44	110.80	-34.36
5875.000	Peak	71.83	1.83	73.66	105.20	-31.54
5925.000	Peak	62.89	2.29	65.18	68.20	-3.02
5929.600	Peak	63.86	2.32	66.17	68.20	-2.03

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

台灣檢驗科技股份有限公司

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Member of SGS Group



Page: 100 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ac80 Test Date :2022-04-26

Test Frequency :5775 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	71.30	1.51	72.82	122.20	-49.38
5855.000	Peak	72.19	1.58	73.77	110.80	-37.03
5875.000	Peak	70.23	1.83	72.06	105.20	-33.14
5925.000	Peak	61.68	2.29	63.97	68.20	-4.23
5934.600	Peak	63.01	2.35	65.35	68.20	-2.85



Page: 101 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5180 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5148.900	Average	48.62	1.22	49.84	54.00	-4.16
5148.900	Peak	67.53	1.22	68.76	74.00	-5.24
5150.000	Average	48.68	1.24	49.92	54.00	-4.08
5150.000	Peak	67.24	1.24	68.48	74.00	-5.52

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 102 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5180 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU :Horizontal Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
-		· J	-			
5148.200	Average	46.56	1.21	47.78	54.00	-6.22
5148.200	Peak	65.62	1.21	66.83	74.00	-7.17
5150.000	Average	47.12	1.24	48.36	54.00	-5.64
5150.000	Peak	65.11	1.24	66.35	74.00	-7.65



Page: 103 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5180 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 26/0 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5121.600	Average	47.75	0.83	48.57	54.00	-5.43
5121.600	Peak	62.62	0.83	63.44	74.00	-10.56
5150.000	Average	47.80	1.24	49.04	54.00	-4.96
5150.000	Peak	60.33	1.24	61.57	74.00	-12.43



Page: 104 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5180 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 26/0 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5115.300	Average	40.39	0.74	41.12	54.00	-12.88
5115.300	Peak	54.39	0.74	55.12	74.00	-18.88
5150.000	Average	40.31	1.24	41.55	54.00	-12.45
5150.000	Peak	53.14	1.24	54.38	74.00	-19.62

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 105 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5180 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 52/37 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5126.500	Average	40.53	0.90	41.43	54.00	-12.57
5126.500	Peak	55.20	0.90	56.10	74.00	-17.90
5150.000	Average	41.24	1.24	42.48	54.00	-11.52
5150.000	Peak	55.40	1.24	56.64	74.00	-17.36

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 106 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5180 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 52/37 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5120.900	Average	40.37	0.82	41.18	54.00	-12.82
5120.900	Peak	54.47	0.82	55.29	74.00	-18.71
5150.000	Average	40.49	1.24	41.73	54.00	-12.27
5150.000	Peak	53.33	1.24	54.56	74.00	-19.44

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 107 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5180 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 106/53 :Vertical Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5148.900	Average	41.66	1.22	42.89	54.00	-11.11
5148.900	Peak	56.04	1.22	57.26	74.00	-16.74
5150.000	Average	41.88	1.24	43.12	54.00	-10.88
5150.000	Peak	55.79	1.24	57.03	74.00	-16.97

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 108 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5180 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 106/53 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5146.100	Average	40.73	1.18	41.91	54.00	-12.09
5146.100	Peak	55.01	1.18	56.19	74.00	-17.81
5150.000	Average	40.96	1.24	42.20	54.00	-11.80
5150.000	Peak	55.32	1.24	56.56	74.00	-17.44

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 109 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5320 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
						_
5350.000	Average	50.41	0.38	50.78	54.00	-3.22
5350.000	Peak	68.02	0.38	68.39	74.00	-5.61
5354.160	Average	47.37	0.41	47.78	54.00	-6.22
5354.160	Peak	70.53	0.41	70.94	74.00	-3.06

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 110 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5320 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	51.21	0.38	51.59	54.00	-2.41
5350.000	Peak	68.65	0.38	69.02	74.00	-4.98
5350.920	Average	50.37	0.38	50.75	54.00	-3.25
5350.920	Peak	71.49	0.38	71.87	74.00	-2.13

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 111 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5320 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 26/8 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	40.15	0.38	40.53	54.00	-13.47
5350.000	Peak	53.14	0.38	53.52	74.00	-20.48
5358.960	Average	39.81	0.45	40.26	54.00	-13.74
5358.960	Peak	54.39	0.45	54.84	74.00	-19.16

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 112 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5320 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 26/8 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5350.000	Average	40.04	0.38	40.42	54.00	-13.58
5350.000	Peak	53.99	0.38	54.36	74.00	-19.64
5368.800	Average	40.61	0.52	41.13	54.00	-12.87
5368.800	Peak	54.38	0.52	54.90	74.00	-19.10

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 113 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5320 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 52/40 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	41.47	0.38	41.84	54.00	-12.16
5350.000	Peak	52.85	0.38	53.23	74.00	-20.77
5395.080	Average	39.22	0.73	39.95	54.00	-14.05
5395.080	Peak	54.06	0.73	54.79	74.00	-19.21

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 114 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5320 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 52/40 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	40.68	0.38	41.06	54.00	-12.94
5350.000	Peak	53.96	0.38	54.33	74.00	-19.67
5351.640	Average	40.16	0.39	40.54	54.00	-13.46
5351.640	Peak	55.60	0.39	55.98	74.00	-18.02

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 115 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5320 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 106/54 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	41.61	0.38	41.99	54.00	-12.01
5350.000	Peak	54.97	0.38	55.34	74.00	-18.66
5352.240	Average	41.43	0.39	41.82	54.00	-12.18
5352.240	Peak	55.60	0.39	55.99	74.00	-18.01

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 116 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5320 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 106/54 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	41.22	0.38	41.59	54.00	-12.41
5350.000	Peak	53.84	0.38	54.21	74.00	-19.79
5351.760	Average	41.38	0.39	41.77	54.00	-12.23
5351.760	Peak	55.00	0.39	55.39	74.00	-18.61

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 117 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5500 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
		•	ID.	_	_	ın
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
5459.600	Average	42.68	0.92	43.60	54.00	-10.40
5459.600	Peak	61.38	0.92	62.30	74.00	-11.70
5460.000	Average	42.85	0.92	43.77	54.00	-10.23
5460.000	Peak	60.16	0.92	61.08	74.00	-12.92
5467.640	Peak	64.49	0.95	65.43	68.20	-2.77
5470.000	Peak	64.06	0.95	65.01	68.20	-3.19

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 118 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5500 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5459.360	Average	44.21	0.92	45.12	54.00	-8.88
5459.360	Peak	61.14	0.92	62.06	74.00	-11.94
5460.000	Average	44.01	0.92	44.93	54.00	-9.07
5460.000	Peak	60.31	0.92	61.23	74.00	-12.77
5468.000	Peak	64.72	0.95	65.67	68.20	-2.53
5470.040	Peak	64.13	0.95	65.09	68.20	-3.11

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



:SAC D

Report No.: TERF2204000360E2

Page: 119 of 190


Report Number :TERF2204000360E2 Test Site

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5500 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 26/0 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5421.440	Average	39.52	0.82	40.34	54.00	-13.66
5421.440	Peak	54.67	0.82	55.49	74.00	-18.51
5460.000	Average	40.62	0.92	41.54	54.00	-12.46
5460.000	Peak	52.73	0.92	53.65	74.00	-20.35
5468.120	Peak	54.48	0.95	55.43	68.20	-12.77
5470.000	Peak	53.79	0.95	54.74	68.20	-13.46

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 120 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5500 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 26/0 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5453.600	Average	40.03	0.90	40.92	54.00	-13.08
5453.600	Peak	54.34	0.90	55.24	74.00	-18.76
5460.000	Average	40.19	0.92	41.11	54.00	-12.89
5460.000	Peak	53.24	0.92	54.16	74.00	-19.84
5465.000	Peak	54.89	0.94	55.82	68.20	-12.38
5470.000	Peak	54.16	0.95	55.11	68.20	-13.09

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 121 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5500 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 52/37 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5440.400	Average	40.17	0.86	41.03	54.00	-12.97
5440.400	Peak	55.07	0.86	55.93	74.00	-18.07
5460.000	Average	40.73	0.92	41.64	54.00	-12.36
5460.000	Peak	53.13	0.92	54.05	74.00	-19.95
5469.680	Peak	55.37	0.95	56.32	68.20	-11.88
5470.000	Peak	54.57	0.95	55.53	68.20	-12.67

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service Price Price



Page: 122 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5500 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 52/37 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5451.320	Average	40.22	0.89	41.11	54.00	-12.89
5451.320	Peak	54.69	0.89	55.58	74.00	-18.42
5460.000	Average	40.61	0.92	41.53	54.00	-12.47
5460.000	Peak	53.34	0.92	54.26	74.00	-19.74
5469.800	Peak	57.05	0.95	58.00	68.20	-10.20
5470.000	Peak	54.18	0.95	55.14	68.20	-13.06

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 123 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5500 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 106/53 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5458.040	Average	43.26	0.91	44.17	54.00	-9.83
5458.040	Peak	59.36	0.91	60.27	74.00	-13.73
5460.000	Average	41.36	0.92	42.28	54.00	-11.72
5460.000	Peak	56.31	0.92	57.23	74.00	-16.77
5465.120	Peak	60.15	0.94	61.09	68.20	-7.11
5470.000	Peak	57.84	0.95	58.80	68.20	-9.40

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 124 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5500 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 106/53 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
Average	42.40	0.91	43.30	54.00	-10.70
Peak	55.47	0.91	56.38	74.00	-17.62
Average	40.65	0.92	41.57	54.00	-12.43
Peak	53.13	0.92	54.05	74.00	-19.95
Peak	55.58	0.95	56.53	68.20	-11.67
Peak	54.32	0.95	55.27	68.20	-12.93
	Mode PK/QP/AV Average Peak Average Peak Peak	Mode PK/QP/AV Reading Level dBμV Average 42.40 Peak 55.47 Average 40.65 Peak 53.13 Peak 55.58	Mode PK/QP/AV Reading Level dBμV dB Average 42.40 0.91 Peak 55.47 0.91 Average 40.65 0.92 Peak 53.13 0.92 Peak 55.58 0.95	Mode PK/QP/AVReading Level dB μVFS dB μV/mAverage42.400.9143.30Peak55.470.9156.38Average40.650.9241.57Peak53.130.9254.05Peak55.580.9556.53	Mode PK/QP/AV Reading Level dB μV FS dB μV/m @3m dB μV/m Average Peak 55.47 0.91 43.30 54.00 Peak 55.47 0.91 56.38 74.00 Average

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 125 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5700 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
	5725.000	Peak	61.91	1.28	63.19	68.20	-5.01
	5726.480	Peak	63.45	1.29	64.74	68.20	-3.46

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 126 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5700 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	60.94	1.28	62.21	68.20	-5.99
5725.160	Peak	61.99	1.28	63.26	68.20	-4.94

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 127 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5700 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 26/8 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	58.46	1.28	59.74	68.20	-8.46
5725.520	Peak	59.38	1.28	60.66	68.20	-7.54

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 128 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-27

Test Frequency :5700 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 26/8 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	56.52	1.28	57.80	68.20	-10.40
5725.880	Peak	56.77	1.29	58.05	68.20	-10.15

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

解析方方式の子、上報音の名性は列風之体の耳具・「同時以後の理味情物人」を報告不能争之も自由計画・不可能的技術。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

IN Ltd. No.134,Wu Kung Road, New Taipei Industrial Park, Wuku District, New Taipei City, Taiwan/新北市五股區新北產業園區五工路 134 號



Page: 129 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5700 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 52/40 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	58.14	1.28	59.42	68.20	-8.78
5725.280	Peak	59.45	1.28	60.73	68.20	-7.47

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 130 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5700 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 52/40 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
						_
5725.000	Peak	56.00	1.28	57.28	68.20	-10.92
5762.720	Peak	57.25	1.63	58.88	68.20	-9.32

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 131 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5700 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 106/54 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	56.91	1.28	58.18	68.20	-10.02
5725.400	Peak	58.01	1.28	59.29	68.20	-8.91

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 132 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5700 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 106/54 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
_	MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
	5725.000	Peak	59.15	1.28	60.42	68.20	-7.78
	5725.160	Peak	60.26	1.28	61.54	68.20	-6.66

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 133 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5720 MHz Temp./Humi. :22.3/68

Test Mode :BE CH MID FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5431.250	Average	39.29	0.84	40.14	54.00	-13.86
5431.250	Peak	53.71	0.84	54.55	74.00	-19.45
5460.000	Average	39.09	0.92	40.01	54.00	-13.99
5460.000	Peak	52.20	0.92	53.12	74.00	-20.88
5470.000	Peak	51.70	0.95	52.65	68.20	-15.55
5480.000	Peak	52.69	0.99	53.68	68.20	-14.52
5850.000	Peak	52.67	1.51	54.18	68.20	-14.02
5933.700	Peak	53.77	2.34	56.11	68.20	-12.09

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 134 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5720 MHz Temp./Humi. :22.3/68

Test Mode :BE CH MID FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5455.300	Average	39.56	0.90	40.46	54.00	-13.54
5455.300	Peak	52.76	0.90	53.67	74.00	-20.33
5460.000	Average	39.33	0.92	40.25	54.00	-13.75
5460.000	Peak	51.60	0.92	52.52	74.00	-21.48
5470.000	Peak	51.32	0.95	52.27	68.20	-15.93
5480.000	Peak	51.45	0.99	52.43	68.20	-15.77
5850.000	Peak	52.50	1.51	54.02	68.20	-14.18
5929.150	Peak	53.42	2.32	55.74	68.20	-12.46

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 135 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 26/0 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



	Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
	N / I I —		•	٩D	_	_	٩D
_	MHz	PK/QP/AV	dΒμV	<u>dB</u>	dBµV/m	dBµV/m	dB
	5455.950	Average	39.03	0.91	39.93	54.00	-14.07
	5455.950	Peak	53.44	0.91	54.35	74.00	-19.65
	5460.000	Average	39.04	0.92	39.96	54.00	-14.04
	5460.000	Peak	51.42	0.92	52.34	74.00	-21.66
	5470.000	Peak	51.52	0.95	52.47	68.20	-15.73
	5480.000	Peak	51.94	0.99	52.93	68.20	-15.27
	5850.000	Peak	52.92	1.51	54.43	68.20	-13.77
	5861.550	Peak	54.06	1.66	55.72	68.20	-12.48

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 136 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 26/0 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5444.900	Average	39.16	0.87	40.03	54.00	-13.97
5444.900	Peak	53.20	0.87	54.08	74.00	-19.92
5460.000	Average	39.00	0.92	39.92	54.00	-14.08
5460.000	Peak	51.30	0.92	52.22	74.00	-21.78
5470.000	Peak	52.12	0.95	53.08	68.20	-15.12
5480.000	Peak	53.22	0.99	54.21	68.20	-13.99
5850.000	Peak	51.89	1.51	53.41	68.20	-14.79
5940.200	Peak	53.07	2.38	55.46	68.20	-12.74

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 137 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 26/8 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5455.300	Average	39.23	0.90	40.14	54.00	-13.86
5455.300	Peak	53.28	0.90	54.19	74.00	-19.81
5460.000	Average	38.92	0.92	39.84	54.00	-14.16
5460.000	Peak	51.19	0.92	52.11	74.00	-21.89
5470.000	Peak	53.03	0.95	53.99	68.20	-14.21
5480.000	Peak	51.97	0.99	52.96	68.20	-15.24
5850.000	Peak	52.31	1.51	53.83	68.20	-14.37
5914.200	Peak	53.77	2.23	56.00	68.20	-12.20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 138 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 26/8 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5452.700	Average	39.45	0.90	40.34	54.00	-13.66
5452.700	Peak	53.19	0.90	54.09	74.00	-19.91
5460.000	Average	38.94	0.92	39.86	54.00	-14.14
5460.000	Peak	51.49	0.92	52.41	74.00	-21.59
5470.000	Peak	52.07	0.95	53.03	68.20	-15.17
5480.000	Peak	52.56	0.99	53.55	68.20	-14.65
5850.000	Peak	52.71	1.51	54.23	68.20	-13.97
5850.500	Peak	54.72	1.52	56.24	68.20	-11.96

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 139 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 52/37 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.650	Average	39.20	0.38	39.58	54.00	-14.42
5350.650	Peak	53.80	0.38	54.18	74.00	-19.82
5460.000	Average	39.24	0.92	40.16	54.00	-13.84
5460.000	Peak	51.91	0.92	52.83	74.00	-21.17
5470.000	Peak	52.75	0.95	53.70	68.20	-14.50
5480.000	Peak	51.18	0.99	52.16	68.20	-16.04
5850.000	Peak	51.78	1.51	53.29	68.20	-14.91
5948.000	Peak	53.92	2.43	56.35	68.20	-11.85

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 140 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 52/37 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5422.150	Average	39.19	0.82	40.01	54.00	-13.99
5422.150	Peak	53.32	0.82	54.14	74.00	-19.86
5460.000	Average	39.27	0.92	40.18	54.00	-13.82
5460.000	Peak	51.29	0.92	52.21	74.00	-21.79
5470.000	Peak	52.31	0.95	53.27	68.20	-14.93
5480.000	Peak	51.90	0.99	52.89	68.20	-15.31
5850.000	Peak	52.49	1.51	54.00	68.20	-14.20
5942.800	Peak	53.63	2.40	56.03	68.20	-12.17

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 141 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 52/40 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5401.350	Average	39.43	0.77	40.20	54.00	-13.80
5401.350	Peak	53.39	0.77	54.16	74.00	-19.84
5460.000	Average	39.38	0.92	40.29	54.00	-13.71
5460.000	Peak	51.78	0.92	52.70	74.00	-21.30
5470.000	Peak	52.33	0.95	53.28	68.20	-14.92
5480.000	Peak	52.24	0.99	53.23	68.20	-14.97
5850.000	Peak	51.60	1.51	53.11	68.20	-15.09
5867.400	Peak	53.98	1.73	55.71	68.20	-12.49

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 142 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 52/40 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5452.050	Average	39.44	0.89	40.33	54.00	-13.67
5452.050	Peak	53.89	0.89	54.78	74.00	-19.22
5460.000	Average	39.23	0.92	40.15	54.00	-13.85
5460.000	Peak	51.78	0.92	52.70	74.00	-21.30
5470.000	Peak	51.82	0.95	52.77	68.20	-15.43
5480.000	Peak	52.16	0.99	53.15	68.20	-15.05
5850.000	Peak	52.55	1.51	54.06	68.20	-14.14
5914.200	Peak	53.89	2.23	56.12	68.20	-12.08

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 143 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 106/53 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
5407.850	Average	39.59	0.79	40.37	54.00	-13.63
5407.850	Peak	54.85	0.79	55.64	74.00	-18.36
5460.000	Average	39.65	0.92	40.57	54.00	-13.43
5460.000	Peak	52.31	0.92	53.23	74.00	-20.77
5470.000	Peak	52.52	0.95	53.48	68.20	-14.72
5480.000	Peak	52.86	0.99	53.85	68.20	-14.35
5850.000	Peak	52.74	1.51	54.25	68.20	-13.95
5946.700	Peak	53.37	2.42	55.79	68.20	-12.41

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 144 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 106/53 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBμV/m	dB
5442.300	Average	39.28	0.87	40.15	54.00	-13.85
5442.300	Peak	53.48	0.87	54.34	74.00	-19.66
5460.000	Average	39.29	0.92	40.21	54.00	-13.79
5460.000	Peak	51.26	0.92	52.18	74.00	-21.82
5470.000	Peak	51.71	0.95	52.66	68.20	-15.54
5480.000	Peak	51.33	0.99	52.32	68.20	-15.88
5850.000	Peak	52.46	1.51	53.97	68.20	-14.23
5917.450	Peak	53.37	2.25	55.62	68.20	-12.58

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 145 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 106/54 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5413.050	Average	39.45	0.80	40.25	54.00	-13.75
5413.050	Peak	53.90	0.80	54.69	74.00	-19.31
5460.000	Average	39.52	0.92	40.44	54.00	-13.56
5460.000	Peak	51.86	0.92	52.78	74.00	-21.22
5470.000	Peak	52.32	0.95	53.27	68.20	-14.93
5480.000	Peak	52.07	0.99	53.05	68.20	-15.15
5850.000	Peak	51.69	1.51	53.20	68.20	-15.00
5927.850	Peak	54.06	2.31	56.37	68.20	-11.83

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 146 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5720 MHz Temp./Humi. :21.8/67

Test Mode :BE CH MID RU 106/54 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5436.450	Average	41.51	0.85	42.36	54.00	-11.64
5436.450	Peak	53.52	0.85	54.37	74.00	-19.63
5460.000	Average	39.41	0.92	40.33	54.00	-13.67
5460.000	Peak	52.44	0.92	53.36	74.00	-20.64
5470.000	Peak	52.18	0.95	53.13	68.20	-15.07
5480.000	Peak	51.69	0.99	52.67	68.20	-15.53
5850.000	Peak	52.90	1.51	54.41	68.20	-13.79
5975.300	Peak	53.83	2.14	55.97	68.20	-12.23

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 147 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5745 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5649.290	Peak	55.52	0.98	56.50	68.20	-11.70
5650.000	Peak	55.48	0.98	56.46	68.20	-11.74
5700.000	Peak	79.21	1.01	80.22	105.20	-24.98
5720.000	Peak	86.18	1.22	87.40	110.80	-23.40
5725.000	Peak	92.75	1.28	94.03	122.20	-28.17

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 148 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5745 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5648.050	Peak	56.31	0.98	57.29	68.20	-10.91
5650.000	Peak	56.09	0.98	57.07	68.20	-11.13
5700.000	Peak	77.73	1.01	78.74	105.20	-26.46
5720.000	Peak	85.79	1.22	87.01	110.80	-23.79
5725.000	Peak	91.67	1.28	92.95	122.20	-29.25

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 149 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5745 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 26/0 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5606.045	Peak	54.56	1.13	55.69	68.20	-12.51
5650.000	Peak	52.49	0.98	53.46	68.20	-14.74
5700.000	Peak	76.06	1.01	77.07	105.20	-28.13
5720.000	Peak	75.71	1.22	76.94	110.80	-33.86
5725.000	Peak	71.60	1.28	72.88	122.20	-49.32

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 150 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5745 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 26/0 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5616.585	Peak	54.16	1.09	55.25	68.20	-12.95
5650.000	Peak	52.93	0.98	53.91	68.20	-14.29
5700.000	Peak	72.97	1.01	73.98	105.20	-31.22
5720.000	Peak	72.98	1.22	74.21	110.80	-36.59
5725.000	Peak	72.64	1.28	73.91	122.20	-48.29



Page: 151 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5745 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 52/37 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5636.425	Peak	54.56	1.02	55.58	68.20	-12.62
5650.000	Peak	52.53	0.98	53.51	68.20	-14.69
5700.000	Peak	66.88	1.01	67.89	105.20	-37.31
5720.000	Peak	73.70	1.22	74.92	110.80	-35.88
5725.000	Peak	78.54	1.28	79.82	122.20	-42.38



Page: 152 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5745 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 52/37 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5617.360	Peak	53.75	1.09	54.84	68.20	-13.36
5650.000	Peak	52.25	0.98	53.22	68.20	-14.98
5700.000	Peak	66.07	1.01	67.08	105.20	-38.12
5720.000	Peak	72.11	1.22	73.33	110.80	-37.47
5725.000	Peak	75.11	1.28	76.39	122.20	-45.81

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 153 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5745 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 106/53 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5607.750	Peak	54.21	1.12	55.33	68.20	-12.87
5650.000	Peak	52.37	0.98	53.35	68.20	-14.85
5700.000	Peak	69.41	1.01	70.42	105.20	-34.78
5720.000	Peak	73.13	1.22	74.35	110.80	-36.45
5725.000	Peak	74.93	1.28	76.21	122.20	-45.99



Page: 154 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5745 MHz Temp./Humi. :21.8/67

Test Mode :BE CH LOW RU 106/53 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5647.895	Peak	54.77	0.98	55.76	68.20	-12.44
5650.000	Peak	53.37	0.98	54.35	68.20	-13.85
5700.000	Peak	72.56	1.01	73.56	105.20	-31.64
5720.000	Peak	76.43	1.22	77.66	110.80	-33.14
5725.000	Peak	79.07	1.28	80.35	122.20	-41.85



Page: 155 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5825 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
Peak	90.79	1.51	92.31	122.20	-29.89
Peak	82.36	1.58	83.94	110.80	-26.86
Peak	72.17	1.83	74.00	105.20	-31.20
Peak	53.88	2.29	56.17	68.20	-12.03
Peak	54.50	2.32	56.82	68.20	-11.38
	Mode PK/QP/AV Peak Peak Peak Peak	Mode PK/QP/AV Reading Level dBμV Peak 90.79 Peak 82.36 Peak 72.17 Peak 53.88	Mode PK/QP/AV Reading Level dBμV dB Peak 90.79 1.51 Peak 82.36 1.58 Peak 72.17 1.83 Peak 53.88 2.29	Mode PK/QP/AV Reading Level dBμV FS dBμV/m Peak 90.79 1.51 92.31 Peak 82.36 1.58 83.94 Peak 72.17 1.83 74.00 Peak 53.88 2.29 56.17	Mode PK/QP/AV Reading Level dBμV FS dBμV/m @3m dBμV/m Peak 90.79 1.51 92.31 122.20 Peak 82.36 1.58 83.94 110.80 Peak 72.17 1.83 74.00 105.20 Peak 53.88 2.29 56.17 68.20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 156 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-26

Test Frequency :5825 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	90.97	1.51	92.48	122.20	-29.72
5855.000	Peak	82.97	1.58	84.55	110.80	-26.25
5875.000	Peak	72.44	1.83	74.27	105.20	-30.93
5925.000	Peak	52.57	2.29	54.86	68.20	-13.34
5929.610	Peak	54.71	2.32	57.03	68.20	-11.17

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 157 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5825 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 26/8 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	75.07	1.51	76.58	122.20	-45.62
5855.000	Peak	66.99	1.58	68.57	110.80	-42.23
5875.000	Peak	63.54	1.83	65.37	105.20	-39.83
5925.000	Peak	51.95	2.29	54.24	68.20	-13.96
5932.500	Peak	59.02	2.34	61.35	68.20	-6.85

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 158 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5825 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 26/8 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	78.69	1.51	80.20	122.20	-42.00
5855.000	Peak	70.40	1.58	71.98	110.80	-38.82
5875.000	Peak	65.99	1.83	67.82	105.20	-37.38
5925.000	Peak	52.22	2.29	54.51	68.20	-13.69
5935.220	Peak	60.08	2.35	62.43	68.20	-5.77



Page: 159 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5825 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 52/40 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	75.97	1.51	77.49	122.20	-44.71
5855.000	Peak	73.27	1.58	74.85	110.80	-35.95
5875.000	Peak	65.27	1.83	67.10	105.20	-38.10
5925.000	Peak	59.04	2.29	61.33	68.20	-6.87
5946.440	Peak	61.58	2.42	64.00	68.20	-4.20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 160 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5825 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 52/40 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	79.19	1.51	80.70	122.20	-41.50
5855.000	Peak	75.65	1.58	77.23	110.80	-33.57
5875.000	Peak	67.88	1.83	69.71	105.20	-35.49
5925.000	Peak	59.92	2.29	62.21	68.20	-5.99
5937.430	Peak	61.53	2.36	63.89	68.20	-4.31

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 161 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5825 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 106/54 Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5850.000	Peak	84.15	1.51	85.66	122.20	-36.54
5855.000	Peak	82.80	1.58	84.38	110.80	-26.42
5875.000	Peak	72.70	1.83	74.53	105.20	-30.67
5925.000	Peak	59.81	2.29	62.10	68.20	-6.10
5932.840	Peak	60.60	2.34	62.94	68.20	-5.26

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 162 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax20 Test Date :2022-04-28

Test Frequency :5825 MHz Temp./Humi. :21.8/67

Test Mode :BE CH HIGH RU 106/54 Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	85.56	1.51	87.07	122.20	-35.13
5855.000	Peak	84.12	1.58	85.70	110.80	-25.10
5875.000	Peak	75.38	1.83	77.21	105.20	-27.99
5925.000	Peak	59.68	2.29	61.97	68.20	-6.23
5949.500	Peak	60.56	2.44	63.00	68.20	-5.20

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 163 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5190 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU :Vertical Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5148.200	Average	49.82	1.21	51.03	54.00	-2.97
5148.200	Peak	67.92	1.21	69.13	74.00	-4.87
5150.000	Average	50.46	1.24	51.70	54.00	-2.30
5150.000	Peak	68.07	1.24	69.31	74.00	-4.69

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 164 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5190 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU :Horizontal Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBµV/m	Limit @3m dBµV/m	Margin dB
IVITZ	PN/QP/AV	иьμν	иь	ασμν/πι	ασμν/πι	UD
5146.800	Average	47.44	1.19	48.63	54.00	-5.37
5146.800	Peak	66.29	1.19	67.48	74.00	-6.52
5150.000	Average	48.42	1.24	49.66	54.00	-4.34
5150.000	Peak	65.98	1.24	67.22	74.00	-6.78



Page: 165 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5310 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU :Vertical Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	48.71	0.38	49.08	54.00	-4.92
5350.000	Peak	67.71	0.38	68.09	74.00	-5.91

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 166 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5310 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU :Horizontal Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5350.000	Average	50.11	0.38	50.48	54.00	-3.52
5350.000	Peak	70.50	0.38	70.88	74.00	-3.12
5356.040	Average	49.91	0.42	50.33	54.00	-3.67
5356.040	Peak	70.98	0.42	71.41	74.00	-2.59

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 167 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5510 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5458.080	Average	43.83	0.91	44.74	54.00	-9.26
5458.080	Peak	58.73	0.91	59.65	74.00	-14.35
5460.000	Average	44.17	0.92	45.08	54.00	-8.92
5460.000	Peak	57.34	0.92	58.26	74.00	-15.74
5466.840	Peak	63.53	0.94	64.48	68.20	-3.72
5470.000	Peak	61.18	0.95	62.13	68.20	-6.07



Page: 168 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5510 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5459.880	Average	44.06	0.92	44.97	54.00	-9.03
5459.880	Peak	58.59	0.92	59.51	74.00	-14.49
5460.000	Average	44.13	0.92	45.05	54.00	-8.95
5460.000	Peak	57.73	0.92	58.65	74.00	-15.35
5467.680	Peak	65.11	0.95	66.05	68.20	-2.15
5470.000	Peak	62.26	0.95	63.21	68.20	-4.99

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 169 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5670 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	62.98	1.28	64.25	68.20	-3.95
5725.880	Peak	64.28	1.29	65.57	68.20	-2.63

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 170 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5670 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU :Horizontal Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	63.06	1.28	64.33	68.20	-3.87
5725.760	Peak	64.68	1.28	65.96	68.20	-2.24



Page: 171 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5710 MHz Temp./Humi. :22.3/68

Test Mode :BE CH MID FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5423.450	Average	39.71	0.82	40.54	54.00	-13.46
5423.450	Peak	53.66	0.82	54.48	74.00	-19.52
5460.000	Average	39.88	0.92	40.80	54.00	-13.20
5460.000	Peak	53.13	0.92	54.05	74.00	-19.95
5470.000	Peak	52.66	0.95	53.62	68.20	-14.58
5480.000	Peak	52.57	0.99	53.55	68.20	-14.65
5850.000	Peak	56.49	1.51	58.00	68.20	-10.20
5853.100	Peak	57.95	1.55	59.51	68.20	-8.69

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 172 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5710 MHz Temp./Humi. :22.3/68

Test Mode :BE CH MID FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBμV/m	dBµV/m	dB
5439.050	Average	39.94	0.86	40.80	54.00	-13.20
5439.050	Peak	53.54	0.86	54.40	74.00	-19.60
5460.000	Average	40.18	0.92	41.10	54.00	-12.90
5460.000	Peak	52.55	0.92	53.47	74.00	-20.53
5470.000	Peak	52.47	0.95	53.42	68.20	-14.78
5480.000	Peak	52.74	0.99	53.73	68.20	-14.47
5850.000	Peak	54.58	1.51	56.10	68.20	-12.10
5860.250	Peak	57.03	1.64	58.67	68.20	-9.53

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 173 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5755 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5647.025	Peak	63.43	0.99	64.41	68.20	-3.79
5650.000	Peak	62.55	0.98	63.53	68.20	-4.67
5700.000	Peak	73.44	1.01	74.45	105.20	-30.75
5720.000	Peak	78.37	1.22	79.59	110.80	-31.21
5725.000	Peak	78.88	1.28	80.15	122.20	-42.05

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 174 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5755 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5648.840	Peak	60.76	0.98	61.74	68.20	-6.46
5650.000	Peak	58.84	0.98	59.82	68.20	-8.38
5700.000	Peak	71.30	1.01	72.30	105.20	-32.90
5720.000	Peak	81.42	1.22	82.64	110.80	-28.16
5725.000	Peak	81.49	1.28	82.77	122.20	-39.43



Page: 175 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5795 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	78.60	1.51	80.12	122.20	-42.08
5855.000	Peak	72.84	1.58	74.41	110.80	-36.39
5875.000	Peak	69.42	1.83	71.25	105.20	-33.95
5925.000	Peak	59.99	2.29	62.29	68.20	-5.91
5927.120	Peak	60.94	2.30	63.25	68.20	-4.95

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 176 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax40 Test Date :2022-04-26

Test Frequency :5795 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	77.15	1.51	78.67	122.20	-43.53
5855.000	Peak	72.51	1.58	74.08	110.80	-36.72
5875.000	Peak	68.91	1.83	70.74	105.20	-34.46
5925.000	Peak	59.09	2.29	61.39	68.20	-6.81
5927.500	Peak	60.98	2.31	63.28	68.20	-4.92

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

台灣檢驗科技股份有限公司

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Member of SGS Group



Page: 177 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-26

Test Frequency :5210 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU :Vertical Antenna Pol.

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
						_
5145.840	Average	49.81	1.18	50.99	54.00	-3.01
5145.840	Peak	65.21	1.18	66.38	74.00	-7.62
5150.000	Average	50.06	1.24	51.30	54.00	-2.70
5150.000	Peak	64.15	1.24	65.39	74.00	-8.61

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 178 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-26

Test Frequency :5210 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5150.000	Average	48.07	1.24	49.31	54.00	-4.69
5150.000	Peak	62.15	1.24	63.39	74.00	-10.61

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 179 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-26

Test Frequency :5290 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5350.000	Average	49.39	0.38	49.77	54.00	-4.23
5350.000	Peak	65.01	0.38	65.38	74.00	-8.62
5354.300	Average	48.89	0.41	49.30	54.00	-4.70
5354.300	Peak	66.14	0.41	66.55	74.00	-7.45

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 180 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-26

Test Frequency :5290 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBμV/m	dB
5350.000	Average	51.18	0.38	51.55	54.00	-2.45
5350.000	Peak	65.71	0.38	66.08	74.00	-7.92
5376.100	Average	50.34	0.58	50.92	54.00	-3.08
5376.100	Peak	68.07	0.58	68.65	74.00	-5.35

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 181 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-26

Test Frequency :5530 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5452.800	Average	48.75	0.90	49.65	54.00	-4.35
5452.800	Peak	64.03	0.90	64.93	74.00	-9.07
5460.000	Average	49.28	0.92	50.20	54.00	-3.80
5460.000	Peak	62.14	0.92	63.06	74.00	-10.94
5467.200	Peak	63.78	0.94	64.73	68.20	-3.47
5470.000	Peak	62.42	0.95	63.37	68.20	-4.83

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 182 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-26

Test Frequency :5530 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBµV	dB	dBµV/m	dBµV/m	dB
						_
5449.400	Average	50.33	0.88	51.21	54.00	-2.79
5449.400	Peak	65.53	0.88	66.41	74.00	-7.59
5460.000	Average	50.55	0.92	51.47	54.00	-2.53
5460.000	Peak	63.85	0.92	64.77	74.00	-9.23
5467.200	Peak	64.90	0.94	65.85	68.20	-2.35
5470.000	Peak	63.78	0.95	64.73	68.20	-3.47



Page: 183 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5610 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5725.000	Peak	61.95	1.28	63.23	68.20	-4.97
5727.980	Peak	63.58	1.31	64.88	68.20	-3.32

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 184 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5610 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



_	_	_	_			
Freq.	Detector	Spectrum	Factor	Actual	Limit	Margin
•	Mode	Reading Level		FS	@3m	
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5725.000	Peak	62.38	1.28	63.66	68.20	-4.54
5731.400	Peak	64.33	1.34	65.67	68.20	-2.53

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Test Site

Report No.: TERF2204000360E2

:SAC D

:22.3/68

Page: 185 of 190


Report Number :TERF2204000360E2

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5690 MHz Temp./Humi.

Test Mode :BE CH MID FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5432.550	Average	40.57	0.84	41.41	54.00	-12.59
5432.550	Peak	53.72	0.84	54.56	74.00	-19.44
5460.000	Average	40.98	0.92	41.89	54.00	-12.11
5460.000	Peak	52.12	0.92	53.04	74.00	-20.96
5470.000	Peak	54.04	0.95	55.00	68.20	-13.20
5480.000	Peak	53.09	0.99	54.08	68.20	-14.12
5850.000	Peak	61.09	1.51	62.61	68.20	-5.59
5854.400	Peak	62.06	1.57	63.63	68.20	-4.57

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 186 of 190

Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5690 MHz Temp./Humi. :22.3/68

Test Mode :BE CH MID FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dBμV	dB	dBµV/m	dBµV/m	dB
5410.450	Average	40.30	0.79	41.09	54.00	-12.91
5410.450	Peak	53.35	0.79	54.14	74.00	-19.86
5460.000	Average	40.89	0.92	41.81	54.00	-12.19
5460.000	Peak	52.16	0.92	53.08	74.00	-20.92
5470.000	Peak	52.46	0.95	53.41	68.20	-14.79
5480.000	Peak	53.36	0.99	54.35	68.20	-13.85
5850.000	Peak	61.66	1.51	63.17	68.20	-5.03
5855.700	Peak	63.02	1.59	64.60	68.20	-3.60

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 187 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5775 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBμV/m	dBµV/m	dB
5649.580	Peak	62.15	0.98	63.12	68.20	-5.08
5650.000	Peak	61.86	0.98	62.83	68.20	-5.37
5700.000	Peak	77.86	1.01	78.87	105.20	-26.33
5720.000	Peak	77.67	1.22	78.89	110.80	-31.91
5725.000	Peak	80.16	1.28	81.43	122.20	-40.77

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。



Page: 188 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5775 MHz Temp./Humi. :22.3/68

Test Mode :BE CH LOW FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5649.210	Peak	63.29	0.98	64.27	68.20	-3.93
5650.000	Peak	62.88	0.98	63.86	68.20	-4.34
5700.000	Peak	78.35	1.01	79.36	105.20	-25.84
5720.000	Peak	78.43	1.22	79.65	110.80	-31.15
5725.000	Peak	80.93	1.28	82.21	122.20	-39.99

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Page: 189 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5775 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Vertical

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	74.76	1.51	76.27	122.20	-45.93
5855.000	Peak	73.17	1.58	74.74	110.80	-36.06
5875.000	Peak	73.42	1.83	75.25	105.20	-29.95
5925.000	Peak	59.15	2.29	61.44	68.20	-6.76
5938.800	Peak	63.33	2.37	65.70	68.20	-2.50



Page: 190 of 190


Report Number :TERF2204000360E2 Test Site :SAC D

Operation Mode :802.11ax80 Test Date :2022-04-27

Test Frequency :5775 MHz Temp./Humi. :22.3/68

Test Mode :BE CH HIGH FULL RU Antenna Pol. :Horizontal

EUT Pol :NB Plane Engineer :Andy Wang



Freq.	Detector Mode	Spectrum Reading Level	Factor	Actual FS	Limit @3m	Margin
MHz	PK/QP/AV	dΒμV	dB	dBµV/m	dBµV/m	dB
5850.000	Peak	75.69	1.51	77.20	122.20	-45.00
5855.000	Peak	74.09	1.58	75.67	110.80	-35.13
5875.000	Peak	74.21	1.83	76.04	105.20	-29.16
5925.000	Peak	57.25	2.29	59.55	68.20	-8.65
5938.800	Peak	61.55	2.37	63.93	68.20	-4.27

~ End of Report ~

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only. 除非另有說明,此報告結果僅對測試之樣品負責,同時此樣品僅保留90天。本報告未經本公司書面許可,不可部份複製。