



# FCC RADIO TEST REPORT

**FCC ID** : HLZRXMG1  
**Equipment** : Notebook Computer  
**Brand Name** : ACER  
**Model Name** : N20C7  
**Applicant** : Acer Incorporated  
8F,. No. 88, Sec. 1, Xintai 5th Rd., Xizhi,  
New Taipei City 22181, Taiwan (R.O.C)  
**Manufacturer** : Acer Incorporated  
8F,. No. 88, Sec. 1, Xintai 5th Rd., Xizhi,  
New Taipei City 22181, Taiwan (R.O.C)  
**Standard** : FCC Part 15 Subpart C §15.247

The product was received on Jul. 01, 2020 and testing was started from Jul. 18, 2020 and completed on Aug. 18, 2020. We, SPORTON INTERNATIONAL INC., EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

*Louis Wu*

Reviewed by: Louis Wu

**SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory**  
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



# Table of Contents

**History of this test report..... 3**

**Summary of Test Result..... 4**

**1 General Description..... 5**

    1.1 Product Feature of Equipment Under Test..... 5

    1.2 Modification of EUT ..... 5

    1.3 Testing Location ..... 6

    1.4 Applicable Standards..... 6

**2 Test Configuration of Equipment Under Test ..... 7**

    2.1 Carrier Frequency Channel ..... 7

    2.2 Test Mode..... 8

    2.3 Connection Diagram of Test System..... 9

    2.4 Support Unit used in test configuration and system ..... 9

    2.5 EUT Operation Test Setup ..... 10

    2.6 Measurement Results Explanation Example..... 10

**3 Test Result..... 11**

    3.1 Number of Channel Measurement ..... 11

    3.2 Hopping Channel Separation Measurement ..... 13

    3.3 Dwell Time Measurement..... 19

    3.4 20dB and 99% Bandwidth Measurement ..... 21

    3.5 Output Power Measurement..... 32

    3.6 Conducted Band Edges Measurement..... 33

    3.7 Conducted Spurious Emission Measurement ..... 40

    3.8 Radiated Band Edges and Spurious Emission Measurement ..... 50

    3.9 AC Conducted Emission Measurement..... 54

    3.10 Antenna Requirements..... 56

**4 List of Measuring Equipment ..... 57**

**5 Uncertainty of Evaluation..... 59**

**Appendix A. Conducted Test Results**

**Appendix B. AC Conducted Emission Test Result**

**Appendix C. Radiated Spurious Emission**

**Appendix D. Radiated Spurious Emission Plots**

**Appendix E. Duty Cycle Plots**

**Appendix F. Setup Photographs**



### History of this test report

Report No.	Version	Description	Issued Date
FR070206A	01	Initial issue of report	Oct. 02, 2020



## Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.247(a)(1)	Number of Channels	Pass	-
3.2	15.247(a)(1)	Hopping Channel Separation	Pass	-
3.3	15.247(a)(1)	Dwell Time of Each Channel	Pass	-
3.4	15.247(a)(1)	20dB Bandwidth	Pass	-
3.4	2.1049	99% Occupied Bandwidth	Reporting only	-
3.5	15.247(b)(1)	Peak Output Power	Pass	-
3.6	15.247(d)	Conducted Band Edges	Pass	-
3.7	15.247(d)	Conducted Spurious Emission	Pass	-
3.8	15.247(d)	Radiated Band Edges and Radiated Spurious Emission	Pass	Under limit 8.37 dB at 914.640 MHz
3.9	15.207	AC Conducted Emission	Pass	Under limit 11.66 dB at 0.175 MHz
3.10	15.203 & 15.247(b)	Antenna Requirement	Pass	-

**Declaration of Conformity:**

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

**Comments and Explanations:**

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

**Reviewed by: Wii Chang**

**Report Producer: Tina Chuang**

# 1 General Description

## 1.1 Product Feature of Equipment Under Test

WCDMA/LTE/5G NR, Bluetooth, Wi-Fi 2.4GHz 802.11b/g/n, Wi-Fi 5GHz 802.11a/n/ac, and GNSS.

Product Specification subjective to this standard	
<b>Antenna Type</b>	WWAN <Ant. 0>: PIFA Antenna <Ant. 2>: PIFA Antenna WLAN <Main>: PIFA Antenna <Aux.>: PIFA Antenna Bluetooth: PIFA Antenna GPS / Glonass / BDS / Galileo : Copule Antenna

Antenna Information			
<b>Antenna 1 (NB Mode)</b>	<b>Antenna Type</b>	PIFA Antenna	PIFA Antenna
	<b>Part number</b>	DC33002GL00 (81ELAU15.G14)	DC33002GL10 (81ELAU15.G15)
	<b>Peak gain (dbi)</b>	Main Antenna : Bluetooth: -1.74	Aux Antenna : -
<b>Antenna 2 (TB Mode)</b>	<b>Antenna Type</b>	PIFA Antenna	PIFA Antenna
	<b>Part number</b>	DC33002GL00 (81ELAU15.G14)	DC33002GL10 (81ELAU15.G15)
	<b>Peak gain (dbi)</b>	Main Antenna : Bluetooth: -2.22	Aux Antenna : -

Remark: All the tests were performed with Antenna 1.

## 1.2 Modification of EUT

No modifications are made to the EUT during all test items.



### 1.3 Testing Location

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	TH05-HY	CO05-HY

**Note:** The test site complies with ANSI C63.4 2014 requirement.

<b>Test Site</b>	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
<b>Test Site Location</b>	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
<b>Test Site No.</b>	<b>Sporton Site No.</b>	
	03CH13-HY	

**Note:** The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW0007

### 1.4 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 DTS Meas. Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01
- ♦ ANSI C63.10-2013

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. The TAF code is not including all the FCC KDB listed without accreditation.—



## 2 Test Configuration of Equipment Under Test

### 2.1 Carrier Frequency Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
2400-2483.5 MHz	0	2402	27	2429	54	2456
	1	2403	28	2430	55	2457
	2	2404	29	2431	56	2458
	3	2405	30	2432	57	2459
	4	2406	31	2433	58	2460
	5	2407	32	2434	59	2461
	6	2408	33	2435	60	2462
	7	2409	34	2436	61	2463
	8	2410	35	2437	62	2464
	9	2411	36	2438	63	2465
	10	2412	37	2439	64	2466
	11	2413	38	2440	65	2467
	12	2414	39	2441	66	2468
	13	2415	40	2442	67	2469
	14	2416	41	2443	68	2470
	15	2417	42	2444	69	2471
	16	2418	43	2445	70	2472
	17	2419	44	2446	71	2473
	18	2420	45	2447	72	2474
	19	2421	46	2448	73	2475
	20	2422	47	2449	74	2476
	21	2423	48	2450	75	2477
	22	2424	49	2451	76	2478
	23	2425	50	2452	77	2479
	24	2426	51	2453	78	2480
	25	2427	52	2454	-	-
	26	2428	53	2455	-	-



### 2.2 Test Mode

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, pre-scanned in Tablet type (three orthogonal panels, X, Y, Z) and Notebook type. The worst cases (X plane) were recorded in this report, and the worst mode of radiated spurious emissions is Bluetooth 3Mbps mode, and recorded in this report.
- b. AC power line Conducted Emission was tested under maximum output power.

The following summary table is showing all test modes to demonstrate in compliance with the standard.

Summary table of Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth BR 1Mbps GFSK	Bluetooth EDR 2Mbps $\pi/4$ -DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted Test Cases	Mode 1: CH00_2402 MHz	Mode 4: CH00_2402 MHz	Mode 7: CH00_2402 MHz
	Mode 2: CH39_2441 MHz	Mode 5: CH39_2441 MHz	Mode 8: CH39_2441 MHz
	Mode 3: CH78_2480 MHz	Mode 6: CH78_2480 MHz	Mode 9: CH78_2480 MHz
Radiated Test Cases	Bluetooth EDR 3Mbps 8-DPSK		
	Mode 1: CH00_2402 MHz		
	Mode 2: CH39_2441 MHz		
Mode 3: CH78_2480 MHz			
AC Conducted Emission	Mode 1 : Bluetooth Link + WLAN (2.4GHz) Link + Hard Disk (Load) + Earphone + Adapter		
<b>Remark:</b> For radiated test cases, the worst mode data rate 3Mbps was reported only since the highest RF output power in the preliminary tests. The conducted spurious emissions and conducted band edge measurement for other data rates were not worse than 3Mbps, and no other significantly frequencies found in conducted spurious emission.			



### 2.3 Connection Diagram of Test System



### 2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
2.	Earphone	SONY	MH750	N/A	unshielded, 1.5m	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
4.	iPod Earphone	Apple	N/A	Verification	Unshielded, 1.0 m	N/A
5.	Hard Disk	Lenovo	F310S	FCC DoC	Shielded, 1.0m	N/A



## 2.5 EUT Operation Test Setup

The RF test items, utility “QRCT V4.0.00156.0” was installed in EUT which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

## 2.6 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

Following shows an offset computation example with cable loss 4.2 dB and 10dB attenuator.

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Test Result

#### 3.1 Number of Channel Measurement

##### 3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


##### 3.1.2 Measuring Instruments

See list of measuring equipment of this test report.

##### 3.1.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = the frequency band of operation; RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. The number of hopping frequency used is defined as the number of total channel.
7. Record the measurement data derived from spectrum analyzer.

##### 3.1.4 Test Setup







### 3.1.5 Test Result of Number of Hopping Frequency

Please refer to Appendix A.

#### Number of Hopping Channel Plot on Channel 00 - 78



Date: 6.AUG.2020 08:03:33



Date: 6.AUG.2020 08:06:27

## 3.2 Hopping Channel Separation Measurement

### 3.2.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

### 3.2.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.2.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.2.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings:  
Span = wide enough to capture the peaks of two adjacent channels;  
RBW = 300kHz; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

### 3.2.4 Test Setup




### 3.2.5 Test Result of Hopping Channel Separation

Please refer to Appendix A.




<1Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 6.AUG.2020 06:38:25


Channel Separation Plot on Channel 39 - 40



Date: 6.AUG.2020 06:40:00




Channel Separation Plot on Channel 77 - 78



Date: 6.AUG.2020 06:41:35

<2Mbps>


Channel Separation Plot on Channel 00 - 01



Date: 6.AUG.2020 07:13:17




Channel Separation Plot on Channel 39 - 40



Date: 6.AUG.2020 07:14:55

Channel Separation Plot on Channel 77 - 78




Date: 6.AUG.2020 07:16:20






<3Mbps>

Channel Separation Plot on Channel 00 - 01



Date: 6.AUG.2020 07:47:20


Channel Separation Plot on Channel 39 - 40



Date: 6.AUG.2020 07:48:56



Channel Separation Plot on Channel 77 - 78



Date: 6.AUG.2020 07:52:28

### 3.3 Dwell Time Measurement

#### 3.3.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

#### 3.3.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.3.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.4.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Enable the EUT hopping function.
5. Use the following spectrum analyzer settings: Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW  $\geq$  RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
6. Measure and record the results in the test report.

#### 3.3.4 Test Setup




#### 3.3.5 Test Result of Dwell Time

Please refer to Appendix A.



Package Transfer Time Plot



Date: 18.JUL.2020 10:57:57

Remark:

1. In normal mode, hopping rate is 1600 hops/s with 6 slots in 79 hopping channels. With channel hopping rate (1600 / 6 / 79) in Occupancy Time Limit (0.4 x 79) (s), Hops Over Occupancy Time comes to (1600 / 6 / 79) x (0.4 x 79) = 106.67 hops.
2. In AFH mode, hopping rate is 800 hops/s with 6 slots in 20 hopping channels. With channel hopping rate (800 / 6 / 20) in Occupancy Time Limit (0.4 x 20) (s), Hops Over Occupancy Time comes to (800 / 6 / 20) x (0.4 x 20) = 53.33 hops.
3. Dwell Time(s) = Hops Over Occupancy Time (hops) x Package Transfer Time

### 3.4 20dB and 99% Bandwidth Measurement

#### 3.4.1 Limit of 20dB and 99% Bandwidth

Reporting only

#### 3.4.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.4.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 6.9.2 and 6.9.3.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Use the following spectrum analyzer settings for 20dB Bandwidth measurement.  
Span = approximately 2 to 5 times the 20 dB bandwidth, centered on a hopping channel;  
RBW  $\geq$  1% of the 20 dB bandwidth; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
5. Use the following spectrum analyzer settings for 99 % Bandwidth measurement.  
Span = approximately 1.5 to 5 times the 99% bandwidth, centered on a hopping channel;  
RBW  $\geq$  1-5% of the 99% bandwidth; VBW  $\geq$  3 \* RBW; Sweep = auto; Detector function = peak;  
Trace = max hold.
6. Measure and record the results in the test report.

#### 3.4.4 Test Setup




#### 3.4.5 Test Result of 20dB Bandwidth

Please refer to Appendix A.




<1Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 6.AUG.2020 06:04:22


20 dB Bandwidth Plot on Channel 39



Date: 6.AUG.2020 06:15:32




20 dB Bandwidth Plot on Channel 78



Date: 6.AUG.2020 06:22:52

<2Mbps>


20 dB Bandwidth Plot on Channel 00



Date: 6.AUG.2020 06:50:32




### 20 dB Bandwidth Plot on Channel 39



Date: 6.AUG.2020 07:00:00

### 20 dB Bandwidth Plot on Channel 78




Date: 6.AUG.2020 07:07:14






<3Mbps>

20 dB Bandwidth Plot on Channel 00



Date: 6.AUG.2020 07:29:32


20 dB Bandwidth Plot on Channel 39



Date: 6.AUG.2020 07:33:45



20 dB Bandwidth Plot on Channel 78



Date: 6.AUG.2020 07:38:39




### 3.4.6 Test Result of 99% Occupied Bandwidth

Please refer to Appendix A.

<1Mbps>


#### 99% Occupied Bandwidth Plot on Channel 00



Date: 6.AUG.2020 06:09:13




99% Occupied Bandwidth Plot on Channel 39



Date: 6.AUG.2020 06:16:43

99% Occupied Bandwidth Plot on Channel 78




Date: 6.AUG.2020 06:24:46




<2Mbps>

99% Occupied Bandwidth Plot on Channel 00



Date: 6.AUG.2020 06:51:54


99% Occupied Bandwidth Plot on Channel 39



Date: 6.AUG.2020 07:00:58




99% Occupied Bandwidth Plot on Channel 78



Date: 6.AUG.2020 07:08:35

<3Mbps>


99% Occupied Bandwidth Plot on Channel 00



Date: 6.AUG.2020 07:30:52




99% Occupied Bandwidth Plot on Channel 39



Date: 6.AUG.2020 07:34:54

99% Occupied Bandwidth Plot on Channel 78



Date: 6.AUG.2020 07:40:05

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

## 3.5 Output Power Measurement

### 3.5.1 Limit of Output Power

The maximum peak conducted output power of the intentional radiator shall not exceed the following:  
For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400-2483.5 MHz band 0.125 watts.


### 3.5.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.5.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.5.
2. The RF output of EUT was connected to the power meter by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Measure the conducted output power with cable loss and record the results in the test report.
5. Measure and record the results in the test report.

### 3.5.4 Test Setup



### 3.5.5 Test Result of Peak Output Power

Please refer to Appendix A.

### 3.5.6 Test Result of Average Output Power (Reporting Only)

Please refer to Appendix A.



## 3.6 Conducted Band Edges Measurement

### 3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.6.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.6.3 Test Procedures

1. The testing follows ANSI C63.10-2013 clause 7.8.6.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Set RBW = 100kHz, VBW = 300kHz. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100kHz RBW. The attenuation shall be 30 dB instead of 20 dB when RMS conducted output power procedure is used.
4. Enable hopping function of the EUT and then repeat step 2. and 3.
5. Measure and record the results in the test report.

### 3.6.4 Test Setup






### 3.6.5 Test Result of Conducted Band Edges


<1Mbps>

#### Low Band Edge Plot on Channel 00



Date: 6.AUG.2020 06:06:27

#### High Band Edge Plot on Channel 78




Date: 6.AUG.2020 06:23:48




<2Mbps>

Low Band Edge Plot on Channel 00



Date: 6.AUG.2020 06:51:09

High Band Edge Plot on Channel 78




Date: 6.AUG.2020 07:07:50




<3Mbps>

Low Band Edge Plot on Channel 00



Date: 6.AUG.2020 07:30:10

High Band Edge Plot on Channel 78




Date: 6.AUG.2020 07:39:27



### 3.6.6 Test Result of Conducted Hopping Mode Band Edges


<1Mbps>

#### Hopping Mode Low Band Edge Plot



Date: 6.AUG.2020 06:32:21

#### Hopping Mode High Band Edge Plot




Date: 6.AUG.2020 06:33:49




<2Mbps>

Hopping Mode Low Band Edge Plot



Date: 6.AUG.2020 07:23:43

Hopping Mode High Band Edge Plot




Date: 6.AUG.2020 07:26:23




<3Mbps>

Hopping Mode Low Band Edge Plot



Date: 6.AUG.2020 07:57:13

Hopping Mode High Band Edge Plot



Date: 6.AUG.2020 07:59:11

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Limit of Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

### 3.7.2 Measuring Instruments

See list of measuring equipment of this test report.

### 3.7.3 Test Procedure

1. The testing follows ANSI C63.10-2013 clause 7.8.8.
2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
3. Set to the maximum power setting and enable the EUT transmit continuously.
4. Set RBW = 100 kHz, VBW = 300kHz, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

### 3.7.4 Test Setup








### 3.7.5 Test Result of Conducted Spurious Emission


<1Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 06:10:48


1Mbps CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 6.AUG.2020 06:11:22




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 06:18:15


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 6.AUG.2020 06:18:53




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 06:25:30

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 6.AUG.2020 06:25:59




<2Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 06:52:32


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 6.AUG.2020 06:53:02




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 07:02:16


CSE Plot on Ch 39 between 2 GHz ~ 25 GHz



Date: 6.AUG.2020 07:02:48




CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 07:10:55

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz




Date: 6.AUG.2020 07:11:24




<3Mbps>

CSE Plot on Ch 00 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 07:31:38


CSE Plot on Ch 00 between 2 GHz ~ 25 GHz



Date: 6.AUG.2020 07:32:09




CSE Plot on Ch 39 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 07:35:46

CSE Plot on Ch 39 between 2 GHz ~ 25 GHz




Date: 6.AUG.2020 07:36:30






CSE Plot on Ch 78 between 30MHz ~ 3 GHz



Date: 6.AUG.2020 07:40:47

CSE Plot on Ch 78 between 2 GHz ~ 25 GHz



Date: 6.AUG.2020 07:44:21



### 3.8 Radiated Band Edges and Spurious Emission Measurement

#### 3.8.1 Limit of Radiated Band Edges and Spurious Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

#### 3.8.2 Measuring Instruments

See list of measuring equipment of this test report.




### 3.8.3 Test Procedures

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. For each suspected emission, the EUT was arranged to its worst case and then tune the Antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level to comply with the guidelines.
4. Set to the maximum power setting and enable the EUT transmit continuously.
5. Use the following spectrum analyzer settings:
  - (1) Span shall wide enough to fully capture the emission being measured;
  - (2) Set RBW=100 kHz for  $f < 1$  GHz, RBW=1MHz for  $f > 1$ GHz ; VBW  $\geq$  RBW; Sweep = auto; Detector function = peak; Trace = max hold for peak
  - (3) For average measurement: use duty cycle correction factor method per 15.35(c).  
Duty cycle = On time/100 milliseconds  
On time =  $N_1 * L_1 + N_2 * L_2 + \dots + N_{n-1} * L_{n-1} + N_n * L_n$   
Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulses, etc.  
Average Emission Level = Peak Emission Level +  $20 * \log(\text{Duty cycle})$
6. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
7. For testing below 1GHz, if the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then peak values of EUT will be reported, otherwise, the emissions will be repeated one by one using the CISPR quasi-peak method and reported.
8. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in average mode also complies with the limit in average mode), then peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.


Note: The average levels were calculated from the peak level corrected with duty cycle correction factor (-24.79dB) derived from  $20 \log(\text{dwell time}/100\text{ms})$ . This correction is only for signals that hop with the fundamental signal, such as band-edge and harmonic. Other spurious signals that are independent of the hopping signal would not use this correction.


### 3.8.4 Test Setup

For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



**For radiated emissions above 1GHz****3.8.5 Test Results of Radiated Spurious Emissions (9 kHz ~ 30 MHz)**

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is a comparison data of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

**3.8.6 Test Result of Radiated Spurious at Band Edges**

Please refer to Appendix C and D.

**3.8.7 Duty Cycle**

Please refer to Appendix E.

**3.8.8 Test Result of Radiated Spurious Emission (30MHz ~ 10<sup>th</sup> Harmonic)**

Please refer to Appendix C and D.



### 3.9 AC Conducted Emission Measurement

#### 3.9.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.


#### 3.9.2 Measuring Instruments

See list of measuring equipment of this test report.

#### 3.9.3 Test Procedures

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

### 3.9.4 Test Setup



### 3.9.5 Test Result of AC Conducted Emission

Please refer to Appendix B.



## **3.10 Antenna Requirements**

### **3.10.1 Standard Applicable**

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the rule.

### **3.10.2 Antenna Anti-Replacement Construction**

An embedded-in antenna design is used.

### **3.10.3 Antenna Gain**

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.





## 4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Jan. 09, 2020	Jul. 31, 2020~ Aug. 18, 2020	Jan. 08, 2021	Radiation (03CH13-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-121 2	1GHz ~ 18GHz	May 20, 2020	Jul. 31, 2020~ Aug. 18, 2020	May 19, 2021	Radiation (03CH13-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	40103&07	30MHz to 1GHz	Apr. 29, 2020	Jul. 31, 2020~ Aug. 18, 2020	Apr. 28, 2021	Radiation (03CH13-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	BBHA9170 584	18GHz- 40GHz	Dec.10, 2019	Jul. 31, 2020~ Aug. 18, 2020	Dec. 09, 2020	Radiation (03CH13-HY)
Preamplifier	Keysight	83017A	MY532701 47	1GHz~26.5GHz	Oct. 28, 2019	Jul. 31, 2020~ Aug. 18, 2020	Oct. 27, 2020	Radiation (03CH13-HY)
Preamplifier	MITEQ	AMF-7D-0010 1800-30-10P	1590074	1GHz~18GHz	May 19, 2020	Jul. 31, 2020~ Aug. 18, 2020	May 18, 2021	Radiation (03CH13-HY)
Amplifier	Sonoma-Instru ment	310 N	187282	9KHz~1GHz	Dec. 17, 2019	Jul. 31, 2020~ Aug. 18, 2020	Dec. 16, 2020	Radiation (03CH13-HY)
Preamplifier	EMEC	EM18G40G	060715	18GHz ~ 40GHz	Dec. 13, 2019	Jul. 31, 2020~ Aug. 18, 2020	Dec. 12, 2020	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY9837/4 PE	9kHz-30MHz	Mar. 12, 2020	Jul. 31, 2020 ~ Aug. 18, 2020	Mar. 11, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 126E	0030/126E	30M-18G	Feb. 12, 2020	Jul. 31, 2020~ Aug. 18, 2020	Feb. 11, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	804793/4	30M-18G	Feb. 12, 2020	Jul. 31, 2020~ Aug. 18, 2020	Feb. 11, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY24961/ 4	30M-18G	Feb. 12, 2020	Jul. 31, 2020~ Aug. 18, 2020	Feb. 11, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY2859/2	30M~40GHz	Mar. 12, 2020	Jul. 31, 2020~ Aug. 18, 2020	Mar. 11, 2021	Radiation (03CH13-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	MY4274/2	30M~40GHz	Mar. 12, 2020	Jul. 31, 2020~ Aug. 18, 2020	Mar. 11, 2021	Radiation (03CH13-HY)
Spectrum Analyzer	Keysight	N9010A	MY542004 85	10Hz~44GHz	Feb. 10, 2020	Jul. 31, 2020~ Aug. 18, 2020	Feb. 09, 2021	Radiation (03CH13-HY)
Controller	EMEC	EM1000	N/A	Control Turn table & Ant Mast	N/A	Jul. 31, 2020~ Aug. 18, 2020	N/A	Radiation (03CH13-HY)
Antenna Mast	EMEC	AM-BS-4500- B	N/A	1m~4m	N/A	Jul. 31, 2020~ Aug. 18, 2020	N/A	Radiation (03CH13-HY)
Turn Table	EMEC	TT2000	N/A	0~360 Degree	N/A	Jul. 31, 2020~ Aug. 18, 2020	N/A	Radiation (03CH13-HY)
Software	AUDIX	E3 6.2009-8-24c	RK-001124	N/A	N/A	Jul. 31, 2020~ Aug. 18, 2020	N/A	Radiation (03CH13-HY)
EMI Test Receiver	Keysight	N9038A(MXE )	MY541300 85	20Hz ~ 8.4GHz	Nov. 01, 2019	Jul. 31, 2020~ Aug. 18, 2020	Oct. 31, 2020	Radiation (03CH13-HY)
Filter	Wainwright	WHKX12-270 0-3000-18000 -60SS	SN2	3GHz High Pass Filter	Jul. 13, 2020	Jul. 31, 2020~ Aug. 18, 2020	Jul. 12, 2021	Radiation (03CH13-HY)
Filter	Wainwright	WLK4-1000-1 530-8000-40S S	SN12	1.53GHz Low Pass Filter	Sep. 16, 2019	Jul. 31, 2020~ Aug. 18, 2020	Sep. 15, 2020	Radiation (03CH13-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Hygrometer	Testo	608-H1	34893241	N/A	Mar. 02, 2020	Jul. 18, 2020~ Aug. 06, 2020	Mar. 01, 2021	Conducted (TH05-HY)
Power Meter	Agilent	E4416A	GB412923 44	N/A	Dec. 27, 2019	Jul. 18, 2020~ Aug. 06, 2020	Dec. 26, 2020	Conducted (TH05-HY)
Power Sensor	Agilent	E9327A	US404415 48	50MHz~18GHz	Dec. 27, 2019	Jul. 18, 2020~ Aug. 06, 2020	Dec. 26, 2020	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSP40	100055	9kHz-40GHz	Dec. 30, 2019	Jul. 18, 2020~ Aug. 06, 2020	Dec. 29, 2020	Conducted (TH05-HY)
Switch Box & RF Cable	EM Electronics	EMSW18SE	SW200302	N/A	Mar. 17, 2020	Jul. 18, 2020~ Aug. 06, 2020	Mar. 16, 2021	Conducted (TH05-HY)
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jul. 27, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jul. 27, 2020	Nov. 14, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jul. 27, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jul. 27, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jul. 27, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jul. 27, 2020	Jan. 01, 2021	Conduction (CO05-HY)



## 5 Uncertainty of Evaluation

### Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	2.3
---	-----

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.8
---	-----

### Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	5.1
---	-----

### Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ( $U = 2Uc(y)$ )	4.8
---	-----

## Appendix A. Test Result of Conducted Test Items

Test Engineer:	MINA LIU	Temperature:	23.5~24.2	°C
Test Date:	2020/7/18~2020/8/6	Relative Humidity:	49~55	%

**TEST RESULTS DATA****20dB and 99% Occupied Bandwidth and Hopping Channel Separation**

Mod.	Data Rate	NTX	CH.	Freq. (MHz)	20db BW (MHz)	99% Bandwidth (MHz)	Hopping Channel Separation Measurement (MHz)	Hopping Channel Separation Measurement Limit (MHz)	Pass/Fail
DH	1Mbps	1	0	2402	0.716	0.792	0.996	0.4773	Pass
DH	1Mbps	1	39	2441	0.752	0.788	1.002	0.5013	Pass
DH	1Mbps	1	78	2480	0.716	0.788	1.008	0.4773	Pass
2DH	2Mbps	1	0	2402	1.134	1.088	1.002	0.7560	Pass
2DH	2Mbps	1	39	2441	1.134	1.084	1.002	0.7560	Pass
2DH	2Mbps	1	78	2480	1.134	1.088	1.008	0.7560	Pass
3DH	3Mbps	1	0	2402	1.158	1.108	1.008	0.7720	Pass
3DH	3Mbps	1	39	2441	1.158	1.104	1.002	0.7720	Pass
3DH	3Mbps	1	78	2480	1.158	1.108	1.014	0.7720	Pass

**TEST RESULTS DATA****Dwell Time**

Mod.	Hopping Channel Number Rate	Hops Over Occupancy Time(hops)	Package Transfer Time (msec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
Nomal	79	106.67	2.90	0.31	0.4	Pass
AFH	20	53.33	2.90	0.15	0.4	Pass

**TEST RESULTS DATA****Peak Power Table**

DH	CH.	NTX	Peak Power (dBm)	Power Limit (dBm)	Test Result	Setting
DH1	0	1	5.05	20.97	Pass	7
	39	1	3.95	20.97	Pass	7
	78	1	5.52	20.97	Pass	7
2DH1	0	1	8.79	20.97	Pass	8
	39	1	7.42	20.97	Pass	8
	78	1	8.81	20.97	Pass	8
3DH1	0	1	9.30	20.97	Pass	8
	39	1	7.88	20.97	Pass	8
	78	1	9.32	20.97	Pass	8

**TEST RESULTS DATA****Average Power Table****(Reporting Only)**

DH	CH.	NTX	Average Power (dBm)	Duty Factor (dB)	Setting
DH1	0	1	5.11	5.21	7
	39	1	3.71	5.21	7
	78	1	5.33	5.21	7
2DH1	0	1	6.42	5.12	8
	39	1	5.02	5.12	8
	78	1	6.56	5.12	8
3DH1	0	1	6.57	5.12	8
	39	1	5.03	5.12	8
	78	1	6.62	5.12	8

**TEST RESULTS DATA****Number of Hopping Frequency**

Number of Hopping (Channel)	Adaptive Frequency Hopping (Channel)	Limits (Channel)	Pass/Fail
79	20	> 15	Pass




## Appendix B. AC Conducted Emission Test Results

Test Engineer :	Tom Lee	Temperature :	23~25°C
		Relative Humidity :	42~50%

# EUT Information

Report NO : 070206  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Line

Full Spectrum



## Final\_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.175290	---	38.48	54.71	16.23	L1	OFF	19.5
0.175290	53.05	---	64.71	11.66	L1	OFF	19.5
0.188250	---	37.09	54.11	17.02	L1	OFF	19.5
0.188250	51.26	---	64.11	12.85	L1	OFF	19.5
0.233250	---	35.52	52.33	16.81	L1	OFF	19.5
0.233250	48.31	---	62.33	14.02	L1	OFF	19.5
0.255210	---	30.79	51.59	20.80	L1	OFF	19.5
0.255210	46.38	---	61.59	15.21	L1	OFF	19.5
0.291660	---	25.64	50.48	24.84	L1	OFF	19.5
0.291660	39.36	---	60.48	21.12	L1	OFF	19.5
0.309750	---	24.22	49.98	25.76	L1	OFF	19.5
0.309750	38.17	---	59.98	21.81	L1	OFF	19.5
0.366000	---	24.62	48.59	23.97	L1	OFF	19.5
0.366000	36.13	---	58.59	22.46	L1	OFF	19.5
3.453000	---	22.46	46.00	23.54	L1	OFF	19.6
3.453000	33.94	---	56.00	22.06	L1	OFF	19.6
3.575850	---	23.29	46.00	22.71	L1	OFF	19.6
3.575850	35.62	---	56.00	20.38	L1	OFF	19.6
3.823350	---	24.02	46.00	21.98	L1	OFF	19.6
3.823350	36.22	---	56.00	19.78	L1	OFF	19.6
4.053750	---	23.32	46.00	22.68	L1	OFF	19.6

4.053750	34.17	---	56.00	21.83	L1	OFF	19.6
4.809750	---	26.30	46.00	19.70	L1	OFF	19.6
4.809750	38.08	---	56.00	17.92	L1	OFF	19.6
5.003250	---	29.89	50.00	20.11	L1	OFF	19.6
5.003250	42.01	---	60.00	17.99	L1	OFF	19.6
5.125920	---	31.30	50.00	18.70	L1	OFF	19.6
5.125920	43.24	---	60.00	16.76	L1	OFF	19.6
5.360550	---	30.05	50.00	19.95	L1	OFF	19.6
5.360550	42.56	---	60.00	17.44	L1	OFF	19.6
7.005480	---	19.10	50.00	30.90	L1	OFF	19.7
7.005480	22.32	---	60.00	37.68	L1	OFF	19.7
8.559330	---	28.20	50.00	21.80	L1	OFF	19.8
8.559330	33.23	---	60.00	26.77	L1	OFF	19.8
9.338370	---	20.67	50.00	29.33	L1	OFF	19.8
9.338370	24.40	---	60.00	35.60	L1	OFF	19.8
10.112010	---	15.28	50.00	34.72	L1	OFF	19.8
10.112010	16.62	---	60.00	43.38	L1	OFF	19.8
12.453000	---	16.51	50.00	33.49	L1	OFF	19.8
12.453000	18.86	---	60.00	41.14	L1	OFF	19.8
14.008470	---	16.02	50.00	33.98	L1	OFF	19.8
14.008470	18.10	---	60.00	41.90	L1	OFF	19.8
16.780740	---	21.33	50.00	28.67	L1	OFF	19.8
16.780740	25.32	---	60.00	34.68	L1	OFF	19.8

# EUT Information

Report NO : 070206  
 Test Mode : Mode 1  
 Test Voltage : 120Vac/60Hz  
 Phase : Neutral

Full Spectrum



## Final\_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.174750	---	35.42	54.73	19.31	N	OFF	19.5
0.174750	50.57	---	64.73	14.16	N	OFF	19.5
0.228840	---	33.14	52.49	19.35	N	OFF	19.5
0.228840	47.30	---	62.49	15.19	N	OFF	19.5
0.288060	---	25.02	50.58	25.56	N	OFF	19.5
0.288060	37.00	---	60.58	23.58	N	OFF	19.5
0.401820	---	20.77	47.82	27.05	N	OFF	19.5
0.401820	32.64	---	57.82	25.18	N	OFF	19.5
3.492960	---	22.99	46.00	23.01	N	OFF	19.6
3.492960	34.54	---	56.00	21.46	N	OFF	19.6
3.691500	---	24.08	46.00	21.92	N	OFF	19.6
3.691500	35.65	---	56.00	20.35	N	OFF	19.6
3.921000	---	24.12	46.00	21.88	N	OFF	19.6
3.921000	35.61	---	56.00	20.39	N	OFF	19.6
4.718310	---	25.49	46.00	20.51	N	OFF	19.6
4.718310	36.46	---	56.00	19.54	N	OFF	19.6
4.817940	---	27.67	46.00	18.33	N	OFF	19.7
4.817940	40.26	---	56.00	15.74	N	OFF	19.7
4.966890	---	30.29	46.00	15.71	N	OFF	19.7
4.966890	42.39	---	56.00	13.61	N	OFF	19.7
5.148600	---	31.77	50.00	18.23	N	OFF	19.7



5.148600	43.82	---	60.00	16.18	N	OFF	19.7
5.348400	---	29.20	50.00	20.80	N	OFF	19.7
5.348400	42.00	---	60.00	18.00	N	OFF	19.7
6.979470	---	31.27	50.00	18.73	N	OFF	19.7
6.979470	32.54	---	60.00	27.46	N	OFF	19.7
8.542500	---	27.87	50.00	22.13	N	OFF	19.8
8.542500	32.79	---	60.00	27.21	N	OFF	19.8
10.857750	---	27.07	50.00	22.93	N	OFF	19.8
10.857750	30.75	---	60.00	29.25	N	OFF	19.8
12.410250	---	24.36	50.00	25.64	N	OFF	19.9
12.410250	29.28	---	60.00	30.72	N	OFF	19.9
13.193250	---	20.35	50.00	29.65	N	OFF	19.9
13.193250	28.03	---	60.00	31.97	N	OFF	19.9
13.970130	---	16.21	50.00	33.79	N	OFF	19.9
13.970130	18.39	---	60.00	41.61	N	OFF	19.9
14.744040	---	21.51	50.00	28.49	N	OFF	19.9
14.744040	28.35	---	60.00	31.65	N	OFF	19.9
16.953000	---	21.51	50.00	28.49	N	OFF	19.9
16.953000	25.63	---	60.00	34.37	N	OFF	19.9



### Appendix C. Radiated Spurious Emission

Test Engineer :	Daniel Lee, Jacky Hong and Wilson Wu	Temperature :	21.5 ~ 23.5°C
		Relative Humidity :	49.5 ~ 55.5%

**2.4GHz 2400~2483.5MHz**

**BT (Band Edge @ 3m)**

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BT CH00 2402MHz		2363.445	46.22	-27.78	74	41.8	27.67	4.04	27.29	102	130	P	H	
		2363.445	21.43	-32.57	54	-	-	-	-	-	-	A	H	
	*	2402	102.47	-	-	98.09	27.6	4.07	27.29	102	130	P	H	
	*	2402	77.68	-	-	-	-	-	-	-	-	A	H	
													H	
			2350.74	45.98	-28.02	74	41.55	27.7	4.02	27.29	283	5	P	V
			2350.74	21.19	-32.81	54	-	-	-	-	-	-	A	V
	*		2402	101.72	-	-	97.34	27.6	4.07	27.29	283	5	P	V
	*		2402	76.93	-	-	-	-	-	-	-	-	A	V
														V
BT CH 39 2441MHz		2383.5	45.17	-28.83	74	40.78	27.63	4.05	27.29	118	124	P	H	
		2383.5	20.38	-33.62	54	-	-	-	-	-	-	A	H	
	*	2441	100.7	-	-	96.35	27.52	4.11	27.28	118	124	P	H	
	*	2441	75.91	-	-	-	-	-	-	-	-	A	H	
			2493.77	45.88	-28.12	74	41.5	27.5	4.15	27.27	118	124	P	H
			2493.77	21.09	-32.91	54	-	-	-	-	-	-	A	H
			2324.14	45.15	-28.85	74	40.7	27.75	4	27.3	273	6	P	V
			2324.14	20.36	-33.64	54	-	-	-	-	-	-	A	V
	*		2441	97.41	-	-	93.06	27.52	4.11	27.28	273	6	P	V
	*		2441	72.62	-	-	-	-	-	-	-	-	A	V
			2483.5	45.71	-28.29	74	41.33	27.5	4.15	27.27	273	6	P	V
			2483.5	20.92	-33.08	54	-	-	-	-	-	-	A	V



<b>BT CH 78 2480MHz</b>	*	2480	102.78	-	-	98.41	27.5	4.14	27.27	102	181	P	H
	*	2480	77.99	-	-	-	-	-	-	-	-	A	H
		2483.8	48.55	-25.45	74	44.17	27.5	4.15	27.27	102	181	P	H
		2483.8	23.76	-30.24	54	-	-	-	-	-	-	A	H
													H
													H
	*	2480	101.79	-	-	97.42	27.5	4.14	27.27	309	6	P	V
	*	2480	77	-	-	-	-	-	-	-	-	A	V
		2483.56	47.87	-26.13	74	43.49	27.5	4.15	27.27	309	6	P	V
		2483.56	23.08	-30.92	54	-	-	-	-	-	-	A	V
													V
													V
<b>Remark</b>	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



2.4GHz 2400~2483.5MHz  
BT (Harmonic @ 3m)

BT	Note	Frequency ( MHz )	Level ( dBμV/m )	Over Limit ( dB )	Limit Line ( dBμV/m )	Read Level ( dBμV )	Antenna Factor ( dB/m )	Path Loss ( dB )	Preamp Factor ( dB )	Ant Pos ( cm )	Table Pos ( deg )	Peak Avg. ( P/A )	Pol. ( H/V )	
BT CH 00 2402MHz		4804	38.02	-35.98	74	57.42	31.11	6.98	57.49	100	0	P	H	
		4804	13.23	-40.77	54	-	-	-	-	-	-	A	H	
													H	
													H	
		4804	39.14	-34.86	74	58.54	31.11	6.98	57.49	100	0	P	V	
		4804	14.35	-39.65	54	-	-	-	-	-	-	-	A	V
														V
														V
BT CH 39 2441MHz		4882	39.67	-34.33	74	58.8	31.2	6.99	57.32	100	0	P	H	
		4882	14.88	-39.12	54	-	-	-	-	-	-	A	H	
		7323	43.69	-30.31	74	55.72	36.75	8.32	57.1	100	0	P	H	
		7323	18.9	-35.1	54	-	-	-	-	-	-	A	H	
		4882	38.53	-35.47	74	57.66	31.2	6.99	57.32	100	0	P	V	
		4882	13.74	-40.26	54	-	-	-	-	-	-	-	A	V
		7323	44.28	-29.72	74	56.31	36.75	8.32	57.1	100	0	P	V	
		7323	19.49	-34.51	54	-	-	-	-	-	-	-	A	V
BT CH 78 2480MHz		4960	38.72	-35.28	74	57.46	31.42	7	57.16	100	0	P	H	
		4960	13.93	-40.07	54	-	-	-	-	-	-	A	H	
		7440	43.7	-30.3	74	55.83	36.82	8.33	57.28	100	0	P	H	
		7440	18.91	-35.09	54	-	-	-	-	-	-	A	H	
		4960	38.83	-35.17	74	57.57	31.42	7	57.16	100	0	P	V	
		4960	14.04	-39.96	54	-	-	-	-	-	-	A	V	
		7440	43.87	-30.13	74	56	36.82	8.33	57.28	100	0	P	V	
		7440	19.08	-34.92	54	-	-	-	-	-	-	-	A	V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission below 1GHz

2.4GHz BT (LF)

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
		( MHz )	( dBμV/m )	( dB )	( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )	
2.4GHz BT LF		71.71	27.39	-12.61	40	46.22	12.67	0.73	32.23	-	-	P	H	
		108.57	32.98	-10.52	43.5	47.28	16.95	0.88	32.13	-	-	P	H	
		208.48	26.86	-16.64	43.5	42.76	15.09	1.29	32.28	-	-	P	H	
		303.54	30.1	-15.9	46	41.3	19.29	1.49	31.98	-	-	P	H	
		313.24	29.48	-16.52	46	40.48	19.42	1.52	31.94	-	-	P	H	
		914.64	37.63	-8.37	46	37.46	28.94	2.68	31.45	100	0	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			32.91	27.28	-12.72	40	35.77	23.25	0.5	32.24	-	-	P	V
			71.71	28.55	-11.45	40	47.38	12.67	0.73	32.23	-	-	P	V
			91.11	27.38	-16.12	43.5	43.7	15.04	0.79	32.15	-	-	P	V
			109.54	25.51	-17.99	43.5	39.76	16.99	0.89	32.13	-	-	P	V
			303.54	27.24	-18.76	46	38.44	19.29	1.49	31.98	-	-	P	V
			913.67	36.65	-9.35	46	36.52	28.91	2.68	31.46	100	0	P	V
														V
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against limit line.													



**Note symbol**

*	<b>Fundamental Frequency</b> which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is <b>over limit</b> line.
P/A	<b>Peak</b> or <b>Average</b>
H/V	<b>Horizontal</b> or <b>Vertical</b>



A calculation example for radiated spurious emission is shown as below:

BT	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
		( MHz )	( dBμV/m )	( dB )	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
					( dBμV/m )	( dBμV )	( dB/m )	( dB )	( dB )	( cm )	( deg )	( P/A )	( H/V )
BT		2390	55.45	-18.55	74	54.51	32.22	4.58	35.86	103	308	P	H
CH 00		2390	43.54	-10.46	54	42.6	32.22	4.58	35.86	103	308	A	H
2402MHz													

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) =  
Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

**For Peak Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)  
= 55.45 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 55.45(dBμV/m) – 74(dBμV/m)  
= -18.55(dB)

**For Average Limit @ 2390MHz:**

1. Level(dBμV/m)  
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)  
= 32.22(dB/m) + 4.58(dB) + 42.6(dBμV) – 35.86 (dB)  
= 43.54 (dBμV/m)
2. Over Limit(dB)  
= Level(dBμV/m) – Limit Line(dBμV/m)  
= 43.54(dBμV/m) – 54(dBμV/m)  
= -10.46(dB)

**Both peak and average measured complies with the limit line, so test result is “PASS”.**



## Appendix D. Radiated Spurious Emission Plots

Test Engineer :	Daniel Lee, Jacky Hong and Wilson Wu	Temperature :	21.5 ~ 23.5°C
		Relative Humidity :	49.5 ~ 55.5%

Note symbol

-L	Low channel location
-R	High channel location







2.4GHz 2400~2483.5MHz

BT (Band Edge @ 3m)

BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
	BT CH00 2402MHz	
	Horizontal	Fundamental
<b>Peak</b>	<p>Date: 2020-08-17</p> <p>Site : 03CH13-1F Condition : PEAK_BE_74 3m HORN_9120D_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 070206 Mode : 1</p>	<p>Date: 2020-08-17</p> <p>Site : 03CH13-1F Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 070206 Mode : 1</p>






BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH00 2402MHz		
	Vertical	Fundamental
<b>Peak</b>	 <p>Site : 03CH13-HY Condition : PEAK_8E_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 070206 Mode : 1</p>	 <p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto Detector : Peak Project : 070206 Mode : 1</p>





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Horizontal	Fundamental
Peak	<p>           Site : 03CH13-HY            Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 2         </p>	<p>           Site : 03CH13-HY            Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 2         </p>
Peak	<p>           Site : 03CH13-HY            Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 2         </p>	Left blank





BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH39 2441MHz		
	Vertical	Fundamental
Peak	 <p>           Site : 03CH13-HY            Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 2         </p>	 <p>           Site : 03CH13-HY            Condition : PEAK_74 3m HORN_91200_1241 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 2         </p>
Peak	 <p>           Site : 03CH13-HY            Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL            : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 2         </p>	Left blank



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
Horizontal		Fundamental
Peak	 <p>Date: 2020-08-17</p> <p>PEAK_BE_74</p> <pre> Site      : 03CH13-HY Condition : PEAK_BE_74 3m HORN_91200_1241 HORIZONTAL RBW      : 1000.000KHz VBW:3000.000KHz SWT:Auto Detector  : Peak Project   : 070206 Mode      : 3           </pre>	 <p>Date: 2020-08-17</p> <p>PEAK_74</p> <pre> Site      : 03CH13-HY Condition : PEAK_74 3m HORN_91200_1241 HORIZONTAL RBW      : 1000.000KHz VBW:3000.000KHz SWT:Auto Detector  : Peak Project   : 070206 Mode      : 3           </pre>



BT	2.4GHz 2400~2483.5MHz Band Edge @ 3m	
BT CH78 2480MHz		
	Vertical	Fundamental
Peak	 <p>Date: 2020-08-17</p> <p>Site : 03CH13-HY            Condition : PEAK_BE_74 3m HORN_91200_1241 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 3</p>	 <p>Date: 2020-08-17</p> <p>Site : 03CH13-HY            Condition : PEAK_74 3m HORN_91200_1241 VERTICAL            RBW:1000.000KHz VBW:3000.000KHz SWT:Auto            Detector : Peak            Project : 070206            Mode : 3</p>





2.4GHz 2400~2483.5MHz

BT (Harmonic @ 3m)



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
	BT CH00 2402MHz	
	Horizontal	Vertical
<p><b>Peak</b></p> <p><b>Avg.</b></p>	<p>Site : 03CH13-1FY            Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL            Detector : Peak            Project : 070206            Mode : 1</p>	<p>Site : 03CH13-1FY            Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL            Detector : Peak            Project : 070206            Mode : 1</p>



BT	2.4GHz 2400~2483.5MHz Harmonic @ 3m	
BT CH39 2441MHz		
	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : Peak Project : 070206 Mode : 2</p>	 <p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL Detector : Peak Project : 070206 Mode : 2</p>







<b>BT</b>	<b>2.4GHz 2400~2483.5MHz Harmonic @ 3m</b>	
	<b>BT CH78 2480MHz</b>	
	<b>Horizontal</b>	<b>Vertical</b>
<b>Peak Avg.</b>	 <p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 HORIZONTAL Detector : Peak Project : 070206 Mode : 3</p>	 <p>Site : 03CH13-HY Condition : PEAK_74 3m HORN_9120D_1241 VERTICAL Detector : Peak Project : 070206 Mode : 3</p>




Emission below 1GHz  
2.4GHz BT (LF)

BT	2.4GHz 2400~2483.5MHz	
BT LF		
Horizontal		Vertical
QP / Peak	 <p data-bbox="422 817 813 884">Site : 03CH13-HY Condition : QP 3m BTLOG_40103 HORIZONTAL Detector : Peak Project : 070206 Mode : 4</p>	 <p data-bbox="901 817 1292 884">Site : 03CH13-HY Condition : QP 3m BTLOG_40103 VERTICAL Detector : Peak Project : 070206 Mode : 4</p>




# Appendix E. Duty Cycle Plots

### 3DH5 on time (One Pulse) Plot on Channel 39



### on time (Count Pulses) Plot on Channel 39



#### Note:

1. Worst case Duty cycle = on time/100 milliseconds =  $2 * 2.88 / 100 = 5.76 \%$
2. Worst case Duty cycle correction factor =  $20 * \log(\text{Duty cycle}) = -24.79 \text{ dB}$
3. 3DH5 has the highest duty cycle worst case and is reported.



**Duty Cycle Correction Factor Consideration for AFH mode:**

Bluetooth normal hopping rate is 1600Hz and reduced to 800Hz in AFH mode; due to the reduced number of hopping frequencies, with the same packet configuration the dwell time in each channel frequency within 100msec period is longer in AFH mode than normal mode.

In AFH mode, the minimum hopping frequencies are 20, to get the longest dwell time DH5 packet is observed; the period to have DH5 packet completing one hopping sequence is

$$2.88 \text{ ms} \times 20 \text{ channels} = 57.6 \text{ ms}$$

There cannot be 2 complete hopping sequences within 100ms period, considering the random hopping behavior, maximum 2 hops can be possibly observed within the period.  $[100 \text{ ms} / 57.6 \text{ ms}] = 2 \text{ hops}$

Thus, the maximum possible ON time:

$$2.88 \text{ ms} \times 2 = 5.76 \text{ ms}$$

Worst case Duty Cycle Correction factor, which is derived from the maximum possible ON time,

$$20 \times \log(5.76 \text{ ms}/100 \text{ ms}) = -24.79 \text{ dB}$$