


FCC RF Test Report

APPLICANT : Acer Incorporated
EQUIPMENT : Tablet Computer
BRAND NAME : Acer
MODEL NAME : A500
FCC ID : HLZTMDMA500
STANDARD : FCC Part 15 Subpart C §15.247
CLASSIFICATION : Digital Spread Spectrum (DSS)

The product was received on Jan. 29, 2011 and completely tested on Mar. 21, 2011. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.4-2003 and shown the compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Roy Wu / Manager



SPORTON INTERNATIONAL INC.

No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C.



TABLE OF CONTENTS

REVISION HISTORY.....3

SUMMARY OF TEST RESULT4

1 GENERAL DESCRIPTION.....5

 1.1 Applicant5

 1.2 Manufacturer.....5

 1.3 Feature of Equipment under Test.....6

 1.4 Testing Site.....7

 1.5 Applied Standards7

 1.6 Ancillary Equipment List8

2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST.....9

 2.1 RF Output Power9

 2.2 Test Mode.....10

 2.3 Connection Diagram of Test System.....11

 2.4 RF Utility11

3 TEST RESULT12

 3.1 Number of Channel Measurement12

 3.2 20dB and 99% Bandwidth Measurement14

 3.3 Hopping Channel Separation Measurement27

 3.4 Dwell Time Measurement.....30

 3.5 Peak Output Power Measurement41

 3.6 Band Edges Measurement48

 3.7 Spurious Emission Measurement.....60

 3.8 AC Conducted Emission Measurement.....70

 3.9 Radiated Emission Measurement.....74

 3.10 Antenna Requirements84

4 LIST OF MEASURING EQUIPMENT.....85

5 UNCERTAINTY OF EVALUATION.....86

APPENDIX A. PHOTOGRAPHS OF EUT

APPENDIX B. SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR112908A	Rev. 01	Initial issue of report	Mar. 03, 2011
FR112908A	Rev. 02	Update report for adding the test data of conducted spurious emissions for GFSK and 8-DPSK mode.	Mar. 21, 2011

**SUMMARY OF TEST RESULT**

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.1	15.247(a)(1)	A8.4(2)	Number of Channels	≥ 15 Chs	Pass	-
3.2	15.247(a)(1)	A8.1(a)	20dB Bandwidth	NA	Pass	-
3.2	-	Gen 4.4.1	99% Bandwidth	-	Pass	-
3.3	15.247(a)(1)	A8.1(b)	Channel Separation	$\geq 2/3$ of 20dB BW	Pass	-
3.4	15.247(a)(1)	A8.1(d)	Dwell Time of Each Channel	≤ 0.4 sec in 31.6sec period	Pass	-
3.5	15.247(b)(1)	A8.1(b)	Peak Output Power	≤ 125 mW	Pass	-
3.6	15.247(d)	A8.5	Frequency Band Edges	≤ 20 dBc	Pass	-
3.7	15.247(d)	A8.5	Spurious Emission	< 20 dBc	Pass	-
3.8	15.207	Gen 7.2.2	AC Conducted Emission	15.207(a)	Pass	Under limit 11.4 dB at 0.17 MHz
3.9	15.247(d)	A8.5	Transmitter Radiated Emission	15.209(a) & 15.247(d)	Pass	Under limit 9.52 dB at 32.97 MHz
3.10	15.203 & 15.247(b)	A8.4	Antenna Requirement	N/A	Pass	-



1 General Description

1.1 Applicant

Acer Incorporated

8F., No. 88, Sec. 1, Xintai 5th Rd., Xizhi Dist., New Taipei City 22181, Taiwan (R.O.C)

1.2 Manufacturer

1. Compal Electronics, Inc.

No. 581, Ruiguang Rd., Neihu District, Taipei City 11492, Taiwan

2. Compal Electronics Technology (Kunshan) Co., Ltd.

No. 25, Third Avenue, A Zone, Kunshan Comprehensive Free Trade Zone, Kunshan, Jiangsu, China

3. Compal Information (Kunshan) Co., Ltd.

No. 15, Third Avenue, A Zone, Kunshan Comprehensive Free Trade Zone, Kunshan, Jiangsu, China

4. Compal Information Technology (Kunshan) Co., Ltd.

No. 58, First Avenue, A Zone, Kunshan Comprehensive Free Trade Zone, Kunshan, Jiangsu, China

5. Compalead Eletrônica Do Brasil Indústria E Comércio Ltda

Rua Kanebo 175, Galpões C1, C2, C3, C4, C5 C6 E C12, Bairro Distrito Industrial Jundiaí Business Park, Cep 13213-090, Jundiaí - São Paulo, Brasil

6. Compal (Vietnam) Co., Ltd.

Ba Thien Industrial Zone, Ba Hien Commune, Binh Xuyen County, Vinh Phuc Province, Vietnam



1.3 Feature of Equipment under Test

Product Feature & Specification	
Equipment	Tablet Computer
Brand Name	Acer
Model Name	A500
FCC ID	HLZTMDMA500
Tx/Rx Frequency Range	2400 MHz ~ 2483.5 MHz
Number of Channels	79
Carrier Frequency of Each Channel	2402+n*1 MHz; n=0~78
Channel Spacing	1 MHz
Maximum Output Power to Antenna	Bluetooth (1Mbps) : 2.81 dBm (0.002 W) Bluetooth EDR (2Mbps) : 5.38 dBm (0.003 W) Bluetooth EDR (3Mbps) : 3.16 dBm (0.002 W)
Antenna Type	PIFA Antenna
Antenna Gain	1.75 dBi
HW Version	Rev:0.2
SW Version	Android version: 3.0 Baseband version:unknown Build number: Acer_PicassoF_0.001.00_EMEA_GEN1
Type of Modulation	Bluetooth (1Mbps) : GFSK Bluetooth EDR (2Mbps) : π /4-DQPSK Bluetooth EDR (3Mbps) : 8-DPSK
EUT Stage	Identical Prototype

Remark:

1. For other wireless features of this EUT, test report will be issued separately.
2. This test report recorded only product characteristics and test results of Digital Spread Spectrum (DSS).
3. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

1.4 Testing Site

Test Site	SPORTON INTERNATIONAL INC.		
Test Site Location	No. 52, Hwa Ya 1 st Rd., Hwa Ya Technology Park, Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL: +886-3-3273456 / FAX: +886-3-3284978		
Test Site No.	Sporton Site No.		FCC/IC Registration No.
	CO05-HY	03CH07-HY	722060/4086B-1

1.5 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC Public Notice DA 00-705
- ♦ ANSI C63.4-2003
- ♦ IC RSS-210 Issue 8

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B (DoC), recorded in a separate test report.



1.6 Ancillary Equipment List

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	Bluetooth Base Station	R&S	CBT32	N/A	N/A	Unshielded, 1.8 m
2.	WLAN AP	D-Link	DIR-628	KA2DIR628A2	N/A	Unshielded, 1.8 m
3.	Notebook	DELL	Vostro 1510	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
4.	Bluetooth Earphone	Nokia	BH-102	PYAHS-107W	N/A	N/A
5.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
6.	iPod Earphone	Apple	N/A	FCC DoC	Unshielded, 1.0 m	N/A
7.	LCD Monitor	Dell	U2410	FCC DoC	Shielded, 1.6 m	Unshielded, 1.8 m

2 Test Configuration of Equipment Under Test

2.1 RF Output Power

Preliminary tests were performed in different data rate and recorded the RF output power in the following table:

Channel	Frequency	Bluetooth RF Output Power		
		Data Rate / Modulation		
		GFSK	π /4-DQPSK	8-DPSK
		1Mbps	2Mbps	3Mbps
Ch00	2402MHz	1.30 dBm	3.82 dBm	1.58 dBm
Ch39	2441MHz	1.90 dBm	4.48 dBm	2.47 dBm
Ch78	2480MHz	2.81 dBm	5.38 dBm	3.16 dBm

Remark:

1. The data rate was set in 2Mbps for all the test items due to the highest RF output power.
2. The EUT is programmed to transmit signals continuously for all testing.

2.2 Test Mode

The EUT has been associated with peripherals pursuant to ANSI C63.4-2003 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).


Pre-scanned tests were conducted to determine the final configuration from all possible combinations.

The following tables are showing the test modes as the worst cases and recorded in this report.


Test Cases			
Test Item	Data Rate / Modulation		
	Bluetooth 1Mbps GFSK	Bluetooth EDR 2Mbps π /4-DQPSK	Bluetooth EDR 3Mbps 8-DPSK
Conducted TCs	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	Mode 4: CH00_2402 MHz Mode 5: CH39_2441 MHz Mode 6: CH78_2480 MHz	Mode 7: CH00_2402 MHz Mode 8: CH39_2441 MHz Mode 9: CH78_2480 MHz
Radiated TCs	N/A	Mode 1: CH00_2402 MHz Mode 2: CH39_2441 MHz Mode 3: CH78_2480 MHz	N/A
AC Conducted Emission	Mode 1 :WLAN Link + Bluetooth Link + TC + Adapter		
Remark:			
<ol style="list-style-type: none"> 1. TC stands for Test Configuration, and consists of iPod, earphone, and monitor. 2. For radiated TCs, the data rate was set in 2Mbps due to the highest RF output power; only the data of these modes was reported. 3. For radiated TCs, E1 plane was the worst case; only the E1 plane of these modes was reported. 			

2.3 Connection Diagram of Test System

<Bluetooth Tx Mode>



<AC Conducted Emission Mode>



2.4 RF Utility

For Bluetooth function, execute command in order to make the EUT into the engineering modes to contact with Bluetooth base station for transmitting and receiving signals continuously.

3 Test Result

3.1 Number of Channel Measurement

3.1.1 Limits of Number of Hopping Frequency

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.


3.1.2 Measuring Instruments

See list of measuring instruments of this test report.

3.1.3 Test Procedure

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The modulation types of EUT are irrelevant to number of hopping channels deviation.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = the frequency band of operation; $RBW \geq 1\%$ of the span; $VBW \geq RBW$; Sweep = auto;
Detector function = peak; Trace = max hold.
5. The number of hopping frequency used is defined as the device has the numbers of total channel.

3.1.4 Test Setup







3.1.5 Test Result of Number of Hopping Frequency

Test Mode :	Mode 4~6	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%
Number of Hopping Channels (Channel)		Limits (Channel)	Pass/Fail
79		> 15	Pass

Number of Hopping Channel Plot on Channel 00 - 78



Date: 2.FEB.2011 14:09:49



Date: 2.FEB.2011 14:14:20

3.2 20dB and 99% Bandwidth Measurement

3.2.1 Limit of 20dB Bandwidth

N/A

3.2.2 Measuring Instruments

See list of measuring instruments of this test report.

3.2.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel;
RBW \geq 1% of the 20 dB bandwidth; VBW \geq RBW; Sweep = auto; Detector function = peak;
Trace = max hold.
5. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

3.2.4 Test Setup






3.2.5 Test Result of 20dB Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	0.940
39	2441	0.944
78	2480	1.020


20 dB Bandwidth Plot on Channel 00



Date: 2.FEB.2011 13:47:59




20 dB Bandwidth Plot on Channel 39



Date: 2.FEB.2011 13:48:13

20 dB Bandwidth Plot on Channel 78




Date: 2.FEB.2011 13:49:47



Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.320
39	2441	1.314
78	2480	1.314


20 dB Bandwidth Plot on Channel 00



Date: 2.FEB.2011 13:50:28




20 dB Bandwidth Plot on Channel 39



Date: 2.FEB.2011 13:51:04

20 dB Bandwidth Plot on Channel 78




Date: 2.FEB.2011 13:52:14



Test Mode :	Mode 7, 8, 9	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	20dB Bandwidth (MHz)
00	2402	1.278
39	2441	1.278
78	2480	1.278


20 dB Bandwidth Plot on Channel 00



Date: 2.FEB.2011 13:52:28




20 dB Bandwidth Plot on Channel 39



Date: 2.FEB.2011 13:52:43

20 dB Bandwidth Plot on Channel 78



Date: 2.FEB.2011 13:53:07




3.2.6 Test Result of 99% Occupied Bandwidth

Test Mode :	Mode 1, 2, 3	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	0.868
39	2441	0.892
78	2480	0.896


99% Bandwidth Plot on Channel 00



Date: 2.FEB.2011 14:19:17




99% Occupied Bandwidth Plot on Channel 39



Date: 2.FEB.2011 14:19:44

99% Occupied Bandwidth Plot on Channel 78




Date: 2.FEB.2011 14:20:09



Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.168
39	2441	1.176
78	2480	1.172


99% Bandwidth Plot on Channel 00



Date: 2.FEB.2011 14:20:40




99% Occupied Bandwidth Plot on Channel 39



Date: 2.FEB.2011 14:21:05

99% Occupied Bandwidth Plot on Channel 78




Date: 2.FEB.2011 14:21:40



Test Mode :	Mode 7, 8, 9	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	99% Occupied Bandwidth (MHz)
00	2402	1.160
39	2441	1.160
78	2480	1.160


99% Bandwidth Plot on Channel 00



Date: 2.FEB.2011 14:22:03




99% Occupied Bandwidth Plot on Channel 39



Date: 2.FEB.2011 14:22:21

99% Occupied Bandwidth Plot on Channel 78



Date: 2.FEB.2011 14:22:43

3.3 Hopping Channel Separation Measurement

3.3.1 Limit of Hopping Channel Separation

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.


3.3.2 Measuring Instruments

See list of measuring instruments of this test report.

3.3.3 Test Procedures

1. Please refer FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. Use the following spectrum analyzer settings:
Span = wide enough to capture the peaks of two adjacent channels; $RBW \geq 1\%$ of the span;
 $VBW \geq RBW$; Sweep = auto; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

3.3.4 Test Setup






3.3.5 Test Result of Hopping Channel Separation

Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	Frequency Separation (MHz)	(2/3 of 20dB BW) Limits (MHz)	Pass/Fail
00	2402	1.002	0.025	Pass
39	2441	1.008	0.025	Pass
78	2480	1.002	0.025	Pass


Channel Separation Plot on Channel 00 - 01



Date: 2.FEB.2011 13:41:27




Channel Separation Plot on Channel 39 - 40



Date: 2.FEB.2011 13:42:24

Channel Separation Plot on Channel 77 - 78



Date: 2.FEB.2011 13:42:59

3.4 Dwell Time Measurement

3.4.1 Limit of Dwell Time

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.


3.4.2 Measuring Instruments

See list of measuring instruments of this test report.

3.4.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.
3. The EUT should be transmitting at its maximum data rate as the worst cases.
4. The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:
Span = zero span, centered on a hopping channel; RBW = 1 MHz; VBW \geq RBW; Sweep = as necessary to capture the entire dwell time per hopping channel; Detector function = peak; Trace = max hold.
5. Use the marker-delta function to calculate the dwell time.

3.4.4 Test Setup



3.4.5 Test Result of Dwell Time

Test Mode :	Mode 2	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
DH1	9.10	500.00	0.14	0.4	Pass
DH3	4.80	1760.00	0.27	0.4	Pass
DH5	3.80	3020.00	0.36	0.4	Pass

Test Mode :	Mode 5	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
2DH1	8.50	502.00	0.13	0.4	Pass
2DH3	5.40	1772.00	0.30	0.4	Pass
2DH5	3.70	3032.00	0.35	0.4	Pass

Test Mode :	Mode 8	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%


Package Mode	Average Hopping Channel	Package Transfer Time (usec)	Dwell Time (sec)	Limits (sec)	Pass/Fail
3DH1	8.60	502.00	0.14	0.4	Pass
3DH3	4.50	1772.00	0.25	0.4	Pass
3DH5	3.40	3052.00	0.33	0.4	Pass

Remark:

1. Dwell Time=79(channels) x 0.4(s) x average hopping channel x package transfer time
2. 79 channels come from the Hopping Channel number.
3. Average Hopping Channel = hops/sweep time
4. t: Package Transfer Time(us)




DH1 Dwell Time (One Pulse) Plot on Channel 39



Date: 3.FEB.2011 12:36:10


DH1 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:45:02




DH3 Dwell Time (One Pulse) Plot on Channel 39



Date: 3.FEB.2011 12:36:49


DH3 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:45:16




DH5 Dwell Time (One Pulse) Plot on Channel 39



Date: 3.FEB.2011 12:37:38


DH5 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:45:31




2DH1 Dwell Time (One Pulse) Plot on Channel 39



Date: 2.FEB.2011 12:47:32


2DH1 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:45:46




2DH3 Dwell Time (One Pulse) Plot on Channel 39



Date: 2.FEB.2011 12:48:00


2DH3 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:46:01




2DH5 Dwell Time (One Pulse) Plot on Channel 39



Date: 2.FEB.2011 12:50:27


2DH5 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:46:15




3DH1 Dwell Time (One Pulse) Plot on Channel 39



Date: 2.FEB.2011 12:51:02


3DH1 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:46:30




3DH3 Dwell Time (One Pulse) Plot on Channel 39



Date: 2.FEB.2011 12:51:19


3DH3 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:46:45




3DH5 Dwell Time (One Pulse) Plot on Channel 39



Date: 2.FEB.2011 12:51:47

3DH5 Dwell Time (Count Pulses) Plot on Channel 39



Date: 2.FEB.2011 13:46:59

3.5 Peak Output Power Measurement

3.5.1 Limit of Peak Output Power

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW (20.97dBm).


3.5.2 Measuring Instruments

See list of measuring instruments of this test report.

3.5.3 Test Procedures

1. The testing follows FCC Public Notice DA 00-705 Measurement Guidelines.
2. The RF output of EUT was connected to the spectrum analyzer by a low loss cable.

3.5.4 Test Setup





3.5.5 Test Result of Peak Output Power

Test Mode :	Mode 1, 2, 3	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	RF Power (dBm)		
		GFSK	Max. Limits (dBm)	Pass/Fail
		1 Mbps		
00	2402	1.30	20.97	Pass
39	2441	1.90	20.97	Pass
78	2480	2.81	20.97	Pass

Test Mode :	Mode 4, 5, 6	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%


Channel	Frequency (MHz)	RF Power (dBm)		
		$\pi/4$ -DQPSK	Max. Limits (dBm)	Pass/Fail
		2 Mbps		
00	2402	3.82	20.97	Pass
39	2441	4.48	20.97	Pass
78	2480	5.38	20.97	Pass

Test Mode :	Mode 7, 8, 9	Temperature :	24~26°C
Test Engineer :	Phoenix Chen	Relative Humidity :	50~53%

Channel	Frequency (MHz)	RF Power (dBm)		
		8-DPSK	Max. Limits (dBm)	Pass/Fail
		3 Mbps		
00	2402	1.58	20.97	Pass
39	2441	2.47	20.97	Pass
78	2480	3.16	20.97	Pass




Peak Output Power Plot on Bluetooth (1Mbps) Channel 00



Date: 2.FEB.2011 12:35:35


Peak Output Power Plot on Bluetooth (1Mbps) Channel 39



Date: 3.FEB.2011 12:48:33




Peak Output Power Plot on Bluetooth (1Mbps) Channel 78



Date: 2.FEB.2011 12:38:07


Peak Output Power Plot on Bluetooth EDR (2Mbps) Channel 00



Date: 2.FEB.2011 12:36:00




Peak Output Power Plot on Bluetooth EDR (2Mbps) Channel 39



Date: 3.FEB.2011 12:47:23


Peak Output Power Plot on Bluetooth EDR (2Mbps) Channel 78



Date: 2.FEB.2011 12:38:32




Peak Output Power Plot on Bluetooth EDR (3Mbps) Channel 00



Date: 2.FEB.2011 12:36:26


Peak Output Power Plot on Bluetooth EDR (3Mbps) Channel 39



Date: 4.FEB.2011 11:53:07



Peak Output Power Plot on Bluetooth EDR (3Mbps) Channel 78



Date: 2.FEB.2011 12:38:57



3.6 Band Edges Measurement

3.6.1 Limit of Band Edges

In any 100 kHz bandwidth outside the intentional radiation frequency band, the radio frequency power shall be at least 20 dB below the highest level of the radiated power. In addition, radiated emissions which fall in the restricted bands must also comply with the radiated emission limits.

3.6.2 Measuring Instruments


See list of measuring instruments of this test report.

3.6.3 Test Procedures


1. The testing follows the guidelines in ANSI C63.4-2003 and FCC Public Notice DA 00-705 Measurement Guidelines.
2. RF antenna conducted test: Set RBW = 300kHz, Video bandwidth (VBW) \geq RBW. Band edge emissions must be at least 20 dB down from the highest emission level within the authorized band as measured with a 300k Hz RBW. Note: If the device complies with the use of power option 2 the attenuation under this paragraph shall be 30 dB instead of 20 dB.
3. Radiated emission test: Applies to band edge emissions that fall in the restricted bands listed in FCC Section 15.205. The maximum permitted average field strength is listed in FCC Section 15.209. A pre-amp is necessary for this measurement. For measurements above 1 GHz, set RBW = 1MHz, VBW = 1MHz, Sweep: Auto for Peak; set RBW = 1MHz, VBW = 10 Hz, Sweep: Auto for Average. If the emission is pulsed, modify the unit for continuous operation; use the settings shown above, then correct the reading by subtracting the peak-average correction factor, derived from the appropriate duty cycle calculation. See FCC Section 15.35(b) and (c).
4. In case the emission is fail due to the used RBW / VBW is too wide, marker-delta method of FCC Public Notice DA 00-705 will be followed.

3.6.4 Test Setup

<Radiated Band Edges>



<Conducted Band Edges>





3.6.5 Test Result of Radiated Band Edges

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	49~50%
		Test Engineer :	Ivan Chiang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2388.66	53.03	-20.97	74	48.67	32.18	6.03	33.85	131	238	Peak
2388.66	38.2	-15.8	54	33.84	32.18	6.03	33.85	131	238	Average

ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2387.9	49.51	-24.49	74	45.15	32.18	6.03	33.85	104	276	Peak
2387.9	35.78	-18.22	54	31.42	32.18	6.03	33.85	104	276	Average



Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
		Test Engineer :	Ivan Chiang

ANTENNA POLARITY : HORIZONTAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	54.47	-19.53	74	49.91	32.28	6.18	33.9	124	240	Peak
2483.5	35.79	-18.21	54	31.23	32.28	6.18	33.9	124	240	Average

Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Peak Result (dBµV/m)	Peak Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	109.33	54.86	54.47	74	-19.53	Pass
Hopping Mode	109.33	56.39	52.94	74	-21.06	Pass

Note : Peak result = Maximum field strength – Delta result

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Average Result (dBµV/m)	Average Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	90.65	54.86	35.79	54	-18.21	Pass
Hopping Mode	90.65	56.39	34.26	54	-19.74	Pass

Note : Average result = Maximum field strength – Delta result



ANTENNA POLARITY : VERTICAL										
Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
2483.5	50.46	-23.54	74	45.9	32.28	6.18	33.9	100	276	Peak
2483.5	32.14	-21.86	54	27.58	32.28	6.18	33.9	100	276	Average

Summary results of marker-delta method:

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Peak Result (dBµV/m)	Peak Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	105.78	55.32	50.46	74	-23.54	Pass
Hopping Mode	105.78	56.02	49.76	74	-24.24	Pass


Note : Peak result = Maximum field strength – Delta result

Test mode	Maximum field strength of the fundamental emission (dBµV/m)	Delta Result (dB)	Average Result (dBµV/m)	Average Limit (dBµV/m)	Margin (dB)	Result
Single Carrier Mode	87.46	55.32	32.14	54	-21.86	Pass
Hopping Mode	87.46	56.02	31.44	54	-22.56	Pass

Note : Average result = Maximum field strength – Delta result



Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Horizontal




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC CLASS-B HF_ANT_100824 HORIZONTAL
 Project : FR 112908
 Mode : Mode 3

	Freq	Level	Over	Limit	Read	Antenna	Cable	Preamp	Ant	Table	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2480.00	109.33	35.33	74.00	104.77	32.28	6.18	33.90	124	240	Peak
2 @	2480.00	90.65	36.65	54.00	86.09	32.28	6.18	33.90	124	240	Average

* Maximum field strength of the fundamental emission




Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Horizontal





Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Horizontal




Trace: (Discrete)
 Site : 03CH07-HY
 Condition : FCC CLASS-B HF_ANT_100824 HORIZONTAL
 Project : FR 112908
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2480.00	107.34	33.34	74.00	102.78	32.28	6.18	33.90	124	240	Peak
2	2483.50	50.95	-23.05	74.00	46.39	32.28	6.18	33.90	124	240	Peak

* Marker-Delta Method (RBW/VBW=100KHz): 56.39 dB , Hopping Mode




Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Vertical






Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Vertical





Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Vertical



Trace: (Discrete)

Site : 03CH07-HY
 Condition : FCC CLASS-B HF_ANT_100824 VERTICAL
 Project : FR 112908
 Mode : Mode 3

	Freq	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Cable Loss	Preamp Factor	Ant Pos	Table Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg	
1 @	2480.00	103.53	29.53	74.00	98.97	32.28	6.18	33.90	100	276	Peak
2	2483.50	47.51	-26.49	74.00	42.95	32.28	6.18	33.90	100	276	Peak


* Marker-Delta Method (RBW/VBW=100KHz): 56.02 dB , Hopping Mode



3.6.6 Test Result of Conducted Band Edges


Test Mode :	Mode 4 and 6	Temperature :	24~26°C
Test Channel :	00 and 78	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Low Band Edge Plot on Channel 00



Date: 2.FEB.2011 13:54:55

High Band Edge Plot on Channel 78



Date: 2.FEB.2011 13:55:47

3.7 Spurious Emission Measurement

3.7.1 Limit of Spurious Emission Measurement

All harmonics/spurious must be at least 20 dB down from the highest emission level within the authorized band.


3.7.2 Measuring Instruments

See list of measuring instruments of this test report.

3.7.3 Test Procedure

1. The transmitter output was connected to the spectrum analyzer via a low lose cable.
2. Set RBW = 100 kHz, Video bandwidth (VBW) \geq RBW, scan up through 10th harmonic. All harmonics / spurs must be at least 20 dB down from the highest emission level within the authorized band as measured with a 100 kHz RBW.

3.7.4 Test Setup






3.7.5 Test Result


Test Mode :	Mode 1	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30 MHz ~ 3 GHz



Date: 21.MAR.2011 13:39:12

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 21.MAR.2011 13:39:24




Test Mode :	Mode 2	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30 MHz ~ 3 GHz



Date: 21.MAR.2011 13:40:16

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 21.MAR.2011 13:40:28




Test Mode :	Mode 3	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30 MHz ~ 3 GHz



Date: 21.MAR.2011 13:41:20

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 21.MAR.2011 13:41:32




Test Mode :	Mode 4	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30 MHz ~ 3 GHz



Date: 2.FEB.2011 14:03:31

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 2.FEB.2011 14:03:54




Test Mode :	Mode 5	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30 MHz ~ 3 GHz



Date: 2.FEB.2011 14:04:16

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 2.FEB.2011 14:04:39




Test Mode :	Mode 6	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30 MHz ~ 3 GHz



Date: 2.FEB.2011 14:05:01

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 2.FEB.2011 14:05:24




Test Mode :	Mode 7	Temperature :	24~26°C
Test Channel :	00	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 21.MAR.2011 13:42:24

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 21.MAR.2011 13:42:46




Test Mode :	Mode 8	Temperature :	24~26°C
Test Channel :	39	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 21.MAR.2011 13:43:17

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz




Date: 21.MAR.2011 13:43:39




Test Mode :	Mode 9	Temperature :	24~26°C
Test Channel :	78	Relative Humidity :	50~53%
		Test Engineer :	Phoenix Chen

Conducted Spurious Emission Plot between 30MHz ~ 3 GHz



Date: 21.MAR.2011 13:44:08

Conducted Spurious Emission Plot between 3 GHz ~ 25 GHz



Date: 21.MAR.2011 13:44:30

3.8 AC Conducted Emission Measurement

3.8.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.8.2 Measuring Instruments

See list of measuring instruments of this test report.

3.8.3 Test Procedures

1. Please follow the guidelines in ANSI C63.4-2003.
2. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
3. Connect EUT to the power mains through a line impedance stabilization network (LISN).
4. All the support units are connecting to the other LISN.
5. The LISN provides 50 ohm coupling impedance for the measuring instrument.
6. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
7. Both sides of AC line were checked for maximum conducted interference.
8. The frequency range from 150 kHz to 30 MHz was searched.
9. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.


3.8.4 Test Setup



AMN = Artificial mains network (LISN)
 AE = Associated equipment
 EUT = Equipment under test
 ISN = Impedance stabilization network

3.8.5 Test Result of AC Conducted Emission

Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Chiang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WLAN Link + Bluetooth Link + TC + Adapter		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1


Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	53.4	Off	L1	19.3	11.4	64.8
0.230000	48.3	Off	L1	19.4	14.1	62.4
0.326000	43.7	Off	L1	19.3	15.9	59.6
0.438000	36.4	Off	L1	19.4	20.7	57.1
3.614000	42.9	Off	L1	19.5	13.1	56.0
16.526000	45.9	Off	L1	19.7	14.1	60.0
26.406000	43.6	Off	L1	19.8	16.4	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	41.8	Off	L1	19.3	13.0	54.8
0.230000	34.5	Off	L1	19.4	17.9	52.4
0.326000	29.3	Off	L1	19.3	20.3	49.6
0.438000	23.7	Off	L1	19.4	23.4	47.1
3.614000	34.2	Off	L1	19.5	11.8	46.0
16.526000	36.6	Off	L1	19.7	13.4	50.0
26.406000	35.1	Off	L1	19.8	14.9	50.0



Test Mode :	Mode 1	Temperature :	20~22°C
Test Engineer :	Novic Chiang	Relative Humidity :	40~42%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WLAN Link + Bluetooth Link + TC + Adapter		
Remark :	All emissions not reported here are more than 10 dB below the prescribed limit.		



Final Result 1

Frequency (MHz)	QuasiPeak (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	52.8	Off	N	19.3	12.0	64.8
0.238000	45.9	Off	N	19.4	16.3	62.2
0.286000	44.1	Off	N	19.3	16.5	60.6
3.558000	40.6	Off	N	19.5	15.4	56.0
16.590000	45.0	Off	N	19.8	15.0	60.0
27.702000	40.9	Off	N	19.9	19.1	60.0

Final Result 2

Frequency (MHz)	Average (dBµV)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBµV)
0.174000	39.3	Off	N	19.3	15.5	54.8
0.238000	33.3	Off	N	19.4	18.9	52.2
0.286000	31.7	Off	N	19.3	18.9	50.6
3.558000	30.8	Off	N	19.5	15.2	46.0
16.590000	35.8	Off	N	19.8	14.2	50.0
27.702000	34.1	Off	N	19.9	15.9	50.0

3.9 Radiated Emission Measurement

3.9.1 Limit of Radiated Emission

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. In addition, radiated emissions which fall in the restricted bands must also comply with the FCC section 15.209 limits as below.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.9.2 Measuring Instruments


See list of measuring instruments of this test report.

3.9.3 Test Procedures


1. The testing follows the guidelines in FCC Public Notice DA 00-705 Measurement Guidelines.
2. Use the following spectrum analyzer settings:
 - (1) If $f < 1$ GHz
Span = wide enough to fully capture the emission being measured; RBW = 100 kHz; VBW 300KHz; Sweep = auto; Detector function = peak; Trace = max hold.
 - (2) If $f \geq 1$ GHz
Span = wide enough to fully capture the emission being measured; RBW = 1 MHz, VBW = 1MHz for Peak mode, RBW = 1 MHz, VBW = 10Hz for Average mode; Sweep = auto; Detector function = peak; Trace = max hold.
 - (3) Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.
Distance extrapolation factor = $20 \log (\text{specific distance [3m]} / \text{test distance [1m]})$ (dB)
3. Follow the guidelines in ANSI C63.4-2003 with respect to maximizing the emission by rotating the EUT, measuring the emission for three EUT orthogonal planes, and adjusting the measurement antenna height and polarization. A pre-amp and a high pass filter are used for this test in order to get the good signal level.

3.9.4 Test Setup


For radiated emissions below 30MHz



For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz





3.9.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

Test Engineer :	Ivan Chiang	Temperature :	23~24°C
		Relative Humidity :	49~50%

Frequency (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.



3.9.6 Test Result of Radiated Emission (30 MHz ~ 10th Harmonic)

Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Horizontal
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
42.69	28.74	-11.26	40	48.01	11.59	0.64	31.5	-	-	Peak
197.94	23.02	-20.48	43.5	44.11	9.09	1.31	31.49	-	-	Peak
285.69	22.81	-23.19	46	39.23	13.24	1.67	31.33	-	-	Peak
341.3	29.92	-16.08	46	44.57	14.75	1.9	31.3	-	-	Peak
399.4	35.53	-10.47	46	48.01	16.56	2.14	31.18	101	225	Peak
799.8	30.04	-15.96	46	35.11	22.47	3.14	30.68	-	-	Peak
2388.66	53.03	-20.97	74	48.67	32.18	6.03	33.85	131	238	Peak
2388.66	38.2	-15.8	54	33.84	32.18	6.03	33.85	131	238	Average
2402	108.2	-	-	103.84	32.18	6.03	33.85	131	238	Peak
2402	89.6	-	-	85.24	32.18	6.03	33.85	131	238	Average
2486	32.61	-21.39	54	28.05	32.28	6.18	33.9	131	238	Average
2486	49.55	-24.45	74	44.99	32.28	6.18	33.9	131	238	Peak



Test Mode :	Mode 1	Temperature :	23~24°C
Test Channel :	00	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Vertical
Remark :	2402 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.97	30.48	-9.52	40	45.59	15.8	0.56	31.47	100	360	Peak
61.05	25.93	-14.07	40	50.97	5.73	0.77	31.54	-	-	Peak
186.06	24.71	-18.79	43.5	45.9	9.06	1.27	31.52	-	-	Peak
570.9	22.31	-23.69	46	31.33	19.32	2.61	30.95	-	-	Peak
685.7	27.3	-18.7	46	34.49	20.73	2.91	30.83	-	-	Peak
819.4	25.09	-20.91	46	29.9	22.7	3.19	30.7	-	-	Peak
2387.9	49.51	-24.49	74	45.15	32.18	6.03	33.85	104	276	Peak
2387.9	35.78	-18.22	54	31.42	32.18	6.03	33.85	104	276	Average
2402	104.37	-	-	100.01	32.18	6.03	33.85	104	276	Peak
2402	86.24	-	-	81.88	32.18	6.03	33.85	104	276	Average
2500	32.63	-21.37	54	28.05	32.3	6.18	33.9	104	276	Average
2500	45.73	-28.27	74	41.15	32.3	6.18	33.9	104	276	Peak



Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	39	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Horizontal
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
61.86	19.16	-20.84	40	44.13	5.79	0.78	31.54	-	-	Peak
186.06	18.8	-24.7	43.5	39.99	9.06	1.27	31.52	-	-	Peak
258.42	20.54	-25.46	46	37.59	12.79	1.58	31.42	-	-	Peak
399.4	35.24	-10.76	46	47.72	16.56	2.14	31.18	114	100	Peak
685.7	24.47	-21.53	46	31.66	20.73	2.91	30.83	-	-	Peak
799.8	31.44	-14.56	46	36.51	22.47	3.14	30.68	-	-	Peak
2390	48.8	-25.2	74	44.44	32.18	6.03	33.85	129	239	Peak
2390	32.26	-21.74	54	27.9	32.18	6.03	33.85	129	239	Average
2441	109.4	-	-	104.93	32.24	6.11	33.88	129	239	Peak
2441	90.49	-	-	86.02	32.24	6.11	33.88	129	239	Average
2486	49.94	-24.06	74	45.38	32.28	6.18	33.9	129	239	Peak
2486	33.5	-20.5	54	28.94	32.28	6.18	33.9	129	239	Average



Test Mode :	Mode 2	Temperature :	23~24°C
Test Channel :	39	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Vertical
Remark :	2441 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.7	29.04	-10.96	40	44.15	15.8	0.56	31.47	100	240	Peak
42.69	27.54	-12.46	40	46.81	11.59	0.64	31.5	-	-	Peak
198.21	27.08	-16.42	43.5	48.17	9.09	1.31	31.49	-	-	Peak
318.2	26.08	-19.92	46	41.56	14.03	1.81	31.32	-	-	Peak
341.3	24.54	-21.46	46	39.19	14.75	1.9	31.3	-	-	Peak
923.7	25.44	-20.56	46	28.76	23.92	3.4	30.64	-	-	Peak
2380	44.87	-29.13	74	40.53	32.16	6.03	33.85	103	275	Peak
2380	32.17	-21.83	54	27.83	32.16	6.03	33.85	103	275	Average
2441	105.91	-	-	101.44	32.24	6.11	33.88	103	275	Peak
2441	87.73	-	-	83.26	32.24	6.11	33.88	103	275	Average
2500	46.22	-27.78	74	41.64	32.3	6.18	33.9	103	275	Peak
2500	32.68	-21.32	54	28.1	32.3	6.18	33.9	103	275	Average



Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Horizontal
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
61.05	17.19	-22.81	40	42.23	5.73	0.77	31.54	-	-	Peak
197.94	22.89	-20.61	43.5	43.98	9.09	1.31	31.49	-	-	Peak
258.42	20.67	-25.33	46	37.72	12.79	1.58	31.42	-	-	Peak
341.3	28.57	-17.43	46	43.22	14.75	1.9	31.3	-	-	Peak
399.4	34.84	-11.16	46	47.32	16.56	2.14	31.18	100	177	Peak
799.8	30.07	-15.93	46	35.14	22.47	3.14	30.68	-	-	Peak
2380	46.4	-27.6	74	42.06	32.16	6.03	33.85	124	240	Peak
2380	32.04	-21.96	54	27.7	32.16	6.03	33.85	124	240	Average
2480	109.25	-	-	104.69	32.28	6.18	33.9	124	240	Peak
2480	90.8	-	-	86.24	32.28	6.18	33.9	124	240	Average
2483.5	54.47	-19.53	74	49.91	32.28	6.18	33.9	124	240	Peak
2483.5	35.79	-18.21	54	31.23	32.28	6.18	33.9	124	240	Average



Test Mode :	Mode 3	Temperature :	23~24°C
Test Channel :	78	Relative Humidity :	49~50%
Test Engineer :	Ivan Chiang	Polarization :	Vertical
Remark :	2480 MHz is Fundamental Signals which can be ignored.		

Frequency (MHz)	Level (dBuV/m)	Over Limit (dB)	Limit Line (dBuV/m)	Read Level (dBuV)	Antenna Factor (dB)	Cable Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Remark
32.7	30.13	-9.87	40	45.24	15.8	0.56	31.47	106	77	Peak
62.13	26.37	-13.63	40	51.34	5.79	0.78	31.54	-	-	Peak
197.94	24.45	-19.05	43.5	45.54	9.09	1.31	31.49	-	-	Peak
456.1	22.72	-23.28	46	34.01	17.49	2.31	31.09	-	-	Peak
685.7	26.72	-19.28	46	33.91	20.73	2.91	30.83	-	-	Peak
845.3	24.09	-21.91	46	28.56	23	3.26	30.73	-	-	Peak
2316	44.46	-29.54	74	40.29	32.07	5.92	33.82	100	276	Peak
2316	32.32	-21.68	54	28.15	32.07	5.92	33.82	100	276	Average
2480	105.55	-	-	100.99	32.28	6.18	33.9	100	276	Peak
2480	87.54	-	-	82.98	32.28	6.18	33.9	100	276	Average
2483.5	50.46	-23.54	74	45.9	32.28	6.18	33.9	100	276	Peak
2483.5	32.14	-21.86	54	27.58	32.28	6.18	33.9	100	276	Average



3.10 Antenna Requirements

3.10.1 Standard Applicable

If directional gain of transmitting antennas is greater than 6dBi, the power shall be reduced by the same level in dB comparing to gain minus 6dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

3.10.2 Antenna Connected Construction

The antennas type used in this product is PIFA Antenna without connector and it is considered to meet antenna requirement.

3.10.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

4 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Due Date	Remark
System Simulator	R&S	CMU200	117995	N/A	Mar. 19, 2009	Mar. 18, 2011	Conducted (TH02-HY)
Spectrum Analyzer	R&S	FSP30	101329	9kHz~30GHz	Apr. 26, 2010	Apr. 25, 2011	Conducted (TH02-HY)
Power Meter	Anritsu	ML2495A	0932001	N/A	Sep. 13, 2010	Sep. 12, 2011	Conducted (TH02-HY)
Power Sensor	Anritsu	MA2411B	0846202	N/A	Sep. 14, 2010	Sep. 13, 2011	Conducted (TH02-HY)
Thermal Chamber	Ten Billion	TTH-D35P	TBN-9307 01	N/A	Jul. 30,2010	Jul. 29, 2011	Conducted (TH02-HY)
EMI Test Receive	R&S	ESCS 30	100356	9KHz – 2.75GHz	Aug. 16, 2010	Aug. 15, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100081	9KHz – 30MHz	Dec. 03, 2010	Dec. 02, 2011	Conduction (CO05-HY)
Two-LISN	R&S	ENV216	11-100080	9KHz – 30MHz	Dec. 01, 2010	Nov. 30, 2011	Conduction (CO05-HY)
AC Power Source	APC	APC-1000W	N/A	N/A	N/A	N/A	Conduction (CO05-HY)
Bilog Antenna	SCHAFFNER	CBL6111C	2726	30MHz ~ 1GHz	Oct. 31, 2010	Oct. 30, 2011	Radiation (03CH07-HY)
Spectrum Analyzer	R&S	FSP	101067	9KHz ~ 30GHz	Dec. 03, 2010	Dec. 02, 2011	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 19, 2010	Aug. 18, 2011	Radiation (03CH07-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA9170 251	15GHz- 40GHz	Oct. 18, 2010	Oct. 17, 2011	Radiation (03CH07-HY)
Pre Amplifier	Agilent	8449B	3008A023 62	1GHz~ 26.5GHz	Dec. 06, 2010	Dec. 05, 2011	Radiation (03CH07-HY)
Pre Amplifier	COM-POWER	PA-103A	161241	10-1000MHz.32 dB.GAIN	Mar. 27, 2010	Mar. 26, 2011	Radiation (03CH07-HY)
Loop Antenna	R&S	HFH2-Z2	860004/00 1	9 kHz~30 MHz	Jul. 29, 2010	Jul. 28, 2011	Radiation (03CH07-HY)
Bluetooth Base Station	R&S	CBT32	100519	N/A	May 12, 2009	May 11, 2011	Radiation (03CH07-HY)

5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.10	Normal (k=2)	0.05
Cable Loss	0.10	Normal (k=2)	0.05
AMN Insertion Loss	2.50	Rectangular	0.63
Receiver Specification	1.50	Rectangular	0.43
Site Imperfection	1.39	Rectangular	0.80
Mismatch	+0.34 / -0.35	U-Shape	0.24
Combined Standard Uncertainty $U_c(y)$	1.13		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.26		

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Contribution	Uncertainty of X_i		$u(X_i)$
	dB	Probability Distribution	
Receiver Reading	0.41	Normal (k=2)	0.21
Antenna Factor Calibration	0.83	Normal (k=2)	0.42
Cable Loss Calibration	0.25	Normal (k=2)	0.13
Pre-Amplifier Gain Calibration	0.27	Normal (k=2)	0.14
RCV/SPA Specification	2.50	Rectangular	0.72
Antenna Factor Interpolation for Frequency	1.00	Rectangular	0.29
Site Imperfection	1.43	Rectangular	0.83
Mismatch	+0.39 / -0.41	U-Shape	0.28
Combined Standard Uncertainty $U_c(y)$	1.27		
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.54		



Uncertainty of Radiated Emission Measurement (1 GHz ~ 40 GHz)

Contribution	Uncertainty of X_i		$u(X_i)$	C_i	$C_i * u(X_i)$
	dB	Probability Distribution			
Receiver Reading	±0.10	Normal (k=2)	0.10	1	0.10
Antenna Factor Calibration	±1.70	Normal (k=2)	0.85	1	0.85
Cable Loss Calibration	±0.50	Normal (k=2)	0.25	1	0.25
Receiver Correction	±2.00	Rectangular	1.15	1	1.15
Antenna Factor Directional	±1.50	Rectangular	0.87	1	0.87
Site Imperfection	±2.80	Triangular	1.14	1	1.14
Mismatch Receiver VSWR $\Gamma_1 = 0.197$ Antenna VSWR $\Gamma_2 = 0.194$ Uncertainty = $20\text{Log}(1-\Gamma_1*\Gamma_2)$	+0.34 / -0.35	U-Shape	0.244	1	0.244
Combined Standard Uncertainty $U_c(y)$	2.36				
Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.72				



Appendix A. Photographs of EUT

Please refer to Sporton report number EP112908 as below.