

We, Acer Incorporated, attest that this device under FCC ID HLZW6 complies with device protocol requirements and operational restrictions. This device's transmit power spectral density is in accordance with the rules for low power indoor access points.

Indoor Access Point (6ID):

- Protocol attestation statement:
  - Contention-based protocol, as demonstrated in the test report, is permanently embedded in the chip (MT7916) and is not host dependent.
  - b. An 11ax IEEE AP's Transmit Power Envelope element has information fields for power limits for connecting client/subordinate devices. The TPE information is embedded in this device's signals and used to tell the connecting clients/subordinate that the max TX powers it is allowed to transmit. There is a regulatory info field in this device's beacon and probe response frames which details this device type when the client/subordinate associates to this device.
- Statement acknowledging device restrictions:
  - a. Low-power indoor Access Point. Access Point operating in the 5.925-7.125 GHz band shall be supplied power from a wired connection, has an integrated antenna, is not battery-powered, and does not have a weatherized enclosure.
  - b. This device's operation will not be allowed on oil platforms, cars, trains, boats, and aircraft, except that operation of this device is permitted in large aircraft while flying above 10,000 feet.
  - c. Indoor access points are prohibited for control of or communications with unmanned aircraft systems, including drones.

RU Jan

Acer Incorporated Tel:886-28691-3289

E-Mail: ru.jan@acer.com

113-