

|  |   |  |   |   |
|--|---|--|---|---|
| <b>Prüfbericht-Nr.:</b><br><i>Test report no.:</i>   | CN24D9D9 001  | <b>Auftrags-Nr.:</b><br><i>Order no.:</i>                  | 48226341  | Seite 1 von 12<br>Page 1 of 12            |
| <b>Kunden-Referenz-Nr.:</b><br><i>Client reference no.:</i>  | N/A   | <b>Auftragsdatum:</b><br><i>Order date:</i>                | 2023-11-21                                      |   |
| <b>Auftraggeber:</b><br><i>Client:</i>   | Acer Incorporated<br>8F, 88, Sec. 1, Xintai 5th Rd. Xizhi, New Taipei City 221 Taiwan |  |   |   |
| <b>Prüfgegenstand:</b><br><i>Test item:</i>  | PREDATOR Connect W6x Wi-Fi 6 Router   |  |   |   |
| <b>Bezeichnung / Typ-Nr.:</b><br><i>Identification / Type no.:</i>   | W6x   |  |   |   |
| <b>Auftrags-Inhalt:</b><br><i>Order content:</i>   | FCC Certification   |  |   |   |
| <b>Prüfgrundlage:</b><br><i>Test specification:</i>  | IEEE Std C95.1<br>47 CFR §2.1091<br>47 CFR §1.1310<br>KDB 447498 D04                  |  |   |   |
| <b>Wareneingangsdatum:</b><br><i>Date of sample receipt:</i>   | 2024-03-18  |  |   |   |
| <b>Prüfmuster-Nr.:</b><br><i>Test sample no.:</i>  | A003677464-003  |  |   |   |
| <b>Prüfzeitraum:</b><br><i>Testing period:</i>   | 2024-03-27 - 2024-05-06   |  |   |   |
| <b>Ort der Prüfung:</b><br><i>Place of testing:</i>  | EMC/RF Taipei Testing Site  |  |   |   |
| <b>Prüflaboratorium:</b><br><i>Testing laboratory:</i>   | Taipei Testing Laboratories   |  |   |   |
| <b>Prüfergebnis*:</b><br><i>Test result*:</i>  | Pass  |  |   |   |
| <b>überprüft von:</b><br><i>compiled by:</i>   | <br>Allen Yu<br>Section Manager   |  | <b>genehmigt von:</b><br><i>authorized by:</i>  | <br>Brenda Chen<br>Senior Project Manager |
| <b>Datum:</b><br><i>Date:</i>  | 2024-05-20  |  | <b>Ausstellungsdatum:</b><br><i>Issue date:</i> | 2024-05-20                                |
| <b>Stellung / Position:</b>  |   |  | <b>Stellung / Position:</b>                     |   |
| <b>Sonstiges / Other:</b>  |   |  |   |   |
| <b>Zustand des Prüfgegenstandes bei Anlieferung:</b><br><i>Condition of the test item at delivery:</i>   | Prüfmuster vollständig und unbeschädigt<br><i>Test item complete and undamaged</i>    |  |   |   |
| * Legende:   | 1 = sehr gut<br>P(ass) = entspricht o.g. Prüfgrundlage(n)                             | 2 = gut<br>F(ail) = entspricht nicht o.g. Prüfgrundlage(n) | 3 = befriedigend<br>N/A = nicht anwendbar       | 4 = ausreichend<br>N/T = nicht getestet   |
| * Legend:  | 1 = very good<br>P(ass) = passed a.m. test specification(s)                           | 2 = good<br>F(ail) = failed a.m. test specification(s)     | 3 = satisfactory<br>N/A = not applicable        | 4 = sufficient<br>N/T = not tested        |
| <b>Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.</b><br><i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i> |   |  |   |   |

Prüfbericht-Nr.: CN24D9D9 001  
Test report no.:

Seite 2 von 12  
Page 2 of 12

**Anmerkungen**  
Remarks

|   |  |
|---|--|
| 1 | <p>Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben.<br/>Detaillierte Informationen bezüglich Prüfkonditionen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden.</p> <p><i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i></p>   |
| 2 | <p>Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: <a href="http://go.tuv.com/digital-signature">go.tuv.com/digital-signature</a></p> <p><i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: <a href="http://go.tuv.com/digital-signature">go.tuv.com/digital-signature</a></i></p> |
| 3 | <p>Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben.<br/>Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt.</p> <p><i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.<br/>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i></p>  |
| 4 | <p>Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2021, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019.</p> <p><i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2021, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i></p>   |

## Contents

|  |           |
|--|-----------|
| <b>HISTORY OF THIS TEST REPORT .....</b>                 | <b>4</b>  |
| <b>1 GENERAL REMARKS .....</b>                           | <b>5</b>  |
| <b>1.1 COMPLEMENTARY MATERIALS.....</b>                  | <b>5</b>  |
| <b>1.2 DECISION RULE OF CONFORMITY .....</b>             | <b>5</b>  |
| <b>2 TEST SITES .....</b>                                | <b>6</b>  |
| <b>2.1 TEST LABORATORY .....</b>                         | <b>6</b>  |
| <b>2.2 TEST FACILITY.....</b>                            | <b>6</b>  |
| <b>3 GENERAL PRODUCT INFORMATION.....</b>                | <b>7</b>  |
| <b>3.1 PRODUCT FUNCTION AND INTENDED USE .....</b>       | <b>7</b>  |
| <b>3.2 RATINGS AND SYSTEM DETAILS.....</b>               | <b>7</b>  |
| <b>4 MAXIMUM PERMISSIBLE EXPOSURE EVALUATION.....</b>    | <b>9</b>  |
| <b>4.1 INTRODUCTION .....</b>                            | <b>9</b>  |
| <b>4.2 REFERENCE LEVELS .....</b>                        | <b>9</b>  |
| <b>4.3 CLASSIFICATION OF THE ASSESSMENT METHODS.....</b> | <b>11</b> |
| <b>5 TEST RESULTS .....</b>                              | <b>12</b> |
| <b>5.1 MPE-BASED EXEMPTION.....</b>                      | <b>12</b> |

### APPENDIX EP - PHOTOGRAPHS OF EUT

Prüfbericht - Nr.: **CN24D9D9 001**  
Test Report No.

Seite 4 von 12  
Page 4 of 12

## HISTORY OF THIS TEST REPORT

| Revision | Description      | Date Issued |
|----------|------------------|-------------|
| R01      | Original Release | 2024-05-20  |

Prüfbericht - Nr.: **CN24D9D9 001**  
Test Report No.Seite 5 von 12  
Page 5 of 12

# 1 General Remarks

## 1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:  
**Appendix EP - Photographs of EUT**

## 1.2 Decision Rule of Conformity

The decision rule of conformity of this test report is following the requirements of the requested standard in the quotation, and agreed among testing laboratory and manufacturer (applicant) to exclude the consideration of Measurement Uncertainty, unless it is required by the specific standard.

## 2 Test Sites

### 2.1 Test Laboratory

Taipei Testing Laboratories

11F. No.758, Sec. 4, Bade Rd., Songshan Dist.  
Taipei City 105  
Taiwan (R.O.C.)

### 2.2 Test Facility

Taipei Testing Laboratories

No.458-18, Sec. 2, Fenliao Rd., Linkou Dist.,  
New Taipei City 244  
Taiwan (R.O.C.)  
FCC Registration No.: 180491  
ISED Registration No.: 25563

**Prüfbericht - Nr.: CN24D9D9 001**  
*Test Report No.*

 Seite 7 von 12  
 Page 7 of 12

### 3 General Product Information

#### 3.1 Product Function and Intended Use

The EUT is PREDATOR Connect W6x Wi-Fi 6 Router. It contains Bluetooth compatible chip enabling the user to communicate data through Bluetooth interface.  
 For details refer to the User Guide, Data Sheet and Circuit Diagram.

#### 3.2 Ratings and System Details

##### Basic Information of EUT

| Item                        | EUT Information                     |
|-----------------------------|-------------------------------------|
| Kind of Equipment/Test Item | PREDATOR Connect W6x Wi-Fi 6 Router |
| Type Identification         | W6x                                 |
| FCC ID                      | HLZW6X                              |

##### Technical Specification of EUT

| Item                      | EUT Information  |
|---------------------------|--|
| Operating Frequency       | WiFi 2.4GHz: 2412 MHz ~ 2462 MHz<br>WiFi 5GHz:<br>Band 1: 5180 MHz ~ 5240 MHz<br>Band 2: 5260 MHz ~ 5320 MHz<br>Band 3: 5500 MHz ~ 5700 MHz<br>Band 4: 5745 MHz ~ 5825 MHz |
| Modulation                | DSSS (DBPSK, DQPSK, CCK)<br>OFDM (BPSK, QPSK, 16QAM, 64QAM, 256QAM)<br>OFDMA (1024QAM)   |
| Operation Voltage         | Adapter input 100-240 Vac, output 12 Vdc   |
| Extreme Temperature Range | 0 ~ 40 °C  |
| Antenna Information       | Refer to note as below   |

Note: The antenna list is as below.

| ANT           | Gain (dBi)             |       |       |       |       | Type   |   |
|---------------|------------------------|-------|-------|-------|-------|--------|---|
|               | 2.4GHz                 | 5GHz  |       |       |       |        |   |
|               |                        | B1    | B2    | B3    | B4    |        |   |
| 1             | 3.49                   | 4.74  | 4.34  | 4.48  | 4.54  | Dipole |   |
| 2             | 3.46                   | 4.69  | 4.41  | 4.58  | 4.66  | Dipole |   |
| 3             | 5.38                   | -     | -     | -     | -     | Dipole |   |
| 4             | 5.24                   | -     | -     | -     | -     | Dipole |   |
| 5             | -                      | 4.69  | 4.41  | 4.58  | 4.66  | Dipole |   |
| 6             | -                      | 4.74  | 4.34  | 4.48  | 4.54  | Dipole |   |
| Max Peak Gain |                        | 5.38  | 4.74  | 4.41  | 4.58  | 4.66   | - |
| CDD           | Power Directional Gain | 5.38  | 4.74  | 4.41  | 4.58  | 4.66   | - |
|               | PSD Directional Gain   | 10.46 | 10.74 | 10.40 | 10.55 | 10.62  | - |
| BFM           | Power Directional Gain | 10.46 | 10.74 | 10.40 | 10.55 | 10.62  | - |
|               | PSD Directional Gain   | 10.46 | 10.74 | 10.40 | 10.55 | 10.62  | - |

 Note: PSD Directional Gain =  $10\log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$



## 4 Maximum Permissible Exposure Evaluation

### 4.1 Introduction

This Standard specifies requirements for, and provides guidance on, assessing compliance with the exposure limits of radiofrequency (RF) safety standards such as IEEE Std C95.1. This includes methodologies for making an assessment (by measurement or computation) of human exposure to ambient RF fields and induced body currents in the frequency range of 0 kHz to 300 GHz.

This Standard may also be used as a guide for making low-level environmental exposure assessments in areas around RF sources listed above, as well as other sources such as Wi-Fi devices.

### 4.2 Reference Levels

Where appropriate, the reference levels are derived from the basic restrictions by mathematical modelling and by extrapolation from the results of laboratory investigations at specific frequencies. They are given for the condition of maximum coupling of the field to the exposed individual, thereby providing maximum protection.

According to FCC 1.1310, the criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b).

The FCC MPE limits from 47 CFR §1.1310 are shown in the table below

| Frequency Range [MHz]                                   | Electric Field Strength [V/m] | Magnetic Field Strength [A/m] | Power Density [mW/cm <sup>2</sup> ] | Average Time [minutes] |
|---|-------------------------------|-------------------------------|-------------------------------------|------------------------|
| (A) Limits for Occupational/Controlled Exposure         |                               |                               |                                     |                        |
| 0.3 – 3.0   | 614                           | 1.63                          | *100                                | 6                      |
| 3.0 – 30  | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                      |
| 30 – 300  | 61.4                          | 0.163                         | 1.0                                 | 6                      |
| 300 – 1500  |                               |                               | f/300                               | 6                      |
| 1500 – 100000   |                               |                               | 5                                   | 6                      |
| (B) Limits for General Population/Uncontrolled Exposure |                               |                               |                                     |                        |
| 0.3 – 1.34  | 614                           | 1.63                          | *100                                | 30                     |
| 1.34 – 30   | 824/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                     |
| 30 – 300  | 27.5                          | 0.073                         | 0.2                                 | 30                     |
| 300 – 1500  |                               |                               | f/1500                              | 30                     |
| 1500 – 100000   |                               |                               | 1.0                                 | 30                     |

NOTE –

- (1)  $f$  is the frequency in MHz.
- (2) Provided that basic restrictions are met and adverse indirect effects can be excluded, field strength values can be exceeded. For the specific case of occupational exposures at frequencies up to 100 kHz, the derived electric fields can be increased by a factor of 2 under conditions in which adverse indirect effects from contact with electrically charged conductors can be excluded.
- (3) For frequencies between 100 kHz and 10 GHz, the quantities  $S_{eq}$ ,  $E_2$  and  $H_2$  are averages over any 6 minutes.
- (4) For frequencies exceeding 10 GHz,  $S_{eq}$ , the quantities  $E_2$  and  $H_2$  are averages over any  $68/f$  1.05 minutes ( $f$  in GHz).

### 4.3 Classification of the Assessment Methods

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user for keeping at least 20cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

#### MPE Calculation Method according to KDB 447498 D04 Interim General RF Exposure Guidance v01

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 of § 1.1307(b)(1)(i)(C) to support an exemption from further evaluation from 300 kHz through 100 GHz.

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

**TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES  
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION**

| RF Source Frequency |   |           | Minimum Distance   |   |                    | Threshold ERP                        |
|---------------------|---|-----------|--------------------|---|--------------------|--------------------------------------|
| $f_L$ MHz           |   | $f_H$ MHz | $\lambda_L / 2\pi$ |   | $\lambda_H / 2\pi$ | W                                    |
| 0.3                 | – | 1.34      | 159 m              | – | 35.6 m             | 1,920 R <sup>2</sup>                 |
| 1.34                | – | 30        | 35.6 m             | – | 1.6 m              | 3,450 R <sup>2</sup> /f <sup>2</sup> |
| 30                  | – | 300       | 1.6 m              | – | 159 mm             | 3.83 R <sup>2</sup>                  |
| 300                 | – | 1,500     | 159 mm             | – | 31.8 mm            | 0.0128 R <sup>2</sup> f              |
| 1,500               | – | 100,000   | 31.8 mm            | – | 0.5 mm             | 19.2R <sup>2</sup>                   |

Subscripts L and H are low and high;  $\lambda$  is wavelength.  
 From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns.

## 5 Test Results

### 5.1 MPE-based Exemption

The Calculated at a distance of 45 cm are shown as below:

#### <CDD>

| Mode        | Frequency (MHz) | Average Output Power (dBm) | Average Output Power (mW) | Tune-up Power (dBm) | Tune-up Power (dBm) | Antenna Gain (dBi) | ERP (mW) | ERP Limit (mW) | Pass / Fail |
|-------------|-----------------|----------------------------|---------------------------|---------------------|---------------------|--------------------|----------|----------------|-------------|
| WiFi 2.4GHz | 2437            | 29.74                      | 942.43                    | 30.00               | 1000.00             | 5.38               | 2103.78  | 3888           | Pass        |
| WiFi 5GHz   | 5745            | 29.97                      | 993.27                    | 30.00               | 1000.00             | 4.66               | 1782.38  | 3888           | Pass        |

#### <Beamforming>

| Mode        | Frequency (MHz) | Average Output Power (dBm) | Average Output Power (mW) | Tune-up Power (dBm) | Tune-up Power (dBm) | Antenna Gain (dBi) | ERP (mW) | ERP Limit (mW) | Pass / Fail |
|-------------|-----------------|----------------------------|---------------------------|---------------------|---------------------|--------------------|----------|----------------|-------------|
| WiFi 2.4GHz | 2437            | 23.33                      | 215.05                    | 23.50               | 223.87              | 10.46              | 1517.05  | 3888           | Pass        |
| WiFi 5GHz   | 5745            | 23.95                      | 248.35                    | 24.00               | 251.19              | 10.62              | 1766.04  | 3888           | Pass        |

#### Conclusion

The device complies with the FCC exposure requirements since the maximum transmitter power density is below the FCC limit.

Either SAR-based or MPE-based exemption may be considered for test exemption for fixed, mobile, or portable device exposure conditions; therefore, the contributions from each exemption in conjunction with the measured SAR shall be used to determine exemption for simultaneous transmission according to Formula repeated from § 1.1307(b)(3)(ii)(B)

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure Limit_k} \leq 1$$

$$\text{WiFi 2.4GHz} + \text{WiFi 5GHz} = 2103.78 / 3888 + 1782.38 / 3888 = 0.9995$$

**Therefore the maximum calculations of above situations are less than the "1" limit.**