

**4.0 System setup including cable interconnection details, support equipment and simplified block diagram. (System Setup)****Method:**

Record the details of EUTcabling, document the support equipment, and show the interconnections in a block diagram.

**Photo:**

Setup photograph

## 7.0 Duty Cycle Determination (FCC 15A - 15.35(c))

### Method:

(c) Unless otherwise specified, e.g. §15.255(b), when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value. The exact method of calculating the average field strength shall be submitted with any application for certification or shall be retained in the measurement data file for equipment subject to notification or verification.

Determine the period of the pulse train, T, in mSec and record the results. T is defined as the time from the beginning of one pulse train to the beginning of the next pulse train.

Count the number of different types of pulses, N and record the results.

For each of the different types of pulses, count the number of occurrences within one pulse train.

Use the Duty Cycle Correction Factor, DCCF, from the results table and use it to adjust the field strength measurements recorded for radiated emissions.

**Results: The sample tested was found to Comply.**

### Photo:



Test set up

## 8.0 Radiated Emissions (FCC 15C - 15.231(b))


### Photo:



Test set up front

## 8.0 Radiated Emissions (FCC 15C - 15.231(b))

**Photo:**



Test set up rear