

Ameritron Engineering  
371 Dean Rd. Barnesville, GA 30204  
Ph 770-358-3335  
Cell 770-596-3514  
Email W8JI@W8JI.com

June 15, 2016  
Attestation Statement  
FCC ID: HO82WUALS606

This certification is for production quantities of an amateur radio service linear amplifier. Maximum power permitted by FCC rules is 1500 watts PEP on all modes licensed for the Amateur Radio service under part 97. This amplifier has a 600-watt PEP maximum power output rating.

Ameritron of Starkville, MS 39759 will be the sole manufacturer of this product. Ameriton is a division of MFJ Enterprises, Inc. MFJ Enterprises is also located in Starkville, MS at 300 Industrial Park Road.

This amplifier meets or exceeds all current requirements of CFR 47 part 97.317 as of this filing:

**§ 97.317 Standards for certification of external RF power amplifiers.**

**(a) To receive a grant of certification, the amplifier must:**

- (1) Satisfy the spurious emission standards of § 97.307 (d) or (e) of this part, as applicable, when the amplifier is operated at the lesser of 1.5 kW PEP or its full output power and when the amplifier is placed in the “standby” or “off” positions while connected to the transmitter.**
- (2) Not be capable of amplifying the input RF power (driving signal) by more than 15 dB gain. Gain is defined as the ratio of the input RF power to the output RF power of the amplifier where both power measurements are expressed in peak envelope power or mean power.**
- (3) Exhibit no amplification (0 dB gain) between 26 MHz and 28 MHz.**

**(b) Certification shall be denied when:**

- (1) The Commission determines the amplifier can be used in services other than the Amateur Radio Service, or**
- (2) The amplifier can be easily modified to operate on frequencies between 26 MHz and 28 MHz.**

**[71 FR 66465, Nov. 15, 2006]**

Section 97.317 (a) (1) This amplifier suppresses spurious and harmonic emissions below levels in 97.307 (d) and (e), both at full rated output of 600 watts PEP and at any power level below full rated output. In addition, when on standby, this amplifier is directly bypassed by a mechanical relay. Since non-linear devices of any kind are not present, it does not alter any signal applied to or passing through radio frequency ports in a bypass mode.

Section 97.317 (a) (2) This amplifier has less than 15 dB gain on all frequencies.

Section 97.317 (a) (3) This amplifier is non-functional as a power amplifier between 25 MHz and 28 MHz. Application of any RF level suitable for communication between 25 and 28 MHz automatically forces this amplifier into lockout, where gain reverts to 0 dB.

Section 97.317 (b) (1) and (2) Because the lockout feature is permanently embedded in the control PIC, the out-of-band lockout feature cannot be removed. There are no jumpers, diodes, or programming steps to defeat the lockout. If the control board is removed or disabled, the amplifier will stop functioning.

This amplifier meets all sections of 97.307 Emission Standards applicable to external RF power amplifiers, as of April 15, 2013:

#### **§ 97.307 Emission standards.**

**(d) For transmitters installed after January 1, 2003, the mean power of any spurious emission from a station transmitter or *external RF power amplifier* transmitting on a frequency below 30 MHz must be at least 43 dB below the mean power of the fundamental emission. For transmitters installed on or before January 1, 2003, the mean power of any spurious emission from a station transmitter or *external RF power amplifier* transmitting on a frequency below 30 MHz must not exceed 50 mW and must be at least 40 dB below the mean power of the fundamental emission. For a transmitter of mean power less than 5 W installed on or before January 1, 2003, the attenuation must be at least 30 dB. A transmitter built before April 15, 1977, or first marketed before January 1, 1978, is exempt from this requirement.**

**(e) The mean power of any spurious emission from a station transmitter or *external RF power amplifier* transmitting on a frequency between 30-225 MHz must be at least 60 dB below the mean power of the fundamental. For a transmitter having a mean power of 25 W or less, the mean power of any spurious emission supplied to the antenna transmission line must not exceed 25  $\mu$ W and must be at least 40 dB below the mean power of the fundamental emission, but need not be reduced below the power of 10  $\mu$ W. A transmitter built before April 15, 1977, or first marketed before January 1, 1978, is exempt from this requirement.**

97.307d specifies harmonic and spurious levels at least 43 dB below fundamental for devices installed after January 1, 2003 when operating below 30 MHz.

97.307e specifies harmonic and spurious levels at least 60 dB below fundamental for operation between 30 MHz and 225 MHz.

This amplifier meets all 97.307 requirements.

A handwritten signature in black ink, appearing to read "Charles T. Rauch".

Charles T. Rauch  
Engineer Ameritron  
6/15/2016