

FCC ID: HOLCL9HS

The following Data is for the Peak to Average requirements of FCC 15.35(b).

EMIU9544A		Handset								
Freq	Pol	Raw (dBuV)	Ant (dB/m)	Cbl (dB)	d (m)	d corr (m)	PreAmp (dB)	Corr (dBuV)	Limits (dBuV)	
1829	H	40.58	25.5		3.1	1	-9.54	34.5	25.14	1
1829	V	68.32	26.6		3.1	1	-9.54	34.5	53.98	1
1829	H	38.25	25.5		3.1	1	-9.54	34.5	22.81	
1829	V	64.73	26.6		3.1	1	-9.54	34.5	50.39	
2743	H	45.82	29.1		4.2	1	-9.54	34.5	35.08	
2743	V	66.41	29.3		4.2	1	-9.54	34.5	55.87	
2743	H	42.73	29.1		4.2	1	-9.54	34.5	31.99	
2743	V	64.15	29.3		4.2	1	-9.54	34.5	53.61	

The above limit is based on the fundamental measurement below:

EMIU9544A	Handset							
Freq	Pol	Raw	Ant	Cbl	d	Corr	Limits	Comments
MHz		(dBuV)	(dB/m)	(dB)	(m)	(dBuV)	(dBuV)	
904.42	V	85.4	23.45	2.77	0	111.62	131	

RBW=3 MHz, VBW = 3 MHz

New spurious limit for non-restricted band measurements:

111.62 - 20dB = 91.62 dBuV

The operating frequency range for this device, from center of lowest channel to the center of the highest channel is:

Channel 1 904.2 MHz

Channel 20 925.8 MHz