

# FCC TEST REPORT

for

47 CFR, Part 15, Subpart C

Equipment : RF Keyboard

Model No. : Kx-yy01/02/10/16/20/30/50/81/82/18/28/38/58;  
(x=F,O,Y; yy=00~99)

FCC ID : HQKKMEKFYY01

Filing Type : Certification

Applicant : Key Mouse Electronic Enterprise Co., Ltd.  
Rm. No. 602, 6F-8, No. 3, Wu-Chuan 1<sup>st</sup> Rd., Hsin-Chuang City,  
Taipei, Taiwan, R.O.C..

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

## ***SPORTON International Inc.***

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

---

## Table of Contents

History of this test report.....	ii
<b>CERTIFICATE OF COMPLIANCE.....</b>	<b>1</b>
<b>1. General Description of Equipment under Test.....</b>	<b>2</b>
1.1. Applicant.....	2
1.2. Manufacturer .....	2
1.3. Basic Description of Equipment under Test .....	2
1.4. Feature of Equipment under Test .....	3
<b>2. Test Configuration of Equipment under Test .....</b>	<b>4</b>
2.1. Test Manner .....	4
2.2. Description of Test System .....	4
2.3. Connection Diagram of Test System .....	5
2.4. Band edge compliance plot per 15.227(b). .....	6
<b>3. Test Software .....</b>	<b>8</b>
<b>4. General Information of Test.....</b>	<b>9</b>
4.1. Test Facility .....	9
4.2. Test Voltage .....	9
4.3. Standard for Methods of Measurement.....	9
4.4. Frequency Range Investigated .....	9
4.5. Frequency Range Investigated .....	9
4.6. Test Distance .....	9
<b>5. Test of Conducted Powerline .....</b>	<b>10</b>
<b>6. Test of Radiated Emission.....</b>	<b>11</b>
6.1. Major Measuring Instruments.....	11
6.2. Test Procedures.....	12
6.3. Typical Test Setup Layout of Radiated Emission.....	13
6.4. Test Result of Radiated Emission .....	14
<b>7. EMI Suppression Component List.....</b>	<b>19</b>
<b>8. Antenna Factor &amp; Cable Loss .....</b>	<b>20</b>
<b>9. List of Measuring Equipments Used .....</b>	<b>21</b>
<b>10. Uncertainty of Test Site .....</b>	<b>22</b>
<b>Appendix A. Photographs of EUT.....</b>	<b>A1 ~ A5</b>
<b>Appendix B. Photographs of Setup.....</b>	<b>B1 ~ B2</b>

**History of this test report**

Original Report Issue Date: Dec. 25, 2003

- No additional attachment.
- Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

# CERTIFICATE OF COMPLIANCE

for

## 47 CFR, Part 15, Subpart C

Equipment : RF Keyboard

Model No. : Kx-yy01/02/10/16/20/30/50/81/82/18/28/38/58;  
(x=F,O,Y; yy=00~99)

FCC ID : HQKKMEKFYY01

Filing Type : Certification

Applicant : Key Mouse Electronic Enterprise Co., Ltd.  
Rm. No. 602, 6F-8, No. 3, Wu-Chuan 1<sup>st</sup> Rd., Hsin-Chuang City,  
Taipei, Taiwan, R.O.C..

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 2001** and the energy emitted by this equipment was **passed** all test items required in FCC Part 15 subpart C, relative to the equipment under test. Testing was carried out on Dec. 23, 2003 at **SPORTON International Inc. LAB.**



Alex Chen Jan. 06, 2004

Alex Chen  
Manager

**SPORTON International Inc.**

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

**1. General Description of Equipment under Test**

**1.1. Applicant**

Key Mouse Electronic Enterprise Co., Ltd.  
Rm. No. 602, 6F-8, No. 3, Wu-Chuan 1<sup>st</sup> Rd., Hsin-Chuang City, Taipei, Taiwan, R.O.C..

**1.2. Manufacturer**

Same as 1.1

**1.3. Basic Description of Equipment under Test**

Equipment : RF Keyboard  
Model No. : Kx-yy01/02/10/16/20/30/50/81/82/18/28/38/58; (x=F,O,Y; yy=00~99)  
FCC ID : HQKKMEKFYY01  
Trade Name : N/A  
Power Supply Type : From battery 4.5V  
AC Power Input : N/A

**1.4. Feature of Equipment under Test**

Product Feature & Specification				
1. Type of Modulation	FSK			
2. Number of Channels	1			
3. Frequency Band	27MHz			
4. Carrier Frequency of each channel	27.145 MHz			
5. Bandwidth of each channel	15KHz			
6. Maximum Output Power to Antenna	10mW			
7. IF & L.O. frequency	455KHz / 26.690MHz			
8. Type of Antenna Connector (Ex: SMA,TNC, MCX, MMCX, UFC.....etc)	None			
9. Antenna Type / Class and Gain	Loop Antenna/-20dBi			
10. Function Type	Transmitter	V	Transceiver	
11. Power Rating (DC/AC , Voltage)	4.5V			
12. Duty Cycle	None			
13. Basic function of product	Wireless Keyboard for PC			
14. Temperature Range (Operating)	0-45°C			
15. Humidity	40-80RH			
16. Other Special	None			

## **2. Test Configuration of Equipment under Test**

### **2.1. Test Manner**

- a. The EUT pursuant to ANSI C63.4-2001 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. The complete test system included EUT for EMI test.
- c. Frequency range investigated: radiation 25 MHz to 1000MHz.

### **2.2. Description of Test System**

The EUT was tested alone. No support unit was needed during the test.


**2.3. Connection Diagram of Test System**





2.4. Band edge compliance plot per 15.227(b).


<HORIZONTAL>



Conformation of the fundamental frequency

Frequency ( MHz )	Antenna Polarity	Cable Factor	Cable Loss	Reading ( dBuV )	Limits ( dBuV/m )	Emission ( uV/m )	Level ( dBuV/m )	Margin ( uV/m )	Margin ( dB )
26.960	H	14.84	0.86	12.00	80.00	10000.00	27.70	24.27	-52.30
27.140	H	14.81	0.87	38.16	80.00	10000.00	53.84	492.04	-26.16
27.280	H	14.80	0.87	16.24	80.00	10000.00	31.91	39.40	-48.09

<VERTICAL>



Conformation of the fundamental frequency

Frequency ( MHz )	Antenna Polarity	Cable Factor	Cable Loss	Reading ( dBuV )	Limits ( dBuV/m )	Emission ( uV/m )	Level ( dBuV/m )	Margin ( uV/m )	Margin ( dB )
26.960	V	14.84	0.86	9.10	69.50	2985.38	24.80	17.38	-44.70
27.140	V	14.81	0.87	31.87	80.00	10000.00	47.55	238.51	-32.45
27.280	V	14.80	0.87	12.87	69.50	2985.38	28.54	26.73	-40.96

### **3. Test Software**

The EUT kept transmitting signals at fixed frequency.

#### **4. General Information of Test**

##### **4.1. Test Facility**

Test Site Location : No. 52, Hwa Ya 1St Road, Hwa Ya Technology Park,  
Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.  
TEL : 886-3-3273456  
FAX : 886-3-3180055  
Test Site No. : 03CH03-HY

##### **4.2. Test Voltage**

DC 4.5V

##### **4.3. Standard for Methods of Measurement**

ANSI C63.4-2001

##### **4.4. Frequency Range Investigated**

FCC Part 15, Subpart C 15.227

##### **4.5. Frequency Range Investigated**

Radiation: from 25 MHz to 1000 MHz

##### **4.6. Test Distance**

The test distance of radiated emission from antenna to EUT is 3 M.

**5. Test of Conducted Powerline**

The power supply of the EUT is from Battery.

So Conducted Powerline test is not applicable to this equipment.

## 6. Test of Radiated Emission

Radiated emissions from 25 MHz to 1 GHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-2001. The EUT was placed on a nonmetallic stand, 0.8 meter above the ground plane, as shown in section 6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.


### 6.1. Major Measuring Instruments

- Amplifier (HP 8447D)
  - RF Gain 30 dB
  - Signal Input 100 KHz to 1.3 GHz
  
- Test Receiver (SCHAFFNER SCR3501)
  - Resolution Bandwidth 120 KHz
  - Frequency Band 9 K – 1 GHz
  - Quasi-Peak Detector ON for Quasi-Peak Mode  
OFF for Peak Mode

**6.2. Test Procedures**

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.

6.3. Typical Test Setup Layout of Radiated Emission






### 6.4. Test Result of Radiated Emission

- Test Distance: 3 M
- Temperature: 23°C
- Relative Humidity: 52 %
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Probe Factor + Cable Loss + Read Level - Preamp Factor = Level


■ The test was passed at the minimum margin that marked by the frame in the following test record



Site : 03CH03-HY  
 Condition : 3m BIC-9124--301 VERTICAL  
 EUT : RF Keyboard  
 Power : Battery


MEMO : Tx

	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
			dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	54.140	19.59	-20.41	40.00	35.80	10.19	1.59	27.99	Peak	105	354
2	62.470	18.62	-21.38	40.00	35.62	9.64	1.33	27.97	Peak	102	357
3	190.140	22.22	-21.28	43.50	32.98	14.57	2.39	27.72	Peak	105	354




Site : 03CH03-HY  
 Condition : 3m LOG-9111-221 VERTICAL  
 EUT : RF Keyboard  
 Power : Battery  
 MODEL : KF-3801  
 MEMO : Tx

	Freq	Level	Over Limit	Limit Line	Read Level	Probe Factor	Cable Loss	Preamp Factor	Remark	Ant Pos	Table Pos
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	352.000	33.27	-12.73	46.00	42.31	15.26	3.26	27.56	Peak	105	354
2	432.800	31.26	-14.74	46.00	39.50	16.25	3.60	28.09	Peak	105	358
3	650.400	31.99	-14.01	46.00	37.37	18.80	4.57	28.75	Peak	105	354



Site : 03CH03-HY  
 Condition : 3m BIC-9124--301 HORIZONTAL  
 EUT : RF Keyboard  
 Power : Battery  
 MODEL : KF-3801  
 MEMO : Tx

	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
			dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1	55.670	33.08	-6.92	40.00	49.23	10.26	1.58	27.99	Peak	104	359
2	63.830	25.22	-14.78	40.00	42.35	9.49	1.35	27.97	Peak	105	354
3	190.140	32.41	-11.09	43.50	43.17	14.57	2.39	27.72	Peak	105	357



Site : 03CH03-HY  
 Condition : 3m LOG-9111-221 HORIZONTAL  
 EUT : RF Keyboard  
 Power : Battery  
 MODEL : KF-3801  
 MEMO : Tx

	Freq	Level	Over	Limit	Read	Probe	Cable	Preamp	Remark	Ant	Table
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor		Pos	Pos
			dB	dBuV/m	dBuV	dB	dB	dB		cm	deg
1 !	324.000	40.75	-5.25	46.00	50.54	14.56	3.07	27.42	Peak	105	354
2 !	352.000	42.03	-3.97	46.00	51.07	15.26	3.26	27.56	Peak	105	358
3 !	406.400	40.00	-6.00	46.00	48.24	15.90	3.72	27.86	Peak	105	356
4 !	957.600	43.55	-2.45	46.00	44.40	21.90	5.49	28.24	Peak	105	358
5 !	957.600	41.45	-4.55	46.00	42.30	21.90	5.49	28.24	QP	105	358

Test Engineer : Jones Tsai  
 Jones Tsai

6.4.1. Photographs of Radiated Emission Test Configuration

- The photographs show the configuration that generates the maximum emission.

FRONT VIEW



REAR VIEW



**7. EMI Suppression Component List**

1. Tune the impedance of loop antenna by modifying the length of it as attached file A, page 3.
2. Changing the location of loop antenna as attached file A, page 4.

## 8. Antenna Factor &amp; Cable Loss

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)
25	15.02	0.81
30	14.47	0.92
35	13.08	1.05
40	11.70	1.08
45	10.64	1.15
50	10.14	1.29
55	10.21	1.63
60	10.21	1.30
65	9.35	1.36
70	8.91	1.43
75	9.12	1.48
80	9.50	1.53
85	9.71	1.61
90	9.30	1.69
95	9.36	1.67
100	9.80	1.76
110	10.44	1.80
120	10.58	1.90
130	11.37	1.61
140	11.74	2.14
150	12.38	2.16
160	12.68	2.16
170	13.26	1.99
180	13.56	2.39
190	14.57	2.38
200	14.80	2.46
200	15.39	2.46
220	14.08	2.59
240	12.85	2.68
260	12.46	2.91
280	12.91	2.92
300	13.21	2.99
320	14.37	3.03
340	15.31	3.22
360	15.23	3.28
380	15.39	3.80
400	15.79	3.80
450	16.52	3.69
500	17.35	3.93
550	17.77	3.56
600	19.00	4.15
650	18.78	4.58
700	19.80	4.73
750	20.01	4.71
800	20.38	4.99
850	20.86	5.24
900	21.08	5.38
950	21.83	5.57
1000	22.23	5.62

## 9. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	25MHz~1GHz	Jun. 21, 2003	Radiation (03CH03-HY)
Spectrum analyzer	R&S	FSP40	100004	9KHZ~40GHz	Aug. 23, 2003	Radiation (03CH03-HY)
Amplifier	HP	8447D	2944A09072	100KHz – 1.3GHz	Nov. 05, 2003	Radiation (03CH03-HY)
Biconical Antenna	SCHWARZBECK	VUSLP	9124-301	25MHz –200MHz	Jul. 24, 2003	Radiation (03CH03-HY)
RF Cable-R03m	Jye Bao	RG142	CB021	30MHz~1GHz	Jan. 02, 2003	Radiation (03CH03-HY)
Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	Radiation (03CH03-HY)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (03CH03-HY)

※ Calibration Interval of instruments listed above is one year.



### 10. Uncertainty of Test Site

Uncertainty of Radiated Emission Measurement

Contribution	Probability Distribution	3m
Antenna factor calibration	normal(k=2)	±1
cable loss calibration	normal(k=2)	±0.3
RCV/SPA specification	rectangular	±2
Antenna Directivity	rectangular	±3
Antenna Factor V.S. Height	rectangular	±2
Antenna Factor Interpolation for Frequency	rectangular	±0.25
site imperfection	rectangular	±2
Mismatch Receiver VSWR $\Gamma_1=0.09$ Antenna VSWR $\Gamma_2=0.67$ Uncertainty= $20\log(1-\Gamma_1\Gamma_2)$	U-shaped	±0.54
combined standard uncertainty $U_e(y)$	normal	±2.7
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	±5.4

$$U = \sqrt{\{(1/2)^2 + (0.3/2)^2 + (2^2 + 0.5^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\}} = 2.2 \text{ for 10m test distance}$$

$$U = \sqrt{\{(1/2)^2 + (0.3/2)^2 + (2^2 + 3^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\}} = 2.7 \text{ for 3m test distance}$$

Uncertainty of Conducted Emission Measurement

Contribution	Probability Distribution	150KHz – 30MHz
Cable and I/P attenuator calibration	normal(k=2)	±0.3
RCV/SPA specification	rectangular	±2
LISN coupling specification	rectangular	±1.5
Transducer factor frequency interpolation	rectangular	±0.2
Mismatch Receiver VSWR $\Gamma_1=0.09$ LISN VSWR $\Gamma_2=0.33$ Uncertainty= $20\log(1-\Gamma_1\Gamma_2)$	U-shaped	0.2
combined standard uncertainty $U_e(y)$	normal	±1.66
Measuring uncertainty for a level of confidence of 95% $U=2U_e(y)$	normal (k=2)	±3.32

$$U = \sqrt{\{(0.3/2)^2 + (2^2 + 1.5^2 + 0.2^2)/3 + (0.2)^2/2\}} = 1.66$$