

# **FCC TEST REPORT**

for

47 CFR, Part 15, Subpart C

Equipment : RF Mouse

Model No. : AGM-9200(Agiler), RO-45G(Aopen),  
ET-6903(Ergotech)

FCC ID : HQXAGM-9200

Filing Type : Certification

Applicant : **Sysgration LTD.**  
8F, No. 542-7, Chung Cheng Rd., Hsin Tien, Taipei,  
Taiwan, R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

***SPORTON International Inc.***

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## Table of Contents

<b>History of this test report .....</b>	<b>ii</b>
<b>CERTIFICATE OF COMPLIANCE.....</b>	<b>1</b>
<b>1. General Description of Equipment under Test .....</b>	<b>2</b>
1.1. Applicant.....	2
1.2. Manufacturer.....	2
1.3. Basic Description of Equipment under Test.....	2
1.4. Feature of Equipment under Test.....	2
<b>2. Test Configuration of Equipment under Test .....</b>	<b>3</b>
2.1. Test Manner .....	3
2.2. Description of Test System.....	3
2.3. Band edge compliance plot per 15.227(b).....	5
2.4. Connection Diagram of Test System.....	6
<b>3. General Information of Test .....</b>	<b>7</b>
3.1. Test Facility .....	7
3.2. Standard for Methods of Measurement.....	7
3.3. Test in Compliance with.....	7
3.4. Frequency Range Investigated.....	7
3.5. Test Distance.....	7
<b>4. Test of Conducted Powerline.....</b>	<b>8</b>
<b>5. Test of Radiated Emission .....</b>	<b>9</b>
5.1. Major Measuring Instruments.....	9
5.1.1. from 30MHz to 1GHz	9
5.2. Test Procedures .....	10
5.3. Typical Test Setup Layout of Radiated Emission .....	11
5.4. Test Result of Radiated Emission .....	12
<b>6. EMI Suppression Component List.....</b>	<b>13</b>
<b>7. Antenna Factor &amp; Cable Loss .....</b>	<b>14</b>
<b>8. List of Measuring Equipments Used .....</b>	<b>15</b>
<b>9. Uncertainty of Test Site.....</b>	<b>16</b>
<b>Appendix A. Photographs of EUT .....</b>	<b>A1 ~ A4</b>



# CERTIFICATE OF COMPLIANCE

for

## 47 CFR, Part 15, Subpart C

Equipment : RF Mouse

Model No. : AGM-9200(Agiler), RO-45G(Aopen),  
ET-6903(Ergotech)

FCC ID : HQXAGM-9200

Applicant : **Sysgration LTD.**  
8F, No. 542-7, Chung Cheng Rd., Hsin Tien, Taiwan,  
R.O.C.

I **HEREBY** CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 1992** and the energy emitted by this equipment was **passed** both radiated and conducted emission limits. Testing was carried out on Jun. 25, 2002 at **SPORTON International Inc.** LAB.

  
K. J. Lin  
Manager

**SPORTON International Inc.**

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

## **1. General Description of Equipment under Test**

### **1.1. Applicant**

Sysgration LTD.  
8F, No. 542-7, Chung Cheng Rd., Hsin Tien, Taipei, Taiwan, R.O.C.

### **1.2. Manufacturer**

Sysgration (Shenzhen) LTD.  
Egongling Village, Pinhu Town, Longgang, Shenzhen

### **1.3. Basic Description of Equipment under Test**

Equipment : RF Mouse  
Model No. : AGM-9200(Agiler), RO-45G(Aopen), ET-6903(Ergotech)  
Trade Name : Agiler, Aopen, Ergotech  
Power Supply Type : From Battery  
AC Power Cord : N/A

### **1.4. Feature of Equipment under Test**

- Working Frequency: 27.045MHz
- Channel number: 1
- ID Number: 256
- RF output power: -4dBm  $\pm$ 2dBm
- Modulation method: FSK
- Power requirements: 3.0V, AA size battery 2 pieces
- Current Dissipation: 25mA (Typ)  $\pm$ 5mA
- Standby Mode Current: 2.5mA (Typ)  $\pm$ 1mA
- Sleeping Mode Current: 0.6mA (Typ)  $\pm$ 0.1mA
- Working Distance: 1.8 meters
- Low Batt. Detect: 2.2V  $\pm$ 0.2V

## 2. Test Configuration of Equipment under Test

### 2.1. Test Manner

- a. The EUT has been configured and operated pursuant to ANSI C63.4-1992 in a manner which tended to maximize its emission characteristics in a typical application.
- b. The complete test system included ASUS PC, REALsync Monitor, GATEWAY Keyboard, Sysgration Receiver and EUT for EMI test.
- c. Frequency range investigated: radiation 30 MHz to 1000MHz.

### 2.2. Description of Test System

#### Support Unit 1. -- Personal Computer (ASUS)

FCC ID : N/A  
Model No. : A7V133  
Power Supply Type : Switching  
Power Cord : Non-Shielded  
Serial No. : SP0039  
Data Cable : Shielded, 360 degree via metal backshells  
Remark : This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

#### Support Unit 2. -- Monitor (REALsync)

FCC ID : N/A  
Model No. : DJ72  
Power Supply Type : Switching  
Power Cord : Non-Shielded  
Serial No. : SP0023  
Data Cable : Shielded, 360 degree via metal backshells, 1.7m  
Remark : This support device was tested to comply with FCC standards and authorized under a declaration of conformity.


#### Support Unit 3. -- PS/2 Keyboard (GATEWAY)

FCC ID : N/A  
Model No. : G9900H  
Serial No. : SP0032  
Data Cable : Shielded, 1.2m  
Remark : This support device was tested to comply with FCC standards and authorized under a declaration of conformity.

Support Unit 4. -- Receiver (Sysgration)

FCC ID : N/A  
Model No. : AGM9200  
Serial No. : SP0019

2.3. Band edge compliance plot per 15.227(b).




Mark 1 : 26.98MHz  
 Mark 3 : 27.28MHz

Conformation of the fundamental frequency

Frequency ( MHz )	Polarity	Antenna Factor ( dB/m )	Cable Loss ( dB )	Reading ( dBuV )	Limits ( dBuV/m ) ( uV/m )	Emission Level ( dBuV/m ) ( uV/m )		Margin ( dB )	Detect Mode
26.980	H	15.40	0.90	23.03	69.54 2999	39.33	92.58	-30.21	Peak
27.050	H	15.40	0.90	30.75	80.00 10000	47.05	225.16	-32.95	Peak
27.280	H	15.40	0.90	3.36	69.54 2999	19.66	9.62	-49.88	Peak



### 2.4. Connection Diagram of Test System



1. The I/O cable is connected from PC to the support unit 2.
2. The I/O cable is connected from PC to the support unit 3.
3. The I/O cable is connected from PC to the support unit 4.

### **3. General Information of Test**

#### **3.1. Test Facility**

Test Site Location : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park,  
Kwei-Shan Hsiag, Tao Yuan Hsien, Taiwan, R.O.C.  
TEL : 886-3-327-3456  
FAX : 886-3-318-0055

Test Site No : SH04

#### **3.2. Standard for Methods of Measurement**

ANSI C63.4-1992

#### **3.3. Test in Compliance with**

FCC Part 15, Subpart C

#### **3.4. Frequency Range Investigated**

- a. Conduction: from 450 kHz to 30 MHz
- b. Radiation : from 30 MHz to 1 GHz

#### **3.5. Test Distance**

The test distance of radiated emission from antenna to EUT is 3 M.

## **4. Test of Conducted Powerline**

The power supply of the EUT is from battery.

So the conducted powerline test is not applicable to the EUT.

## 5. Test of Radiated Emission

Radiated emissions from 30 MHz to 1 GHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 5.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

### 5.1. Major Measuring Instruments


#### 5.1.1. from 30MHz to 1GHz

- Amplifier (HP 8447D )
  - Attenuation 0 dB
  - RF Gain 30 dB
  - Signal Input 100 KHz to 1.3 GHz
  
- Spectrum Analyzer (RAHDE&SCHEARZ & FSP )
  - Attenuation 0 dB
  - Start Frequency 30 MHz
  - Stop Frequency 1000 MHz
  - Resolution Bandwidth 120 KHz
  - Signal Input 9 KHz to 7 GHz

**5.2. Test Procedures**

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 6 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 6 dB margin will be repeated one by one using the quasi-peak method and reported.

5.3. Typical Test Setup Layout of Radiated Emission



**5.4. Test Result of Radiated Emission**

- Test Distance : 3 M
- Temperature : 26.1°C
- Relative Humidity : 57 %
- Test Date : Jun. 25, 2002
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

**The Radiated Emission test was passed at minimum margin**

**270.570 MHz / 37.39 dBuV/m (HORIZONTAL) Antenna Height 2 Meter, Turntable Degree 60 °.**

Frequency ( MHz )	Polarity	Antenna Factor ( dB/m )	Cable Loss ( dB )	Reading ( dBuV )	Limits		Emission Level		Margin ( dB )	Detect Mode
					( dBuV/m )	( uV/m )	( dBuV/m )	( uV/m )		
270.570	H	12.50	2.95	21.94	46.00	200	37.39	74.05	-8.61	Peak
297.570	H	12.90	3.10	14.64	46.00	200	30.64	34.04	-15.36	Peak
351.800	H	14.19	3.36	8.42	46.00	200	25.97	19.88	-20.03	Peak
37.290	V	14.39	1.10	14.21	40.00	100	29.70	30.55	-10.30	Peak
40.260	V	12.77	1.14	14.11	40.00	100	28.02	25.18	-11.98	Peak
270.570	V	12.50	2.95	13.79	46.00	200	29.24	28.97	-16.76	Peak

Test Engineer : Wayue Hsu  
Wayue Hsu

## **6. EMI Suppression Component List**

No EMI suppression components.



## 7. Antenna Factor & Cable Loss

Frequency ( Mhz )	Antenna Factor ( dB )	Cable Loss ( dB )
25	17.40	0.89
30	18.10	0.99
35	16.00	1.07
40	13.29	1.13
45	10.75	1.20
50	8.10	1.26
55	6.40	1.32
60	5.36	1.40
65	4.94	1.41
70	5.19	1.51
75	6.05	1.57
80	6.96	1.60
85	8.04	1.70
90	8.76	1.70
95	9.70	1.75
100	10.30	1.79
110	11.17	1.93
120	11.60	1.95
130	11.23	2.01
140	10.61	2.12
150	10.10	2.20
160	9.20	2.26
170	9.01	2.33
180	8.71	2.40
190	8.80	2.52
200	8.24	2.55
220	8.80	2.64
240	10.72	2.78
260	13.20	2.89
280	12.50	2.98
300	12.96	3.11
320	13.50	3.20
340	13.93	3.25
360	14.39	3.44
380	14.70	3.63
400	15.76	3.50
450	16.35	3.82
500	17.29	4.01
550	18.50	4.16
600	18.43	4.39
650	18.85	4.72
700	18.93	4.71
750	19.75	4.83
800	19.92	5.27
850	20.24	5.22
900	20.30	5.22
950	20.46	5.54
1000	20.80	5.81

## 8. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	RAHDE & SCHEARZ	FSP	838858/037	9KHz – 7GHz	Jan. 08, 2002	Radiation (SH04)
Amplifier	HP	8447D	2944A09072	100KHz – 1.3GHz	Sep. 26, 2001	Radiation (SH04)
Bilog Antenna	SCHAFFNER	CBL6112B	2687	30MHz –2GHz	Dec. 23, 2001	Radiation (SH04)
Turn Table	HD	DS 420	420/650/00	0 ~ 360 degree	N/A	Radiation (SH04)
Antenna Mast	HD	MA 240	240/560/00	1 m - 4 m	N/A	Radiation (SH04)
Half-wave dipole antenna	Schwarzbeck	UHAP VHAP	995+99 1024+1024	30MHz - 1GHz	Sep. 27, 2001	Radiation (SH04)

Calibration Interval of instruments listed above is one year.

### 9. Uncertainty of Test Site

#### Uncertainty of Radiated Emission Measurement

Contribution	Probability Distribution	3m
Antenna factor calibration	normal(k=2)	±1
cable loss calibration	normal(k=2)	±0.3
RCV/SPA specification	rectangular	±2
Antenna Directivity	rectangular	±3
Antenna Factor V.S. Height	rectangular	±2
Antenna Factor Interpolation for Frequency	rectangular	±0.25
site imperfection	rectangular	±2
Mismatch Receiver VSWR $\Gamma_1=0.09$ Antenna VSWR $\Gamma_2=0.67$ Uncertainty= $20\log(1-\Gamma_1*\Gamma_2)$	U-shaped	±0.54
<b>combined standard uncertainty Ue(y)</b>	<b>normal</b>	<b>±2.7</b>
<b>Measuring uncertainty for a level of confidence of 95% U=2Ue(y)</b>	<b>normal (k=2)</b>	<b>±5.4</b>

$U = \{(1/2)^2 + (0.3/2)^2 + (2^2 + 0.5^2 + 2^2 + 0.25^2 + 2^2) / 3 + (0.54)^2 / 2\} = 2.2$  for 10m test distance

$U = \{(1/2)^2 + (0.3/2)^2 + (2^2 + 3^2 + 2^2 + 0.25^2 + 2^2) / 3 + (0.54)^2 / 2\} = 2.7$  for 3m test distance

#### Uncertainty of Conducted Emission Measurement

Contribution	Probability Distribution	150KHz – 30MHz
Cable and I/P attenuator calibration	normal(k=2)	±0.3
RCV/SPA specification	rectangular	±2
LISN coupling specification	rectangular	±1.5
Transducer factor frequency interpolation	rectangular	±0.2
Mismatch Receiver VSWR $\Gamma_1=0.09$ LISN VSWR $\Gamma_2=0.33$ Uncertainty= $20\log(1-\Gamma_1*\Gamma_2)$	U-shaped	0.2
<b>combined standard uncertainty Ue(y)</b>	<b>normal</b>	<b>±1.66</b>
<b>Measuring uncertainty for a level of confidence of 95% U=2Ue(y)</b>	<b>normal (k=2)</b>	<b>±3.32</b>

$U = \{(0.3/2)^2 + (2^2 + 1.5^2 + 0.2^2) / 3 + (0.2)^2 / 2\} = 1.66$