

FCC Part 15 Subpart C
EMI TEST REPORT

of

E.U.T. : Wireless Keyboard

FCC ID. : HQXAK7500

MODEL : AK7500

Working Frequency : 27.145MHz

Issued Dated : Nov. 14, 2001

for

APPLICANT : SYSGRATION LTD.

ADDRESS : 8Fl., No.542-7, Chung Cheng Rd., Hsin Tien, Taipei,
Taiwan, R.O.C.

Test Performed by

ELECTRONICS TESTING CENTER, TAIWAN

NO. 8 LANE 29, WENMIMG ROAD,
LOSHAN TSUN, KWEISHAN HSIANG,
TAOYUAN, TAIWAN, R.O.C.

Tel:(03)3276170-3276174

Fax:(03)3276188

Report Number : ET90S-10-017-02

TEST REPORT CERTIFICATION

Applicant : SYSGRATION LTD.
8Fl, No. 542-7, Chung Cheng Rd., Hsin Tien, Taipei, Taiwan, R.O.C.

Manufacturer : SYSGRATION (Shenzhen) LTD.
Egongling Village, Pinhu Town, Longgang, Shenzhen City, Guang Dong, China

Description of EUT :

- a) Type of EUT : Wireless Keyboard
- b) Trade Name : SYSGRATION or Agiler
- c) Model No. : AK7500
- d) FCC ID : HQXAK7500
- e) Working Frequency : 27.145MHz
- f) Power Supply : DC 3V Battery

Regulation Applied : FCC Rules and Regulations Part 15 Subpart C (1996)

I HEREBY CERTIFY THAT; The data shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the device was founded to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

- Note :
1. The results of the testing report relate only to the items tested.
 2. The testing report shall not be reproduced except in full, without the written approval of ETC.

Test Date : Oct. 24, 2001

Test Engineer : Ricci Hu

Approve & Authorized Signer : Win-Po Tsai

Win-Po Tsai, Manager, NVLAP Signatory
EMC Dept. I of ELECTRONICS
TESTING CENTER, TAIWAN

Table of Contents

Page

1. GENERAL INFORMATION.....	1
1.1 PRODUCT DESCRIPTION.....	1
1.2 CHARACTERISTICS OF DEVICE:.....	1
1.3 TEST METHODOLOGY	1
1.4 TEST FACILITY.....	1
2. DEFINITION AND LIMITS.....	2
2.1 DEFINITION.....	2
2.2 RESTRICTED BANDS OF OPERATION	2
2.3 LIMITATION	2
2.4 LABELING REQUIREMENT	4
2.5 USER INFORMATION	4
3. RADIATED EMISSION MEASUREMENT.....	5
3.1 APPLICABLE STANDARD.....	5
3.2 DEVICES FOR TESTED SYSTEM	5
3.3 MEASUREMENT PROCEDURE	5
3.4 TEST DATA.....	8
3.5 FIELD STRENGTH CALCULATION	11
3.6 RADIATED TEST EQUIPMENT	11
3.7 MEASURING INSTRUMENT SETUP	12
3.7 RADIATED MEASUREMENT PHOTOS.....	12
4. CONDUCTED EMISSION MEASUREMENT.....	13
4.1 APPLICABLE STANDARD.....	13
5. BANDEGE COMPLIANCE MEASUREMENT.....	13
PHOTOS OF RADIATION MEASURING SETUP	A1

1. GENERAL INFORMATION

1.1 Product Description

a) Type of EUT	: Wireless Keyboard
b) Trade Name	: SYSGRATION or Agiler
c) Model No.	: AK7500
d) FCC ID	: HQXAK7500
e) Working Frequency	: 27.145MHz
f) Power Supply	: DC 3V Battery

1.2 Characteristics of Device:

It's easy to use in wireless environment. It just need only one receiver to receive signal from keyboard.

1.3 Test Methodology

Radiated testing were performed according to the procedures in chapter 13 of ANSI C63.4. The Wireless Keyboard under test was operated continuously in its normal operating mode for the purpose of the measurements. In order to secure the continuous operation of the device under test, rewiring in the circuit was done by the manufacturer so as to affect its intended operation. The receiving antenna was varied from 1 to 4 meters and the wooden turntable was rotated through 360 degrees to obtain the highest reading on the field strength meter or on the display of the spectrum analyzer. And also, each emission was to be maximized by changing the orientation of the Wireless Keyboard under test. The hand-held or body-worn devices rotated through three orthogonal axes to determine which attitude and configuration produces the highest emission relatives to the limit.

1.4 Test Facility

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C.

This site has been accreditation as a FCC filing site.

2. DEFINITION AND LIMITS

2.1 Definition

Intentional radiator:

A device that intentionally generates and emits radio frequency energy by radiation or induction.

2.2 Restricted Bands of Operation

Only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42-16.423	399.9-410	4.5-5.25
0.495 - 0.505 **	16.69475 - 16.69525	608-614	5.35-5.46
2.1735 - 2.1905	16.80425 - 16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475 - 156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2655-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3360-4400	Above 38.6
13.36-13.41			

Remark “***” : Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz

2.3 Limitation

(1) Conducted Emission Limits :

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the conducted limit is the following:

Frequency (MHz)	Emission (μV)	Emission (dBμV)
0.45 - 30.0	250	48.0

(2) Radiated Emission Limits :

According to 15.227 the field strength of emissions from intentional radiators operated under these frequency bands shall not exceed the following:

Fundamental Frequency (MHz)	Field Strength of Fundamental	
	$\mu\text{V}/\text{meter}$	$\text{dB}\mu\text{V}/\text{meter}$
26.96-27.28	10000	80

Field strength limits are at the distance of 3 meters, emissions radiated outside of the specified bands, shall be according to the general radiated limits in 15.209,as following table:

Other Frequencies (MHz)	Field Strength of Fundamental	
	$\mu\text{V}/\text{meter}$	$\text{dB}\mu\text{V}/\text{meter}$
30 – 88	100	40.0
88 – 216	150	43.5
216 – 960	200	46.0
Above 960	500	54.0

As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20 dB under any condition of modulation.

2.4 Labeling Requirement

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

2.5 User Information

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

3. RADIATED EMISSION MEASUREMENT

3.1 Applicable Standard

1. The field strength of any emission within this band(26.96-27.28MHz) shall not exceed 10,000 microvolts/meter at 3 meters. The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in Section 15.35 for limiting peak emissions apply.
2. The field strength of any emissions which appear outside of this band shall not exceed the general radiated emission limits in Section 15.209.

3.2 Devices for Tested System

Description	Model	Manufacturer	Cable
Wireless Keyboard *	AM7500	SYSGRATION (Shenzhen) LTD.	----
Wireless Mouse	AK7500	SYSGRATION (Shenzhen) LTD.	----
Receiver for wireless keyboard & wireless mouse	AR7500	SYSGRATION (Shenzhen) LTD.	Signal cable:1.5m, Unshielded
PC	11W	IBM	Power cable:1.8m, Unshielded
Monitor	G51	IBM	Power cable:2.0m, Unshielded Signal cable:1.8m, Shielded(with one core)
Printer	C4582A	HP	Power cable:1.8m, Unshielded/ Adaptor Signal cable:1.7m, Shielded
Modem	2400U	Smartlink	Power cable:1.8m, Unshielded Signal cable:1.7m, Shielded

“*” -- Equipment Under Test

3.3 Measurement Procedure

a1 Below 30MHz

1. Setup the configuration per figure 1 and 2 for frequencies measured below 30MHz. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured is performed in a semi-anechoic chamber.
3. For emission measured, set the spectrum analyzer on a 10 KHz and 30 KHz resolution bandwidth respectively for fundamental frequency measured in step 2.
4. Change the orientation of EUT on the table over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the EMI test receiver. Rotate Loop Antenna over a range from 0° to 360° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the EMI test receiver. Vary the Loop Antenna height and record the highest value as a final reading. The Loop Antenna is to be raised and lowered over a range from 1 to 1.8m.

b1 Above 30MHz and below 1GHz

1. Setup the configuration per figure 3 and 4 for frequencies measured above 30 MHz and below 1 GHz. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured is performed in a semi-anechoic chamber.
3. For emission measured, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.

Figure 1 : Below 30 MHz chamber Setup Diagram





Figure 2 : Above 30 MHz chamber Setup Diagram



3.4 Test Data**Data 1 : Fundamental & Harmonics**

Temperature : 21
 Humidity : 67%
 Test Date : Oct. 24, 2001

Frequency (MHz)	Ant Pol H/V	Reading (dBuV) Peak	Correct Factor (dB)	Result @3m (dBuV/m) Peak	Limit @3m (dBuV/m) Peak AVG.	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
27.138	H	10.1	34.0	44.1	100 80	-35.9	30	1.2

Frequency (MHz)	Ant Pol H/V	Reading (dBuV) Peak	Correct Factor (dB)	Result @3m (dBuV/m) Peak	Limit @3m (dBuV/m) Q.P.	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
54.276	H	12.8	7.8	20.6	40.0	-19.4	75	1.0
54.276	V	21.2	7.8	29.0	40.0	-11.0	60	2.1
81.414	H	14.2	10.1	24.3	40.0	-15.7	360	1.1
81.414	V	19.0	10.1	29.1	40.0	-10.9	45	1.3
108.552	H	17.8	9.1	26.9	43.5	-16.6	50	2.5
108.552	V	15.5	9.1	24.6	43.5	-18.9	70	1.4
135.690	H	15.3	10.6	25.9	43.5	-17.6	30	1.0
135.690	V	***	***	***	***	***	***	***
162.828	H	14.0	11.6	25.6	43.5	-17.9	345	1.4
162.828	V	14.8	11.6	26.4	43.5	-17.1	30	1.8
189.966	H	11.6	12.3	23.9	43.5	-19.6	45	1.2
189.966	V	9.7	12.3	22.0	43.5	-21.5	0	1.7
217.104	H	23.0	13.4	36.4	46.0	-9.6	35	1.4
217.104	V	10.7	13.4	24.1	46.0	-21.9	60	1.5
244.242	H	12.5	14.5	27.0	46.0	-19.0	30	1.0
244.242	V	14.8	14.5	29.3	46.0	-16.7	60	1.5
271.380	H	14.1	16.5	30.6	46.0	-15.4	330	1.3

271.380	V	12.8	16.5	29.3	46.0	-16.7	45	1.6
---------	---	------	------	------	------	-------	----	-----

Note :

1. Limit on the field strength of fundamental (Average)
 $50\text{mV/m} = 20 \times \log(50000) = 94.0 \text{ dB } \mu \text{ V/m}$
2. Limit on the field strength of Harmonics(Average)
 $500 \mu \text{ V/m} = 20 \times \log(500) = 54.0 \text{ dB } \mu \text{ V/m}$
3. If the measured frequencies fall in the restricted frequency band, the limit employed is § 15.209 general requirement when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function, no duty factor applied.
4. The radiation emissions have been measured to beyond the tenth harmonic of the fundamental frequency and show the significant frequencies, other means the value is too low to be detected.
5. If the data table appeared symbol of “***” means the value is too low to be measured.
6. The system amplitude accuracy of the measurement made during the radiated emission tests was $\pm 4\text{dB}$.

Data 2: Other emissions

Temperature : 21
 Humidity : 67%
 Test Date : Oct. 24, 2001

Frequency (MHz)	Ant Pol H/V	Reading (dBUV) Peak	Correct Factor (dB)	Result @3m (dBUV/m) Peak	Limit @3m (dBUV/m) Q.P.	Margin (dB)	Table Degree (Deg.)	Ant. High (m)
48.930	V	34.0	8.0	32.4	40.0	-7.6	30	1.4
70.930	V	19.5	9.2	28.7	40.0	-11.3	90	1.3
95.680	H	22.1	9.6	31.7	43.5	-11.8	50	1.0
98.970	V	17.5	9.4	26.9	43.5	-16.6	40	1.4
113.550	H	20.6	9.1	29.7	43.5	-13.8	45	1.0
113.550	V	20.0	9.1	29.1	43.5	-14.4	70	1.3
120.430	V	19.4	9.4	28.8	43.5	-14.7	0	1.5
212.550	V	23.7	12.7	36.4	43.5	-7.1	40	1.0
218.600	H	15.2	13.4	28.6	46.0	-17.4	75	1.2
255.180	V	12.6	15.6	28.2	46.0	-17.8	60	1.5
259.850	V	17.2	15.6	32.8	46.0	-13.2	340	1.3
382.600	H	17.5	20.6	38.1	46.0	-7.9	75	1.1
477.800	H	16.7	22.3	39.0	46.0	-7.0	30	1.0
477.800	V	14.1	22.3	36.4	46.0	-9.6	0	1.2

Note:

1. AH means antenna height, DRT means degrees of rotation of turntable.
2. If the data table appeared symbol of “****” means the value is too low to be measured.
3. The system amplitude accuracy of the measurement made during the radiated emission tests was ± 4 dB.

3.5 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation with a sample calculation is as follows:

$$\text{RESULT} = \text{READING} + \text{CORR. FACTOR}$$

where CORR. FACTOR = Antenna FACTOR + Cable FACTOR

Assume a receiver reading of 22.5 dB μ V is obtained. The Antenna Factor of 14.5 and a Cable Factor of 1.5 is added. The total of field strength is 38.5 dB μ V/m.

$$\text{RESULT} = 22.5 + 14.5 + 1.5 = 38.5 \text{ dB } \mu \text{ V/m}$$

$$\begin{aligned} \text{Level in } \mu \text{ V/m} &= \text{Common Antilogarithm}[(38.5 \text{ dB } \mu \text{ V/m})/20] \\ &= 84.14 \mu \text{ V/m} \end{aligned}$$

3.6 Radiated Test Equipment

The following instrument are used for radiated emissions measurement :

Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
EMI Test Receiver	Hewlett-Packard	8546A	13054404-001	Nov. 06, 2001
LogBicone Antenna	Schwarzbeck	VULB9160	13057310-001	Oct. 18, 2002
Horn Antenna	EMCO	3115	9804-5454	May 15, 2002
Amplifier	Hewlett-Packard	8449B	3008400936	May 10, 2002
Spectrum	Hewlett-Packard	8564E	11760	Apr. 23, 2002

Note: The standards used to perform this calibration are traceable to NML/ROC, NIST/USA and NPL.

Measuring instrument setup in measured frequency band when specified detector function is used :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi-Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz
	Spectrum Analyzer	Average	1 MHz	Auto

3.7 Measuring Instrument Setup

Explanation of measuring instrument setup in frequency band measured is as following :

Frequency Band (MHz)	Instrument	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	RF Test Receiver	Quasi Peak	120 kHz	N/A
	Spectrum Analyzer	Peak	100 kHz	100 kHz
Above 1000	Spectrum Analyzer	Peak	1 MHz	1 MHz

3.7 Radiated Measurement Photos

Please see Test Setup Photos files: "RE01.jpg", "RE02.jpg".


4. CONDUCTED EMISSION MEASUREMENT


4.1 Applicable Standard


This EUT is excused from investigation of conducted emission, for it is powered by battery only. According to § 15.207 (d), measurements to demonstrate compliance with the conducted limits are not required for devices which only employ battery power for operation and which do not operate from the AC power lines or contain provisions for operation while connected to the AC power lines.

5. BANDEDGE COMPLIANCE MEASUREMENT

The scanning test data is shown on next page.







Photos of Radiation Measuring Setup

