

FCC ID: HQXAXM-105678

Operational Description of the equipment

The EUT is an excellent tool for mobile professionals. The equipment consists of the following: Mouse Transmitter, Keyboard + Mouse Receiver, Mouse Receiver.

PRODUCT	Wireless Optical Mouse
TRADE NAME	Agiler, Sysgration
MODEL NO.	AXM-105xxx, AXM-A5xxx, ARM-105xxx, ARM-A5xxx, AGM-105xxx, AGM-A5xxx, AKM-105C35xxx, AKM-A5C35xxx, XM-173, 57288 AXM-106xxx, AXM-A6xxx, ARM-106xxx, ARM-A6xxx, AGM-106xxx, AGM-A6xxx, AKM-106C35xxx, AKM-A6C35xxx AXM-107xxx, AXM-A7xxx, ARM-107xxx, ARM-A7xxx, AGM-107xxx, AGM-A7xxx, AKM-107C35xxx, AKM-A7C35xxx AXM-108xxx, AXM-A8xxx, ARM-108xxx, ARM-A8xxx, AGM-108xxx, AGM-A8xxx, AKM-108C35xxx, AKM-A8C35xxx, SYMS-1607

RF Mouse Transmitter

WORKING FREQUENCY	27.045MHz
CHANNEL NUMBER	1
ID NUMBERS	256
RF OUTPUT POWER	-4dBm±2dBm
DEVIATION	6KHz±2KHz
MODULATION METHOD	FSK
POWER REQUIREMENTS	3.0V, AAA size (Ni-MH) batteries x2
CURRENT DISSIPATION	<30mA
STANDBY MODE CURRENT	5±1mA
SLEEPING MODE CURRENT	0.63mA
TRANSMITTING ANGLE	360 °
WORKING DISTANCE	1.0 meter (Min.)
CHARGER CURRENT	300mA(Max.)
CHARGE TIME	4 Hours (Min.)
LOW BATTERY	1.9V

RF Receiver

WORKING FREQUENCY	27MHz
CHANNEL NUMBER	1
ID NUMBERS	256
CURRENT DISSIPATION	15mA (Typ)
WORKING DISTANCE	1.0 meter (Min.)