

*SYSGRATION LTD.  
FCC ID.: HQXPC98317-04  
EUT : Uninterruptable Power Supply*

# ***Exhibit C ..... Measurement Report***

# EMI TEST REPORT

FCC ID. : HQXPC98317-04  
Product : Uninterruptable Power Supply  
Model No. : PRO 700  
Applicant : SYSGRATION LTD.  
Manufacturer : SYSGRATION LTD.  
Regulation Applied : FCC Rules and Regulations Part 15 Subpart B  
(1997)  
Report Number : ET88S-06-095  
Issued Date : Jul. 15, 1999

The compliance test is only certified for the test equipment and the results of the testing report relate only to the item tested. The compliance test of this report was conducted in accordance with the appropriate standards. It's not intention to assure the quality and performance of the product. This report shall not be reproduced except in full, without the approval of ETC. This report must not be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

BSMI ISO 9002 and Guide 25.

TÜV Product Service ISO9002 and EN45001.

NIST NVLAP Accredited Laboratory for FCC Part 15/ CISPR 22/ AS/NZS 3548.

CNLA ISO/ IEC Guide 25.

NEMKO, FIMKO , SGS , TÜV Laboratory Assessment EN45001.

FCC, VCCI Registered.



# TEST REPORT CERTIFICATE

Applicant : SYSGRATION LTD.  
 8Fl., No. 542-7, Chung Cheng Rd., Hsin Tien, Taipei,  
 Taiwan, R.O.C.

Manufacturer : SYSGRATION LTD.  
 No. 26, Industrial N. Road Nan-Kang Industrial Park, Nan-Tou City,  
 Taiwan, R.O.C.

Description of EUT :

a) Type of EUT : Uninterruptable Power Supply  
 b) Model No./Type No. : PRO 700  
 c) Power Source : 115V, 60Hz, 455W

Comment Issues : a) The data also apply to PRO 320/PRO 520  
 b). The different models which has differnet output capacity as following:  
 PRO 700:700VA/with AVR  
 PRO 520:520VA/with AVR  
 PRO 320:320VA/with AVR

Regulation Applied : FCC Rules and Regulations Part 15 Subpart B (1997)

I HEREBY CERTIFY THAT: The data shown in this report were made in accordance with the procedures given in ANSI C63.4 and the energy emitted by the device was found to be within the limits applicable. I assume full responsibility for accuracy and completeness of these data.

Test Date : Jul. 06, 1999

Test Engineer : Bu-cheng Lin

Approve & Authorized Signer : Win-Po Tsai Jul. 15, 1999  
 Win-Po Tsai, Supervisor, NVLAP Signatory  
 EMC Dept. of ELECTRONICS  
 TESTING CENTER, TAIWAN



# ELECTRONICS TESTING CENTER, TAIWAN

## Table of Contents

|  | Page      |
|--|-----------|
| EMI TEST REPORT .....                          | 1         |
| TEST REPORT CERTIFICATE .....                  | 2         |
| TABLE OF CONTENTS.....                         | 3         |
| <b>1. GENERAL INFORMATION .....</b>            | <b>4</b>  |
| 1.1 Product Description .....                  | 4         |
| 1.2 Test Methodology .....                     | 4         |
| 1.3 Test Facility.....                         | 4         |
| <b>2. PROVISIONS APPLICABLE .....</b>          | <b>5</b>  |
| 2.1 Definition.....                            | 5         |
| 2.2 Requirement for Compliance.....            | 5         |
| 2.3 Labelling Requirement .....                | 7         |
| 2.4 User Information .....                     | 7         |
| <b>3. SYSTEM TEST CONFIGURATION.....</b>       | <b>8</b>  |
| 3.1 EUT configuration and operating .....      | 8         |
| 3.2 Devices for Tested System.....             | 8         |
| 3.3 Modification Record .....                  | 8         |
| <b>4. RADIATED EMISSION MEASUREMENT .....</b>  | <b>9</b>  |
| 4.1 Applicable Standard.....                   | 9         |
| 4.2 Measurement Procedure .....                | 9         |
| 4.3 Radiated Emission Data.....                | 11        |
| 4.4 Field Strength Calculation.....            | 13        |
| 4.5 Radiated Measuring Instrument.....         | 14        |
| 4.6 Photos of Radiation Measuring Setup .....  | 15        |
| <b>5. CONDUCTED EMISSION MEASUREMENT.....</b>  | <b>16</b> |
| 5.1 Applicable Standard.....                   | 16        |
| 5.2 Measurement Procedure .....                | 16        |
| 5.3 Conducted Emission Data.....               | 17        |
| 5.4 Result Data Calculation .....              | 23        |
| 5.5 Conducted Measurement Equipment.....       | 23        |
| 5.6 Photos of Conduction Measuring Setup ..... | 24        |

## **1. GENERAL INFORMATION**

### **1.1 Product Description**

The UPS is a extremely reliable standby uninterrupted power system designed to keep computers and peripheral devices such as monitors, storage subsystems, modems, tape drives, etc., performing from utility line failures which could result in damage of data. In the event of utility failure, the UPS supplies power to your equipment driven from a battery within the UPS and provides visual and audible indicators which alert you to utility line failures therefore the user has ample time to save file and close operations.

### **1.2 Test Methodology**

Both conducted and radiated emissions were performed according to the procedures in ANSI C63.4.

### **1.3 Test Facility**

The semi-anechoic chamber and conducted measurement facility used to collect the radiated and conducted data are located inside the Building at No.8, Lane 29, Wen-ming Road, Lo-shan Tsun, Kweishan Hsiang, Taoyuan, Taiwan, R.O.C. .  
This site has been accreditation as a FCC filing site.

**2. PROVISIONS APPLICABLE****2.1 Definition****Unintentional radiator:**

A device that intentionally generates radio frequency energy for use within the device, or that sends radio frequency signals by conduction to associated equipment via connecting wiring, but which is not intended to emit RF energy by radiation or induction.

**Class B Digital Device :**

A digital device which is marketed for use in a residential environment notwithstanding use in a commercial, business or industrial environment. Example of such devices that are marketed for the general public.

Note : A manufacturer may also qualify a device intended to be marketed in a commercial, business, or industrial environment as a Class B digital device, and in fact is encouraged to do so, provided the device complies with the technical specifications for a Class B Digital Device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B Digital Device, Regardless of its intended use.

**2.2 Requirement for Compliance****(1) Conducted Emission Requirement**

For unintentional device, according to **FCC § 15.107(a)** Line Conducted Emission Limits class B is as following:

| <b>Frequency<br/>MHz</b> | <b>Emissions<br/><math>\mu V</math></b> | <b>Emissions<br/>dB <math>\mu V</math></b> |
|--------------------------|---|--|
| 0.45 - 30.0              | 250                                     | 48.0                                       |

For unintentional device, according to **CISPR 22** Line Conducted Emission Limits class B is as following:

| <b>Frequency<br/>MHz</b> | <b>Quasi Peak<br/>dB <math>\mu V</math></b> | <b>Average<br/>dB <math>\mu V</math></b> |
|--------------------------|---|--|
| 0.15 - 0.5               | 66-56                                       | 56-46                                    |
| 0.5 - 5.0                | 56  | 46                                       |
| 5.0 - 30.0               | 60  | 50                                       |

For unintentional device, according to AS/NZS 3548 Line Conducted Emission Limits class B is as following:

| Frequency<br>MHz | Quasi Peak<br>dB $\mu$ V | Average<br>dB $\mu$ V |
|------------------|--------------------------|-----------------------|
| 0.15 - 0.5       | 66-56                    | 56-46                 |
| 0.5 - 5.0        | 56                       | 46                    |
| 5.0 - 30.0       | 60                       | 50                    |

## (2) Radiated Emission Requirement

For unintentional device, according to FCC § 15.109(a), the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values:

| Frequency<br>MHz | Distance<br>Meters | Radiated<br>$\mu$ V/m | Radiated<br>dB $\mu$ V/m |
|------------------|--------------------|-----------------------|--------------------------|
| 30 - 88          | 3                  | 100                   | 40.0                     |
| 88 - 216         | 3                  | 150                   | 43.5                     |
| 216 - 960        | 3                  | 200                   | 46.0                     |
| above 960        | 3                  | 500                   | 54.0                     |

For unintentional device, according to CISPR 22 Radiated Emission Limits class B is as following:

| Frequency<br>MHz | Distance<br>Meters | Radiated<br>dB $\mu$ V/m |
|------------------|--------------------|--------------------------|
| 30 to 230        | 10                 | 30                       |
| 230 to 1000      | 10                 | 37                       |

For unintentional device, according to AS/ NZS 3548 Radiated Emission Limits class B is as following:

| Frequency<br>MHz | Distance<br>Meters | Radiated<br>dB $\mu$ V/m |
|------------------|--------------------|--------------------------|
| 30 to 230        | 10                 | 30                       |
| 230 to 1000      | 10                 | 37                       |

### **2.3 Labelling Requirement**

The device shall bear the following statement in a conspicuous location on the device :

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions : (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

### **2.4 User Information**

The users manual or instruction manual for an intentional or unintentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

For a Class B digital device or peripheral, the instructions furnished the user shall include the following or similar statement, placed in a prominent location in the text of the manual.

The Federal Communications Commission Radio Frequency Interference Statement includes the following paragraph.

This equipment has been tested and found to comply with the limits for a Class B Digital Device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instruction may cause harmful interference to radio communication. However, there is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.



**3. SYSTEM TEST CONFIGURATION****3.1 EUT configuration and operating**

The system was configured for testing in a typical fashion, as a customer would normally use it. Measurement was performed under the condition that the EUT was connected with peripherals. During the test, the PC run the program "Management software of sysgration's UPS".

**3.2 Devices for Tested System**

| Description                     | Model         | Manufacturer    | Cable  |
|---------------------------------|---------------|-----------------|--|
| Uninterruptable Power Supply *1 | PRO 700       | SYSGRATION LTD. | AC Power Cord (Unshielded)                           |
| Monitor                         | P750          | NEC             | 1.8m Shielded Cable<br>1.8m Unshielded AC Power Cord |
| PC                              | VE 5/200      | Hewlett-Packard | 1.8m Shielded Cable<br>1.8m Unshielded AC Power Cord |
| Keyboard                        | E03633YLTW3-C | Hewlett-Packard | 1.8m Unshielded Cable                                |
| Mouse                           | M-S34         | IBM             | 1.8m Unshielded Cable                                |
| Incondescent Lamps              | ----          | ----            | ----   |

“\*” -- Equipment Under Test

**3.3 Modification Record**

(If any deviation from additions to or exclusions from test method must be stated)

N/A

## **4. RADIATED EMISSION MEASUREMENT**


### **4.1 Applicable Standard**

For unintentional radiator digital devices, the radiated emission shall comply with § 15.109(a). And according to § 15.109 (g), as an alternative to the radiated emission limits is CISPR 22.

### **4.2 Measurement Procedure**

1. Setup the configuration per figure 1.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a semi-anechoic chamber to determine the accurate frequencies of higher emissions then each selected frequency in precisely measured.
3. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that the highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading. A RF test receiver is also used to confirm emissions measured.
4. Repeat step 3 until all frequencies need to be measured were complete.
5. Repeat step 4 with search antenna in vertical polarized orientations.
6. Check the frequency of the highest emission with varying the placement of cables associated with EUT to obtain the worst case and record the result.

Figure 1 : Frequencies measured below 1 GHz configuration





**4.3 Radiated Emission Data**

Below 1GHz

A.

Model No./Type No. : PRO 700

Operation Mode : Line Mode

EUT Power : AC 110V/60Hz

Test Date : Jul. 06, 1999

Temperature : 27 °C

Humidity : 71%

| Emission Frequency<br>(MHz) | Meter Reading<br>(dB $\mu$ V) |      | Corr'd Factor<br>(dB) | Results<br>(dB $\mu$ V/m) |      | AH<br>(m) |      | DRT<br>degree |      | Limit @3m<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|-----------------------------|-------------------------------|------|-----------------------|---------------------------|------|-----------|------|---------------|------|-----------------------------|----------------|
|                             | Hor.                          | Ver. |                       | Hor.                      | Ver. | Hor.      | Ver. | Hor.          | Ver. |                             |                |
| 45.036                      | ***                           | 22.5 | 9.5                   | ***                       | 32.0 | ***       | 1.0  | ***           | 0    | 40.0                        | -8.0           |
| 45.602                      | 24.3                          | ***  | 9.5                   | 33.8                      | ***  | 1.2       | ***  | 0             | ***  | 40.0                        | -6.2           |
| 51.331                      | 19.3                          | ***  | 8.0                   | 27.3                      | ***  | 1.2       | ***  | 62            | ***  | 40.0                        | -12.7          |
| 51.872                      | ***                           | 25.7 | 8.0                   | ***                       | 33.7 | ***       | 1.0  | ***           | 52   | 40.0                        | -6.3           |
| 63.024                      | 24.7                          | ***  | 8.4                   | 33.1                      | ***  | 1.5       | ***  | 12            | ***  | 40.0                        | -6.9           |
| 92.695                      | ***                           | 22.8 | 9.6                   | ***                       | 32.4 | ***       | 1.1  | ***           | 0    | 43.5                        | -11.1          |
| 93.014                      | 20.7                          | ***  | 9.6                   | 30.3                      | ***  | 1.5       | ***  | 0             | ***  | 43.5                        | -13.2          |
| 100.759                     | 15.1                          | ***  | 9.4                   | 24.5                      | ***  | 1.0       | ***  | 121           | ***  | 43.5                        | -19.0          |
| 103.483                     | ***                           | 22.4 | 9.4                   | ***                       | 31.8 | ***       | 1.1  | ***           | 3    | 43.5                        | -11.7          |
| 111.838                     | 14.6                          | ***  | 9.1                   | 23.7                      | ***  | 1.5       | ***  | 0             | ***  | 43.5                        | -19.8          |
| 117.852                     | ***                           | 22.5 | 9.4                   | ***                       | 31.9 | ***       | 1.0  | ***           | 12   | 43.5                        | -11.6          |
| 126.019                     | ***                           | 17.0 | 10.6                  | ***                       | 27.6 | ***       | 1.0  | ***           | 0    | 43.5                        | -15.9          |

Note:

1. AH means antenna height, DRT means degrees of rotation of turntable.
2. The symbol of "\*\*\*\*" means the value is too low to be detected.



# ELECTRONICS TESTING CENTER, TAIWAN

## B.

Model No./Type No. : PRO 700

Operation Mode : Bat Mode

EUT Power : AC 110V/60Hz

Test Date : Jul. 06, 1999

Temperature : 27 °C

Humidity : 71%

| Emission Frequency<br>(MHz) | Meter Reading<br>(dB $\mu$ V) |      | Corr'd Factor<br>(dB) | Results<br>(dB $\mu$ V/m) |      | AH<br>(m) |      | DRT<br>degree |      | Limit<br>@3m<br>(dB $\mu$ V/m) | Margin<br>(dB) |
|-----------------------------|-------------------------------|------|-----------------------|---------------------------|------|-----------|------|---------------|------|--------------------------------|----------------|
|                             | Hor.                          | Ver. |                       | Hor.                      | Ver. | Hor.      | Ver. | Hor.          | Ver. |                                |                |
| 40.156                      | ***                           | 21.7 | 11.1                  | ***                       | 32.8 | ***       | 1.0  | ***           | 12   | 40.0                           | -7.2           |
| 40.751                      | 16.2                          | ***  | 11.1                  | 27.3                      | ***  | 1.2       | ***  | 15            | ***  | 40.0                           | -12.7          |
| 51.839                      | ***                           | 28.3 | 8.0                   | ***                       | 36.3 | ***       | 1.0  | ***           | 57   | 40.0                           | -3.7           |
| 52.475                      | 13.9                          | ***  | 8.0                   | 21.9                      | ***  | 1.0       | ***  | 52            | ***  | 40.0                           | -18.1          |
| 72.516                      | 13.7                          | ***  | 9.6                   | 23.3                      | ***  | 1.0       | ***  | 5             | ***  | 40.0                           | -16.7          |
| 73.705                      | ***                           | 23.9 | 9.6                   | ***                       | 33.5 | ***       | 1.1  | ***           | 12   | 40.0                           | -6.5           |
| 81.005                      | 14.9                          | ***  | 10.1                  | 25.0                      | ***  | 1.5       | ***  | 0             | ***  | 40.0                           | -15.0          |
| 97.418                      | 15.0                          | ***  | 9.6                   | 24.6                      | ***  | 1.3       | ***  | 145           | ***  | 43.5                           | -18.9          |
| 98.392                      | ***                           | 20.4 | 9.4                   | ***                       | 29.8 | ***       | 1.0  | ***           | 0    | 43.5                           | -13.7          |
| 103.147                     | ***                           | 22.0 | 9.4                   | ***                       | 31.4 | ***       | 1.1  | ***           | 5    | 43.5                           | -12.1          |
| 110.077                     | 14.4                          | ***  | 9.1                   | 23.5                      | ***  | 1.5       | ***  | 3             | ***  | 43.5                           | -20.0          |
| 117.872                     | ***                           | 24.0 | 9.4                   | ***                       | 33.4 | ***       | 1.0  | ***           | 15   | 43.5                           | -10.2          |

Note:

1. AH means antenna height, DRT means degrees of rotation of turntable.
2. The symbol of "\*\*\*\*" means the value is too low to be detected.

#### **4.4 Field Strength Calculation**

The field strength is calculated by adding the Antenna Factor, High Pass Filter Loss and Cable Loss, and subtracting the Amplifier Gain (if any) from the measured reading. The basic equation calculation is as follows:

$$\mathbf{Result = Reading + Corrected Factor}$$

where

$$\text{Corrected Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

#### 4.5 Radiated Measuring Instrument

The following instrument are used for radiated emissions measurement :

| Equipment         | Manufacturer    | Model No. | Serial No. | Calibrated until |
|-------------------|-----------------|-----------|------------|------------------|
| EMI Test Receiver | Hewlett-Packard | 8546A     | 3411A00192 | Nov. 04, 1999    |
| BiconiLog Antenna | EMCO            | 3142      | 9702-1142  | Aug. 20, 1999    |

Note: The standards used to perform this calibration are traceable to NML/ROC and NIST/USA.

Measuring instrument setup in measured frequency band when specified detector function is used :

| Frequency Band (MHz) | Instrument       | Function   | Resolution bandwidth | Video Bandwidth |
|----------------------|------------------|------------|----------------------|-----------------|
| 30 to 1000           | RF Test Receiver | Quasi-Peak | 120 kHz              | N/A             |

## 5. CONDUCTED EMISSION MEASUREMENT


### 5.1 Applicable Standard

For unintentional digital devices, Line Conducted Emission Limits are in accordance to § 15.107(a). And according to § 15.107(e), an alternative to the conducted limits is CISPR 22.

### 5.2 Measurement Procedure

1. Setup the configuration per figure 2.
2. A preliminary scan with a spectrum monitor is performed to identify the frequency of emission that has the highest amplitude relative to the limit by operating the EUT in selected modes of operation, typical cable positions, and with a typical system configuration.
3. Record the 4 to 8 highest emissions relative to the limit.
4. Measure each frequency obtained from step 3 by a test receiver set on quasi peak detector function, and then record the accuracy frequency and emission level. If all emissions measured in the specified band are attenuated more than 20 dB from the limit, this step would be ignored, and the peak detector function would be used.
5. Confirm the highest emissions with variation of the EUT cable configuration and record the final data.
6. Repeat all above procedures on measuring each operation mode of EUT.

Figure 2 : Conducted emissions measurement configuration







5.3 Conducted Emission Data

A.

Model No./Type No. : PRO 700

Operation Mode : Line Mode

EUT Power : AC 110V/60Hz

Test Date : Jul. 06, 1999


Temperature : 26 °C

Humidity : 70%

| Emission Frequency (MHz) | Meter Reading (dBuV) |      | CORR'd Factor (dB) | Results (dBuV) |      | Limit (dBuV) | Margins (dB) |
|--------------------------|----------------------|------|--------------------|----------------|------|--------------|--------------|
|                          | L1                   | L2   |                    | L1             | L2   |              |              |
| 0.487                    | ***                  | 42.2 | 0.1                | ***            | 42.3 | 48.0         | -5.7         |
| 0.535                    | 40.1                 | ***  | 0.1                | 40.2           | ***  | 48.0         | -7.8         |
| 0.780                    | ***                  | 41.6 | 0.1                | ***            | 41.7 | 48.0         | -6.3         |
| 0.848                    | 40.2                 | ***  | 0.1                | 40.3           | ***  | 48.0         | -7.7         |
| 1.182                    | 39.2                 | ***  | 0.2                | 39.4           | ***  | 48.0         | -8.6         |
| 1.204                    | ***                  | 40.4 | 0.2                | ***            | 40.6 | 48.0         | -7.4         |
| 2.855                    | 31.2                 | ***  | 0.2                | 31.4           | ***  | 48.0         | -16.6        |
| 3.077                    | ***                  | 31.4 | 0.2                | ***            | 31.6 | 48.0         | -16.4        |
| 7.468                    | 32.0                 | ***  | 0.3                | 32.3           | ***  | 48.0         | -15.7        |
| 7.608                    | ***                  | 33.0 | 0.3                | ***            | 33.3 | 48.0         | -14.7        |

Note :


1. "\*\*\*\*" means the noise is too low to be measured.
2. The full frequency range scanning test data is shown in next two pages.



dBuV 80 70 60 50 40 30 20 10 0

Mkr 0.473705MHZ 41.8dBuV

Date 06.JUL.'99 Time 14:01:53  
FCC PART 15 LINE: L1 LINE MODE FULL LOAD



----- Date 06. JUL. '99 Time 14:04:52  
FCC PART 15 LINE: L2 LINE MODE FULL LOAD



# ELECTRONICS TESTING CENTER, TAIWAN

## B.

Model No./Type No. : PRO 700

Operation Mode : Battery Mode

EUT Power : AC 110V/60Hz

Test Date : Jul. 06, 1999

Temperature : 26 °C

Humidity : 70%


| Emission Frequency (MHz) | Meter Reading (dBuV) |      | CORR'd Factor (dB) | Results (dBuV) |      | Limit (dBuV) | Margins (dB) |
|--------------------------|----------------------|------|--------------------|----------------|------|--------------|--------------|
|                          | L1                   | L2   |                    | L1             | L2   |              |              |
| 0.500                    | ***                  | 43.6 | 0.1                | ***            | 43.7 | 48.0         | -4.3         |
| 0.524                    | 41.4                 | ***  | 0.1                | 41.5           | ***  | 48.0         | -6.5         |
| 0.766                    | 40.0                 | ***  | 0.1                | 40.1           | ***  | 48.0         | -7.9         |
| 1.092                    | ***                  | 43.8 | 0.2                | ***            | 44.0 | 48.0         | -4.0         |
| 1.117                    | 39.4                 | ***  | 0.2                | 39.6           | ***  | 48.0         | -8.4         |
| 2.060                    | ***                  | 43.0 | 0.2                | ***            | 43.2 | 48.0         | -4.8         |
| 2.391                    | 43.2                 | ***  | 0.2                | 43.4           | ***  | 48.0         | -4.6         |
| 7.573                    | 31.6                 | ***  | 0.3                | 31.9           | ***  | 48.0         | -16.1        |
| 7.861                    | ***                  | 34.4 | 0.3                | ***            | 34.7 | 48.0         | -13.3        |
| 13.134                   | ***                  | 36.8 | 0.4                | ***            | 37.2 | 48.0         | -10.8        |
| 13.570                   | 35.4                 | ***  | 0.4                | 35.8           | ***  | 48.0         | -12.2        |
| 15.978                   | ***                  | 37.0 | 0.4                | ***            | 37.4 | 48.0         | -10.6        |

Note :


1. "\*\*\*\*" means the noise is too low to be measured.
2. The full frequency range scanning test data is shown in next two pages.



ELECTRONICS TESTING CENTER TAIWAN



!---- Date 06. JUL. '99 Time 14:12:07  
FCC PART 15 LINE: L1 BAT. MODE FULL LOAD



!---- Date 06.JUL.'99 Time 14:16:27  
FCC PART 15 LINE:L2 BAT. MODE FULL LOAD

#### 5.4 Result Data Calculation

The result data is calculated by adding the LISN Factor to the measured reading. The basic equation with a sample calculation is as follows:

$$\mathbf{RESULT = READING + LISN FACTOR}$$

Assume a receiver reading of 22.5 dB  $\mu$  V is obtained, and LISN Factor is 0.1 dB, then the total of field strength is 22.6 dB  $\mu$  V.

$$\mathbf{RESULT = 22.5 + 0.1 = 22.6 \text{ dB } \mu \text{ V}}$$

$$\begin{aligned} \text{Level in } \mu \text{ V} &= \text{Common Antilogarithm}[(22.6 \text{ dB } \mu \text{ V})/20] \\ &= 13.48 \mu \text{ V} \end{aligned}$$

#### 5.5 Conducted Measurement Equipment

The following test equipment are used during the conducted test .

| Equipment                            | Manufacturer      | Model No. | Serial No. | Calibrated until |
|--------------------------------------|-------------------|-----------|------------|------------------|
| EMI Test Receiver                    | Rohde and Schwarz | ESH3      | 894718/018 | Jan. 20, 2000    |
| Line Impedance Stabilization network | EMCO              | 3825/2    | 9704-2677  | Oct. 29, 1999    |
| Line Impedance Stabilization network | EMCO              | 3825/2    | 9704-2678  | Oct. 29, 1999    |
| Plotter                              | Hewlett-Packard   | 7470A     | ----       | N/A              |

Note: The standards used to perform this calibration are traceable to NML/ROC and NIST/USA.