

Certification Exhibit

FCC ID: HSW-CCT24 IC: 4492A-CCT24

FCC Rule Part: 15.247 IC Radio Standards Specification: RSS-210

ACS Project Number: 14-0204

Manufacturer: RF Monolithics Model: CCT24

RF Exposure

Model: CCT24 FCC ID: HSW-CCT24 IC: 4492A-CCT24

General Information:

Applicant: RF Monolithics

Device Category: Mobile

Environment: General Population/Uncontrolled Exposure

Technical Information:

Antenna Type / Gain: Dipole, 9dBi

Corner Reflector, 14dBi

Patch, 12dBi Yagi, 13.9dBi PIFA, 4dBi CP Beam, 14dBi

Maximum Transmitter Conducted Power: 18.52 dBm, 71.12 mW

Maximum System EIRP: 32.52 dBm, 1786.49 mW Exposure Conditions: Greater than 20 centimeters

MPE Calculation

The Power Density (mW/cm²) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment							
Limits for General Population/Uncontrolled Exposure*							
Transmit	Radio	Power	Radio	Antenna	Antenna	Distance	Power
Frequency	Power	Density Limit	Power	Gain	Gain		Density
(MHz)	(dBm)	(mW/Cm2)	(mW)	(dBi)	(mW eq.)	(cm)	(mW/cm^2)
2443.75	18.52	1.00	71.12	14	25.119	20	0.355

Installation Guidelines

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

RF Exposure

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

Conclusion

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.