

## **Certification Exhibit**

**FCC ID: HSW-DNT900  
IC: 4492A-DNT900**

**FCC Rule Part: 15.247  
IC Radio Standards Specification: RSS-210**

**ACS Report Number: 12-0339**

Manufacturer: Cirronet Inc.  
Model(s): DNT900C, DNT900P

## **RF Exposure**

**General Information:**

Applicant: Cirronet, Inc.  
 Device Category: Mobile  
 Environment: General Population/Uncontrolled Exposure

**Technical Information DTS:**

Antenna Type: Printed Circuit Inverted F antenna  
 Antenna Gain: 0 dBi  
 Maximum Transmitter Conducted Power: 17.53dBm  
 Maximum System EIRP: 17.53 dBm, 230.7 mW  
 Exposure Conditions: Greater than 20 centimeters

**Technical Information DSS:**

Antenna Type: Printed Circuit Inverted F antenna  
 Antenna Gain: 0 dBi  
 Maximum Transmitter Conducted Power: 29.72dBm  
 Maximum System EIRP: 29.72 dBm, 3733 mW  
 Exposure Conditions: Greater than 20 centimeters

**MPE Calculation**

The Power Density (mW/cm<sup>2</sup>) is calculated as follows:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

MPE Calculator for Mobile Equipment Limits for General Population/Uncontrolled Exposure*							
Transmit Frequency (MHz)	Radio Power (dBm)	Power Density Limit (mW/Cm2)	Radio Power (mW)	Antenna Gain (dBi)	Antenna Gain (mW eq.)	Distance (cm)	Power Density (mW/cm^2)
915.25	17.53	0.61	56.62	0	1.000	20	0.011
902.75	29.72	0.60	937.56	0	1.000	20	0.187

**Installation Guidelines**

The installation manual should contain text similar to the following advising how to install the equipment to maintain compliance with the FCC RF exposure requirements:

**RF Exposure**

In accordance with FCC requirements of human exposure to radio frequency fields, the radiating element shall be installed such that a minimum separation distance of 20 centimeters will be maintained.

**Conclusion**

This device complies with the MPE requirements by providing adequate separation between the device, any radiating structure and the general population.