

U.S. Technologies, Inc
Rev: 040103
Issue Date: March 20, 2006
Model:WIT2410 G

FCC Part 15C
Report Number: 05-0311
CustomerC:irronet Corporation

RF EXPOSURE

5.1 RF Safety Requirements to 2.1091 for Mobile Transmitters

The unit under evaluation has one integral antenna. Cirronet Corporation calculated the MPE emission values for an EM2420HP. They used the formula shown in OET Bulletin 65 and calculated the minimum distance between antenna and unsuspecting user as 20 cm.

5.1 RF Safety Requirements to 2.1091 for Mobile Transmitters – Cont.

Power Output

The EUT's maximum expected output power as shown in Section 2.6 was

| Frequency of Fundamental (MHz) | Measurement (dBm)* | Measurement (mW)* | FCC Limit (Watt) |
|--------------------------------|--------------------|-------------------|------------------|
| 2405.43 | 17.86 | 61.09 | 1.0 |
| 2444.30 | 17.67 | 58.48 | 1.0 |
| 2475.50 | 17.62 | 57.81 | 1.0 |

The maximum EIRP expected is with a +0 dBi gain patch antenna. This would yield a maximum EIRP of 17.86 dBm.

+17.81 dBm

Antilog (17.81 dBm/10) = 61.09 mW

MPE Calculations

The limits for this unit (uncontrolled exposure) are 1.0 mW/cm². Taking the RF Density Field Equation:

$S = (\text{EIRP in mW}) / (4\pi R^2)$ and solving for Density S at 20 cm.

$$S = 61.09 / 4\pi 20^2$$

$$S = 61.09 / 5026.55$$

$$S = 0.012 \text{ mW/cm}^2$$

All manual instructions will specify 20 cm for all installations.