



NOTES:

1. MATERIAL: 2 MIL WHITE MYLAR, WITH 1 MIL CLEAR LAMINATE OVER SERIAL #'S TO PREVENT RUBBING OFF WHEN EXPOSED TO ALCOHOL OR OTHER CLEANING FLUIDS.
2. ADHESIVE: 3M - 350 SERIES ADHESIVES.
3. MATING MATERIAL: BLACK MINI-TEX POWDER COAT #UFB-400-T3.
4. TEMPERATURE RANGE: -40°C TO 70°C
5. DECAL: BLACK BACKGROUND WITH WHITE TEXT.
6. SERIAL NUMBER: WHITE BACKGROUND WITH BLACK TEXT AND BARCODE.
7. FONT: TIMES
8. SERIAL # MUST NOT DISOLVE (RUB OFF) WHEN EXPOSED TO ALCOHOL OR OTHER CLEANING FLUIDS.
9. UNIQUE SERIAL NUMBER SEQUENCE TO BE STATED WITH PURCHASE ORDER. (REPRESENTED BY "XXXXX")
10. USE LEADING ZERO(S) AS PLACE HOLDER(S) FOR A TOTAL OF 5 DIGITS.



Actual Size



PROPRIETARY AND CONFIDENTIAL  
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SONCELL NORTH AMERICA. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SONCELL NORTH AMERICA IS PROHIBITED.

SCALE:	2:1	UNLESS OTHERWISE SPECIFIED:
DRAWN:	DFox	DIMENSIONS ARE IN INCHES
MFG APPR:		TOLERANCES:
CHECKED:	TCottle	ANGULAR: ±1 degree
ENG APPR:		TWO SPACE DECIMAL: ± .030
MATERIAL:	2 Mil White Mylar	THREE SPACE DECIMAL: ± .010
FINISH:	1 Mil Clear Laminate	

DESCRIPTION: SI-3 Serial Tag		
SIZE A	SW-FILE NAME: S1051-85A_ AEP PART NUMBER: DEI PART NUMBER: S1051-85	REV. B
DATE:	7/29/2013	SHEET 1 OF 1



**Decatur Electronics, Inc.**

3433 East Wood St. Phoenix, AZ. 85040 (888) 428-4315

MODEL: SI-3 FCC ID: HTR-SI3 IC: 1270A-SI3

This device complies with Part 15 of the FCC Rules and with Industry Canada license-exempt RSS standard(s). Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation.

S/N:



SI3-XXXXX