



- **Material:** 8mil Autotex XE Velvet Polyester.
- **Adhesive:** 3M 350 Series Adhesive.
- **Mating Material:** Smooth ABS Plastic.
- **Temperature Range:** -40°C to 70°C
- **Revision C:** Updated Phone number & Canada 310
- **Serialization:**
 - Must Resist Cleaning Solvents Such as Alcohol.
 - Unique Serial Numbers Sequence to be Stated with Purchase Order.
 - Use leading Zero(s) as Place Holder(s) for a Total of Five Digits.
 - White Background with Black Text and Barcode.



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF SONCELL NORTH AMERICA. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF SONCELL NORTH AMERICA IS PROHIBITED.

SCALE:	1:1
DRAWN:	DFox
MFG APPR:	
CHECKED:	
ENG APPR:	
MATERIAL:	8mil Autptex XE Velvet Polyester
FINISH:	Velvet

UNLESS OTHERWISE SPECIFIED:	
DIMENSIONS ARE IN INCHES	
TOLERANCES:	
ANGULAR:	±1 degree
TWO SPACE DECIMAL:	± .030
THREE SPACE DECIMAL:	± .010

DESCRIPTION: SI-3L Serial Decal			
SIZE A	SW-FILE NAME:	S1051-156	REV. C
	AEP PART NUMBER:		
	DEI PART NUMBER:	S1051-156	
DATE:	2/7/2013	SHEET 1 OF 1	