

RF Exposure Evaluation Report

FCC ID : HV4CTL6100WLA
Equipment : Pen Tablet
Brand Name : Wacom
Model Name : CTL-6100WL, CTL-6100WLA
Applicant : Wacom Co., Ltd.
2-510-1 Toyonodai, Kazo-shi, Saitama 349-1148 Japan
Manufacturer : Wacom Co., Ltd.
2-510-1 Toyonodai, Kazo-shi, Saitama 349-1148 Japan
Standard : 47 CFR FCC Part 2 Subpart J, section 2.1093

The product was received on Sep. 15, 2021, and testing was started from Sep. 27, 2021 and completed on Nov. 02, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in KDB447498 D01 General RF Exposure Guidance v06 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.



Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

1. General Description.....4

1.1. EUT General Information4

1.2. Antenna Information.....4

1.3. Table for Multiple Listing4

1.4. Testing Location Information4

2. RF Exposure Evaluation5

2.1. Applicable Standard5

2.2. SAR evaluation5

Photographs of EUT V01



History of This Test Report

Report No.	Version	Description	Issued Date
FA7N1310-09	01	Initial issue of report	Nov. 19, 2021

Reviewed by: Sam Tsai

Report Producer: Michelle Tsai



1. General Description

1.1. EUT General Information

RF General Information			
Evaluation Mode	Frequency Range (MHz)	Operating Frequency (MHz)	Modulation Type
Bluetooth	2400-2483.5	2402-2480	BR / EDR: FHSS (GFSK / $\pi/4$ -DQPSK / 8DPSK)

1.2. Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	-	pcbmonoA2	PCB antenna	I-PEX	0

Note 1: The EUT has one antenna.

For BT function:

For IEEE 802.15.1 Bluetooth mode (1TX/1RX)

Only Ant. 1 (port 1) can be used as transmitting/receiving.

1.3. Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Model Name	Description
CTL-6100WL***** (* may be alphanumeric/symbol or blank)	All the models are identical, the different model served as marketing strategy.

1.4. Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory	
<input checked="" type="checkbox"/> Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.) TEL: 886-3-327-3456 FAX: 886-3-327-0973 Test site Designation No. TW3785 with FCC.
<input type="checkbox"/> Wen 33rd.St. (TAF: 3785)	ADD: No.14-1, Ln. 19, Wen 33rd St., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: 886-3-318-0787 FAX: 886-3-318-0287 Test site Designation No. TW0008 with FCC.



2. RF Exposure Evaluation

2.1. Applicable Standard

In accordance with FCC 47 CFR part 2 (2.1093) this device has been defined as a portable device which is defined as a transmitting device designed to be used so that the radiating structure(s) of the device is/are within 20 centimeters of the body of the user.

Portable devices must be evaluated using the specified in FCC 47 CFR part 2 (2.1093) and ANSI/IEEE C95.1-1992, and had been tested in accordance with the measurement methods and procedures specified in IEEE 1528-2003.

2.2. SAR evaluation

1. Per FCC KDB 447498 D01 v06, the 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot$$

$$[\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR}$$

- ♦ $f_{(\text{GHz})}$ is the RF channel transmit frequency in GHz
- ♦ Power and distance are rounded to the nearest mW and mm before calculation
- ♦ The result is rounded to one decimal place for comparison

Max. Power (dBm)	Tolerance (dB)	Tune-up Max. Power (dBm)	Tune-up Max. Power (mW)	Test Distance (mm)	Frequency (GHz)	Exclusion Thresholds
5.69	0.0	5.69	3.71	5	2.480	1.17

2. Per FCC KDB 447498 D01 v06 exclusion thresholds is $1.17 < 3$, RF exposure evaluation is not required.

—————THE END—————