


# FCC Test Report

**Equipment** : LCD Tablet  
**Brand Name** : Wacom  
**Model No.** : DTH-1620  
**FCC ID** : HV4DTH1620  
**Standard** : 47 CFR FCC Part 15.209  
**RF Specification** : SRD  
**Operating Band** : 667kHz  
**FCC Classification** : DCD  
**Applicant / Manufacturer** : Wacom Co., Ltd.  
2-510-1 Toyonodai, Kazo-shi, Saitama 349-1148 Japan

The product sample received on Oct. 05, 2016 and completely tested on Oct. 18, 2016. We, SPORTON, would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.10-2013 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by:



Phoenix Chen / Assistant Manager





## Table of Contents

<b>1</b>	<b>GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1	Information.....	5
1.2	Testing Applied Standards .....	6
1.3	Testing Location Information .....	6
1.4	Measurement Uncertainty .....	7
<b>2</b>	<b>TEST CONFIGURATION OF EUT.....</b>	<b>8</b>
2.1	The Worst Case Modulation Configuration .....	8
2.2	Test Channel Frequencies Configuration.....	8
2.3	The Worst Case Measurement Configuration.....	8
2.4	Accessory and Support Equipment.....	9
2.5	Test Setup Diagram .....	10
<b>3</b>	<b>TRANSMITTER TEST RESULT .....</b>	<b>11</b>
3.1	AC Power-line Conducted Emissions .....	11
3.2	Transmitter Radiated Emissions .....	15
3.3	Emission Bandwidth .....	23
<b>4</b>	<b>TEST EQUIPMENT AND CALIBRATION DATA.....</b>	<b>25</b>

### APPENDIX A. TEST PHOTOS

#### PHOTOGRAPHS OF EUT V01



### Summary of Test Result

Conformance Test Specifications					
Report Clause	Ref. Std. Clause	Description	Measured	Limit	Result
1.1.3	15.203	Antenna Requirement	Antenna connector mechanism complied	FCC 15.203	Complied
3.1	15.207	AC Power-line Conducted Emissions	[dBuV]: 0.45MHz 34.62 (Margin 12.31dB) - AV 43.49 (Margin 13.44dB) - QP	FCC 15.207	Complied
3.2	15.209	Transmitter Radiated Emissions	[dBuV/m at 3m]: 30.00MHz 15.97 (Margin 24.03dB) - QP	FCC 15.209	Complied
3.3	15.215(c)	Emission Bandwidth	99% Bandwidth: 29.37 [kHz] 20dB Bandwidth: 33.50 [kHz]	N/A	Complied



### Revision History

Report No.	Version	Description	Issued Date
FR6O0419	Rev. 01	Initial issue of report	Feb. 22, 2017



# 1 General Description

## 1.1 Information

### 1.1.1 Product Details

The difference between the report no. : N/A	
The Difference	N/A

Evaluated Test Items	N/A
----------------------	-----

### 1.1.2 RF General Information

RF General Information			
Frequency		667kHz	
Modulation	Ch. Frequency (kHz)	Channel Number	Field Strength (dBuV/@1m)
ASK	667	1	49.30

Note 1: Field strength performed peak level at 1m.

### 1.1.3 Antenna Information

Antenna Category	
<input checked="" type="checkbox"/>	Integral antenna (antenna permanently attached)
<input type="checkbox"/>	Temporary RF connector provided
<input checked="" type="checkbox"/>	No temporary RF connector provided Transmit chains bypass antenna and soldered temporary RF connector provided for connected measurement. In case of conducted measurements the transmitter shall be connected to the measuring equipment via a suitable attenuator and correct for all losses in the RF path.
<input type="checkbox"/>	External antenna (dedicated antennas)

Antenna General Information		
No.	Ant. Cat.	Ant. Type
1	Integral	Array Coli Pointing

**1.1.4 Type of EUT**

Identify EUT	
EUT Serial Number	N/A
Presentation of Equipment	<input checked="" type="checkbox"/> Production ; <input type="checkbox"/> Pre-Production ; <input type="checkbox"/> Prototype
Type of EUT	
<input checked="" type="checkbox"/>	Stand-alone
<input type="checkbox"/>	Combined (EUT where the radio part is fully integrated within another device) Combined Equipment - Brand Name / Model No.: ...
<input type="checkbox"/>	Plug-in radio (EUT intended for a variety of host systems) Host System - Brand Name / Model No.: ...
<input type="checkbox"/>	Other:

**1.1.5 Test Signal Duty Cycle**

Operated Mode for Worst Duty Cycle	
<input checked="" type="checkbox"/>	Operated normal mode for worst duty cycle
<input type="checkbox"/>	Operated test mode for worst duty cycle
Test Signal Duty Cycle (x)	
<input checked="" type="checkbox"/>	100.00%

**1.1.6 EUT Operational Condition**

<b>Supply Voltage</b>	<input checked="" type="checkbox"/> AC mains	<input checked="" type="checkbox"/> DC	
<b>Type of DC Source</b>	<input checked="" type="checkbox"/> External AC adapter	<input checked="" type="checkbox"/> From Battery	<input type="checkbox"/> From System

**1.2 Testing Applied Standards**

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR FCC Part 15
- ♦ ANSI C63.10-2013

**1.3 Testing Location Information**

Testing Location				
<input checked="" type="checkbox"/>	HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.		
		TEL : 886-3-327-3456 FAX : 886-3-327-0973		
Test Site Registration Number: 553509				
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
AC Conduction	CO04-HY	Ryan	23°C / 60%	18/10/2016
RF Conducted	TH01-HY	Lisa	23°C / 63%	12/10/2016
Radiated Emission	03CH03-HY	Jeff	24.1°C / 54%	12/10//2016

Test Site Registration Number: 553509

## 1.4 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))

Measurement Uncertainty		
Test Item		Uncertainty
AC power-line conducted emissions		±2.3 dB
Emission bandwidth, 6dB bandwidth		±0.6 %
RF output power, conducted		±0.1 dB
Power density, conducted		±0.6 dB
Unwanted emissions, conducted	9 – 150 kHz	±0.4 dB
	0.15 – 30 MHz	±0.4 dB
	30 – 1000 MHz	±0.6 dB
	1 – 18 GHz	±0.5 dB
	18 – 40 GHz	±0.5 dB
	40 – 200 GHz	N/A
All emissions, radiated	9 – 150 kHz	±2.5 dB
	0.15 – 30 MHz	±2.3 dB
	30 – 1000 MHz	±2.6 dB
	1 – 18 GHz	±3.6 dB
	18 – 40 GHz	±3.8 dB
	40 – 200 GHz	N/A
Temperature		±0.8 °C
Humidity		±5 %
DC and low frequency voltages		±0.9 %
Time		±1.4 %
Duty Cycle		±0.6 %

## 2 Test Configuration of EUT

### 2.1 The Worst Case Modulation Configuration




Transmitter Mode	Field Strength (dBuV/m@1m)	Field Strength (dBuV/m@3m)
Touch Pen	49.30	30.22

### 2.2 Test Channel Frequencies Configuration

Modulation	Test Channel Frequencies (kHz)
ASK	667

### 2.3 The Worst Case Measurement Configuration

The Worst Case Mode for Following Conformance Tests	
Tests Item	AC power-line conducted emissions
Condition	AC power-line conducted measurement for line and neutral Test Voltage: 120Vac / 60Hz
Operating Mode	Operating Mode Description
1	Adapter Mode

The Worst Case Mode for Following Conformance Tests			
Tests Item	Emission Bandwidth, Field Strength of Fundamental Emissions Transmitter Radiated Unwanted Emissions		
Test Condition	Radiated measurement		
User Position	<input type="checkbox"/> EUT will be placed in fixed position.		
	<input type="checkbox"/> EUT will be placed in mobile position and operating multiple positions. EUT shall be performed three orthogonal planes.		
	<input checked="" type="checkbox"/> EUT will be a hand-held or body-worn battery-powered devices and operating multiple positions.		
Operating Mode	Operating Mode Description		
1	Adapter Mode		
Transmitter Mode	Touch Pen		
Orthogonal Planes of EUT	X Plane	Y Plane	Z Plane
			
Worst Planes of EUT			V





### 2.4 Accessory and Support Equipment

Accessories Information				
AC Adapter	Brand Name	WACOM	Model Name	ADP-45XE B
	Power Rating	I/P: 100-240Vac, 50-60Hz, 1.2A, O/P: 20Vdc, 2.2.5A or 15Vdc, 3A or 9Vdc, 3A or 5Vdc, 3A		
	Power Cord	1.75 meter, non-shielded cable, w/o ferrite core		
Type-C USB Cable	Brand Name	ACON	Model Name	STJ-A368
	Signal Line	1 meter, non-shielded cable, with w/o ferrite core		
USB cable	Brand Name	ACON	Model Name	STJ-A370
	Signal Line	1.8 meter, non-shielded cable, with w/o ferrite core		
Mini DP to Mini DP cable	Brand Name	ACON	Model Name	STJ-A369
	Signal Line	1.8 meter, non-shielded cable, with w/o ferrite core		
LCD Panel	Brand Name	BOE	Model Name	WAP1551-01
Touch Pen	Brand Name	Wacom	Model Name	KP-504E-00
Dongle	Brand Name	Wacom	Model Name	INF-A123


Note: Regarding to more detail and other information, please refer to user manual.

Support Equipment – RF Conducted			
No.	Equipment	Brand Name	Model Name
1	-	-	-

Support Equipment – AC Line Conducted Emission			
No.	Equipment	Brand Name	Model Name
1	-	-	-

Support Equipment – Radiated Emission			
No.	Equipment	Brand Name	Model Name
1	-	-	-

## 2.5 Test Setup Diagram



### 3 Transmitter Test Result

#### 3.1 AC Power-line Conducted Emissions

##### 3.1.1 AC Power-line Conducted Emissions Limit

AC Power-line Conducted Emissions Limit		
Frequency Emission (MHz)	Quasi-Peak	Average
0.15-0.5	66 - 56 *	56 - 46 *
0.5-5	56	46
5-30	60	50

Note 1: \* Decreases with the logarithm of the frequency.


##### 3.1.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

##### 3.1.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10-2013, clause 6.2 for AC power-line conducted emissions.
<input checked="" type="checkbox"/>	If AC conducted emissions fall in operating band, then following below test method confirm final result.
<input type="checkbox"/>	Accept measurements done with a suitable dummy load replacing the antenna under the following conditions: (1) Perform the AC line conducted tests with the antenna connected to determine compliance with FCC 15.207 limits outside the transmitter's fundamental emission band; (2) Retest with a dummy load to determine compliance with FCC 15.207 limits within the transmitter's fundamental emission band.
<input checked="" type="checkbox"/>	For a device with a permanent antenna operating at or below 30 MHz, accept measurements done with a suitable dummy load, in lieu of the permanent antenna under the following conditions: (1) Perform the AC line conducted tests with the permanent antenna to determine compliance with the FCC 15.207 limits outside the transmitter's fundamental emission band; (2) Retest with a dummy load in lieu of the permanent antenna to determine compliance with the FCC 15.207 limits within the transmitter's fundamental emission band.


### 3.1.4 Test Setup





3.1.5 Test Result of AC Power-line Conducted Emissions

AC Power-line Conducted Emissions Result			
Operating Mode	1	Power Phase	Neutral
Ch. Frequency (kHz)	667		




	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Aux Factor	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	dB	
1	0.16	37.20	-18.36	55.56	27.00	0.10	0.23	9.87	Average
2	0.16	50.75	-14.81	65.56	40.55	0.10	0.23	9.87	QP
3	0.20	29.63	-24.13	53.76	19.35	0.11	0.30	9.87	Average
4	0.20	43.07	-20.69	63.76	32.79	0.11	0.30	9.87	QP
5	0.24	27.23	-24.81	52.04	17.01	0.11	0.24	9.87	Average
6	0.24	37.75	-24.29	62.04	27.53	0.11	0.24	9.87	QP
7	0.42	31.85	-15.65	47.50	21.75	0.12	0.10	9.88	Average
8	0.42	41.95	-15.55	57.50	31.85	0.12	0.10	9.88	QP
9	0.54	25.84	-20.16	46.00	15.74	0.12	0.10	9.88	Average
10	0.54	35.70	-20.30	56.00	25.60	0.12	0.10	9.88	QP
11	1.24	25.72	-20.28	46.00	15.54	0.14	0.16	9.88	Average
12	1.24	35.01	-20.99	56.00	24.83	0.14	0.16	9.88	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)  
 Note 3: When emissions are in operating band over limits, retest with a dummy load for final in-band results.



**AC Power-line Conducted Emissions Result**

<b>Operating Mode</b>	1	<b>Power Phase</b>	Line
<b>Ch. Frequency (kHz)</b>	667		



	Freq	Level	Over	Limit	Read	LISN	Cable	Aux	Remark
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Factor	
			dB	dBuV	dBuV	dB	dB	dB	
1	0.16	35.92	-19.64	55.56	25.71	0.11	0.23	9.87	Average
2	0.16	50.37	-15.19	65.56	40.16	0.11	0.23	9.87	QP
3	0.20	34.10	-19.37	53.47	23.82	0.11	0.30	9.87	Average
4	0.20	42.92	-20.55	63.47	32.64	0.11	0.30	9.87	QP
5	0.25	33.07	-18.84	51.91	22.85	0.11	0.24	9.87	Average
6	0.25	40.01	-21.90	61.91	29.79	0.11	0.24	9.87	QP
7	0.38	29.06	-19.23	48.29	18.94	0.12	0.12	9.88	Average
8	0.38	40.60	-17.69	58.29	30.48	0.12	0.12	9.88	QP
9	0.45	34.62	-12.31	46.93	24.52	0.12	0.10	9.88	Average
10	0.45	43.49	-13.44	56.93	33.39	0.12	0.10	9.88	QP
11	0.62	24.51	-21.49	46.00	14.41	0.12	0.10	9.88	Average
12	0.62	35.24	-20.76	56.00	25.14	0.12	0.10	9.88	QP

Note 1: ">20dB" means emission levels that exceed the level of 20 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found emissions (No emissions were detected.)  
 Note 3: When emissions are in operating band over limits, retest with a dummy load for final in-band results.

### 3.2 Transmitter Radiated Emissions

#### 3.2.1 Transmitter Radiated Emissions Limit

Transmitter Radiated Emissions Limit			
Frequency Range (MHz)	Field Strength (uV/m)	Field Strength (dBuV/m)	Measure Distance (m)
0.009~0.490	2400/F(kHz)	48.5 - 13.8	300
0.490~1.705	24000/F(kHz)	33.8 - 23	30
1.705~30.0	30	29	30
30~88	100	40	3
88~216	150	43.5	3
216~960	200	46	3
Above 960	500	54	3

Note 1: Test distance for frequencies at or above 30 MHz, measurements may be performed at a distance other than the limit distance provided they are not performed in the near field and the emissions to be measured can be detected by the measurement equipment. When performing measurements at a distance other than that specified, the results shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade (inverse of linear distance for field-strength measurements, inverse of linear distance-squared for power-density measurements).

Note 2: Test distance for frequencies at below 30 MHz, measurements may be performed at a distance closer than the EUT limit distance; however, an attempt should be made to avoid making measurements in the near field. When performing measurements below 30 MHz at a closer distance than the limit distance, the results shall be extrapolated to the specified distance by either making measurements at a minimum of two or more distances on at least one radial to determine the proper extrapolation factor or by using the square of an inverse linear distance extrapolation factor (40 dB/decade). The test report shall specify the extrapolation method used to determine compliance of the EUT.

Note 3: the frequency bands 9-90 kHz, 110-490 kHz measurements employing an average detector and other below 1GHz measurements employing a CISPR quasi-peak detector.

#### 3.2.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.




3.2.3 Test Procedures

Test Method	
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.5 for radiated emissions from 30 MHz to 1 GHz and test distance is 3m.
<input checked="" type="checkbox"/>	Refer as ANSI C63.10, clause 6.4 for radiated emissions from below 30 MHz. The frequency bands 9-90 kHz, 110-490 kHz measurements employing an average detector and other below 30MHz measurements employing a CISPR quasi-peak detector. Test distance is 3m.
<input checked="" type="checkbox"/>	At frequencies below 30 MHz, measurements may be performed at a distance closer than that specified in the requirements; however, an attempt should be made to avoid making measurements in the near field. Pending the development of an appropriate measurement procedure for measurements performed below 30 MHz, when performing measurements at a closer distance than specified, the results shall be following below methods. Note: If fundamental emission level is smaller than noise at 3m , we will change distance to 1m.
<input type="checkbox"/>	The results shall be extrapolated to the specified distance by making measurements at a minimum of two distances on at least one radial to determine the proper extrapolation factor.
<input checked="" type="checkbox"/>	The results shall be by using the square of an inverse linear distance extrapolation factor (40 dB/decade).
<input checked="" type="checkbox"/>	For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.
<input checked="" type="checkbox"/>	The any unwanted emissions level shall not exceed the fundamental emission level.
<input checked="" type="checkbox"/>	All amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.




### 3.2.4 Test Setup





3.2.5 Transmitter Radiated Emissions (Below 30MHz)

Transmitter Radiated Emissions (667 kHz)			
Mode	Touch Pen	Test Freq.(kHz)	667
Operating Mode	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	0.667	49.30	-40.91	90.21	28.33	20.74	0.23	0.00	Peak

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.  
 Note 5: Test fundamental emission at 1m  
 Note 6: Below 30MHz of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.



Transmitter Radiated Emissions (9kHz~150kHz)			
Mode	Touch Pen	Test Freq.(kHz)	667
Operating Mode	1	Polarization	H




	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor	
			dB	dBuV/m	dBuV	dB	dB	
1	0.063	13.55	-98.09	111.64	-7.60	21.00	0.15	0.00 QP
2	0.073	19.91	-90.40	110.31	-1.24	21.00	0.15	0.00 QP
3	0.093	19.87	-88.36	108.23	-1.39	21.10	0.16	0.00 QP

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.  
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.  
 Note 6: Below 30MHz of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.



Transmitter Radiated Emissions (150kHz~30MHz)			
Mode	Touch Pen	Test Freq.(kHz)	667
Operating Mode	1	Polarization	H




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB
1	13.045	15.65	-53.89	69.54	-6.19	21.36	0.48	0.00 QP
2	21.881	14.36	-55.18	69.54	-7.87	21.54	0.69	0.00 QP
3	27.075	13.48	-56.06	69.54	-8.92	21.64	0.76	0.00 QP

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement worst emissions of receive antenna polarization: H (Horizontal).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.  
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.  
 Note 6: Below 30MHz of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.



3.2.6 Transmitter Radiated Emissions (Above 30MHz)

Transmitter Radiated Emissions (Above 30MHz)			
Mode	Touch Pen	Test Freq.(kHz)	667
Operating Mode	1	Polarization	V




	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	43.580	15.33	-24.67	40.00	26.17	15.73	0.95	27.52	QP
2	132.820	16.40	-27.10	43.50	25.13	16.72	1.79	27.24	QP
3	200.720	14.17	-29.33	43.50	24.44	14.37	2.28	26.92	QP
4	307.420	19.07	-26.93	46.00	24.61	18.48	2.68	26.70	QP
5	394.720	19.19	-26.81	46.00	21.91	20.76	3.22	26.70	QP
6	532.460	19.17	-26.83	46.00	20.06	23.37	3.61	27.87	QP

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.  
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.



**Transmitter Radiated Emissions (Above 30MHz)**

<b>Mode</b>	Touch Pen	<b>Test Freq.(kHz)</b>	667
<b>Operating Mode</b>	1	<b>Polarization</b>	H



Date: 2016-10-12

FCC/IC/NCC-B  
3dB

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Antenna Factor	Cable Loss	Preamp Factor	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	
1	30.000	15.97	-24.03	40.00	20.72	22.02	0.78	27.55	QP
2	156.100	18.97	-24.53	43.50	28.91	15.23	1.96	27.13	QP
3	266.680	19.37	-26.63	46.00	25.45	18.18	2.51	26.77	QP
4	344.280	16.59	-29.41	46.00	21.05	19.21	3.03	26.70	QP
5	540.220	19.85	-26.15	46.00	20.55	23.57	3.62	27.89	QP
6	747.800	18.90	-27.10	46.00	17.53	24.71	4.52	27.86	QP

Note 1: ">20dB" means spurious emission levels that exceed the level of 6 dB below the applicable limit.  
 Note 2: "N/F" means Nothing Found spurious emissions (No spurious emissions were detected.)  
 Note 3: Measurement receive antenna polarization: H (Horizontal), V (Vertical).  
 Note 4: No level of unwanted emissions exceeds the level of the fundamental emission.  
 Note 5: Except fundamental emission, other emissions from digital circuitry used to control additional panel functions or display capabilities other than the touch panel radio transmission. While disable touch panel radio transmission, other emissions have the same levels. Therefore other emissions level could be exceed the fundamental emission level.

### 3.3 Emission Bandwidth

#### 3.3.1 Emission Bandwidth Limit

Emission Bandwidth Limit
N/A


#### 3.3.2 Measuring Instruments

Refer a test equipment and calibration data table in this test report.

#### 3.3.3 Test Procedures

Test Method
<input checked="" type="checkbox"/> For the emission bandwidth refer ANSI C63.10, clause 6.9.3 for occupied bandwidth testing.
<input checked="" type="checkbox"/> For radiated measurement. Loop antenna was rotated about the horizontal and vertical axis and the equipment to be measured and the test antenna shall be oriented to obtain the maximum emitted field strength level.



#### 3.3.4 Test Setup





### 3.3.5 Test Result of Emission Bandwidth

Occupied Channel Bandwidth Result			
Transmitter Mode	Frequency (kHz)	99% Bandwidth (kHz)	20dB Bandwidth (kHz)
Touch Pen	667	29.37	33.50
Limit		N/A	
Result		Complied	







## 4 Test Equipment and Calibration Data

### <AC Power-line Conducted Emissions>

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date
EMC Receiver	R&S	ESR-3	102051	9KHz ~ 3.6GHz	19/04/2016	18/04/2017
LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	8127-477	9kHz ~ 30MHz	26/01/2016	25/01/2017
LISN (Support Unit)	R&S	ENV216	101295	9kHz ~ 30MHz	04/11/2015	03/11/2016
RF Cable-CON	HUBER+SUHNER	RG213/U	07611832020001	9kHz ~ 30MHz	30/10/2015	29/10/2016
EMI Filter	LINDGREN	LRE-2030	2651	< 450 Hz	NCR	NCR

NCR : Non-Calibration Require

### <RF Conducted>

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date
Spectrum Analyzer	R&S	FSV 40	101013	9KHz~40GHz	16/02/2016	15/02/2017

### <Radiated Emission>

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Calibration Due Date
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	30MHz ~ 1GHz 3m	28/11/2015	27/11/2016
3m Semi Anechoic Chamber	SIDT FRANKONIA	SAC-3M	03CH03-HY	1GHz ~ 18GHz 3m	16/12/2015	15/12/ 2016
Amplifier	HP	8447D	2944A08033	10kHz ~ 1.3GHz	10/05//2016	09/05/2017
Spectrum	R&S	FSP 40	100305	9kHz ~ 40GHz	16/02/2016	15/02/2017
Bilog Antenna	SCHAFFNER	CBL 6112B	2723	30MHz ~ 1GHz	01/10/2016	30/09/2017
Loop Antenna	TESEQ	HLA 6120	31244	9 kHz~30 MHz	02/02/2015	01/02/2017