



Maximum Permissible Exposure

FCC ID : HV4DTH167
Equipment : LCD TABLET
Brand Name : Wacom
Model Name : DTH167, DTH167K0A
Applicant : Wacom Co., Ltd.
2-510-1, Toyonodai, Kazo-shi, Saitama 349-1148 Japan
Manufacturer : Wacom Co., Ltd.
2-510-1, Toyonodai, Kazo-shi, Saitama 349-1148 Japan
Standard : 47 CFR Part 2.1093

The product was received on Apr. 14, 2021, and testing was started from Apr. 20, 2021 and completed on Apr. 20, 2021. We, SPORTON INTERNATIONAL INC. Hsinhua Laboratory, would like to declare that the tested sample has been evaluated in accordance with the procedures given in 47 CFR Part 2.1093 and shown compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. Hsinhua Laboratory, the test report shall not be reproduced except in full.

Approved by: Allen Lin

SPORTON INTERNATIONAL INC. Hsinhua Laboratory

No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)



Table of Contents

HISTORY OF THIS TEST REPORT3

1 GENERAL DESCRIPTION5

1.1 Information.....5

1.2 Testing Applied Standards6

1.3 Testing Location Information6

2 HUMAN EXPOSURE ASSESSMENT7

2.1 Maximum Permissible Exposure7

3 TEST EQUIPMENT AND CALIBRATION DATA10

APPENDIX A. TEST PHOTOS

PHOTOGRAPHS OF EUT V01



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
2	-	Maximum Permissible Exposure	PASS	-

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

None

Reviewed by: Sam Tsai

Report Producer: Amber Chiu



1 General Description

1.1 Information

1.1.1 EUT General Information

RF General Information			
Evaluation Mode	Frequency Range	Operating Frequency	Modulation Type
SRD	667 kHz	669.4 kHz	ASK

1.1.2 Antenna Information

Ant.	Brand	Model Name	Antenna Type	Connector
1	-	-	Array Coil Pointing	NA

1.1.3 Table for Multiple Listing

The model names in the following table are all refer to the identical product.

Brand Name	Model Name	Description
Wacom	DTH167, DTH167K0A	All the models are identical, the different models served as marketing strategy.

1.1.4 Accessories

Accessories				
AC Adapter	Brand Name	Delta	Model Name	DPS-65VB
	Power Rating	I/P: 100- 240Vac, 2A, O/P: 12Vdc, 5.417A		
Digital Pen	Brand Name	Wacom	Model Name	KP-504E-00
Pen Seat	Brand Name	Wacom	Model Name	-
USB Type-C to Type-A Cable	Brand Name	-	Model Name	JPA-W-J335-000
	Power Cord	1.8 meter, shielded cable, w/o ferrite core		
USB Type-C to Type-C Cable	Brand Name	-	Model Name	CBAUB-H39-100A
	Power Cord	1 meter, shielded cable, w/o ferrite core		
HDMI Cable	Brand Name	Wacom	Model Name	JPA-W-J163-000
	Power Cord	1.8 meter, shielded cable, w/o ferrite core		

Reminder: Regarding to more detail and other information, please refer to user manual.

1.1.5 Support Equipment

Support Equipment					
No.	Equipment	Brand Name	Model Name	FCC ID	Remark
1	Notebook	DELL	E5410	-	-
2	Adapter for NB	DELL	HA65NM130	-	-

1.2 Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2.1093

1.3 Testing Location Information

Test Lab. : Sporton International Inc. Hsinhua Laboratory				
<input checked="" type="checkbox"/>	Hsinhua (TAF: 3785)	ADD: No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333411, Taiwan (R.O.C.)		
		TEL: 886-3-327-3456	FAX: 886-3-327-0973	
Test site Designation No. TW3785 with FCC.				
Test Condition	Test Site No.	Test Engineer	Test Environment	Test Date
RF Conducted	TH01-HY	Vivi Jiang	20.1~26.9°C / 50~60%	20/Apr/2021



2 Human Exposure Assessment

2.1 Maximum Permissible Exposure

2.1.1 Limit of Maximum Permissible Exposure

(A) Limits for Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	-	-	F/300	6
1500-100,000	-	-	5	6

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	F/1500	30
1500-100,000	-	-	1.0	30

Note: f = frequency in MHz ; *Plane-wave equivalent power density


2.1.2 The Worst Condition

Ancillary Equipment	Operation condition
Touch Pen	Touch Panel

2.1.3 Test Method

Test Method	
<input checked="" type="checkbox"/>	Performed aggregate both leakage E-field and H-field at surrounding the device from all simultaneous transmitting coils.
<input checked="" type="checkbox"/>	During testing, the EUT was placed on a non-conductive table top and the ancillary equipment (e.g., mobile phone) was placed on the EUT for charging. Maximum E-field and H-field measurements were tested 0 cm from each side of the EUT. Along the side of the EUT to center of E-field probe and H-field probe were positioned at the location to search maximum field strength.
<input checked="" type="checkbox"/>	E-field transfer to H-field
-	E-field = Z ₀ × H-field H-field = E-field ÷ Z ₀ Where Z ₀ = Free Space Impedance = 377Ω

2.1.4 Test Setup



Note 1 : find worst position for each axis.



2.1.5 Result of Maximum Permissible Exposure

Maximum Permissible Exposure				
Charging Condition	Separation	Probe from EUT Side	E-field (V/m)	H-field (A/m)
Operating	0cm	Left	1.6875	0.0178
	0cm	Right	0.7813	0.0188
	0cm	Top	0.9219	0.0178
	0cm	Bottom	0.625	0.0188
	0cm	Y-axis above EUT	2.0469	0.0225
Limit			614.00	1.63
Margin Limit (%)			0.33%	1.38%



3 Test Equipment and Calibration Data

Instrument for Conducted Test

Instrument	Manufacturer/ Brand Name	Model No.	Serial No.	Spec.	Calibration Date	Calibration Due Date
Electric and Magnetic field Probe - Analyzer	Narda S.T.S. / PMM	EHP 200AC	180ZX00640	3kHz~30MHz	09/Nov/2020	08/Nov/2021