

**Token EMC Engineering Co., Ltd.**  
28-1 Kitahara-aza Hanashimashinden-ohaza  
Tsukuba-city Ibaragi 305-0875 Japan  
Tel +81-298-37-2400 Fax +81-298-37-2401

## EMC TEST REPORT

*for*

**WACOM Co., Ltd.**


2-510-1, Toyonodai, Otone-machi,  
Kitasaitama-gun, Saitama 349-1148, JAPAN

Equipment Under Test: Digitizer  
model name : GD-1212-U

Category: FCC Part 15 Sub.part C Class B Digital Device

Token Report No.: T6G9933919

Date of Issue: April 14, 1999

  
Hiro Shida 15/4/99  
Manager, Tsukuba Testing Lab.  
Token EMC Engineering Co., Ltd.

-- ATTENTION --

The test results in this report relate only to the following EUTs, and this report shall not be reproduced except in full, without the written approval of the laboratory.

**NVLAQ<sup>®</sup>**

## ***Contents***

### ***Page***


|           |  |          |
|-----------|--|----------|
| <b>1</b>  | <b>DESCRIPTION OF DEVICE .....</b>                               | <b>1</b> |
| <b>2</b>  | <b>TEST FACILITY .....</b>                                       | <b>2</b> |
| <b>3</b>  | <b>SUMMARY OF RESULTS</b>  |          |
| 3.1       | Electromagnetic Emission .....                                   | 2        |
| 3.2       | Modification to The EUT.....                                     | 2        |
| <b>4</b>  | <b>TESTED SYSTEM DETAILS</b>                                     |          |
| 4.1       | Peripherals and Others .....                                     | 3        |
| 4.2       | Type of Used Cables .....  | 3        |
| <b>5</b>  | <b>TECHNICAL COUNTERMEASURE .....</b>                            | <b>3</b> |
| <b>6</b>  | <b>TEST RESULTS</b>  |          |
| 6.1       | RFI Voltage Measurement  |          |
| 6.1.1     | Measurement Instrumentation Used .....                           | 4        |
| 6.1.2     | Measurement Procedure.....                                       | 4        |
| 6.1.3     | Measurement Uncertainty .....                                    | 4        |
| 6.1.4     | Test Data .....  | 5 ~ 6    |
| 6.2       | RFI Field Strength Measurement                                   |          |
| 6.2.1     | Measurement Instrumentation Used .....                           | 7        |
| 6.2.2     | Measurement Procedure.....                                       | 8        |
| 6.2.3     | Measurement Uncertainty .....                                    | 8        |
| 6.2.4     | Test Data .....  | 9 ~ 12   |
| 6.3       | Minimum Margin.....  | 13       |
| 6.4       | Sample Calculation .....   | 13       |
| <b>7</b>  | <b>MEASUREMENT PHOTOS</b>  |          |
| Photo 7.1 | Setup with the Maximized RFI Voltage Emission Level .....        | 14       |
| Photo 7.2 | Setup with the Maximized RFI Field Strength Emission Level ..... | 15       |

## 1 DESCRIPTION OF DEVICE

- A) Kind of Equipment : Digitizer
- B) Model Name : GD-1212-U
- C) Serial No. : 9CJP00001
- D) Type of Sample Tested : Pre-production
- E) High Frequency Used : 18.432MHz, 6MHz ( CPU clock )  
384.0kHz, 460.8kHz ( Operating frequency )
- F) Rating Power Supply : DC+5V, 0.5A
- G) Tested Power Supply : DC+5V, 0.5A from PC  
( PC power supply : 1phase AC120V, 50Hz )
- H) Date of Manufacture : March 1999
- I) Manufacturer : WACOM Co., Ltd.  
2-510-1, Toyonodai, Otone-machi, Kitasaitama-gun,  
Saitama 349-1148, JAPAN
- J) Description of Operating : DISPLAY : ALL H DISPLAY  
USB Communication
- K) Date of Sample Received : March 23, 1999
- L) Test Engineer : Yasuhiro Umamo

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer

## 2 TEST FACILITY

The open field test site and conducted measurement facility are used for this measurement, where is located following address. This facility was fully described in a report dated Jan.31, 19994, that was submitted to the FCC. And we had accepted in a letter dated Apr.8, 1994 (31040/SIT). This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200221-0.

Tokin EMC Engineering Co., Ltd.  
Tsukuba Testing Laboratory, Open Field Test Site No.6 and Shielded Room No.2

Address ; 28-1, Kitahara-aza, Hanashimashinden-ohaza, Tsukuba-city, Ibaragi 305-0875, Japan

## 3 SUMMARY OF RESULTS

### 3.1 Electromagnetic Emission

RFI Voltage Measurement ..... **PASS**


RFI Field Strength Measurement ..... **PASS**

Although the measured emissions indicate that the EUT complies with the required limits, some measurements are close to these limits. When the uncertainty of measurement is considered, there is some possibility that the EUT may not be compliant.  
Test results are traceable to JQA, MKK and NIST.

**3.2 Modifications to The EUT :** This EUT had taken countermeasures.

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer

## 4 TESTED SYSTEM DETAILS

### 4.1 Peripherals and Others :

| Description | Model Name           | Serial No.     | Manufacturer              | FCC ID              |
|-------------|----------------------|----------------|---------------------------|---------------------|
| PC          | DP2000<br>5166MMXJPN | 7725BK         | Compaq                    | DoC                 |
| Display     | 9060S                | 56475129 S-US  | Nanao                     | GCI9060             |
| Mouse       | M-S34                | None           | Compaq                    | DZL211029           |
| Printer     | J250                 | 4300911101326  | Star Micronics<br>America | B6Z8MFJ250          |
| Modem       | T1200-SD2            | S87309509      | Omnitel                   | D786JC<br>T1200-SD2 |
| Keyboard    | None                 | B07020A39EY2Y5 | Compaq                    | AQ6-72BC15          |
| CCD camera  | LPC-U20              | None           | LG                        | DoC                 |

### 4.2 Type of Used Cables :

| Description       | Length  | Type of shield | Model name  | Manufacturer |
|-------------------|---------|----------------|-------------|--------------|
| Display AC cable  | 2.2m    | Non-shielded   | None        | Nanao        |
| Display I/F cable | 1.8m    | Shielded       | V20         | Nanao        |
| PC AC cable       | 2.0m    | Shielded       | None        | Compaq       |
| Printer cable     | 1.8m    | Shielded       | None        | None         |
| Modem I/F cable   | 1.5m    | Shielded       | C232N-J3115 | Elecom       |
| Modular cable     | 1.0m x2 | Non-shielded   | None        | None         |
| USB cable         | 1.5m    | Non-shielded   | None        | LG           |

## 5 TECHNICAL COUNTERMEASURE

| Parts number       | Description  | Circuit sign                                | Quantity | Maker                          |
|--------------------|--------------|---|----------|--------------------------------|
| BLM11A601S         | Coil         | F 1,2,3,4,5,6,7,201,202,<br>203,204,205,206 | 13       | Murata manufacturing co., ltd. |
| PLP3216S551SL2     | Coil         | F 101                                       | 1        | Murata manufacturing co., ltd. |
| F6 RH 6.4x10.0x3.2 | Ferrite core |   | 1        | Ferrico corp.                  |
| CU7636R            | Copper tape  |   | 1        | Sony chemicals corporation     |
| 97-606-01          | Clip finger  |   | 1        | Kitagawa industries co., ltd.  |

Report processed by

*A. Oyama*

Akiko Oyama  
 14/Apr./1999

*Y. Umamo*

Yasuhiro Umamo, Engineer

## 6 TEST RESULTS

### 6.1 RFI Voltage Measurement

#### 6.1.1 Measurement Instrumentation Used

( model/serial no./manufacturer/Token control no./last calibration/next calibration )

Field strength meter ..... ( FCKL1528/1528124/Schwarzbeck/RE039/02 Oct.'98/Oct.'99 )

L.I.S.N. .... ( KNW-407/8-578-14/Kyoirtsu/LI012/31 Aug.'98/Aug.'99 )

Spectrum analyzer ..... ( TR4135/67800030/Advantest/SP014/29 Sep.'98/Sep.'99 )

Coaxial cable..... ( ---/---/---/DK125/02 Mar.'98/Mar.'99 )

Shielded Room No.2 ..... ( Tsukuba No.2/---/Token/SA017/---/--- )

#### 6.1.2 Measurement Procedure


The power line conducted interference measurements were performed according to ANSI C63.4-1992 in a shielded enclosure No.2 with peripherals placed on a table, 0.8m high over a metal floor. It was located more than required distance away from the shielded enclosure wall. Deviations from the standard was none.


The EUT was plugged into the LISN and the frequency range of interest scanned.  
Reported are maximized emission levels.

#### 6.1.3 Measurement Uncertainty

Measurement uncertainty of RFI Voltage Measurement test was estimated at  $\pm 1.8\text{dB}(k=2)$ .

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer

6.1.4 Test Data

Table 6.1-1 RFI Voltage Measurement Results

Operating mode: DISPLAY : ALL H DISPLAY  
 USB Communication  
 Test procedure: ANSI C63.4-1992

Date of measurement: March 24, 1999  
 Temperature: 24 degree C  
 Humidity: 45 %

|             | Frequency<br>(MHz) | Level<br>(dBμV) | Total<br>Factor(dB) | Result<br>(dBμV) | Result<br>(μV) | Limit<br>(μV) | Margin<br>(dB) |
|-------------|--------------------|-----------------|---------------------|------------------|----------------|---------------|----------------|
| <b>L1-E</b> | 0.462              | 28.5            | 0.2                 | 28.7             | 27.23          | 250           | 19.3           |
|             | 0.491              | 40.5            | 0.2                 | 40.7             | 108.39         | 250           | 7.3            |
|             | 0.606              | 38.5            | 0.2                 | 38.7             | 86.10          | 250           | 9.3            |
|             | 10.480             | 27.0            | 0.4                 | 27.4             | 23.44          | 250           | 20.6           |
|             | 15.970             | 27.0            | 0.6                 | 27.6             | 23.99          | 250           | 20.4           |
|             | 18.435             | 35.0            | 0.8                 | 35.8             | 61.66          | 250           | 12.2           |
| <b>N-E</b>  | 0.462              | 28.5            | 0.2                 | 28.7             | 27.23          | 250           | 19.3           |
|             | 0.491              | 40.5            | 0.2                 | 40.7             | 108.39         | 250           | 7.3            |
|             | 0.606              | 38.0            | 0.2                 | 38.2             | 81.28          | 250           | 9.8            |
|             | 10.480             | 29.0            | 0.4                 | 29.4             | 29.51          | 250           | 18.6           |
|             | 15.970             | 28.0            | 0.6                 | 28.6             | 26.92          | 250           | 19.4           |
|             | 18.435             | 35.0            | 0.8                 | 35.8             | 61.66          | 250           | 12.2           |

Report processed by

  
 Akiko Oyama  
 14/Apr./1999

  
 Yasuhiro Umamo, Engineer




Figure 6.1-1 RFI Voltage Measurement Results



## 6.2 RFI Field Strength Measurement

### 6.2.1 Measurement Instrumentation Used

( model/serial no./manufacturer/Tokin control no./last calibration/next calibration )

#### < 0.009MHz ~ 30MHz >

Loop antenna..... ( HFH2-Z2/893503-014/Rohde&Schwarz/AN009/06 May '98/May '99 )  
Spectrum analyzer ..... ( TR4135/67800030/Advantest/SP014/29 Sep.'98/Sep.'99 )  
Coaxial cable..... ( ---/---/---/DK125/02 Mar.'98/Mar.'99 )  
Shielded Room No.2..... ( Tsukuba No.2/---/Tokin/SA017/---/--- )


#### < 30MHz ~ 1000MHz >

Field strength meter ..... ( KNM-5002/4N-171-4/Kyoritsu/RE006/28 Sep.'98/Sep.'99 )  
Frequency converter ..... ( KCV-6002/4-248-1/Kyoritsu/RC006/28 Sep.'98/Sep.'99 )  
Biconical antenna ..... ( BBA9106/TB006/Schwarzbeck/TB006/10 Sep.'98/Sep.'99 )  
Logperiodic antenna..... ( UHALP9108-A/0115/Schwarzbeck/TL021/07 Jul.'98/Jul.'99 )  
Pre-amplifier ..... ( 8447D/2727A05431/Hewlett Packard/AM006/12 Mar.'98/Mar.'99 )  
Spectrum analyzer ..... ( R3261A/81720103/Advantest/SP006/12 Nov.'98/Nov.'99 )  
Coaxial cable..... ( ---/CL6/---/DK090/31 Jul.'98/Jul.'99 )  
Open field test site ..... ( Tsukuba No.6/---/Tokin/SA006/17 Nov.'98/Nov.'99 )

#### < Over 1000MHz >

Double ridged guide  
horn antenna..... ( 3115/90053420/EMCO/AN003/03 Feb.'98/Feb.'99 )  
Pre-amplifier ..... ( 8449B/3008A00681/Hewlett Packard/rental/24 Nov.'98/Nov.'99 )  
Coaxial cable..... ( SUCOFLEX 104 2m/49402-4/SUCOFLEX/DK001/24 Nov.'98/Nov.'99 )  
Coaxial cable..... ( SUCOFLEX 104/51100-4/SUCOFLEX/DK002/24 Nov.'98/Nov.'99 )  
Coaxial cable..... ( SUCOFLEX 104 15m/51507-4/SUCOFLEX/DK003/24 Nov.'98/Nov.'99 )  
Coaxial cable..... ( MW3.0D-FF-2500/910215-8/Hitachi/DK006/24 Nov.'98/Nov.'99 )  
Coaxial cable..... ( MW3.0D-FF-2500/910215-10/Hitachi/DK007/24 Nov.'98/Nov.'99 )  
Open field test site ..... ( Tsukuba No.6/---/Tokin/SA006/17 Nov.'98/Nov.'99 )

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umano, Engineer

## 6.2.2 Measurement Procedure

Final test was performed according to ANSI C63.4-1992 at the open field test site No.6. Deviations from the standard was none.


The EUT was placed in a 0.8m high table along with the peripherals. The turn table was separated from the antenna distance 3meters. Cables were placed in a position to produce maximum emissions as determined by experimentation, and operation mode was selected for maximum.


The frequencies and amplitudes of maximum emission were measured at varying azimuths, antenna heights and antenna polarities. Reported are maximized emission levels.

## 6.2.3 Measurement Uncertainty

Measurement uncertainty of RFI Field Strength Measurement test was estimated at  $\pm 3.4\text{dB}(k=2)$ .

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer






Figure 6.2-1 RFI Field Strength Measurement Results

**Table 6.2-2** RFI Field Strength Measurement Results ( Over 30MHz )

| Operating mode: DISPLAY : ALL H DISPLAY |                      |      |                          |                       |                      | Date of measurement: March 23, 1999 |      |        |        |                                  |        |      |
|---|----------------------|------|--------------------------|-----------------------|----------------------|-------------------------------------|------|--------|--------|----------------------------------|--------|------|
| USB Communication                       |                      |      |                          |                       |                      | Temperature: 24 degree C            |      |        |        |                                  |        |      |
| Test procedure: ANSI C63.4-1992         |                      |      |                          |                       |                      | Humidity: 45 %                      |      |        |        |                                  |        |      |
| Frequency<br>(MHz)                      | Level                |      | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Amp.<br>Gain<br>(dB) | Result                              |      | Result |        | 3 Meter<br>Limit<br>( $\mu$ V/m) | Margin |      |
|   | Ver.<br>(dB $\mu$ V) | Hor. |                          |                       |                      | Ver.                                | Hor. | Ver.   | Hor.   |                                  | Ver.   | Hor. |
| 51.40                                   | -                    | 30.5 | 11.6                     | 2.6                   | 27.6                 | -                                   | 17.1 | -      | 7.16   | 100                              | -      | 22.9 |
| 68.90                                   | 42.0                 | -    | 5.8                      | 3.2                   | 27.7                 | 23.3                                | -    | 14.62  | -      | 100                              | 16.7   | -    |
| 75.16                                   | 44.5                 | 45.0 | 6.2                      | 3.4                   | 27.7                 | 26.4                                | 26.9 | 20.89  | 22.13  | 100                              | 13.6   | 13.1 |
| 110.33                                  | -                    | 37.0 | 11.9                     | 4.2                   | 27.5                 | -                                   | 25.6 | -      | 19.05  | 150                              | -      | 17.9 |
| 158.07                                  | -                    | 37.0 | 14.6                     | 5.0                   | 27.3                 | -                                   | 29.3 | -      | 29.17  | 150                              | -      | 14.2 |
| 158.08                                  | 35.0                 | -    | 14.6                     | 5.0                   | 27.3                 | 27.3                                | -    | 23.17  | -      | 150                              | 16.2   | -    |
| 332.79                                  | 41.5                 | 42.0 | 13.7                     | 7.2                   | 27.0                 | 35.4                                | 35.9 | 58.88  | 62.37  | 200                              | 10.6   | 10.1 |
| 408.00                                  | 39.5                 | 40.0 | 15.7                     | 8.2                   | 27.5                 | 35.9                                | 36.4 | 62.37  | 66.07  | 200                              | 10.1   | 9.6  |
| 665.58                                  | 34.0                 | -    | 20.1                     | 10.9                  | 28.5                 | 36.5                                | -    | 66.83  | -      | 200                              | 9.5    | -    |
| 665.60                                  | -                    | 32.0 | 20.1                     | 10.9                  | 28.5                 | -                                   | 34.5 | -      | 53.09  | 200                              | -      | 11.5 |
| 998.35                                  | 31.5                 | 33.0 | 22.8                     | 13.7                  | 27.3                 | 40.7                                | 42.2 | 108.39 | 128.82 | 500                              | 13.3   | 11.8 |
| 1331.00                                 | 38.5                 | 37.8 | 25.6                     | 6.9                   | 34.3                 | 36.7                                | 36.0 | 68.39  | 63.10  | 500                              | 17.3   | 18.0 |

**Class B limit**

Radiated Emission – 3 meter distance

| Frequency (MHz) | dB $\mu$ V/m | $\mu$ V/m |
|-----------------|--------------|-----------|
| 30 - 88         | 40.0         | 100       |
| 88 - 216        | 43.5         | 150       |
| 216 - 960       | 46.0         | 200       |
| > 960           | 54.0         | 500       |

Report processed by

*A. Oyama*

Akiko Oyama  
 14/Apr./1999

*Y. Umamo*

Yasuhiro Umamo, Engineer




Figure 6.2-2 RFI Field Strength Measurement Results

### 6.3 Minimum Margin

Table 6.3-1 Minimum Margin

| Conducted emission                  |                |             |        |
|-------------------------------------|----------------|-------------|--------|
| DISPLAY : ALL HI DISPLAY            | operation mode | 0.491 MHz,  | 7.3 dB |
| USB Communication Radiated emission |                |             |        |
|                                     | operation mode | 665.58 MHz, | 9.5 dB |

### 6.4 Sample Calculation

Table 6.4-1 Sample Calculation

The maximum radiating emission can be obtained at the frequency of 665.58 MHz, Vertical polarization on DISPLAY : ALL HI DISPLAY operation mode. USB Communication

Each value at frequency is as follows;

|     |                              |   |      |        |
|-----|------------------------------|---|------|--------|
| R : | Field strength meter reading | = | 34.0 | (dBμV) |
| A : | Antenna factor               | = | 20.1 | (dB/m) |
| C : | Cable loss                   | = | 10.9 | (dB)   |
| G : | Amplifier gain               | = | 28.5 | (dB)   |

Then radiated emission E(dBμV/m) is ;

$$E = R + A + C - G$$

Therefore, the maximum radiated emission is ;

$$36.5 \text{ (dBμV/m)}$$

Report processed by

A. Oyama  
 Akiko Oyama  
 14/Apr./1999

Y. Umano  
 Yasuhiro Umano, Engineer

*Token EMC Engineering Co., Ltd.*  
*28-1 Kitahara-aza Hanashimashinden-ohaza*  
*Tsukuba-city Ibaragi 305-0875 Japan*  
*Tel +81-298-37-2400 Fax +81-298-37-2401*

## EMC TEST REPORT

*for*

**WACOM Co., Ltd.**


2-510-1, Toyonodai, Otone-machi,  
Kitasaitama-gun, Saitama 349-1148, JAPAN

Equipment Under Test: Digitizer  
model name : GD-1212-U

Category: FCC Part 15 Sub.part B Class B Digital Device

Token Report No.: T6G9933923

Date of Issue: April 14, 1999

  
Hiro Shida  
15/4/99  
Manager, Tsukuba Testing Lab.  
Token EMC Engineering Co., Ltd.

-- ATTENTION --

The test results in this report relate only to the following EUTs, and this report shall not be reproduced except in full, without the written approval of the laboratory.

**NVLAQ<sup>®</sup>**



## *Contents*


|  | <i>Page</i> |
|--|-------------|
| 1 DESCRIPTION OF DEVICE .....  | 1           |
| 2 TEST FACILITY .....  | 2           |
| 3 SUMMARY OF RESULTS   |             |
| 3.1 Electromagnetic Emission .....   | 2           |
| 3.2 Modification to The EUT.....   | 2           |
| 4 TESTED SYSTEM DETAILS  |             |
| 4.1 Peripherals and Others .....   | 3           |
| 4.2 Type of Used Cables .....  | 3           |
| 5 TECHNICAL COUNTERMEASURE.....  | 3           |
| 6 TEST RESULTS   |             |
| 6.1 RFI Voltage Measurement  |             |
| 6.1.1 Measurement Instrumentation Used .....                               | 4           |
| 6.1.2 Measurement Procedure.....   | 4           |
| 6.1.3 Measurement Uncertainty .....  | 4           |
| 6.1.4 Test Data .....  | 5 ~ 6       |
| 6.2 RFI Field Strength Measurement   |             |
| 6.2.1 Measurement Instrumentation Used .....                               | 7           |
| 6.2.2 Measurement Procedure.....   | 7           |
| 6.2.3 Measurement Uncertainty .....  | 7           |
| 6.2.4 Test Data .....  | 8 ~ 9       |
| 6.3 Minimum Margin.....  | 10          |
| 6.4 Sample Calculation .....   | 10          |
| 7 MEASUREMENT PHOTOS   |             |
| Photo 7.1 Setup with the Maximized RFI Voltage Emission Level .....        | 11          |
| Photo 7.2 Setup with the Maximized RFI Field Strength Emission Level ..... | 12          |

## 1 DESCRIPTION OF DEVICE

- A) Kind of Equipment : Digitizer
- B) Model Name : GD-1212-U
- C) Serial No. : 9CJP00001
- D) Type of Sample Tested : Pre-production
- E) High Frequency Used : 18.432MHz, 6MHz ( CPU clock )  
384.0kHz, 460.8kHz ( Operating frequency )
- F) Rating Power Supply : DC+5V, 0.5A
- G) Tested Power Supply : DC+5V, 0.5A from PC  
( PC power supply : 1phase AC120V, 50Hz )
- H) Date of Manufacture : March 1999
- I) Manufacturer : WACOM Co., Ltd.  
2-510-1, Toyonodai, Otone-machi, Kitasaitama-gun,  
Saitama 349-1148, JAPAN
- J) Description of Operating : DISPLAY : ALL H DISPLAY  
USB Communication
- K) Date of Sample Received : March 23, 1999
- L) Test Engineer : Yasuhiro Umamo

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer

## 2 TEST FACILITY

The open field test site and conducted measurement facility are used for this measurement, where is located following address. This facility was fully described in a report dated Jan.31, 1994, that was submitted to the FCC. And we had accepted in a letter dated Apr.8, 1994 (31040/SIT). This laboratory is accredited by NVLAP for NVLAP Lab. Code : 200221-0.

Token EMC Engineering Co., Ltd.  
Tsukuba Testing Laboratory, Open Field Test Site No.6 and Shielded Room No.2

Address ; 28-1, Kitahara-aza, Hanashimashinden-ohaza, Tsukuba-city, Ibaragi 305-0875, Japan

## 3 SUMMARY OF RESULTS

### 3.1 Electromagnetic Emission

RFI Voltage Measurement ..... **PASS**

RFI Field Strength Measurement ..... **PASS**

Although the measured emissions indicate that the EUT complies with the required limits, some measurements are close to these limits. When the uncertainty of measurement is considered, there is some possibility that the EUT may not be compliant.  
Test results are traceable to JQA, MKK and NIST.

**3.2 Modifications to The EUT :**      This EUT had taken countermeasures.

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer

## 4 TESTED SYSTEM DETAILS

### 4.1 Peripherals and Others :

| Description | Model Name           | Serial No.     | Manufacturer              | FCC ID              |
|-------------|----------------------|----------------|---------------------------|---------------------|
| PC          | DP2000<br>5166MMXJPN | 7725BK         | Compaq                    | DoC                 |
| Display     | 9060S                | 56475129 S-US  | Nanao                     | GCJ9060             |
| Mouse       | M-S34                | None           | Compaq                    | DZL211029           |
| Printer     | J250                 | 4300911101326  | Star Micronics<br>America | B6Z8MFJ250          |
| Modem       | T1200-SD2            | S87309509      | Omnitel                   | D786JC<br>T1200-SD2 |
| Keyboard    | None                 | B07020A39EY2Y5 | Compaq                    | AQ6-72BC15          |
| CCD camera  | LPC-U20              | None           | LG                        | DoC                 |


### 4.2 Type of Used Cables :


| Description       | Length  | Type of shield | Model name  | Manufacturer |
|-------------------|---------|----------------|-------------|--------------|
| Display AC cable  | 2.2m    | Non-shielded   | None        | Nanao        |
| Display I/F cable | 1.8m    | Shielded       | V20         | Nanao        |
| PC AC cable       | 2.0m    | Shielded       | None        | Compaq       |
| Printer cable     | 1.8m    | Shielded       | None        | None         |
| Modem I/F cable   | 1.5m    | Shielded       | C232N-J3115 | Elecom       |
| Modular cable     | 1.0m x2 | Non-shielded   | None        | None         |
| USB cable         | 1.5m    | Non-shielded   | None        | LG           |

## 5 TECHNICAL COUNTERMEASURE

| Parts number       | Description  | Circuit sign                                | Quantity | Maker                          |
|--------------------|--------------|---|----------|--------------------------------|
| BLM11A601S         | Coil         | F 1,2,3,4,5,6,7,201,202,<br>203,204,205,206 | 13       | Murata manufacturing co., ltd. |
| PLP3216S551SL2     | Coil         | F 101                                       | 1        | Murata manufacturing co., ltd. |
| F6 RH 6.4x10.0x3.2 | Ferrite core |   | 1        | Ferrico corp.                  |
| CU7636R            | Copper tape  |   | 1        | Sony chemicals corporation     |
| 97-606-01          | Clip finger  |   | 1        | Kitagawa industries co., ltd.  |

Report processed by

  
 Akiko Oyama  
 14/Apr./1999

  
 Yasuhiro Umamo, Engineer

## 6 TEST RESULTS

### 6.1 RFI Voltage Measurement

#### 6.1.1 Measurement Instrumentation Used

( model/serial no./manufacturer/Token control no./last calibration/next calibration )

Field strength meter ..... ( FCKL1528/1528124/Schwarzbeck/RE039/02 Oct.'98/Oct.'99 )

L.I.S.N. .... ( KNW-407/8-578-14/Kyoirtsu/LI012/31 Aug.'98/Aug.'99 )

Spectrum analyzer ..... ( TR4135/67800030/Advantest/SP014/29 Sep.'98/Sep.'99 )

Coaxial cable..... ( ---/---/---/DK125/02 Mar.'98/Mar.'99 )

Shielded Room No.2 ..... ( Tsukuba No.2/---/Token/SA017/---/--- )

#### 6.1.2 Measurement Procedure

The power line conducted interference measurements were performed according to ANSI C63.4-1992 in a shielded enclosure No.2 with peripherals placed on a table, 0.8m high over a metal floor. It was located more than required distance away from the shielded enclosure wall. Deviations from the standard was none.


The EUT was plugged into the LISN and the frequency range of interest scanned.  
Reported are maximized emission levels.

#### 6.1.3 Measurement Uncertainty

Measurement uncertainty of RFI Voltage Measurement test was estimated at  $\pm 1.8\text{dB}(k=2)$ .

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer

6.1.4 Test Data

Table 6.1-1 RFI Voltage Measurement Results


Operating mode: DISPLAY : ALL H DISPLAY  
 USB Communication  
 Test procedure: ANSI C63.4-1992

Date of measurement: March 24, 1999  
 Temperature: 24 degree C  
 Humidity: 45 %

|             | Frequency<br>(MHz) | Level<br>(dBμV) | Total<br>Factor(dB) | Result<br>(dBμV) | Result<br>(μV) | Limit<br>(μV) | Margin<br>(dB) |
|-------------|--------------------|-----------------|---------------------|------------------|----------------|---------------|----------------|
| <b>L1-E</b> | 0.462              | 28.5            | 0.2                 | 28.7             | 27.23          | 250           | 19.3           |
|             | 0.491              | 40.5            | 0.2                 | 40.7             | 108.39         | 250           | 7.3            |
|             | 0.606              | 38.5            | 0.2                 | 38.7             | 86.10          | 250           | 9.3            |
|             | 10.480             | 27.0            | 0.4                 | 27.4             | 23.44          | 250           | 20.6           |
|             | 15.970             | 27.0            | 0.6                 | 27.6             | 23.99          | 250           | 20.4           |
|             | 18.435             | 35.0            | 0.8                 | 35.8             | 61.66          | 250           | 12.2           |
| <b>N-E</b>  | 0.462              | 28.5            | 0.2                 | 28.7             | 27.23          | 250           | 19.3           |
|             | 0.491              | 40.5            | 0.2                 | 40.7             | 108.39         | 250           | 7.3            |
|             | 0.606              | 38.0            | 0.2                 | 38.2             | 81.28          | 250           | 9.8            |
|             | 10.480             | 29.0            | 0.4                 | 29.4             | 29.51          | 250           | 18.6           |
|             | 15.970             | 28.0            | 0.6                 | 28.6             | 26.92          | 250           | 19.4           |
|             | 18.435             | 35.0            | 0.8                 | 35.8             | 61.66          | 250           | 12.2           |

Report processed by

  
 Akiko Oyama  
 14/Apr./1999

  
 Yasuhiro Umamo, Engineer




Figure 6.1-1 RFI Voltage Measurement Results

## 6.2 RFI Field Strength Measurement

### 6.2.1 Measurement Instrumentation Used

*( model/serial no./manufacturer/Token control no./last calibration/next calibration )*

Field strength meter ..... ( KNM-5002/4N-171-4/Kyoritsu/RE006/28 Sep.'98/Sep.'99 )  
Frequency converter ..... ( KCV-6002/4-248-1/Kyoritsu/RC006/28 Sep.'98/Sep.'99 )  
Biconical antenna ..... ( BBA9106/TB006/Schwarzbeck/TB006/10 Sep.'98/Sep.'99 )  
Logperiodic antenna..... ( UHALP9108-A/0115/Schwarzbeck/TL021/07 Jul.'98/Jul.'99 )  
Pre-amplifier ..... ( 8447D/2727A05431/Hewlett Packard/AM006/12 Mar.'98/Mar.'99 )  
Spectrum analyzer ..... ( R3261A/81720103/Advantest/SP006/12 Nov.'98/Nov.'99 )  
Coaxial cable..... ( ---/CL6/---/DK090/31 Jul.'98/Jul.'99 )  
Open field test site ..... ( Tsukuba No.6/---/Token/SA006/17 Nov.'98/Nov.'99 )

### 6.2.2 Measurement Procedure

Final test was performed according to ANSI C63.4-1992 at the open field test site No.6. Deviations from the standard was none.


The EUT was placed in a 0.8m high table along with the peripherals. The turn table was separated from the antenna distance 3meters. Cables were placed in a position to produce maximum emissions as determined by experimentation, and operation mode was selected for maximum.


The frequencies and amplitudes of maximum emission were measured at varying azimuths, antenna heights and antenna polarities. Reported are maximized emission levels.

### 6.2.3 Measurement Uncertainty

Measurement uncertainty of RFI Field Strength Measurement test was estimated at  $\pm 3.4\text{dB}(k=2)$ .

Report processed by

  
Akiko Oyama  
14/Apr./1999

  
Yasuhiro Umamo, Engineer



6.2.4 Test Data

Table 6.2-1 RFI Field Strength Measurement Results

| Operating mode: DISPLAY : ALL H DISPLAY<br>USB Communication |                 |      |                          |                       |                      | Date of measurement: March 23, 1999 |      |                  |        |                            |                |      |
|--|-----------------|------|--------------------------|-----------------------|----------------------|-------------------------------------|------|------------------|--------|----------------------------|----------------|------|
| Test procedure: ANSI C63.4-1992                              |                 |      |                          |                       |                      | Temperature: 24 degree C            |      | Humidity: 45 %   |        |                            |                |      |
| Frequency<br>(MHz)   | Level<br>(dBμV) |      | Ant.<br>Factor<br>(dB/m) | Cable<br>Loss<br>(dB) | Amp.<br>Gain<br>(dB) | Result<br>(dBμV/m)                  |      | Result<br>(μV/m) |        | 3 Meter<br>Limit<br>(μV/m) | Margin<br>(dB) |      |
|  | Ver.            | Hor. |                          |                       |                      | Ver.                                | Hor. | Ver.             | Hor.   |                            | Ver.           | Hor. |
| 51.40  | -               | 30.5 | 11.6                     | 2.6                   | 27.6                 | -                                   | 17.1 | -                | 7.16   | 100                        | -              | 22.9 |
| 68.90  | 42.0            | -    | 5.8                      | 3.2                   | 27.7                 | 23.3                                | -    | 14.62            | -      | 100                        | 16.7           | -    |
| 75.16  | 44.5            | 45.0 | 6.2                      | 3.4                   | 27.7                 | 26.4                                | 26.9 | 20.89            | 22.13  | 100                        | 13.6           | 13.1 |
| 110.33   | -               | 37.0 | 11.9                     | 4.2                   | 27.5                 | -                                   | 25.6 | -                | 19.05  | 150                        | -              | 17.9 |
| 158.07   | -               | 37.0 | 14.6                     | 5.0                   | 27.3                 | -                                   | 29.3 | -                | 29.17  | 150                        | -              | 14.2 |
| 158.08   | 35.0            | -    | 14.6                     | 5.0                   | 27.3                 | 27.3                                | -    | 23.17            | -      | 150                        | 16.2           | -    |
| 332.79   | 41.5            | 42.0 | 13.7                     | 7.2                   | 27.0                 | 35.4                                | 35.9 | 58.88            | 62.37  | 200                        | 10.6           | 10.1 |
| 408.00   | 39.5            | 40.0 | 15.7                     | 8.2                   | 27.5                 | 35.9                                | 36.4 | 62.37            | 66.07  | 200                        | 10.1           | 9.6  |
| 665.58   | 34.0            | -    | 20.1                     | 10.9                  | 28.5                 | 36.5                                | -    | 66.83            | -      | 200                        | 9.5            | -    |
| 665.60   | -               | 32.0 | 20.1                     | 10.9                  | 28.5                 | -                                   | 34.5 | -                | 53.09  | 200                        | -              | 11.5 |
| 998.35   | 31.5            | 33.0 | 22.8                     | 13.7                  | 27.3                 | 40.7                                | 42.2 | 108.39           | 128.82 | 500                        | 13.3           | 11.8 |

Class B limit

Radiated Emission – 3 meter distance

| Frequency (MHz) | dBμV/m | μV/m |
|-----------------|--------|------|
| 30 - 88         | 40.0   | 100  |
| 88 - 216        | 43.5   | 150  |
| 216 - 960       | 46.0   | 200  |
| > 960           | 54.0   | 500  |

Report processed by

*A. Oyama*  
 Akiko Oyama  
 14/Apr./1999

*Y. Umano*  
 Yasuhiro Umano, Engineer




Figure 6.2-1 RFI Field Strength Measurement Results

### 6.3 Minimum Margin

Table 6.3-1 Minimum Margin

|   |             |        |
|---|-------------|--------|
| Conducted emission<br>DISPLAY: ALL H DISPLAY operation mode                     | 0.491 MHz,  | 7.3 dB |
| USB Communication<br>Radiated emission<br>DISPLAY: ALL H DISPLAY operation mode | 665.58 MHz, | 9.5 dB |
| USB Communication   |             |        |

### 6.4 Sample Calculation

Table 6.4-1 Sample Calculation

The maximum radiating emission can be obtained at the frequency of 665.58 MHz,  
 Vertical polarization on DISPLAY: ALL H DISPLAY operation mode.  
 USB Communication

Each value at frequency is as follows;

|     |                              |   |      |        |
|-----|------------------------------|---|------|--------|
| R : | Field strength meter reading | = | 34.0 | (dBμV) |
| A : | Antenna factor               | = | 20.1 | (dB/m) |
| C : | Cable loss                   | = | 10.9 | (dB)   |
| G : | Amplifier gain               | = | 28.5 | (dB)   |


Then radiated emission E(dBμV/m) is ;


$$E = R + A + C - G$$

Therefore, the maximum radiated emission is ;

$$36.5 \text{ (dBμV/m)}$$

Report processed by

  
 Akiko Oyama  
 14/Apr./1999

  
 Yasuhiro Umamo, Engineer