



Test Report

Class II Change

For

Applicant : Mustek Systems Inc.
Equipment Type : Scanner
Model : BearPaw 1200F, BP 1200F, 1200 DUF
FCC ID : HWFBEARPAW
Project Name : B6U12KF

Report No. : 007H013FI



Test Report Certification

Quietek Corporation

No.75-1, Wang-Yeh Valley, Yung-Hsing, Chiung-Lin,

Hsin-Chu County, Taiwan, R.O.C.

Tel : 886-3-592-8858, Fax: 886-3-592-8859

E-Mail : quietek@ms24.hinet.net

Accredited by NIST(NVLAP), VCCI, BSMI, DNV, TUV

Applicant : Mustek Systems Inc.

Address : No. 25, R&D Road II, Science-Based Industrial Park,
Hsin-Chu, Taiwan, R.O.C.

Equipment Type : Scanner

Model : BearPaw 1200F, BP 1200F, 1200 DUF

FCC ID. : HWFBEARPAW

Measurement Standard : CISPR 22/1985

Measurement Procedure : ANSI C63.4 /1992

Operation Voltage : 110VAC/ 60Hz

Classification : Class B

Test Result : Complied

Test Date : July 23, 2000

Report No. : 007H013FI



The Test Results relate only to the samples tested.

The test report shall not be reproduced except in full without the written approval of Quietek Corporation.

This report must not be used to claim product endorsement by NVLAP any agency of the U.S. Government

Documented by: Shelly Fan

Test Engineer: Robin Lin

Approved: Gene Chang



TABLE OF CONTENTS

| Description | Page |
|---|-----------|
| 1. GENERAL INFORMATION | 4 |
| 1.1 EUT Description | 4 |
| 1.2 Tested System Details | 5 |
| 1.3 EUT Configuration..... | 7 |
| 1.4 EUT Exercise Software | 7 |
| 1.5 Test performed | 7 |
| 1.6 Test Facility | 8 |
| 2. CONDUCTED EMISSION | 9 |
| 2.1 Test Equipment List..... | 9 |
| 2.2 Test Setup..... | 9 |
| 2.3 Limits | 9 |
| 2.4 Test Procedure..... | 10 |
| 2.5 Test Results..... | 10 |
| 3. RADIATED EMISSION..... | 11 |
| 3.1 Test Equipment | 11 |
| 3.2 Test Setup..... | 11 |
| 3.3 Limits | 12 |
| 3.4 Test Procedure..... | 12 |
| 3.5 Test Results..... | 12 |
| 4. EMI REDUCTION METHOD DURING COMPLIANCE TESTING..... | 13 |
| 5. ATTACHMENT..... | 14 |
| ATTACHMENT 1: SUMMARY OF TEST RESULTS | |
| ATTACHMENT 2: EUT TEST PHOTOGRAPHS | |
| ATTACHMENT 3: EUT DETAILED PHOTOGRAPHS | |



1. General Information

1.1 EUT Description

| | |
|-------------------|---|
| Applicant | : Mustek Systems Inc. |
| Address | : No. 25, R&D Road II, Science-Based Industrial Park, Hsin-Chu, Taiwan, R.O.C. |
| Equipment Type | : Scanner |
| Model | : BearPaw 1200F, BP 1200F, 1200 DUF |
| Operation Voltage | : 110VAC/ 60Hz |
| FCC ID | : HWFBEARPAW |
| USB Data Cable | : Non-Shielded, 0.8m |
| Power Adapter | : HIGH POWER, HPW-2012X Cable out: Non-Shielded, 1.8m, a ferrite core bonded |

Remark :

1. The EUT is a Scanner.
2. The EUT have three models, the BP 1200F and 1200 DUF are for OEM customer.
3. The class II change is owing to the change of crystal device. Second source of the crystal operated in the same frequency was used during the test.
4. QuieTek had verified the construction and function in typical operation, then shown in this test report.



1.2 Tested System Details

The types for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

1.2.1 Host Personal Computer

Model Number : DESK PRO 2000
Manufacturer : Compaq
Serial Number : N/A
FCC ID : DoC
Power Cord : Non-Shielded,1.8m

1.2.2 Scanner (EUT)

Model Number : BearPaw 1200F
Serial Number : N/A
FCC ID : HWFBEARPAW
Manufacturer : Mustek
USB Data Cable : Non-Shielded, 0.8m
Auto Document Feeder : Mustek, ADF-III
Power Adapter : HIGH POWER, HPW-2012X
Cable out: Non-Shielded, 1.8m, a ferrite core bonded

1.2.3 Monitor

Model Number : KM-511
Serial Number : 829H0684
FCC ID : ARFKM411511
Manufacturer : SAMPO
Data Cable : Shielded, 1.5m, a ferrite core bonded
Power Cord : Non-Shielded, 1.8m

1.2.4 Keyboard

Model Number : 6311-TW4C
Serial Number : 916590704C91F24438
FCC ID : DoC
Manufacturer : ACER
Data Cable : Shielded, 1.8m



1.2.5 Modem

Model Number : 1414
Serial Number : 980033039
FCC ID : IFAXDM1414
Manufacturer : ACEEX
Data Cable : Shielded, 1.5m
Power Adapter : ACCEX, SCP41-91000A
Cable Output : Shielded, 1.5m

1.2.6 Printer

Model Number : C2642A
Serial Number : MY75N1D2Y1
FCC ID : B94C2642X
Manufacturer : HP
Data Cable : Shielded, 1.2m
Power Adapter : NMB, C2175A
Cable for AC IN: Non-Shielded, 0.7m
Cable for AC Out: Non-Shielded, 1.5m

1.2.7 Mouse


Model Number : M-S34
Serial Number : LZA71178588
FCC ID : DZL211029
Manufacturer : HP
Data Cable : Shielded, 1.8m

1.2.8 Mouse

Model Number : M-UE55
Serial Number : DVT-325
FCC ID : DoC
Manufacturer : Logitech
Data Cable : Shielded, 1.8m



1.3 EUT Configuration



1.4 EUT Exercise Software

The EUT exercise program used during conducted testing was designed to exercise the EUT in a manner similar to a typical use. The exercise sequence is listed as below:

- 1.4.1 Setup the EUT and simulators as shown on 1.3
- 1.4.2 Turn on the power of all equipment.
- 1.4.3 Boot the PC from Hard Disk .
- 1.4.4 PC reads test software from disk and then sent to scanner..
- 1.4.5 The Scanner (EUT) will start to operate and scan the video figure into PC.
- 1.4.6 PC will display “video figure” on monitor.
- 1.4.7 Printer and modem will keep at standby mode during Scanner operation.
- 1.4.8 Repeat the above procedure 1.4.4 to 1.4.7

1.5 Test performed

Conducted emissions were investigated over the frequency range from **0.15MHz to 30MHz** using a receiver bandwidth of 9kHz.

Radiated emissions were investigated over the frequency range from **30MHz to 1000MHz** using a receiver bandwidth of 120kHz. Radiated testing was performed at an antenna to EUT distance of 10 meters .

1.6 Test Facility

Ambient conditions in the laboratory:

| Items | Required (IEC 68-1) | Actual |
|----------------------------|---------------------|----------|
| Temperature (°C) | 15-35 | 20-35 |
| Humidity (%RH) | 25-75 | 50-65 |
| Barometric pressure (mbar) | 860-1060 | 950-1000 |

Site Description: November 3, 1998 File on
Federal Communications Commission
FCC Engineering Laboratory
7435 Oakland Mills Road
Columbia, MD 21046
Reference 31040/SIT1300F2



September 30, 1998 Accreditation on NVLAP
NVLAP Lab Code: 200347-0

February 23, 1999 Accreditation on DNV
Statement No. : 413-99-LAB11



December 8, 1998 Registration on VCCI
Registration No. for No.2 Shielded Room C-858
Registration No. for No.1 Open Area Test Site R-823
Registration No. for No.2 Open Area Test Site R-835



January 04, 1999 Accreditation on TÜV Rheinland
Certificate No.: I9865712-9901



Name of firm : QuieTek Corporation

Site location : No.75-1, Wang-Yeh Valley, Yung-Hsing Tsuen,
Chiung-Lin, Hsin-Chu County, Taiwan, R.O.C.



2. Conducted Emission


2.1 Test Equipment List

The following test equipment are used during the conducted emission test:

| Item | Instrument | Manufacturer | Type No./Serial No | Last Cal.. | Remark |
|------|--------------------|--------------|--------------------|------------|-------------|
| 1 | Test Receiver | R & S | ESCS 30/825442/17 | May, 2000 | |
| 2 | L.I.S.N. | R & S | ESH3-Z5/825016/6 | May, 2000 | EUT |
| 3 | L.I.S.N. | Kyoritsu | KNW-407/8-1420-3 | May, 2000 | Peripherals |
| 4 | Pulse Limiter | R & S | ESH3-Z2 | N/A | |
| 5 | N0.2 Shielded Room | | | N/A | |

Note: All equipment upon which need to calibrated are with calibration period of 1 year.

2.2 Test Setup



2.3 Limits

| CISPR 22 Limits (dBuV) | | | | | FCC Part 15 Subpart B (dBuV) | | | | |
|------------------------|---------|----|---------|-------|------------------------------|---------|------|---------|------|
| Frequency MHz | Class A | | Class B | | Frequency MHz | Class A | | Class B | |
| | QP | AV | QP | AV | | uV | dBuV | uV | dBuV |
| 0.15 - 0.50 | 79 | 66 | 66-56 | 56-46 | 0.45-1.705 | 1000 | 60.0 | 250 | 48.0 |
| 0.50-5.0 | 73 | 60 | 56 | 46 | 1.705-30 | 3000 | 69.5 | 250 | 48.0 |
| 5.0 - 30 | 73 | 60 | 60 | 50 | | | | | |

Remarks : In the above table, the tighter limit applies at the band edges.

2.4 Test Procedure

The EUT and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50 ohm /50uH coupling impedance for the measuring equipment. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refers to the block diagram of the test setup and photographs.)

Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4 /1992 on conducted measurement.

The bandwidth of the field strength meter (R & S Test Receiver ESCS 30) is set at 9kHz.

2.5 Test Results

The conducted emission from the EUT is measured and shown in attachment 1 of test report. The acceptance criterion was met and the EUT passed the test.



3. Radiated Emission


3.1 Test Equipment

The following test equipment are used during the radiated emission test:

| Test Site | | Equipment | Manufacturer | Model No./Serial No. | Last Cal. |
|-----------|---|-------------------|--------------|----------------------|------------|
| Site # 1 | X | Test Receiver | R & S | ESCS 30 / 825442/14 | May, 2000 |
| | | Spectrum Analyzer | Advantest | R3261C / 71720140 | May, 2000 |
| | | Pre-Amplifier | HP | 8447D/3307A01812 | May, 2000 |
| | X | Bilog Antenna | Chase | CBL6112B / 12452 | Sep., 1999 |
| | X | Horn Antenna | EM | EM6917 / 103325 | May, 2000 |
| Site # 2 | X | Test Receiver | R & S | ESCS 30 / 825442/17 | May, 2000 |
| | | Spectrum Analyzer | Advantest | R3261C / 71720609 | May, 2000 |
| | | Pre-Amplifier | HP | 8447D/3307A01814 | May, 2000 |
| | X | Bilog Antenna | Chase | CBL6112B / 2455 | Sep., 1999 |
| | X | Horn Antenna | EM | EM6917 / 103325 | May, 2000 |

- Note:
1. All equipment upon which need to calibrated are with calibration period of 1 year.
 - 2.. Mark "X" test instruments are used to measure the final test results.

3.2 Test Setup



3.3 Limits

| CISPR 22 Limits | | | | | FCC Part 15 Subpart B | | | | |
|-----------------|--------------|--------|--------------|--------|-----------------------|---------|--------|---------|--------|
| Frequency | Class A | | Class B | | Frequency | Class A | | Class B | |
| MHz | Distance (m) | dBuV/m | Distance (m) | dBuV/m | | uV/m | dBuV/m | uV/m | dBuV/m |
| 30 – 230 | 10 | 40 | 10 | 30 | 30 – 88 | 90 | 39 | 100 | 40.0 |
| 230 – 1000 | 10 | 47 | 10 | 37 | 88 – 216 | 150 | 43.5 | 150 | 43.5 |
| | | | | | 216 – 960 | 210 | 46.5 | 200 | 46.0 |
| | | | | | 960 - 2000 | 300 | 49.5 | 500 | 54.0 |

- Remark: 1. The tighter limit shall apply at the edge between two frequency bands.
2. Distance refers to the distance in meters between the measuring instrument antenna and the closed point of any part of the device or system.
3. RF Line Voltage (dBuV/m) = 20 log RF Line Voltage (uV/m)

3.4 Test Procedure

The EUT and its simulators are placed on a turn table which is 0.8 meter above ground. The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT was positioned such that the distance from antenna to the EUT was 10 meters . The antenna can move up and down between 1 meter and 4 meters to find out the maximum emission level.

Both horizontal and vertical polarization of the antenna are set on measurement. In order to find the maximum emission, all of the interface cables must be manipulated according to ANSI C63.4 /1992 on radiated measurement.

The bandwidth below 1GHz setting on the field strength meter (R&S Test Receiver ESCS 30) is 120 kHz.

3.5 Test Results

The radiated emission from the EUT is measured and shown in attachment 1 of test report. The acceptance criterion was met and the EUT passed the test.

4. EMI Reduction Method During Compliance Testing

No modification was made during testing.



5. Attachment

| | |
|--|--------------------|
| Attachment 1: Summary of Test Results | Number of Pages: 5 |
| Attachment 2: EUT Test photographs | Number of Pages: 2 |
| Attachment 3: EUT Detailed Photographs | Number of Pages: 2 |

Attachment 1 : Summary of Test Results

The test results in the emission were performed according to the requirements of measurement standard and process. QuieTek Corporation is assumed full responsibility for the accuracy and completeness of these measurements. The test data of the emission are listed as the attached data.

All the tests were carried out with the EUT in normal operation, which was defined as:

(1) Mode 1: BearPaw 1200F

The EUT passed all the tests.

The uncertainty is calculated in accordance with NAMAS NIS 81, The total uncertainty for this test is as follows:

► Emission Test

- Uncertainty in the Conducted Emission Test: $< \pm 2.0$ dB
- Uncertainty in the field strength measured: $< \pm 4.0$ dB

CONDUCTED EMISSION DATA

Date of Test : July 23, 2000 EUT : Scanner
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

| Frequency | Cable Loss | LISN Factor | Reading Level | Measurement Level | Limits |
|-----------------|------------|-------------|---------------|-------------------|--------|
| MHz | dB | dB | Line1 dBuV | Line1 dBuV | dBuV |
| * 0.211 | 0.02 | 0.10 | 51.07 | 51.19 | 63.16 |
| 0.318 | 0.04 | 0.10 | 38.86 | 39.00 | 59.76 |
| 0.427 | 0.06 | 0.10 | 38.28 | 38.44 | 57.32 |
| 1.066 | 0.10 | 0.10 | 40.17 | 40.38 | 56.00 |
| 1.263 | 0.11 | 0.11 | 40.48 | 40.70 | 56.00 |
| 1.896 | 0.14 | 0.13 | 40.09 | 40.36 | 56.00 |
| Average: | | | | | |
| 0.211 | 0.02 | 0.10 | 38.20 | 38.32 | 53.17 |
| 0.318 | 0.04 | 0.10 | 26.90 | 27.04 | 49.76 |
| 0.427 | 0.06 | 0.10 | 31.90 | 32.06 | 47.31 |
| 1.066 | 0.10 | 0.10 | 27.50 | 27.71 | 46.00 |
| 1.263 | 0.11 | 0.11 | 26.00 | 26.22 | 46.00 |
| 1.896 | 0.14 | 0.13 | 23.90 | 24.17 | 46.00 |

Remarks :

1. “ * ” means that this data is the worst emission level.

CONDUCTED EMISSION DATA

Date of Test : July 23, 2000 EUT : Scanner
 Test Mode : Mode 1 Detect Mode : Quasi-Peak & Average

| Frequency MHz | Cable Loss dB | LISN Factor dB | Reading Level Line2 dBuV | Measurement Level Line2 dBuV | Limits dBuV |
|------------------|---------------------|----------------------|--------------------------------|------------------------------------|----------------|
| * 0.215 | 0.02 | 0.10 | 49.79 | 49.91 | 63.01 |
| 0.322 | 0.04 | 0.10 | 39.54 | 39.68 | 59.66 |
| 0.428 | 0.06 | 0.10 | 40.31 | 40.47 | 57.30 |
| 0.428 | 0.06 | 0.10 | 40.29 | 40.45 | 57.30 |
| 0.765 | 0.09 | 0.10 | 39.88 | 40.07 | 56.00 |
| 0.765 | 0.09 | 0.10 | 39.86 | 40.05 | 56.00 |
| 1.095 | 0.11 | 0.10 | 39.02 | 39.23 | 56.00 |
| 1.900 | 0.14 | 0.13 | 40.22 | 40.49 | 56.00 |
| 1.900 | 0.14 | 0.13 | 40.20 | 40.47 | 56.00 |

Average:

| | | | | | |
|-------|------|------|-------|-------|-------|
| 0.215 | 0.02 | 0.10 | 41.10 | 41.22 | 53.01 |
| 0.322 | 0.04 | 0.10 | 32.60 | 32.74 | 49.66 |
| 0.428 | 0.06 | 0.10 | 34.00 | 34.16 | 47.29 |
| 0.765 | 0.09 | 0.10 | 28.20 | 28.39 | 46.00 |
| 1.095 | 0.11 | 0.10 | 24.60 | 24.81 | 46.00 |
| 1.900 | 0.14 | 0.13 | 23.90 | 24.17 | 46.00 |

Remarks :

1. “ * ” means that this data is the worst emission level.

RADIATED EMISSION DATA

Date of Test : July 23, 2000 EUT : Scanner
 Test Mode : Mode 1 Test Site : No.2 Open Test Site

| Freq. | Cable Loss | Probe Factor | PreAMP | Reading Level | Measurement Horizontal | Margin | Limit | Ant | Turn |
|-----------|------------|--------------|--------|---------------|------------------------|--------|--------|-----|------|
| MHz | dB | dB/m | dB | dBuV | dBuV/m | dB | dBuV/m | cm | deg |
| 41.825 | 1.26 | 11.71 | 0.00 | 0.83 | 13.80 | 16.20 | 30.00 | 397 | 115 |
| 120.000 | 2.02 | 12.02 | 0.00 | 2.92 | 16.96 | 13.04 | 30.00 | 397 | 93 |
| 132.000 | 2.13 | 11.39 | 0.00 | 3.59 | 17.12 | 12.88 | 30.00 | 397 | 93 |
| * 167.997 | 2.48 | 9.59 | 0.00 | 10.92 | 22.98 | 7.02 | 30.00 | 397 | 109 |
| 192.000 | 2.71 | 9.00 | 0.00 | 7.46 | 19.17 | 10.83 | 30.00 | 397 | 76 |
| 198.068 | 2.77 | 9.15 | 0.00 | 7.05 | 18.97 | 11.03 | 30.00 | 397 | 76 |
| 233.137 | 3.11 | 10.71 | 0.00 | 10.57 | 24.39 | 12.61 | 37.00 | 397 | 110 |
| 287.995 | 3.63 | 13.11 | 0.00 | 8.56 | 25.30 | 11.70 | 37.00 | 338 | 202 |
| 307.992 | 3.79 | 13.43 | 0.00 | 4.59 | 21.81 | 15.19 | 37.00 | 301 | 145 |

Remarks:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. “ * ”, means this data is the worst emission level.
3. Emission Level = Reading Level + Antenna Factor + Cable loss

RADIATED EMISSION DATA

Date of Test : July 23, 2000 EUT : Scanner
 Test Mode : Mode 1 Test Site : No.2 Open Test Site

| Freq. | Cable Loss | Probe Factor | PreAMP | Reading Level | Measurement Vertical | Margin | Limit | Ant | Turn |
|-----------|------------|--------------|--------|---------------|----------------------|--------|--------|-----|------|
| MHz | dB | dB/m | dB | dBuV | dBuV/m | dB | dBuV/m | cm | deg |
| 119.995 | 2.02 | 11.56 | 0.00 | 5.04 | 18.62 | 11.38 | 30.00 | 99 | 87 |
| 132.040 | 2.13 | 11.49 | 0.00 | 6.22 | 19.85 | 10.15 | 30.00 | 99 | 33 |
| * 168.000 | 2.48 | 9.67 | 0.00 | 7.78 | 19.93 | 10.07 | 30.00 | 99 | 193 |
| 192.000 | 2.71 | 8.88 | 0.00 | 4.24 | 15.83 | 14.17 | 30.00 | 99 | 29 |
| 233.137 | 3.11 | 10.51 | 0.00 | 12.24 | 25.86 | 11.14 | 37.00 | 99 | 203 |
| 307.990 | 3.79 | 14.04 | 0.00 | 1.51 | 19.34 | 17.66 | 37.00 | 99 | 5 |

Remarks:

1. All Readings below 1GHz are Quasi-Peak, above are average value.
2. “ * ”, means this data is the worst emission level.
3. Emission Level = Reading Level + Antenna Factor + Cable loss

Attachment 2: EUT Test Setup Photographs

Front View of Conducted Test (Mode 1)



Back View of Conducted Test (Mode 1)



Front View of Radiated Test (Mode 1)



Back View of Radiated Test (Mode 1)

