

Introducing
Be@rPaw 1200F

Mustek Systems, Inc.



FCC ID: HWFBEARPAW

FCC Statement

This digital equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and if it is not installed and used according to the instruction manual, it may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment causes harmful interference to radio or television reception, which can be determined by turning the equipment off or on, you are encouraged to try to correct the interference by one or more of the following measures:

- Reorient the receiving antenna
- Increase the distance between the equipment and the receiver
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected
- Consult the dealer or an experienced radio/TV technician for help

NOTE:

1. The changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.
2. Shielded interface cables and AC power cord, if any, must be used in order to comply with the emission limits.

Specifications

Scanner Type	Color Flatbed
Scan Area	21.6 cm x 29.7 cm (8.5" x 11.7")
Scan Modes	
True Color	36-bit (Internal), 68.7 billion colors
	24-bit (External), 16.7 million colors
	48-bit (software enhanced)
Gray Mode	12-bit (Internal), 4096 shades of gray
	8-bit (External), 256 shades of gray
Text/Line Art	1 bit/pixel (2 levels)
Scan Method	Single Pass Scanning
Resolution Control	
Optical	600dpi (H) x 1200dpi (V)
Enhanced	19200dpi x 19200dpi (software controlled)
Scanning Data Buffer	512KB (maximum)
Interface	USB (Universal Serial Bus)
Voltage Requirement	100 ~ 240 Vac, 50 ~ 60 Hz
Power Consumption	15W (12V DC), 1.25A switching power adapter
Operating Temperature	10°C ~ 40°C (50°F ~ 104°F)
Operating Humidity	35% ~ 80% RH, Non-Condensing
Storage Temperature	-10°C ~ 60°C (14°F ~ 140°F)
Storage Humidity	20% ~ 80% RH, Non-Condensing
Dimensions	464 x 290 x 100 mm (L x W x H)
Weight	2.8 Kg