

# **RADIO TEST REPORT**

## **Test Report No. 15388555H**

<b>Customer</b>	DENSO CORPORATION
<b>Description of EUT</b>	Smart Card Key
<b>Model Number of EUT</b>	14CNA
<b>FCC ID</b>	HYQ14CNA
<b>Test Regulation</b>	FCC Part 15 Subpart C
<b>Test Result</b>	Complied
<b>Issue Date</b>	September 3, 2024
<b>Remarks</b>	-

**Representative test engineer**Yuichiro Yamazaki  
Engineer**Approved by**Shinichi Miyazono  
Leader

CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
- ☒ There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 23.0

# ANNOUNCEMENT

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.  
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

# REVISION HISTORY

Original Test Report No. 15388555H

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	15388555H	September 3, 2024	-

## Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer Information .....</b>	<b>5</b>
<b>SECTION 2: Equipment Under Test (EUT).....</b>	<b>5</b>
<b>SECTION 3: Test Specification, Procedures &amp; Results .....</b>	<b>6</b>
<b>SECTION 4: Operation of EUT during testing .....</b>	<b>9</b>
<b>SECTION 5: Radiated Spurious Emission.....</b>	<b>10</b>
<b>SECTION 6: Automatically deactivate .....</b>	<b>12</b>
<b>SECTION 7: -20 dB Bandwidth and 99% emission bandwidth .....</b>	<b>12</b>
<b>APPENDIX 1: Test Data .....</b>	<b>13</b>
Automatically deactivate .....	13
Radiated Emission (Fundamental and Spurious Emission).....	14
-20 dB Bandwidth / 99% emission bandwidth.....	17
<b>APPENDIX 2: Test Instruments .....</b>	<b>18</b>
<b>APPENDIX 3: Photographs of Test Setup .....</b>	<b>19</b>
Radiated Spurious Emission.....	19
Worst Case Position .....	21

## **SECTION 1: Customer Information**

Company Name	DENSO CORPORATION
Address	1-1, Showa-cho, Kariya-shi, Aichi-ken, 448-8661, Japan
Telephone Number	+81-566-61-7496
Contact Person	Koji Yamashita

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

## **SECTION 2: Equipment Under Test (EUT)**

### **2.1 Identification of EUT**

Description	Smart Card Key
Model Number	14CNA
Serial Number	Refer to SECTION 4.2
Condition	Engineering prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	August 2, 2024
Test Date	August 6 and 19, 2024

### **2.2 Product Description**

#### **General Specification**

Rating	DC 3 V
--------	--------

#### **Radio Specification**

Equipment Type	Transmitter
Frequency of Operation	433.58 MHz / 434.42 MHz* *These two different frequencies are not emitted simultaneously.
Type of Modulation	FSK (F1D)
Type of Battery	One lithium battery
Antenna type	Built-in type (Fixed)

Equipment Type	Receiver
Frequency of Operation	125 kHz

\*Original model: 14CNA has the following two types; Type A, Type B  
The worst case was confirmed with Type A and Type B at pre check.  
The test was performed with Type A as representative as its result was the worst one.

## SECTION 3: Test Specification, Procedures & Results

### 3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47CFR Part15 Radio Frequency Device Subpart C Intentional Radiators Section 15.231 Periodic operation in the band 40.66-40.70 MHz and above 70 MHz.

### 3.2 Procedures and Results

Item	Test Procedure	Specification	Worst margin	Results	Remarks
Conducted emission	<b>FCC:</b> ANSI C63.10:2013 6 Standard test methods  <b>ISED:</b> RSS-Gen 8.8	<b>FCC:</b> Section 15.207  <b>ISED:</b> RSS-Gen 8.8	N/A	N/A	*1)
Automatically Deactivate	<b>FCC:</b> ANSI C63.10:2013 6 Standard test methods  <b>ISED:</b> -	<b>FCC:</b> Section 15.231(a)(1)  <b>ISED:</b> RSS-210 A1.2	N/A	Complied	Radiated
Electric Field Strength of Fundamental Emission	<b>FCC:</b> ANSI C63.10:2013 6 Standard test methods  <b>ISED:</b> RSS-Gen 6.12	<b>FCC:</b> Section 15.231(b)  <b>ISED:</b> RSS-210 A1.3	9.2 dB 434.420 MHz Vertical PK with Duty Factor	Complied	Radiated
Electric Field Strength of Spurious Emission	<b>FCC:</b> ANSI C63.10:2013 6 Standard test methods  <b>ISED:</b> RSS-Gen 6.13	<b>FCC:</b> Section 15.205 Section 15.209 Section 15.231(b) <b>ISED:</b> RSS-210 A1.3 RSS-Gen 8.9	5.3 dB 3909.780 MHz Vertical PK with Duty Factor	Complied	Radiated
-20 dB Bandwidth	<b>FCC:</b> ANSI C63.10:2013 6 Standard test methods  <b>ISED:</b> -	<b>FCC:</b> Section 15.231(c)  <b>ISED:</b> Reference data	N/A	Complied	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

\*1) The test is not applicable since the EUT does not have AC Mains.

#### **FCC Part 15.31 (e)**

The test was performed with the New Battery during the tests.  
Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the EUT.

Therefore, the equipment complies with the antenna requirement of Section 15.203.

### 3.3 Addition to Standard

Item	Test Procedure	Specification	Worst margin	Results	Remarks
99% emission bandwidth	ANSI C63.10:2013 6 Standard test methods	Reference data	N/A	-	Radiated

Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593.

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.  
Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k = 2$ .

#### Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	3.3
10 m			dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	dB	5.0
		Vertical	dB	5.0
	200 MHz to 1000 MHz	Horizontal	dB	5.2
		Vertical	dB	6.2
10 m	30 MHz to 200 MHz	Horizontal	dB	5.5
		Vertical	dB	5.4
	200 MHz to 1000 MHz	Horizontal	dB	5.5
		Vertical	dB	5.5
3 m	1 GHz to 6 GHz		dB	5.1
	6 GHz to 18 GHz		dB	5.4
1 m	10 GHz to 18 GHz		dB	5.4
	18 GHz to 26.5 GHz		dB	5.3
	26.5 GHz to 40 GHz		dB	4.8
0.5 m	26.5 GHz to 40 GHz		dB	5.0

#### Automatically Deactivate, -20 dB Bandwidth and 99% Occupied Bandwidth

Item	Unit	Calculated Uncertainty (+/-)
Bandwidth (OBW)	%	0.96
Time readout (time span upto 100 msec)	%	0.11
Time readout (time span upto 1000 msec)	%	0.11
Time readout (time span upto 60 sec)	%	0.02

### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

\*A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

### 3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.




## SECTION 4: Operation of EUT during testing

### 4.1 Operating Mode(s)

Test mode	Remarks
1) Normal use mode (Tx 433.58 MHz / 434.42 MHz)	Automatically Deactivate
2) Transmitting mode (Tx 433.58 MHz)	Electric Field Strength of Fundamental Emission Electric Field Strength of Spurious Emission -20 dB Bandwidth / 99% emission bandwidth
3) Transmitting mode (Tx 434.42 MHz)	
* The system was configured in typical fashion (as a user would normally use it) for testing.	
*Power of the EUT was set by the software as follows; Software:           Product program Version: 0A010107 (Date: 2024.02.07, Storage location: EUT memory)	
*This setting of software is the worst case. Any conditions under the normal use do not exceed the condition of setting. In addition, end users cannot change the settings of the output power of the product.	
Justification: The system was configured in typical fashion (as a user would normally use it) for testing.	

This EUT has two modes which mechanical key is inserted or not. The worst case was confirmed with and without mechanical key inserted, as a result, the test with mechanical key inserted was the worst case. Therefore, the test with mechanical key inserted was performed only.

### 4.2 Configuration and Peripherals



\* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

#### Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remark
A	Smart Card Key	14CNA	No.4 *1) No.3 *2)	DENSO CORPORATION	EUT
B	Test Bench	-	-	DENSO CORPORATION	*1)

#### List of Cables Used

No.	Name	Length (m)	Shield		Remark
			Cable	Connector	
1	DC Cable	1.2	Unshielded	Unshielded	*1)

\*1) Used for Automatically deactivate test

\*2) Used for other tests except for Automatically deactivate test

## **SECTION 5: Radiated Spurious Emission**

### **Test Procedure**

[For below 30 MHz]

The noise level was checked by moving a search-coil (Loop Antenna) close to the EUT.

[For 30 MHz to 1 GHz]

EUT was placed on a urethane platform of nominal size, 1.0 m by 1.5 m, raised 0.8 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane.

The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane.

The measuring antenna height was varied between 1 and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The measurements were performed for both vertical and horizontal antenna polarization.


The radiated emission measurements were made with the following detector function of the test receiver / spectrum analyzer.

### **Test Antennas are used as below;**

Frequency	Below 30 MHz	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Loop	Biconical	Logperiodic	Horn


Frequency	From 9 kHz to 90 kHz and From 110 kHz to 150 kHz	From 90 kHz to 110 kHz	From 150 kHz to 490 kHz	From 490 kHz to 30 MHz	From 30 MHz to 1 GHz	Above 1 GHz
Detector Type	Peak	Peak	Peak	Peak	Peak and Peak with Duty factor	Peak and Peak with Duty factor
IF Bandwidth	200 Hz	200 Hz	9.1 kHz	9.1 kHz	120 kHz	PK: S/A: RBW: 1 MHz, VBW: 3 MHz

[Test Setup]  
Below 1 GHz



Test Distance: 3 m

1 GHz to 4.4 GHz



Distance Factor:  $20 \times \log (3.75 \text{ m} / 3.0 \text{ m}) = 1.94 \text{ dB}$   
\* Test Distance:  $(3 + \text{SVSWR Volume} / 2) - r = 3.75 \text{ m}$

SVSWR Volume : 1.5 m  
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)  
 $r = 0.0 \text{ m}$

\* The test was performed with  $r = 0.0 \text{ m}$  since EUT is small and it was the rather conservative condition.

- The carrier level and noise levels were confirmed at each position of X, Y and Z axes of EUT to see the position of maximum noise, and the test was made at the position that has the maximum noise.

The test results and limit are rounded off to one decimal place, so some differences might be observed.

Measurement range : 9 kHz to 4.4 GHz  
Test data : APPENDIX  
Test result : Pass

---

## **SECTION 6: Automatically deactivate**

### **Test Procedure**

The measurement was performed with Electric field strength using a spectrum analyzer.

Test data : APPENDIX  
Test result : Pass

## **SECTION 7: -20 dB Bandwidth and 99% emission bandwidth**

### **Test Procedure**

The test was measured with a spectrum analyzer using a test fixture.

Test	Span	RBW	VBW	Sweep	Detector	Trace	Instrument used
-20 dB Bandwidth / 99% emission bandwidth	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak *1)	Max Hold *1)	Spectrum Analyzer
*1) Peak hold was applied as Worst-case measurement.							


Test data : APPENDIX  
Test result : Pass

APPENDIX 1: Test Data

Automatically deactivate

Test place                      Ise EMC Lab.  
Shielded Room                No.6  
Date                             August 6, 2024  
Temperature / Humidity       25 deg. C / 55 % RH  
Engineer                        Yuichiro Yamazaki  
Mode                             Mode 1

Tx Freq. [MHz]	Time of Transmitting [s]	Limit [s]	Result
433.58	0.2698	5.00	Pass
434.42	0.2698	5.00	Pass



\* The EUT transmits UHF when LF signal is received from a car. The UHF transmission is stopped within 5 seconds. (Refer to Theory of operation-specification.)

## Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.2
Date	August 19, 2024
Temperature / Humidity	25 deg. C / 56 % RH
Engineer	Yuichiro Yamazaki
Mode	Mode 2

Polarity [Hori/Vert]	Frequency [MHz]	Reading (PK) [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (PK) [dBuV/m]	Result (PK with Duty Factor) [dBuV/m]	Limit (PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (PK) [dB]	Margin (AV) [dB]	Inside or Outside of Restricted Bands	Remarks
Hori.	433.580	74.0	16.3	9.5	28.7	-	71.1	71.1	100.8	80.8	29.7	9.7	Carrier	
Hori.	867.160	39.3	21.9	11.7	28.9	-	44.0	44.0	80.8	60.8	36.8	16.8	Outside	
Hori.	1300.740	48.2	26.1	4.3	36.6	-	42.0	42.0	73.9	53.9	31.9	11.9	Inside	
Hori.	1734.320	49.0	25.2	4.6	36.3	-	42.5	42.5	80.8	60.8	38.3	18.3	Outside	
Hori.	2167.900	56.0	28.2	4.9	36.1	-	53.0	53.0	80.8	60.8	27.8	7.8	Outside	
Hori.	2601.480	48.4	27.7	5.1	36.1	-	45.1	45.1	80.8	60.8	35.7	15.7	Outside	
Hori.	3035.060	48.8	28.6	5.4	36.2	-	46.6	46.6	80.8	60.8	34.2	14.2	Outside	
Hori.	3468.640	48.1	28.7	5.7	35.9	-	46.6	46.6	80.8	60.8	34.2	14.2	Outside	
Hori.	3902.220	48.0	29.8	6.0	35.7	-	48.1	48.1	73.9	53.9	25.8	5.8	Inside	
Hori.	4335.800	44.5	30.7	6.2	35.6	-	45.8	45.8	73.9	53.9	28.1	8.1	Inside	
Vert.	433.580	74.4	16.3	9.5	28.7	-	71.5	71.5	100.8	80.8	29.3	9.3	Carrier	
Vert.	867.160	36.5	21.9	11.7	28.9	-	41.2	41.2	80.8	60.8	39.6	19.6	Outside	
Vert.	1300.740	46.2	26.1	4.3	36.6	-	40.0	40.0	73.9	53.9	33.9	13.9	Inside	
Vert.	1734.320	48.6	25.2	4.6	36.3	-	42.1	42.1	80.8	60.8	38.7	18.7	Outside	
Vert.	2167.900	56.3	28.2	4.9	36.1	-	53.3	53.3	80.8	60.8	27.5	7.5	Outside	
Vert.	2601.480	46.1	27.7	5.1	36.1	-	42.8	42.8	80.8	60.8	38.0	18.0	Outside	
Vert.	3035.060	49.3	28.6	5.4	36.2	-	47.1	47.1	80.8	60.8	33.7	13.7	Outside	
Vert.	3468.640	46.3	28.7	5.7	35.9	-	44.8	44.8	80.8	60.8	36.0	16.0	Outside	
Vert.	3902.220	46.6	29.8	6.0	35.7	-	46.7	46.7	73.9	53.9	27.2	7.2	Inside	
Vert.	4335.800	44.5	30.7	6.2	35.6	-	45.8	45.8	73.9	53.9	28.1	8.1	Inside	

Sample calculation:

Result of PK = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)} - Gain (Amplifier)

Result of PK with Duty factor (PK / W) = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)} - Gain (Amplifier) + Duty factor

For above 1 GHz: Distance Factor:  $20 \times \log (3.75 \text{ m}/3.0 \text{ m}) = 1.94 \text{ dB}$

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Since the peak emission result satisfied the average limit, duty factor was omitted.

Although Duty of this product was 100% or less, the result of AV (PK with Duty factor) was calculated by applying Duty 100 % as worst.

If Gain 0.0 dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.

## Radiated Emission (Fundamental and Spurious Emission)

Test place	Ise EMC Lab.	No.2
Semi Anechoic Chamber	No.2	August 19, 2024
Date	August 19, 2024	August 19, 2024
Temperature / Humidity	25 deg. C / 56 % RH	22 deg. C / 59 % RH
Engineer	Yuichiro Yamazaki	Nachi Konegawa
	(Below 1 GHz)	(Above 1 GHz)
Mode	Mode 3	

Polarity [Hori/Vert]	Frequency [MHz]	Reading (PK) [dBuV]	Ant Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (PK) [dBuV/m]	Result (PK with Duty Factor) [dBuV/m]	Limit (PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (PK) [dB]	Margin (AV) [dB]	Inside or Outside of Restricted Bands	Remarks
Hori.	434.420	73.9	16.3	9.5	28.7	-	71.0	71.0	100.8	80.8	29.8	9.8	Carrier	
Hori.	868.840	39.0	21.9	11.7	28.9	-	43.7	43.7	80.8	60.8	37.1	17.1	Outside	
Hori.	1303.260	47.9	26.1	4.3	36.6	-	41.7	41.7	73.9	53.9	32.2	12.2	Inside	
Hori.	1737.680	50.1	25.2	4.6	36.3	-	43.6	43.6	80.8	60.8	37.2	17.2	Outside	
Hori.	2172.100	55.7	28.2	4.9	36.1	-	52.7	52.7	80.8	60.8	28.1	8.1	Outside	
Hori.	2606.520	48.2	27.7	5.1	36.1	-	44.9	44.9	80.8	60.8	35.9	15.9	Outside	
Hori.	3040.940	49.2	28.6	5.4	36.2	-	47.0	47.0	80.8	60.8	33.8	13.8	Outside	
Hori.	3475.360	47.5	28.7	5.7	35.9	-	46.0	46.0	80.8	60.8	34.8	14.8	Outside	
Hori.	3909.780	48.4	29.8	6.0	35.7	-	48.5	48.5	73.9	53.9	25.4	5.4	Inside	
Hori.	4344.200	45.7	30.7	6.2	35.6	-	47.0	47.0	73.9	53.9	26.9	6.9	Inside	
Vert.	434.420	74.5	16.3	9.5	28.7	-	71.6	71.6	100.8	80.8	29.2	9.2	Carrier	
Vert.	868.840	36.8	21.9	11.7	28.9	-	41.5	41.5	80.8	60.8	39.3	19.3	Outside	
Vert.	1303.260	47.4	26.1	4.3	36.6	-	41.2	41.2	73.9	53.9	32.7	12.7	Inside	
Vert.	1737.680	50.5	25.2	4.6	36.3	-	44.0	44.0	80.8	60.8	36.8	16.8	Outside	
Vert.	2172.100	56.4	28.2	4.9	36.1	-	53.4	53.4	80.8	60.8	27.4	7.4	Outside	
Vert.	2606.520	47.5	27.7	5.1	36.1	-	44.2	44.2	80.8	60.8	36.6	16.6	Outside	
Vert.	3040.940	50.6	28.6	5.4	36.2	-	48.4	48.4	80.8	60.8	32.4	12.4	Outside	
Vert.	3475.360	47.8	28.7	5.7	35.9	-	46.3	46.3	80.8	60.8	34.5	14.5	Outside	
Vert.	3909.780	48.5	29.8	6.0	35.7	-	48.6	48.6	73.9	53.9	25.3	5.3	Inside	
Vert.	4344.200	46.0	30.7	6.2	35.6	-	47.3	47.3	73.9	53.9	26.6	6.6	Inside	

Sample calculation:

Result of PK = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)} - Gain (Amplifier)

Result of PK with Duty factor (PK / W) = Reading + Ant Factor + Loss {Cable + Attenuator + Filter (above 1 GHz) + Distance factor (above 1 GHz)} - Gain (Amplifier) + Duty factor

For above 1 GHz: Distance Factor:  $20 \times \log(3.75 \text{ m}/3.0 \text{ m}) = 1.94 \text{ dB}$

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

Since the peak emission result satisfied the average limit, duty factor was omitted.

Although Duty of this product was 100% or less, the result of AV (PK with Duty factor) was calculated by applying Duty 100 % as worst.



If Gain 0.0 dB shown in the above table, pre-amplifier was not used to avoid the influence of carrier power. The pre-amplifier used for carrier frequency measurement was not saturated.

## **Radiated Spurious Emission** **(Plot data, Worst case for Spurious Emission)**

Test place  
Semi Anechoic Chamber  
Date  
Temperature / Humidity  
Engineer  
Mode

Ise EMC Lab.  
No.2  
August 19, 2024  
25 deg. C / 56 % RH  
Yuichiro Yamazaki  
(Below 1 GHz)  
Mode 3

No.2  
August 19, 2024  
22 deg. C / 59 % RH  
Nachi Konegawa  
(Above 1 GHz)





**-20 dB Bandwidth / 99% emission bandwidth**

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.2
Date	August 19, 2024
Temperature / Humidity	25 deg. C / 56 % RH
Engineer	Yuichiro Yamazaki
Mode	Mode 2, Mode 3

Bandwidth Limit : Fundamental Frequency       $433.58 \text{ MHz} \times 0.25 \% = 1083.950 \text{ kHz}$

\* The above limit was calculated from more stringent nominal frequency.

\* Method of KDB 926416 for systems employing non sweeping frequencies was referred.

<b>433.58 MHz</b>	<b>434.42 MHz</b>
-20 dB Bandwidth [kHz]	-20 dB Bandwidth [kHz]
70.133	70.099


-20 dB Bandwidth [kHz]	Bandwidth Limit [kHz]	Result
140.232	1083.950	Pass

Bandwidth Limit : Fundamental Frequency       $433.58 \text{ MHz} \times 0.25 \% = 1083.950 \text{ kHz}$

99% emission bandwidth [kHz]	Bandwidth Limit [kHz]	Result
74.7236	1083.950	Pass

Bandwidth Limit : Fundamental Frequency       $434.42 \text{ MHz} \times 0.25 \% = 1086.050 \text{ kHz}$

99% emission bandwidth [kHz]	Bandwidth Limit [kHz]	Result
74.5915	1086.050	Pass



## APPENDIX 2: Test Instruments

### Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
RE	141265	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-190	07/10/2024	12
RE	141317	Coaxial Cable	UL Japan	-	-	09/12/2023	12
RE	141393	Microwave Cable	Junkosha	MWX221	1604S254(1 m) / 1608S088(5 m)	07/06/2024	12
RE	141405	High Pass Filter 0.7-5GHz	TOKIMEC	TF305CCA	601	06/06/2024	12
RE	141427	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103B+BBA9106	08031	07/30/2024	12
RE	141512	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	254	10/17/2023	12
RE	141542	Digital Tester	Fluke Corporation	FLUKE 26-3	78030611	08/06/2024	12
RE	141558	Digital Tester(TRUE RMS MULTIMETER)	Fluke Corporation	115	17930030	05/17/2024	12
RE	141576	Pre Amplifier	Keysight Technologies Inc	8449B	3008A01671	02/17/2024	12
RE	141594	Pre Amplifier	Keysight Technologies Inc	8447D	2944A10150	02/17/2024	12
RE	141899	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY46180655	05/09/2024	12
RE	141949	Test Receiver	Rohde & Schwarz	ESCI	100767	06/05/2024	12
RE	141978	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY46180899	05/09/2024	12
RE	142004	AC2_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-06902	12/12/2023	24
RE	142006	AC2_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-06902	04/17/2023	24
RE	142225	Tape Measure	ASKUL	-	-	-	-
RE	142228	Measure, Tape, Steel	KOMELON	KMC-36	-	-	-
RE	142645	Loop Antenna	UL Japan	-	-	-	-
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	220646	Attenuator	Huber+Suhner	6806_N-50-1	-	03/12/2024	12
RE	244707	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202102	01/25/2024	12
RE	244712	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202106	01/25/2024	12

\*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

RE: Radiated Emission