

# RADIO TEST REPORT

## Test Report No. 15474876H-B-R2

Customer	DENSO CORPORATION
Description of EUT	Cockpit Control Unit
Model Number of EUT	DNNS125
FCC ID	HYQDNNS125
Test Regulation	FCC Part 15 Subpart C
Test Result	Complied
Issue Date	November 29, 2024
Remarks	Bluetooth (BR / EDR) parts

**Representative Test Engineer**Yuta Moriya  
Engineer**Approved By**Ryota Yamanaka  
Engineer

CERTIFICATE 5107.02

- ☐ The testing in which "Non-accreditation" is displayed is outside the accreditation scopes in UL Japan, Inc.
- ☒ There is no testing item of "Non-accreditation".

Report Cover Page - Form-ULID-003532 (DCS:13-EM-F0429) Issue# 23.0

## **ANNOUNCEMENT**

- This test report shall not be reproduced in full or partial, without the written approval of UL Japan, Inc.
- The results in this report apply only to the sample tested. (Laboratory was not involved in sampling.)
- This sample tested is in compliance with the limits of the above regulation.
- The test results in this test report are traceable to the national or international standards.
- This test report must not be used by the customer to claim product certification, approval, or endorsement by the A2LA accreditation body.
- This test report covers Radio technical requirements.  
It does not cover administrative issues such as Manual or non-Radio test related Requirements. (if applicable)
- The all test items in this test report are conducted by UL Japan, Inc. Ise EMC Lab.
- The opinions and the interpretations to the result of the description in this report are outside scopes where UL Japan, Inc. has been accredited.
- The information provided by the customer for this report is identified in SECTION 1.
- The laboratory is not responsible for information provided by the customer which can impact the validity of the results.
- For test report(s) referred in this report, the latest version (including any revisions) is always referred.

## **REVISION HISTORY**

### **Original Test Report No.: 15474876H-B**

This report is a revised version of 15474876H-B-R1. 15474876H-B-R1 is replaced with this report.

Revision	Test Report No.	Date	Page Revised Contents
- (Original)	15474876H-B	September 6, 2024	-
1	15474876H-B-R1	October 25, 2024	P.6 and correspondence page Correction of Antenna gain for 2.4 GHz band: WLAN: from 1.10 dBi to 1.78 dBi Bluetooth: from 1.10 dBi to 1.83 dBi
1	15474876H-B-R1	October 25, 2024	P.10 Correction of Power Setting value
1	15474876H-B-R1	October 25, 2024	P.28 Deletion of unnecessary symbol
1	15474876H-B-R1	October 25, 2024	P.47 Correction of test Mode from DH5 to 3DH5
2	15474876H-B-R2	November 29, 2024	P.10 Deletion of table for Simultaneous Transmission

## Reference: Abbreviations (Including words undescribed in this report)

A2LA	The American Association for Laboratory Accreditation	ICES	Interference-Causing Equipment Standard
AC	Alternating Current	IEC	International Electrotechnical Commission
AFH	Adaptive Frequency Hopping	IEEE	Institute of Electrical and Electronics Engineers
AM	Amplitude Modulation	IF	Intermediate Frequency
Amp, AMP	Amplifier	ILAC	International Laboratory Accreditation Conference
ANSI	American National Standards Institute	ISED	Innovation, Science and Economic Development Canada
Ant, ANT	Antenna	ISO	International Organization for Standardization
AP	Access Point	JAB	Japan Accreditation Board
ASK	Amplitude Shift Keying	LAN	Local Area Network
Atten., ATT	Attenuator	LIMS	Laboratory Information Management System
AV	Average	MCS	Modulation and Coding Scheme
BPSK	Binary Phase-Shift Keying	MRA	Mutual Recognition Arrangement
BR	Bluetooth Basic Rate	N/A	Not Applicable
BT	Bluetooth	NIST	National Institute of Standards and Technology
BT LE	Bluetooth Low Energy	NS	No signal detect.
BW	BandWidth	NSA	Normalized Site Attenuation
Cal Int	Calibration Interval	NVLAP	National Voluntary Laboratory Accreditation Program
CCK	Complementary Code Keying	OBW	Occupied Band Width
Ch., CH	Channel	OFDM	Orthogonal Frequency Division Multiplexing
CISPR	Comite International Special des Perturbations Radioelectriques	P/M	Power meter
CW	Continuous Wave	PCB	Printed Circuit Board
DBPSK	Differential BPSK	PER	Packet Error Rate
DC	Direct Current	PHY	Physical Layer
D-factor	Distance factor	PK	Peak
DFS	Dynamic Frequency Selection	PN	Pseudo random Noise
DQPSK	Differential QPSK	PRBS	Pseudo-Random Bit Sequence
DSSS	Direct Sequence Spread Spectrum	PSD	Power Spectral Density
EDR	Enhanced Data Rate	QAM	Quadrature Amplitude Modulation
EIRP, e.i.r.p.	Equivalent Isotropically Radiated Power	QP	Quasi-Peak
EMC	ElectroMagnetic Compatibility	QPSK	Quadri-Phase Shift Keying
EMI	ElectroMagnetic Interference	RBW	Resolution Band Width
EN	European Norm	RDS	Radio Data System
ERP, e.r.p.	Effective Radiated Power	RE	Radio Equipment
EU	European Union	RF	Radio Frequency
EUT	Equipment Under Test	RMS	Root Mean Square
Fac.	Factor	RSS	Radio Standards Specifications
FCC	Federal Communications Commission	Rx	Receiving
FHSS	Frequency Hopping Spread Spectrum	SA, S/A	Spectrum Analyzer
FM	Frequency Modulation	SG	Signal Generator
Freq.	Frequency	SVSWR	Site-Voltage Standing Wave Ratio
FSK	Frequency Shift Keying	TR	Test Receiver
GFSK	Gaussian Frequency-Shift Keying	Tx	Transmitting
GNSS	Global Navigation Satellite System	VBW	Video BandWidth
GPS	Global Positioning System	Vert.	Vertical
Hori.	Horizontal	WLAN	Wireless LAN

---

<b>CONTENTS</b>	<b>PAGE</b>
<b>SECTION 1: Customer Information .....</b>	<b>5</b>
<b>SECTION 2: Equipment Under Test (EUT).....</b>	<b>5</b>
<b>SECTION 3: Test Specification, Procedures &amp; Results .....</b>	<b>7</b>
<b>SECTION 4: Operation of EUT during testing .....</b>	<b>10</b>
<b>SECTION 5: Radiated Spurious Emission.....</b>	<b>15</b>
<b>SECTION 6: Antenna Terminal Conducted Tests .....</b>	<b>18</b>
<b>APPENDIX 1: Test data .....</b>	<b>19</b>
20dB Bandwidth, 99%Occupied Bandwidth and Carrier Frequency Separation .....	19
Number of Hopping Frequency.....	23
Dwell time .....	25
Maximum Peak Output Power .....	28
Average Output Power.....	29
Radiated Spurious Emission.....	31
Conducted Spurious Emission.....	44
Conducted Emission Band Edge compliance .....	50
<b>APPENDIX 2: Test Instruments .....</b>	<b>52</b>
<b>APPENDIX 3: Photographs of test setup.....</b>	<b>53</b>
Radiated Spurious Emission.....	53
Antenna Terminal Conducted Tests .....	54

## **SECTION 1: Customer Information**

Company Name	DENSO CORPORATION
Address	1-1 Showa-cho, Kariya-shi, Aichi ken, 448-8661 Japan
Telephone Number	+81-70-2236-5904
Contact Person	Naoto Makino

The information provided by the customer is as follows;

- Customer, Description of EUT, Model Number of EUT, FCC ID on the cover and other relevant pages
- Operating/Test Mode(s) (Mode(s)) on all the relevant pages
- SECTION 1: Customer Information
- SECTION 2: Equipment Under Test (EUT) other than the Receipt Date and Test Date
- SECTION 4: Operation of EUT during testing

## **SECTION 2: Equipment Under Test (EUT)**

### **2.1 Identification of EUT**

Description	Cockpit Control Unit
Model Number	DNNS125
Serial Number	Refer to SECTION 4.2
Condition	Production prototype (Not for Sale: This sample is equivalent to mass-produced items.)
Modification	No Modification by the test lab
Receipt Date	May 31, 2024
Test Date	June 17 to 23, 2024

### **2.2 Product Description**

#### **General Specification**

Rating	DC 13.2 V
Operating temperature	-30 deg. C to 65 deg. C

## Radio Specification

This report contains data provided by the customer which can impact the validity of results. UL Japan, Inc. is only responsible for the validity of results after the integration of the data provided by the customer. The data provided by the customer is marked "a)" in the table below.

### WLAN (IEEE802.11b/11g/11n-20)

Equipment Type	Transceiver	
Frequency of Operation	2412 MHz to 2462 MHz	
Type of Modulation	DSSS, OFDM	
Antenna Gain <sup>a)</sup>	Main Antenna: Chain 0	Sub Antenna: Chain 1
	1.78 dBi	1.78 dBi

### Bluetooth (BR / EDR)

Equipment Type	Transceiver	
Frequency of Operation	2402 MHz to 2480 MHz	
Type of Modulation	FHSS (GFSK, $\pi/4$ DQPSK, 8 DPSK)	
Antenna Type	External Antenna	
Antenna Gain <sup>a)</sup>	1.83 dBi	

### WLAN (IEEE802.11a/11n-20/11ac-20/11n-40/11ac-40/11ac-80)

Equipment Type	Transceiver	
Frequency of Operation	20 MHz Band	5180 MHz to 5240 MHz 5745 MHz to 5825 MHz
	40 MHz Band	5190 MHz to 5230 MHz 5755 MHz to 5795 MHz
	80 MHz Band	5210 MHz 5775 MHz
Type of Modulation	OFDM	
Antenna Gain <sup>a)</sup>	Main Antenna: Chain 0	Sub Antenna: Chain 1
	0.30 dBi (5180 MHz to 5240 MHz) 0.99 dBi (5745 MHz to 5825 MHz)	0.30 dBi (5180 MHz to 5240 MHz) 0.99 dBi (5745 MHz to 5825 MHz)

### AM/FM (incl. RDS)

Equipment Type	Receiver	
Frequency of Operation	522 kHz to 1710 kHz	
	87 MHz to 108 MHz	

FM tuner specification Intermediate frequency: 220 kHz

## SECTION 3: Test Specification, Procedures & Results

### 3.1 Test Specification

Test Specification	FCC Part 15 Subpart C The latest version on the first day of the testing period
Title	FCC 47 CFR Part 15 Radio Frequency Device Subpart C Intentional Radiators Section 15.207 Conducted limits Section 15.247 Operation within the bands 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz

### 3.2 Procedures and Results

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
Conducted Emission	FCC: ANSI C63.10-2013 6. Standard test methods ISED: RSS-Gen 8.8	FCC: Section 15.207 ISED: RSS-Gen 8.8	-	N/A	*1)
Carrier Frequency Separation	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1) ISED: RSS-247 5.1 (b)	See data.	Complied	Conducted
20dB Bandwidth	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1) ISED: RSS-247 5.1 (a)		Complied	Conducted
Number of Hopping Frequency	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied	Conducted
Dwell time	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: -	FCC: Section15.247(a)(1)(iii) ISED: RSS-247 5.1 (d)		Complied	Conducted
Maximum Peak Output Power	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.12	FCC: Section15.247(b)(1) ISED: RSS-247 5.4 (b)		Complied	Conducted
Spurious Emission & Band Edge Compliance	FCC: KDB 558074 D01 15.247 Meas Guidance v05r02 ISED: RSS-Gen 6.13	FCC: Section15.247(d) ISED: RSS-247 5.5 RSS-Gen 8.9 RSS-Gen 8.10	0.8 dB 3509.1 MHz, AV, Vertical	Complied	Conducted/ Radiated (above 30 MHz) *1)
Note: UL Japan, Inc.'s EMI Work Procedures: Work Instructions-ULID-003591 and Work Instructions-ULID-003593. * In case any questions arise about test procedure, ANSI C63.10: 2013 is also referred.  *1) The test is not applicable since the EUT is not the device that is designed to be connected to the public utility (AC) power line. *2) Radiated test was selected over 30 MHz based on section 15.247(d).					

#### **FCC Part 15.31 (e)**

This EUT provides stable voltage constantly to the wireless transmitter regardless of input voltage. Instead of a new battery, DC power supply was used for the test. Therefore, this EUT complies with the requirement.

#### **FCC Part 15.203 Antenna requirement**

It is impossible for end users to replace the antenna, because the antenna is mounted inside of the vehicle. Therefore, the equipment complies with the antenna requirement of Section 15.203.

### 3.3 Addition to Standard

Item	Test Procedure	Specification	Worst Margin	Results	Remarks
99% Occupied Bandwidth	ISED: RSS-Gen 6.7	ISED: -	N/A	-	Conducted

Other than above, no addition, exclusion nor deviation has been made from the standard.

### 3.4 Uncertainty

Measurement uncertainty is not taken into account when stating conformity with a specified requirement.  
Note: When margins obtained from test results are less than the measurement uncertainty, the test results may exceed the limit.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor  $k = 2$ .

#### Radiated emission

Measurement distance	Frequency range		Unit	Calculated Uncertainty (+/-)
3 m	9 kHz to 30 MHz		dB	3.3
10 m			dB	3.1
3 m	30 MHz to 200 MHz	Horizontal	dB	4.7
		Vertical	dB	4.7
	200 MHz to 1000 MHz	Horizontal	dB	4.8
		Vertical	dB	6.0
10 m	30 MHz to 200 MHz	Horizontal	dB	5.2
		Vertical	dB	5.1
	200 MHz to 1000 MHz	Horizontal	dB	5.2
		Vertical	dB	5.2
3 m	1 GHz to 6 GHz		dB	5.0
	6 GHz to 18 GHz		dB	5.2
1 m	10 GHz to 18 GHz		dB	5.3
	18 GHz to 26.5 GHz		dB	5.2
	26.5 GHz to 40 GHz		dB	4.7
0.5 m	26.5 GHz to 40 GHz		dB	4.8

#### Antenna Terminal Conducted

Item	Unit	Calculated Uncertainty (+/-)
Antenna terminated conducted emission / Power density / Burst power	dB	3.47
Adjacent channel power (ACP)	dB	2.28
Bandwidth (OBW)	%	0.96
Time readout (time span upto 100 msec)	%	0.11
Time readout (time span upto 1000 msec)	%	0.11
Time readout (time span upto 60 sec)	%	0.02
Power measurement (Power meter < 8 GHz)	dB	1.46
Power measurement (Call box < 6 GHz)	dB	1.69
Frequency readout (Frequency counter)	ppm	0.67
Frequency readout (Spectrum analyzer frequency readout function)	ppm	2.13
Temperature (constant temperature bath)	deg. C	0.69
Humidity (constant temperature bath)	%RH	2.98
Modulation characteristics	%	6.93
Frequency for mobile	ppm	0.08
Contention-based protocol	dB	2.26



### 3.5 Test Location

UL Japan, Inc. Ise EMC Lab.

4383-326 Asama-cho, Ise-shi, Mie-ken 516-0021 Japan

Telephone: +81-596-24-8999

A2LA Certificate Number: 5107.02 / FCC Test Firm Registration Number: 884919

ISED Lab Company Number: 2973C / CAB identifier: JP0002

Test site	Width x Depth x Height (m)	Size of reference ground plane (m) / horizontal conducting plane	Other rooms	Maximum measurement distance
No.1 semi-anechoic chamber	19.2 x 11.2 x 7.7	7.0 x 6.0	No.1 Power source room	10 m
No.2 semi-anechoic chamber	7.5 x 5.8 x 5.2	4.0 x 4.0	-	3 m
No.3 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.3 Preparation room	3 m
No.3 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.4 semi-anechoic chamber	12.0 x 8.5 x 5.9	6.8 x 5.75	No.4 Preparation room	3 m
No.4 shielded room	4.0 x 6.0 x 2.7	N/A	-	-
No.5 semi-anechoic chamber	6.0 x 6.0 x 3.9	6.0 x 6.0	-	-
No.5 measurement room	6.4 x 6.4 x 3.0	6.4 x 6.4	-	-
No.6 shielded room	4.0 x 4.5 x 2.7	4.0 x 4.5	-	-
No.6 measurement room	4.75 x 5.4 x 3.0	4.75 x 4.15	-	-
No.7 shielded room	4.7 x 7.5 x 2.7	4.7 x 7.5	-	-
No.8 measurement room	3.1 x 5.0 x 2.7	3.1 x 5.0	-	-
No.9 measurement room	8.8 x 4.6 x 2.8	2.4 x 2.4	-	-
No.10 shielded room	3.8 x 2.8 x 2.8	3.8 x 2.8	-	-
No.11 measurement room	4.0 x 3.4 x 2.5	N/A	-	-
No.12 measurement room	2.6 x 3.4 x 2.5	N/A	-	-
Large Chamber	16.9 x 22.1 x 10.17	16.9 x 22.1	-	10 m
Small Chamber	5.3 x 6.69 x 3.59	5.3 x 6.69	-	-

### 3.6 Test Data, Test Instruments, and Test Set Up

Refer to APPENDIX.

## SECTION 4: Operation of EUT during testing

### 4.1 Operating Mode(s)

Mode	Remarks*
Bluetooth (BT)	BR / EDR, Payload: PRBS9
<p>*EUT has the power settings by the software as follows;  Power Setting: BR : -1.7 dBm  EDR : -2.2 dBm  Software: MSoC Version: F67WHM010-708  (Date: November 12, 2020, Storage location: EUT memory)</p> <p>*This setting of software is the worst case.  Any conditions under the normal use do not exceed the condition of setting.  In addition, end users cannot change the settings of the output power of the product.</p>	

#### Details of Operating Mode(s)

Test Item	Mode	Hopping	Tested Frequency
Radiated Spurious Emission (Below 1 GHz)	Tx 3DH5 *1)	Off	2480 MHz
Radiated Spurious Emission (Above 1 GHz), Conducted Spurious Emission	Tx DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Carrier Frequency Separation	Tx DH5 Tx 3DH5	On	2402 MHz 2441 MHz 2480 MHz
20dB Bandwidth	Tx DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Number of Hopping Frequency	Tx DH5 Tx 3DH5	On	-
Dwell time	Tx DH1, DH3, DH5 Tx 3DH1, 3DH3, 3DH5	On	-
Maximum Peak Output Power	Tx DH5 Tx 2DH5 Tx 3DH5	Off	2402 MHz 2441 MHz 2480 MHz
Band Edge Compliance (Conducted)	Tx DH5 Tx 3DH5	On Off	2402 MHz 2480 MHz
99% Occupied Bandwidth	Tx DH5 Tx 3DH5	On Off	2402 MHz 2441 MHz 2480 MHz

\*As a result of preliminary test, the formal test was performed with the above modes, which had the maximum payload length (except Dwell time test)


\*2DH mode (2Mb/s EDR: pi/4DQPSK) was excluded for other tests than power measurement by using 3DH mode (3 Mb/s EDR: 8DPSK) as a representative.

\*It is considered that the non-tested packet type (e.g. inquiry) can be omitted as it is complied with above all the test items based on Bluetooth Core specification.

\*1) Conducted emissions and Spurious emissions for frequencies below 1 GHz were limited to the channel that had the highest power during the antenna terminal test, as preliminary testing indicated that changing the operating frequency had no significant impact on the emissions in those frequency bands.

4.2 Configuration and Peripherals

For Radiated Emission



\* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.


### Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remarks
A	Cockpit Control Unit	DNNS125	04687264005002430 0000000	DENSO CORPORATION	EUT
B	Display (CID)	DNNS132-2	86412FN450	DENSO CORPORATION	-
C	Mic	-	-	Panasonic	-
D	USB BOX	86257AN00A	No.7	SUBARU	-
E	Meter	TN257550-6773	85002AN02A	DENSO CORPORATION	-
F	Speaker	SPEAKER ASSY 4FD	-	FOSTER	-
G	Speaker	SPEAKER ASSY 4FD	-	FOSTER	-
H	Speaker	SPEAKER ASSY 4RD	-	FOSTER	-
I	Speaker	SPEAKER ASSY 4RD	-	FOSTER	-

### List of Cables Used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	0.2	Unshielded	Unshielded	-
2	Signal Cable	0.2	Unshielded	Unshielded	-
3	GND Cable	0.2	Unshielded	Unshielded	-
4	GND Cable	0.2	Unshielded	Unshielded	-
5	GND Cable	0.2	Unshielded	Unshielded	-
6	GND Cable	0.2	Unshielded	Unshielded	-
7	RF Cable	0.1	Shielded	Shielded	-
8	RF Cable	0.1	Shielded	Shielded	-
9	Mic Cable	1.0	Unshielded	Unshielded	-
10	Signal Cable	0.5	Unshielded	Unshielded	-
11	Signal Cable	1.0	Unshielded	Unshielded	-
12	DC Cable	2.5	Unshielded	Unshielded	-
13	Speaker Cable	2.0	Unshielded	Unshielded	-
14	Speaker Cable	2.0	Unshielded	Unshielded	-
15	Speaker Cable	2.0	Unshielded	Unshielded	-
16	Speaker Cable	2.0	Unshielded	Unshielded	-
17	Antenna Cable	1.5	Shielded	Shielded	-
18	Antenna Cable	1.5	Shielded	Shielded	-
19	Antenna Cable	1.0	Shielded	Shielded	-
20	Signal Cable	1.0	Unshielded	Unshielded	-
21	Signal Cable	1.0	Unshielded	Unshielded	-
22	Signal Cable	1.0	Unshielded	Unshielded	-
23	DC Cable	2.5	Unshielded	Unshielded	-

For Antenna Terminal Conducted test



\* Cabling and setup(s) were taken into consideration and test data was taken under worse case conditions.

#### Description of EUT and Support Equipment

No.	Item	Model number	Serial Number	Manufacturer	Remarks
A	Cockpit Control Unit	DNNS125	046872640050024330100091	DENSO CORPORATION	EUT
B	Display (CID)	DNNS132-2	86412FN450	DENSO CORPORATION	-
C	Mic	-	-	Panasonic	-
D	USB BOX	86257AN00A	No.7	SUBARU	-
E	USB-LAN Adapter	LUA3-U2-ATX	26495680506450	BUFFALO INC.	-
F	USB-LAN Adapter	LUA3-U2-ATX	26495680506351	BUFFALO INC.	-
G	Laptop PC	PR63PBAA337AD7X	6F053983H	TOSHIBA	-
H	AC Adapter	PA51770-1ACA	G71C000GZ120	TOSHIBA	-
I	Meter	TN257550-6773	85002AN02A	DENSO CORPORATION	-
J	Speaker	SPEAKER ASSY 4FD	-	FOSTER	-
K	Speaker	SPEAKER ASSY 4FD	-	FOSTER	-
L	Speaker	SPEAKER ASSY 4RD	-	FOSTER	-
M	Speaker	SPEAKER ASSY 4RD	-	FOSTER	-

#### List of Cables Used

No.	Name	Length (m)	Shield		Remarks
			Cable	Connector	
1	DC Cable	0.2	Unshielded	Unshielded	-
2	Signal Cable	0.2	Unshielded	Unshielded	-
3	GND Cable	0.2	Unshielded	Unshielded	-
4	GND Cable	0.2	Unshielded	Unshielded	-
5	GND Cable	0.2	Unshielded	Unshielded	-
6	GND Cable	0.2	Unshielded	Unshielded	-
7	RF Cable	0.1	Shielded	Shielded	-
8	RF Cable	0.1	Shielded	Shielded	-
9	Mic Cable	1.0	Unshielded	Unshielded	-
10	Signal Cable	0.5	Unshielded	Unshielded	-
11	USB Cable	0.2	Shielded	Shielded	-
12	LAN Cable	1.5	Unshielded	Unshielded	-
13	USB Cable	0.2	Shielded	Shielded	-
14	DC Cable	1.3	Unshielded	Unshielded	-
15	AC Cable	0.8	Unshielded	Unshielded	-
16	Signal Cable	1.0	Unshielded	Unshielded	-
17	DC Cable	2.5	Unshielded	Unshielded	-
18	Speaker Cable	2.0	Unshielded	Unshielded	-
19	Speaker Cable	2.0	Unshielded	Unshielded	-
20	Speaker Cable	2.0	Unshielded	Unshielded	-
21	Speaker Cable	2.0	Unshielded	Unshielded	-
22	Antenna Cable	1.5	Shielded	Shielded	-
23	Antenna Cable	1.5	Shielded	Shielded	-
24	Antenna Cable	1.0	Shielded	Shielded	-
25	Signal Cable	1.0	Unshielded	Unshielded	-
26	Signal Cable	1.0	Unshielded	Unshielded	-
27	Signal Cable	1.0	Unshielded	Unshielded	-
28	DC Cable	2.5	Unshielded	Unshielded	-

## **SECTION 5: Radiated Spurious Emission**

### **Test Procedure**

[For below 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 1.0 m, raised 0.8 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with a ground plane.

[For above 1 GHz]

EUT was placed on a urethane platform of nominal size, 0.5 m by 0.5 m, raised 1.5 m above the conducting ground plane. The Radiated Electric Field Strength has been measured in a Semi Anechoic Chamber with absorbent materials lined on a ground plane. Test antenna was aimed at the EUT for receiving the maximum signal and always kept within the illumination area of the 3 dB beamwidth of the antenna.

The height of the measuring antenna varied between 1 m and 4 m and EUT was rotated a full revolution in order to obtain the maximum value of the electric field strength.

The measurements were performed for both vertical and horizontal antenna polarization with the Test Receiver, or the Spectrum Analyzer.

The measurements were made with the following detector function of the test receiver and the Spectrum analyzer (in linear mode).

The test was made with the detector (RBW/VBW) in the following table.

When using Spectrum analyzer, the test was made with adjusting span to zero by using peak hold.

### **Test Antennas are used as below;**

Frequency	30 MHz to 200 MHz	200 MHz to 1 GHz	Above 1 GHz
Antenna Type	Biconical	Logperiodic	Horn

In any 100 kHz bandwidth outside the restricted band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator confirmed 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on a radiated measurement.


**20 dBc was applied to the frequency over the limit of FCC 15.209 / Table 4 of RSS-Gen 8.9 (ISED) and outside the restricted band of FCC15.205 / Table 6 of RSS-Gen 8.10 (ISED).**

Frequency	Below 1 GHz	Above 1 GHz		20 dBc
Instrument used	Test Receiver	Spectrum Analyzer		Spectrum Analyzer
Detector	QP	PK	AV	PK
IF Bandwidth	BW 120 kHz	RBW: 1 MHz VBW: 3 MHz	RBW: 1 MHz VBW: 3 MHz Detector: Power Averaging (RMS) Trace: 100 traces Duty factor was added to the results.	RBW: 100 kHz VBW: 300 kHz



Figure 1: Test Setup


Below 1 GHz



× : Center of turn table

Test Distance: 3 m

1 GHz to 6 GHz




r : Radius of an outer periphery of EUT  
× : Center of turn table

Distance Factor:  $20 \times \log (3.8 \text{ m} / 3.0 \text{ m}) = 2.06 \text{ dB}$   
\* Test Distance:  $(3 + \text{SVSWR Volume} / 2) - r = 3.8 \text{ m}$

SVSWR Volume : 2.0 m  
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)  
r = 0.2 m

6 GHz to 10 GHz




r : Radius of an outer periphery of EUT  
× : Center of turn table

Distance Factor:  $20 \times \log (4.8 \text{ m} / 3.0 \text{ m}) = 4.09 \text{ dB}$   
\* Test Distance:  $(4.3 + \text{SVSWR Volume} / 2) - r = 4.8 \text{ m}$

SVSWR Volume : 1.4 m  
(SVSWR Volume has been calibrated based on CISPR 16-1-4.)  
r = 0.2 m

10 GHz to 26.5 GHz



× : Center of turn table

Distance Factor:  $20 \times \log (1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$   
\*Test Distance: 1 m

The test was made on EUT at the normal use position.

Test results are rounded off and limit are rounded down, so some differences might be observed.

Measurement Range : 30 MHz to 26.5 GHz  
Test Data : APPENDIX  
Test Result : Pass

## SECTION 6: Antenna Terminal Conducted Tests

### Test Procedure

The tests were made with below setting connected to the antenna port.

Test	Span	RBW	VBW	Sweep time	Detector	Trace	Instrument Used
20dB Bandwidth	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
99% Occupied Bandwidth *1)	Enough width to display emission skirts	1 to 5 % of OBW	Three times of RBW	Auto	Peak	Max Hold	Spectrum Analyzer
Maximum Peak Output Power	-	-	-	Auto	Peak/Average *2)	-	Power Meter (Sensor: 50MHz BW)
Carrier Frequency Separation	3 MHz	30 kHz	100 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Number of Hopping Frequency	30 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer
Dwell Time	Zero Span	100 kHz, 1 MHz	300 kHz, 3 MHz	As necessary capture the entire dwell time per hopping channel	Peak	Clear Write	Spectrum Analyzer
Conducted Spurious Emission *3) *4)	9 kHz to 150 kHz	200 Hz	620 Hz	Auto	Peak	Max Hold	Spectrum Analyzer
	150 kHz to 30 MHz	10 kHz	30 kHz				
	30 MHz to 25 GHz	100 kHz	300 kHz				
Conducted Spurious Emission Band Edge compliance	10 MHz	100 kHz	300 kHz	Auto	Peak	Max Hold	Spectrum Analyzer

\*1) Peak hold was applied as Worst-case measurement.

\*2) Reference data

\*3) In the frequency range below 30MHz, RBW was narrowed to separate the noise contents.

Then, wide-band noise near the limit was checked separately, however the noise was low enough as shown in the chart.  
(9 kHz - 150 kHz: RBW = 200 Hz, 150 kHz - 30 MHz: RBW = 10 kHz).

\*4) The limits in CFR 47, Part 15, Subpart C, paragraph 15.209(a), are identical to those in RSS-Gen section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377 Ohms. For example, the measurement at frequency 9 kHz resulted in a level of 45.5 dBuV/m, which is equivalent to  $45.5 - 51.5 = -6.0$  dBuA/m, which has the same margin, 3 dB, to the corresponding RSS-Gen Table 6 limit as it has to 15.209(a) limit.

Test results are rounded off and limit are rounded down, so some differences might be observed.  
The equipment and cables were not used for factor 0 dB of the data sheets.

Test Data : APPENDIX  
Test Result : Pass

## APPENDIX 1: Test data

### 20dB Bandwidth, 99%Occupied Bandwidth and Carrier Frequency Separation


Test place	Ise EMC Lab. No.3 Preparation room
Date	June 17, 2024
Temperature / Humidity	23 deg. C / 54 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping Off, Tx, Hopping On

Mode	Freq. [MHz]	20 dB Bandwidth [MHz]	99 % Occupied Bandwidth [kHz]	Carrier Frequency Separation [MHz]	Limit for Carrier Frequency separation [MHz]
DH5	2402.0	0.972	902.346	1.000	>= 0.648
DH5	2441.0	0.972	902.707	1.000	>= 0.648
DH5	2480.0	1.028	<b>905.684</b>	1.000	>= 0.685
DH5	Hopping On	-	78610.400	-	-
3DH5	2402.0	1.310	<b>1182.500</b>	1.000	>= 0.873
3DH5	2441.0	1.309	1175.300	1.000	>= 0.873
3DH5	2480.0	1.308	1180.100	1.000	>= 0.872
3DH5	Hopping On	-	78702.700	-	-


Limit: Two-thirds of 20 dB Bandwidth or 25 kHz (whichever is greater).

No limit applies to 20 dB Bandwidth.


20dB Bandwidth and 99% Occupied Bandwidth



20dB Bandwidth and 99% Occupied Bandwidth



Carrier Frequency Separation




### **Number of Hopping Frequency**

Test place	Ise EMC Lab. No.3 Preparation room
Date	June 17, 2024
Temperature / Humidity	23 deg. C / 54 % RH
Engineer	Yuta Moriya
Mode	Tx, Hopping On

Mode	Number of channel [channels]	Limit [channels]
DH5	79	>= 15
3DH5	79	>= 15

Test was not performed at AFH mode whose number of hopping channel is 20 channels because this Bluetooth radio is in compliance of Bluetooth Specification.

Number of Hopping Frequency





## Dwell time

Test place Ise EMC Lab. No.3 Preparation room  
Date June 17, 2024  
Temperature / Humidity 23 deg. C / 54 % RH  
Engineer Yuta Moriya  
Mode Tx, Hopping On

Mode	Number of transmission in a 31.6 (79 Hopping x 0.4) / 12.8 (32 Hopping x 0.4) second period					Length of transmission [ms]	Result [ms]	Limit [ms]
DH1	50.4 times	/	5 s	x	31.6 s = 319 times	0.401	128	400
DH3	25.4 times	/	5 s	x	31.6 s = 161 times	1.662	268	400
DH5	17.4 times	/	5 s	x	31.6 s = 110 times	2.910	320	400
3DH1	51.0 times	/	5 s	x	31.6 s = 323 times	0.407	131	400
3DH3	25.6 times	/	5 s	x	31.6 s = 162 times	1.662	269	400
3DH5	16.0 times	/	5 s	x	31.6 s = 102 times	2.917	298	400

Sample Calculation

Result = Number of transmission x Length of transmission

\*Average data of 5 tests.(except Inquiry)


Mode	Sampling [times]					Average [times]
	1	2	3	4	5	
DH1	51	50	50	51	50	50.4
DH3	22	28	27	25	25	25.4
DH5	17	19	16	17	18	17.4
3DH1	51	51	51	51	51	51
3DH3	26	30	24	22	26	25.6
3DH5	14	17	11	21	17	16

Sample Calculation


Average = Summation (Sampling 1 to 5) / 5

This device complies with the Bluetooth protocol for FHSS operation, employing a pseudo random channel selection and hopping rate to ensure that the occupancy time in  $N \times 0.4$  s, where  $N$  is the number of channels being used in the hopping sequence ( $20 \leq N \leq 79$ ), is always less than 0.4 s regardless of packet size. This is confirmed in the test report for  $N = 79$ .

Dwell time



Dwell time



## Maximum Peak Output Power

Test place                      Ise EMC Lab. No.3 Preparation room  
Date                              June 17, 2024  
Temperature / Humidity      23 deg. C / 54 % RH  
Engineer                        Yuta Moriya  
Mode                              Tx, Hopping Off

Mode	Freq.	Reading	Cable Loss	Atten. Loss	Conducted Power					Antenna Gain	e.i.r.p. for RSS-247				
					Result		Limit		Margin		Result		Limit		Margin
					[dBm]	[mW]	[dBm]	[mW]			[dB]	[dBm]	[mW]	[dBm]	
DH5	2402.0	-10.64	3.16	6.13	-1.35	0.73	20.96	125	22.31	1.83	0.48	1.12	36.02	4000	35.54
DH5	2441.0	-9.99	3.17	6.13	-0.69	0.85	20.96	125	21.65	1.83	1.14	1.30	36.02	4000	34.88
DH5	2480.0	-9.54	3.18	6.13	<b>-0.23</b>	<b>0.95</b>	20.96	125	21.19	1.83	<b>1.60</b>	<b>1.44</b>	36.02	4000	34.42
2DH5	2402.0	-9.01	3.16	6.13	0.28	1.07	20.96	125	20.68	1.83	2.11	1.62	36.02	4000	33.91
2DH5	2441.0	-8.33	3.17	6.13	0.97	1.25	20.96	125	19.99	1.83	2.80	1.90	36.02	4000	33.22
2DH5	2480.0	-8.05	3.18	6.13	<b>1.26</b>	<b>1.34</b>	20.96	125	19.70	1.83	<b>3.09</b>	<b>2.04</b>	36.02	4000	32.93
3DH5	2402.0	-8.90	3.16	6.13	0.39	1.09	20.96	125	20.57	1.83	2.22	1.67	36.02	4000	33.80
3DH5	2441.0	-8.31	3.17	6.13	0.99	1.26	20.96	125	19.97	1.83	2.82	1.91	36.02	4000	33.20
3DH5	2480.0	-8.01	3.18	6.13	<b>1.30</b>	<b>1.35</b>	20.96	125	19.66	1.83	<b>3.13</b>	<b>2.05</b>	36.02	4000	32.89

Sample Calculation:

Result = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss

e.i.r.p. Result = Conducted Power Result + Antenna Gain

Test was not performed at AFH mode, because the decrease of number of channel (min: 20 ch) at AFH mode does not influence on the output power and bandwidth of the EUT.

As this device had AFH mode and frequency separation could not meet the requirement of over 20 dB BW without 2/3 relaxation, 125 mW power limit was applied to it.

## Average Output Power (Reference data for RF Exposure)

Test place	Ise EMC Lab.	
	No.3 Preparation room	No.8 Measurement room
Date	June 17, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 54 % RH	20 deg. C / 55 % RH
Engineer	Yuta Moriya	Junya Okuno
Mode	Tx, Hopping Off	

Mode	Freq. [MHz]	Reading [dBm]	Cable Loss [dB]	Atten. Loss [dB]	Result (Time average)		Duty factor [dB]	Result (Burst power average)	
					[dBm]	[mW]		[dBm]	[mW]
DH5	2402.0	-12.27	3.16	6.13	-2.98	0.50	1.11	-1.87	0.65
DH5	2441.0	-11.49	3.17	6.13	-2.19	0.60	1.11	-1.08	0.78
DH5	2480.0	-10.98	3.18	6.13	<b>-1.67</b>	<b>0.68</b>	1.11	<b>-0.56</b>	<b>0.88</b>
2DH5	2402.0	-12.74	3.16	6.13	-3.45	0.45	1.11	-2.34	0.58
2DH5	2441.0	-12.38	3.17	6.13	-3.08	0.49	1.11	-1.97	0.63
2DH5	2480.0	-11.62	3.18	6.13	<b>-2.31</b>	<b>0.59</b>	1.11	<b>-1.20</b>	<b>0.76</b>
3DH5	2402.0	-12.71	3.16	6.13	-3.42	0.45	1.10	-2.32	0.59
3DH5	2441.0	-12.35	3.17	6.13	-3.05	0.50	1.10	-1.95	0.64
3DH5	2480.0	-11.59	3.18	6.13	<b>-2.28</b>	<b>0.59</b>	1.10	<b>-1.18</b>	<b>0.76</b>

Sample Calculation:

Result (Time average) = Reading + Cable Loss (including the cable(s) customer supplied) + Attenuator Loss


Result (Burst power average) = Time average + Duty factor

\*The equipment and cables were not used for factor 0 dB of the data sheets.


**Burst Rate Confirmation**

Test place	Ise EMC Lab.	
	No.3 Preparation room	No.8 Measurement room
Date	June 17, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 54 % RH	20 deg. C / 55 % RH
Engineer	Yuta Moriya	Junya Okuno
Mode	Tx, Hopping Off	


**DH5**



**2DH5**



**3DH5**



## Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	June 19, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 59 % RH	23 deg. C / 56 % RH
Engineer	Hiroki Numata (1 GHz to 10 GHz)	Hiroki Numata (Above 10 GHz)
Mode	Tx, Hopping Off, DH5 2402 MHz	

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	2390.0	41.0	33.3	27.5	5.1	32.2	1.1	41.3	34.7	73.9	53.9	32.6	19.2	*1)
Hori.	3509.1	49.7	47.6	28.8	7.1	31.7	-	53.9	51.8	73.9	53.9	20.0	2.1	
Hori.	4804.0	41.1	32.6	31.4	7.2	31.2	-	48.4	40.0	73.9	53.9	25.5	14.0	Floor noise
Hori.	7206.0	40.0	32.1	35.6	10.3	32.0	-	53.9	46.0	73.9	53.9	20.0	7.9	Floor noise
Hori.	9608.0	41.2	32.2	35.6	10.9	32.6	-	55.0	46.1	73.9	53.9	18.9	7.8	Floor noise
Vert.	2390.0	42.8	33.1	27.5	5.1	32.2	1.1	43.1	34.6	73.9	53.9	30.8	19.3	*1)
Vert.	3509.1	52.1	48.7	28.8	7.1	31.7	-	56.3	52.9	73.9	53.9	17.6	1.0	
Vert.	4804.0	41.0	32.0	31.4	7.2	31.2	-	48.3	39.4	73.9	53.9	25.6	14.5	Floor noise
Vert.	7206.0	39.5	32.2	35.6	10.3	32.0	-	53.4	46.1	73.9	53.9	20.5	7.8	Floor noise
Vert.	9608.0	41.2	32.5	35.6	10.9	32.6	-	55.0	46.3	73.9	53.9	18.9	7.6	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
 \*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
 \*QP detector was used up to 1GHz.  
 \*1) Not Out of Band emission(Leakage Power)

## 20dBc Data Sheet



Polarity	Frequency	Reading (PK)	Ant Factor	Loss	Gain	Result	Limit	Margin	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dB/m]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Hori.	2402.0	91.0	27.5	5.1	32.2	91.4	-	-	Carrier
Hori.	2400.0	35.7	27.5	5.1	32.2	36.1	71.4	35.3	
Vert.	2402.0	89.8	27.5	5.1	32.2	90.2	-	-	Carrier
Vert.	2400.0	36.9	27.5	5.1	32.2	37.3	70.2	32.9	

$$\text{Result} = \text{Reading} + \text{Ant Factor} + \text{Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz))} - \text{Gain(Amplifier)}$$

Distance factor:	1 GHz - 6 GHz	$20\log(3.8 \text{ m} / 3.0 \text{ m}) = 2.06 \text{ dB}$
	6 GHz - 10 GHz	$20\log(4.8 \text{ m} / 3.0 \text{ m}) = 4.09 \text{ dB}$
	10 GHz - 26.5 GHz	$20\log(1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$

**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	June 19, 2024
Temperature / Humidity	23 deg. C / 59 % RH
Engineer	Hiroki Numata
	(1 GHz to 6 GHz)
Mode	Tx, Hopping Off, DH5 2402 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
Final result of restricted band edge and authorized band edge were shown in tabular data.



## Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	June 19, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 59 % RH	23 deg. C / 56 % RH
Engineer	Hiroki Numata (1 GHz to 10 GHz)	Hiroki Numata (Above 10 GHz)
Mode	Tx, Hopping Off, DH5 2441 MHz	

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	3509.1	49.8	47.6	28.8	7.1	31.7	-	54.0	51.8	73.9	53.9	19.9	2.1	
Hori.	4882.0	40.5	32.4	31.4	7.2	31.2	-	47.9	39.9	73.9	53.9	26.0	14.0	Floor noise
Hori.	7323.0	39.8	32.2	35.6	10.4	32.1	-	53.7	46.0	73.9	53.9	20.2	7.9	Floor noise
Hori.	9764.0	41.5	32.4	35.9	11.0	32.7	-	55.7	46.6	73.9	53.9	18.2	7.3	Floor noise
Vert.	3509.1	52.1	48.8	28.8	7.1	31.7	-	56.3	53.0	73.9	53.9	17.6	0.9	
Vert.	4882.0	40.1	32.5	31.4	7.2	31.2	-	47.6	39.9	73.9	53.9	26.3	14.0	Floor noise
Vert.	7323.0	39.6	32.2	35.6	10.4	32.1	-	53.5	46.1	73.9	53.9	20.5	7.8	Floor noise
Vert.	9764.0	40.8	32.5	35.9	11.0	32.7	-	54.9	46.6	73.9	53.9	19.0	7.3	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
 \*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
 \*QP Detection was used up to 1GHz.

Distance factor:	1 GHz - 6 GHz	$20\log(3.8\text{ m} / 3.0\text{ m}) = 2.06\text{ dB}$
	6 GHz - 10 GHz	$20\log(4.8\text{ m} / 3.0\text{ m}) = 4.09\text{ dB}$
	10 GHz - 26.5 GHz	$20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

## Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	June 19, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 59 % RH	23 deg. C / 56 % RH
Engineer	Hiroki Numata	Hiroki Numata
	(1 GHz to 10 GHz)	(Above 10 GHz)
Mode	Tx, Hopping Off, DH5 2480 MHz	

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	2483.5	42.5	33.5	27.4	5.1	32.2	1.1	42.8	34.9	73.9	53.9	31.1	19.0	*1)
Hori.	3509.1	49.8	47.6	28.8	7.1	31.7	-	54.0	51.8	73.9	53.9	19.9	2.1	
Hori.	4960.0	40.4	32.7	31.6	7.2	31.1	-	48.0	40.3	73.9	53.9	25.9	13.6	Floor noise
Hori.	7440.0	39.9	32.4	35.5	10.4	32.1	-	53.6	46.1	73.9	53.9	20.3	7.8	Floor noise
Hori.	9920.0	41.4	32.5	36.1	11.0	32.8	-	55.8	46.9	73.9	53.9	18.2	7.1	Floor noise
Vert.	2483.5	41.3	33.3	27.4	5.1	32.2	1.1	41.6	34.7	73.9	53.9	32.3	19.2	*1)
Vert.	3509.1	52.1	48.7	28.8	7.1	31.7	-	56.3	52.9	73.9	53.9	17.6	1.0	
Vert.	4960.0	41.3	32.4	31.6	7.2	31.1	-	48.9	40.1	73.9	53.9	25.0	13.9	Floor noise
Vert.	7440.0	39.6	32.3	35.5	10.4	32.1	-	53.3	46.0	73.9	53.9	20.6	7.9	Floor noise
Vert.	9920.0	40.8	32.5	36.1	11.0	32.8	-	55.1	46.8	73.9	53.9	18.8	7.1	Floor noise



Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
\*QP detector was used up to 1GHz.  
\*1) Not Out of Band emission(Leakage Power)

Distance factor:	1 GHz - 6 GHz	20log (3.8 m / 3.0 m) = 2.06 dB
	6 GHz - 10 GHz	20log (4.8 m / 3.0 m) = 4.09 dB
	10 GHz - 26.5 GHz	20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission**  
**(Reference Plot for bandto edge)**

Test place  
Semi Anechoic Chamber  
Date  
Temperature / Humidity  
Engineer  
  
Mode

Ise EMC Lab.  
No.3  
June 19, 2024  
23 deg. C / 59 % RH  
Hiroki Numata  
(1 GHz to 6 GHz)  
Tx, Hopping Off, DH5 2480 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
Final result of restricted band edge was shown in tabular data.

## Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	June 19, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 59 % RH	23 deg. C / 56 % RH
Engineer	Hiroki Numata	Hiroki Numata
	(1 GHz to 10 GHz)	(Above 10 GHz)
Mode	Tx, Hopping Off, 3DH5 2402 MHz	

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	2390.0	42.7	31.6	27.5	5.1	32.2	1.1	43.0	33.1	73.9	53.9	30.9	20.8	*1)
Hori.	3509.1	49.7	46.5	28.8	7.1	31.7	-	53.9	50.7	73.9	53.9	20.0	3.2	
Hori.	4804.0	41.0	32.7	31.4	7.2	31.2	-	48.4	40.1	73.9	53.9	25.5	13.8	Floor noise
Hori.	7206.0	39.9	32.2	35.6	10.3	32.0	-	53.8	46.1	73.9	53.9	20.1	7.8	Floor noise
Hori.	9608.0	41.0	32.2	35.6	10.9	32.6	-	54.8	46.1	73.9	53.9	19.1	7.9	Floor noise
Vert.	2390.0	43.0	33.6	27.5	5.1	32.2	1.1	43.3	35.1	73.9	53.9	30.6	18.8	*1)
Vert.	3509.1	52.2	48.8	28.8	7.1	31.7	-	56.4	53.0	73.9	53.9	17.5	0.9	
Vert.	4804.0	40.1	32.3	31.4	7.2	31.2	-	47.5	39.7	73.9	53.9	26.4	14.2	Floor noise
Vert.	7206.0	32.2	32.3	35.6	10.3	32.0	-	46.1	46.2	73.9	53.9	27.8	7.7	Floor noise
Vert.	9608.0	41.6	32.6	35.6	10.9	32.6	-	55.4	46.4	73.9	53.9	18.5	7.5	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor

\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).

\*QP detector was used up to 1GHz.

\*1) Not Out of Band emission(Leakage Power)

### 20dBc Data Sheet



Polarity	Frequency	Reading (PK)	Ant Factor	Loss	Gain	Result	Limit	Margin	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dB/m]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dB]	
Hori.	2402.0	89.1	27.5	5.1	32.2	89.4	-	-	Carrier
Hori.	2400.0	36.5	27.5	5.1	32.2	36.8	69.4	32.6	
Vert.	2402.0	90.0	27.5	5.1	32.2	90.4	-	-	Carrier
Vert.	2400.0	36.3	27.5	5.1	32.2	36.6	70.4	33.8	

Result = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)

Distance factor:  
 1 GHz - 6 GHz      20log (3.8 m / 3.0 m) = 2.06 dB  
 6 GHz - 10 GHz    20log (4.8 m / 3.0 m) = 4.09 dB  
 10 GHz - 26.5 GHz   20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	June 19, 2024
Temperature / Humidity	23 deg. C / 59 % RH
Engineer	Hiroki Numata
	(1 GHz to 6 GHz)
Mode	Tx, Hopping Off, 3DH5 2402 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.

Final result of restricted band edge and authorized band edge were shown in tabular data.

## Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	June 19, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 59 % RH	23 deg. C / 56 % RH
Engineer	Hiroki Numata (1 GHz to 10 GHz)	Hiroki Numata (Above 10 GHz)
Mode	Tx, Hopping Off, 3DH5 2441 MHz	

Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	3509.1	49.8	47.7	28.8	7.1	31.7	-	54.0	51.9	73.9	53.9	19.9	2.1	
Hori.	4882.0	40.5	32.2	31.4	7.2	31.2	-	48.0	39.7	73.9	53.9	25.9	14.2	Floor noise
Hori.	7323.0	39.6	32.3	35.6	10.4	32.1	-	53.5	46.2	73.9	53.9	20.4	7.7	Floor noise
Hori.	9764.0	42.1	32.6	35.9	11.0	32.7	-	56.2	46.7	73.9	53.9	17.7	7.2	Floor noise
Vert.	3509.1	52.2	48.7	28.8	7.1	31.7	-	56.4	52.9	73.9	53.9	17.5	1.0	
Vert.	4882.0	40.1	32.2	31.4	7.2	31.2	-	47.6	39.7	73.9	53.9	26.3	14.2	Floor noise
Vert.	7323.0	40.0	32.4	35.6	10.4	32.1	-	53.8	46.3	73.9	53.9	20.1	7.6	Floor noise
Vert.	9764.0	41.0	32.7	35.9	11.0	32.7	-	55.2	46.9	73.9	53.9	18.7	7.0	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
 \*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
 \*QP Test was used up to 1GHz.

Distance factor:	1 GHz - 6 GHz	$20\log(3.8 \text{ m} / 3.0 \text{ m}) = 2.06 \text{ dB}$
	6 GHz - 10 GHz	$20\log(4.8 \text{ m} / 3.0 \text{ m}) = 4.09 \text{ dB}$
	10 GHz - 26.5 GHz	$20\log(1.0 \text{ m} / 3.0 \text{ m}) = -9.5 \text{ dB}$

**Radiated Spurious Emission**

Test place	Ise EMC Lab.		
Semi Anechoic Chamber	No.3	No.3	No.3
Date	June 19, 2024	June 18, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 59 % RH	23 deg. C / 56 % RH	23 deg. C / 56 % RH
Engineer	Hiroki Numata	Hiroki Numata	Hiroki Numata
	(1 GHz to 10 GHz)	(Above 10 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz		



Polarity	Frequency	Reading (QP / PK)	Reading (AV)	Ant. Factor	Loss	Gain	Duty Factor	Result (QP / PK)	Result (AV)	Limit (QP / PK)	Limit (AV)	Margin (QP / PK)	Margin (AV)	Remark
[Hori/Vert]	[MHz]	[dBuV]	[dBuV]	[dB/m]	[dB]	[dB]	[dB]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dBuV/m]	[dB]	[dB]	
Hori.	46.3	46.2	-	12.5	7.2	32.2	-	33.7	-	40.0	-	6.3	-	
Hori.	55.9	43.2	-	9.3	7.3	32.2	-	27.6	-	40.0	-	12.4	-	
Hori.	67.0	39.6	-	6.7	7.5	32.2	-	21.6	-	40.0	-	18.5	-	
Hori.	225.1	39.4	-	11.3	9.1	32.0	-	27.7	-	46.0	-	18.3	-	
Hori.	247.6	33.1	-	11.6	9.2	32.0	-	21.9	-	46.0	-	24.1	-	
Hori.	365.0	34.9	-	15.1	10.1	32.0	-	28.0	-	46.0	-	18.0	-	
Hori.	2483.5	45.2	34.1	27.4	5.1	32.2	1.1	45.5	35.5	73.9	53.9	28.4	18.4	*1)
Hori.	3509.1	49.8	47.7	28.8	7.1	31.7	-	54.0	51.9	73.9	53.9	19.9	2.0	
Hori.	4960.0	40.5	32.4	31.6	7.2	31.1	-	48.1	40.0	73.9	53.9	25.8	13.9	Floor noise
Hori.	7440.0	39.8	32.3	35.5	10.4	32.1	-	53.5	46.0	73.9	53.9	20.4	7.9	Floor noise
Hori.	9920.0	42.3	32.5	36.1	11.0	32.8	-	56.6	46.9	73.9	53.9	17.3	7.1	Floor noise
Vert.	38.3	44.7	-	15.4	7.1	32.2	-	35.0	-	40.0	-	5.0	-	
Vert.	47.9	47.7	-	11.9	7.2	32.2	-	34.7	-	40.0	-	5.3	-	
Vert.	55.4	51.1	-	9.4	7.3	32.2	-	35.6	-	40.0	-	4.4	-	
Vert.	259.0	36.6	-	12.1	9.3	32.0	-	26.0	-	46.0	-	20.0	-	
Vert.	368.0	28.9	-	15.0	10.1	32.0	-	22.0	-	46.0	-	24.0	-	
Vert.	458.1	27.5	-	16.8	10.7	32.0	-	22.9	-	46.0	-	23.1	-	
Vert.	2483.5	40.9	33.6	27.4	5.1	32.2	1.1	41.2	35.0	73.9	53.9	32.7	18.9	*1)
Vert.	3509.1	52.1	48.9	28.8	7.1	31.7	-	56.3	53.1	73.9	53.9	17.6	0.8	
Vert.	4960.0	41.3	32.7	31.6	7.2	31.1	-	48.9	40.3	73.9	53.9	25.0	13.6	Floor noise
Vert.	7440.0	39.5	32.2	35.5	10.4	32.1	-	53.2	45.9	73.9	53.9	20.7	8.0	Floor noise
Vert.	9920.0	41.7	32.3	36.1	11.0	32.8	-	56.1	46.7	73.9	53.9	17.8	7.3	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
\*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
\*QP detector was used up to 1GHz.  
\*1) Not Out of Band emission(Leakage Power)

Distance factor:      1 GHz - 6 GHz      20log (3.8 m / 3.0 m) = 2.06 dB  
                              6 GHz - 10 GHz      20log (4.8 m / 3.0 m) = 4.09 dB  
                              10 GHz - 26.5 GHz      20log (1.0 m / 3.0 m) = -9.5 dB

**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**

Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	June 19, 2024
Temperature / Humidity	23 deg. C / 59 % RH
Engineer	Hiroki Numata
	(1 GHz to 6 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
Final result of restricted band edge was shown in tabular data.



## Radiated Spurious Emission

Test place	Ise EMC Lab.	
Semi Anechoic Chamber	No.3	No.3
Date	June 23, 2024	June 23, 2024
Temperature / Humidity	23 deg. C / 60 % RH	22 deg. C / 59 % RH
Engineer	Junya Okuno (Above 1 GHz)	Hiroki Numata (Below 1 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz + 11ac-20 5220 MHz	



Polarity	Frequency	Reading (QP / PK) [dBuV]	Reading (AV) [dBuV]	Ant. Factor [dB/m]	Loss [dB]	Gain [dB]	Duty Factor [dB]	Result (QP / PK) [dBuV/m]	Result (AV) [dBuV/m]	Limit (QP / PK) [dBuV/m]	Limit (AV) [dBuV/m]	Margin (QP / PK) [dB]	Margin (AV) [dB]	Remark
[Hori/Vert]	[MHz]													
Hori.	47.4	30.6	-	12.1	7.2	32.2	-	17.7	-	40.0	-	22.3	-	
Hori.	148.6	34.6	-	14.8	8.4	32.1	-	25.7	-	43.5	-	17.8	-	
Hori.	168.7	27.3	-	15.8	8.6	32.1	-	19.6	-	43.5	-	23.9	-	
Hori.	221.2	40.5	-	11.3	9.0	32.0	-	28.7	-	46.0	-	17.3	-	
Hori.	310.6	32.4	-	13.7	9.7	32.0	-	23.8	-	46.0	-	22.2	-	
Hori.	449.8	28.0	-	16.5	10.6	32.0	-	23.1	-	46.0	-	22.9	-	
Hori.	2483.5	44.0	33.9	27.4	5.1	32.2	1.1	44.3	35.3	73.9	53.9	29.6	18.6	*1)
Hori.	3509.1	49.5	47.3	28.8	7.1	31.7	-	53.7	51.5	73.9	53.9	20.3	2.4	
Hori.	4960.0	41.0	32.6	31.6	7.2	31.1	-	48.6	40.2	73.9	53.9	25.3	13.7	Floor noise
Hori.	7440.0	40.0	32.6	35.5	10.4	32.1	-	53.7	46.3	73.9	53.9	20.2	7.7	Floor noise
Hori.	9920.0	42.1	32.6	36.1	11.0	32.8	-	56.5	46.9	73.9	53.9	17.5	7.0	Floor noise
Vert.	44.2	37.4	-	13.3	7.1	32.2	-	25.6	-	40.0	-	14.4	-	
Vert.	56.7	44.6	-	9.0	7.3	32.2	-	28.7	-	40.0	-	11.3	-	
Vert.	148.6	35.2	-	14.8	8.4	32.1	-	26.3	-	43.5	-	17.2	-	
Vert.	221.2	38.2	-	11.3	9.0	32.0	-	26.4	-	46.0	-	19.6	-	
Vert.	371.8	29.2	-	15.0	10.1	32.0	-	22.3	-	46.0	-	23.7	-	
Vert.	504.3	26.1	-	17.8	10.9	32.0	-	22.8	-	46.0	-	23.2	-	
Vert.	2483.5	42.5	33.4	27.4	5.1	32.2	1.1	42.8	34.8	73.9	53.9	31.1	19.1	*1)
Vert.	3509.1	51.9	48.9	28.8	7.1	31.7	-	56.1	53.1	73.9	53.9	17.8	0.8	
Vert.	4960.0	41.1	32.6	31.6	7.2	31.1	-	48.7	40.2	73.9	53.9	25.2	13.7	Floor noise
Vert.	7440.0	40.0	32.5	35.5	10.4	32.1	-	53.7	46.2	73.9	53.9	20.2	7.7	Floor noise
Vert.	9920.0	42.0	32.5	36.1	11.0	32.8	-	56.3	46.9	73.9	53.9	17.6	7.1	Floor noise

Result (QP / PK) = Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier)  
 Result (AV)= Reading + Ant Factor + Loss (Cable+Attenuator+Filter+Distance factor(above 1 GHz)) - Gain(Amplifier) + Duty factor  
 \*Other frequency noises omitted in this report were not seen or had enough margin (more than 20 dB).  
 \*QP detector was used up to 1GHz.  
 \*1) Not Out of Band emission(Leakade Power)

Distance factor:	1 GHz - 6 GHz	$20\log(3.8\text{ m} / 3.0\text{ m}) = 2.06\text{ dB}$
	6 GHz - 10 GHz	$20\log(4.8\text{ m} / 3.0\text{ m}) = 4.09\text{ dB}$
	10 GHz - 26.5 GHz	$20\log(1.0\text{ m} / 3.0\text{ m}) = -9.5\text{ dB}$

**Radiated Spurious Emission**  
**(Reference Plot for band-edge)**


Test place	Ise EMC Lab.
Semi Anechoic Chamber	No.3
Date	June 23, 2024
Temperature / Humidity	23 deg. C / 60 % RH
Engineer	Junya Okuno
	(1 GHz to 6 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz + 11ac-20 5220 MHz



\* The measurement was conducted for a sufficiently long enough time to detect any possible spurious emissions.  
Final result of restricted band edge was shown in tabular data.

**Radiated Spurious Emission**  
**(Plot data, Worst case mode for Maximum Peak Output Power)**

Test place	Ise EMC Lab.	No.3	No.3
Semi Anechoic Chamber	No.3	No.3	No.3
Date	June 19, 2024	June 18, 2024	June 18, 2024
Temperature / Humidity	23 deg. C / 59 % RH	23 deg. C / 56 % RH	23 deg. C / 56 % RH
Engineer	Hiroki Numata	Hiroki Numata	Hiroki Numata
	(1 GHz to 10 GHz)	(Above 10 GHz)	(Below 1 GHz)
Mode	Tx, Hopping Off, 3DH5 2480 MHz		





\*These plots data contain sufficient number to show the trend of characteristic features for EUT.

Conducted Spurious Emission

Test place	Ise EMC Lab. No.3 Preparation room	
Date	June 17, 2024	June 17, 2024
Temperature / Humidity	23 deg. C / 54 % RH	23 deg. C / 54 % RH
Engineer	Yuta Moriya	Yuta Moriya
Mode	Tx, Hopping Off, DH5	



2402 MHz



Conducted Spurious Emission

Test place                   Ise EMC Lab. No.3 Preparation room  
Date                         June 17, 2024  
Temperature / Humidity   23 deg. C / 54 % RH  
Engineer                  Yuta Moriya  
Mode                       Tx, Hopping Off, DH5



2441 MHz



Conducted Spurious Emission

Test place                   Ise EMC Lab. No.3 Preparation room  
Date                         June 17, 2024  
Temperature / Humidity   23 deg. C / 54 % RH  
Engineer                  Yuta Moriya  
Mode                       Tx, Hopping Off, DH5



2480 MHz



Conducted Spurious Emission

Test place                      Ise EMC Lab. No.3 Preparation room  
Date                              June 17, 2024  
Temperature / Humidity      23 deg. C / 54 % RH  
Engineer                        Yuta Moriya  
Mode                              Tx, Hopping Off, 3DH5



2402 MHz



Conducted Spurious Emission

Test place                   Ise EMC Lab. No.3 Preparation room  
Date                         June 17, 2024  
Temperature / Humidity   23 deg. C / 54 % RH  
Engineer                  Yuta Moriya  
Mode                       Tx, Hopping Off, 3DH5

2441 MHz







Conducted Spurious Emission

Test place                   Ise EMC Lab. No.3 Preparation room  
Date                         June 17, 2024  
Temperature / Humidity   23 deg. C / 54 % RH  
Engineer                  Yuta Moriya  
Mode                       Tx, Hopping Off, 3DH5


2480 MHz




Conducted Emission Band Edge compliance

Test place                      Ise EMC Lab. No.3 Preparation room  
Date                              June 17, 2024  
Temperature / Humidity        23 deg. C / 54 % RH  
Engineer                        Yuta Moriya  
Mode                              Tx DH5

Hopping On




Hopping Off




Conducted Emission Band Edge compliance

Test place                      Ise EMC Lab. No.3 Preparation room  
Date                              June 17, 2024  
Temperature / Humidity      23 deg. C / 54 % RH  
Engineer                        Yuta Moriya  
Mode                              Tx 3DH5

Hopping On



Hopping Off



## APPENDIX 2: Test Instruments

### Test Equipment

Test Item	LIMS ID	Description	Manufacturer	Model	Serial	Last Calibration Date	Cal Int
AT	141156	Attenuator(10dB)	Weinschel Corp	2	BL1173	11/17/2023	12
AT	141172	Attenuator(6dB) (above1GHz)	HIROSE ELECTRIC CO.,LTD.	AT-106	-	12/11/2023	12
AT	141279	Microwave Cable	Junkosha	MMX221-00500DMSDMS	1502S303	03/04/2024	12
AT	141327	Coaxial Cable	UL Japan	-	-	02/09/2024	12
AT	141328	Microwave Cable 1G-40GHz	Suhner	SUCOFLEX102	28636/2	04/01/2024	12
AT	141557	DIGITAL HiTESTER	HIOKI E.E. CORPORATION	3805	070900530	01/31/2024	12
AT	141809	Power Meter	Anritsu Corporation	ML2495A	825002	05/22/2024	12
AT	141810	Power Meter	Anritsu Corporation	ML2495A	824014	12/12/2023	12
AT	141830	Power sensor	Anritsu Corporation	MA2411B	738285	05/22/2024	12
AT	141832	Power sensor	Anritsu Corporation	MA2411B	738174	12/12/2023	12
AT	141901	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY48250080	01/26/2024	12
AT	141903	Spectrum Analyzer	Keysight Technologies Inc	E4440A	MY46186390	01/26/2024	12
AT	244709	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202103	01/25/2024	12
AT	244711	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202105	01/25/2024	12
RE	141232	High Pass Filter 3.5-18.0GHz	UL Japan	HPF SELECTOR	001	09/04/2023	12
RE	141266	Logperiodic Antenna (200-1000MHz)	Schwarzbeck Mess-Elektronik OHG	VUSLP9111B	9111B-191	08/10/2023	12
RE	141323	Coaxial cable	UL Japan	-	-	09/10/2023	12
RE	141424	Biconical Antenna	Schwarzbeck Mess-Elektronik OHG	VHA9103 +BBA9106	1915	03/15/2024	12
RE	141507	Horn Antenna 1-18GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9120D	258	11/20/2023	12
RE	141513	Horn Antenna 15-40GHz	Schwarzbeck Mess-Elektronik OHG	BBHA9170	BBHA9170306	07/19/2023	12
RE	141532	DIGITAL HiTESTER	HIOKI E.E. CORPORATION	3805	051201197	01/31/2024	12
RE	141580	MicroWave System Amplifier	Keysight Technologies Inc	83017A	MY39500779	03/08/2024	12
RE	141582	Pre Amplifier	SONOMA INSTRUMENT	310	260834	02/17/2024	12
RE	141899	Spectrum Analyzer	Keysight Technologies Inc	E4448A	MY46180655	05/09/2024	12
RE	142008	AC3_Semi Anechoic Chamber(NSA)	TDK	Semi Anechoic Chamber 3m	DA-10005	12/11/2023	24
RE	142013	AC3_Semi Anechoic Chamber(SVSWR)	TDK	Semi Anechoic Chamber 3m	DA-10005	04/12/2023	24
RE	142183	Measure	KOMELON	KMC-36	-	10/20/2023	12
RE	142314	Attenuator	Pasternack Enterprises	PE7390-6	D/C 1504	06/06/2024	12
RE	144196	Test Receiver	Rohde & Schwarz	ESCI	100608	10/18/2023	12
RE	178648	EMI measurement program	TSJ (Techno Science Japan)	TEPTO-DV	-	-	-
RE	244709	Thermo-Hygrometer	HIOKI E.E. CORPORATION	LR5001	231202103	01/25/2024	12
RE	245787	Double Ridge Horn Antenna	Schwarzbeck Mess-Elektronik OHG	BBHA 9120 C	689	03/06/2024	12
RE	246001	Microwave Cable	Huber+Suhner	SF103/11PC35/ 11PC35/1000mm / SF126E/5000mm	800673(1m) / 610204(5m)	03/06/2024	12

\*Hyphens for Last Calibration Date and Cal Int (month) are instruments that Calibration is not required (e.g. software), or instruments checked in advance before use.

The expiration date of the calibration is the end of the expired month.

As for some calibrations performed after the tested dates, those test equipment have been controlled by means of an unbroken chains of calibrations.

All equipment is calibrated with valid calibrations. Each measurement data is traceable to the national or international standards.

Test item:

AT: Antenna Terminal Conducted test

RE: Radiated Emission