



RF EXPOSURE REPORT

REPORT NO.: SA110721C33B

MODEL NO.: AP-8100

FCC ID: HZB-AP8100

RECEIVED: Jul. 21, 2011

TESTED: Oct. 27 ~ Dec. 30, 2011

ISSUED: Mar. 27, 2012

APPLICANT: Proxim Wireless Corporation

ADDRESS: 1561 Buckeye Drive, Milpitas, California,
United States, 95035

ISSUED BY: Bureau Veritas Consumer Products Services
(H.K.) Ltd., Taoyuan Branch

LAB ADDRESS: No. 47, 14th Ling, Chia Pau Vil., Lin Kou Dist.,
New Taipei City, Taiwan (R.O.C)

TEST LOCATION: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan,
R.O.C.

This test report consists of 6 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced, except in full, without the written approval of our laboratory. The client should not use it to claim product, certification, approval, or endorsement by any government agency. The test results in the report only apply to the tested sample.



TABLE OF CONTENTS

RELEASE CONTROL RECORD	3
1. CERTIFICATION	4
2. RF EXPOSURE.....	5
2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	5
2.2 MPE CALCULATION FORMULA	5
2.3 CLASSIFICATION	5
2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA110721C33B	Original release	Mar. 27, 2012

1. CERTIFICATION

PRODUCT: Wireless 802.11 abgn Router
MODEL: AP-8100
BRAND: Proxim
APPLICANT: Proxim Wireless Corporation
TESTED: Oct. 27 ~ Nov. 29, 2011
TEST SAMPLE: ENGINEERING SAMPLE
STANDARDS: **FCC Part 2 (Section 2.1091)**
FCC OET Bulletin 65, Supplement C (01-01)
IEEE C95.1

The above equipment (Model: AP-8100) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Andrea Hsia , DATE : Mar. 27, 2012
Andrea Hsia / Specialist

APPROVED BY : Gary Chang , DATE : Mar. 27, 2012
Gary Chang / Technical Manager

2. RF EXPOSURE

2.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	F/1500	30
1500-100,000	1.0	30

F = Frequency in MHz

2.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 21cm away from the body of the user. So, this device is classified as **Mobile Device**.

2.4 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

FOR RF IC: AR9382

FREQUENCY BAND (MHz)	MODULATION MODE	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	802.11b	19.6	6	21	0.066	1
	802.11g	28.3	6	21	0.486	1
	802.11n (20MHz)	28.2	3	21	0.238	1
	802.11n (40MHz)	27.6	3	21	0.207	1

FOR RF IC: AR9344

FREQUENCY BAND (MHz)	MODULATION MODE	MAX POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2412-2462	802.11b	24.2	6	21	0.189	1
	802.11g	29.6	6	21	0.655	1
	802.11n (20MHz)	29.6	3	21	0.328	1
	802.11n (40MHz)	28.6	3	21	0.261	1
5180-5240	802.11a	13.4	7	21	0.020	1
	802.11n (20MHz)	13.6	4	21	0.010	1
	802.11n (40MHz)	15.4	4	21	0.016	1
5745-5825	802.11a	27.0	7	21	0.453	1
	802.11n (20MHz)	26.8	4	21	0.217	1
	802.11n (40MHz)	26.8	4	21	0.217	1

NOTE:

802.11b & 802.11g: Directional gain = 3dBi + 10log(2)=6dBi

802.11a: Directional gain = 4dBi + 10log(2)=7dBi

CONCLUSION:

Only 2.4 and 5GHz can transmit simultaneously, 2.4 and 2.4GHz does not. The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$1. \text{ WLAN 2.4G} + \text{WLAN 5.0G} = 0.486 + 0.453 = 0.939$$

Therefore, the maximum calculation of this situation is 0.939, which is less than the "1" limit.