

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
1	5729	37.5	13.7	-38	-60	22
2	5729.05	36.9	13.1	-38.6	-60	21.4
3	5729.1	35.9	12.1	-39.6	-60	20.4
4	5729.15	34.5	10.7	-41	-60	19
5	5729.2	34.4	10.6	-41.1	-60	18.9
6	5729.25	34.3	10.5	-41.2	-60	18.8
7	5729.3	33.3	9.5	-42.2	-60	17.8
8	5729.35	33.4	9.6	-42.1	-60	17.9
9	5729.4	33.1	9.3	-42.4	-60	17.6
10	5729.45	32.3	8.5	-43.2	-60	16.8
11	5729.5	32.3	8.5	-43.2	-60	16.8
12	5729.55	31.9	8.1	-43.6	-60	16.4
13	5729.6	31.6	7.8	-43.9	-60	16.1
14	5729.65	31.5	7.7	-44	-60	16
15	5729.7	30.5	6.7	-45	-60	15
16	5729.75	30.5	6.7	-45	-60	15
17	5729.8	30.6	6.8	-44.9	-60	15.1
18	5729.85	29.5	5.7	-46	-60	14
19	5729.9	29.3	5.5	-46.2	-60	13.8
20	5729.95	29.3	5.5	-46.2	-60	13.8
21	5730	28.3	4.5	-47.2	-60	12.8
22	5730.05	28.4	4.6	-47.1	-60	12.9
23	5730.1	28.4	4.6	-47.1	-60	12.9
24	5730.15	27.3	3.5	-48.2	-60	11.8
25	5730.2	27.3	3.5	-48.2	-60	11.8
26	5730.25	27.5	3.7	-48	-60	12
27	5730.3	26.6	2.8	-48.9	-60	11.1
28	5730.35	26.5	2.7	-49	-60	11
29	5730.4	26.2	2.4	-49.3	-60	10.7
30	5730.45	25.7	1.9	-49.8	-60	10.2
31	5730.5	25.8	2	-49.7	-60	10.3
32	5730.55	25.3	1.5	-50.2	-60	9.8
33	5730.6	24.9	1.1	-50.6	-60	9.4
34	5730.65	24.8	1	-50.7	-60	9.3
35	5730.7	24.3	0.5	-51.2	-60	8.8
36	5730.75	24.4	0.6	-51.1	-60	8.9
37	5730.8	24.3	0.5	-51.2	-60	8.8
38	5730.85	23.4	-0.4	-52.1	-60	7.9
39	5730.9	23.4	-0.4	-52.1	-60	7.9
40	5730.95	23.5	-0.3	-52	-60	8
41	5731	22.7	-1.1	-52.8	-60	7.2
42	5731.05	22.6	-1.2	-52.9	-60	7.1
43	5731.1	22.5	-1.3	-53	-60	7
44	5731.15	21.7	-2.1	-53.8	-60	6.2
45	5731.2	21.8	-2	-53.7	-60	6.3
46	5731.25	21.8	-2	-53.7	-60	6.3
47	5731.3	21.1	-2.7	-54.4	-60	5.6
48	5731.35	21.1	-2.7	-54.4	-60	5.6
49	5731.4	21	-2.8	-54.5	-60	5.5

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
50	5731.45	20.7	-3.1	-54.8	-60	5.2
51	5731.5	20.7	-3.1	-54.8	-60	5.2
52	5731.55	20.2	-3.6	-55.3	-60	4.7
53	5731.6	20	-3.8	-55.5	-60	4.5
54	5731.65	20.1	-3.7	-55.4	-60	4.6
55	5731.7	19.6	-4.2	-55.9	-60	4.1
56	5731.75	19.4	-4.4	-56.1	-60	3.9
57	5731.8	19.3	-4.5	-56.2	-60	3.8
58	5731.85	18.7	-5.1	-56.8	-60	3.2
59	5731.9	18.8	-5	-56.7	-60	3.3
60	5731.95	18.8	-5	-56.7	-60	3.3
61	5732	18.1	-5.7	-57.4	-60	2.6
62	5732.05	18	-5.8	-57.5	-60	2.5
63	5732.1	18.2	-5.6	-57.3	-60	2.7
64	5732.15	17.6	-6.2	-57.9	-60	2.1
65	5732.2	17.5	-6.3	-58	-60	2
66	5732.25	17.4	-6.4	-58.1	-60	1.9
67	5732.3	16.8	-7	-58.7	-60	1.3
68	5732.35	16.9	-6.9	-58.6	-60	1.4
69	5732.4	16.8	-7	-58.7	-60	1.3
70	5732.45	16.4	-7.4	-59.1	-60	0.9
71	5732.5	16.3	-7.5	-59.2	-60	0.8
72	5732.55	16.3	-7.5	-59.2	-60	0.8
73	5732.6	16.2	-7.6	-59.3	-60	0.7
74	5732.65	16.2	-7.6	-59.3	-60	0.7
75	5732.7	15.9	-7.9	-59.6	-60	0.4
76	5732.75	15.8	-8	-59.7	-60	0.3
77	5732.8	16	-7.8	-59.5	-60	0.5
78	5732.85	15.7	-8.1	-59.8	-60	0.2
79	5732.9	15.6	-8.2	-59.9	-60	0.1
80	5732.95	15.4	-8.4	-60.1	-60	-0.1
81	5733	15.1	-8.7	-60.4	-60	-0.4
82	5733.05	15.2	-8.6	-60.3	-60	-0.3
83	5733.1	15.2	-8.6	-60.3	-60	-0.3
84	5733.15	14.7	-9.1	-60.8	-60	-0.8
85	5733.2	14.6	-9.2	-60.9	-60	-0.9
86	5733.25	14.7	-9.1	-60.8	-60	-0.8
87	5733.3	14.6	-9.2	-60.9	-60	-0.9
88	5733.35	14.6	-9.2	-60.9	-60	-0.9
89	5733.4	14.4	-9.4	-61.1	-60	-1.1
90	5733.45	14.1	-9.7	-61.4	-60	-1.4
91	5733.5	14.2	-9.6	-61.3	-60	-1.3
92	5733.55	14.2	-9.6	-61.3	-60	-1.3
93	5733.6	14	-9.8	-61.5	-60	-1.5
94	5733.65	13.8	-10	-61.7	-60	-1.7
95	5733.7	13.7	-10.1	-61.8	-60	-1.8
96	5733.75	13.8	-10	-61.7	-60	-1.7
97	5733.8	13.9	-9.9	-61.6	-60	-1.6
98	5733.85	13.5	-10.3	-62	-60	-2

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
99	5733.9	13.5	-10.3	-62	-60	-2
100	5733.95	13.6	-10.2	-61.9	-60	-1.9
101	5734	13.5	-10.3	-62	-60	-2
102	5734.05	13.4	-10.4	-62.1	-60	-2.1
103	5734.1	13.3	-10.5	-62.2	-60	-2.2
104	5734.15	13	-10.8	-62.5	-60	-2.5
105	5734.2	13.1	-10.7	-62.4	-60	-2.4
106	5734.25	13.1	-10.7	-62.4	-60	-2.4
107	5734.3	12.8	-11	-62.7	-60	-2.7
108	5734.35	12.6	-11.2	-62.9	-60	-2.9
109	5734.4	12.7	-11.1	-62.8	-60	-2.8
110	5734.45	12.7	-11.1	-62.8	-60	-2.8
111	5734.5	12.7	-11.1	-62.8	-60	-2.8
112	5734.55	12.6	-11.2	-62.9	-60	-2.9
113	5734.6	12.5	-11.3	-63	-60	-3
114	5734.65	12.6	-11.2	-62.9	-60	-2.9
115	5734.7	12.7	-11.1	-62.8	-60	-2.8
116	5734.75	12.6	-11.2	-62.9	-60	-2.9
117	5734.8	12.5	-11.3	-63	-60	-3
118	5734.85	12.4	-11.4	-63.1	-60	-3.1
119	5734.9	12.5	-11.3	-63	-60	-3
120	5734.95	12.6	-11.2	-62.9	-60	-2.9
121	5735	12.5	-11.3	-63	-60	-3
122	5735.05	12.4	-11.4	-63.1	-60	-3.1
123	5735.1	12.5	-11.3	-63	-60	-3
124	5735.15	12.7	-11.1	-62.8	-60	-2.8
125	5735.2	12.7	-11.1	-62.8	-60	-2.8
126	5735.25	12.6	-11.2	-62.9	-60	-2.9
127	5735.3	12.5	-11.3	-63	-60	-3
128	5735.35	12.6	-11.2	-62.9	-60	-2.9
129	5735.4	12.7	-11.1	-62.8	-60	-2.8
130	5735.45	12.6	-11.2	-62.9	-60	-2.9
131	5735.5	12.4	-11.4	-63.1	-60	-3.1
132	5735.55	12.3	-11.5	-63.2	-60	-3.2
133	5735.6	12.4	-11.4	-63.1	-60	-3.1
134	5735.65	12.5	-11.3	-63	-60	-3
135	5735.7	12.4	-11.4	-63.1	-60	-3.1
136	5735.75	12.3	-11.5	-63.2	-60	-3.2
137	5735.8	12.4	-11.4	-63.1	-60	-3.1
138	5735.85	12.5	-11.3	-63	-60	-3
139	5735.9	12.6	-11.2	-62.9	-60	-2.9
140	5735.95	12.4	-11.4	-63.1	-60	-3.1
141	5736	12.4	-11.4	-63.1	-60	-3.1
142	5736.05	12.4	-11.4	-63.1	-60	-3.1
143	5736.1	12.5	-11.3	-63	-60	-3
144	5736.15	12.4	-11.4	-63.1	-60	-3.1
145	5736.2	12.3	-11.5	-63.2	-60	-3.2
146	5736.25	12.3	-11.5	-63.2	-60	-3.2
147	5736.3	12.5	-11.3	-63	-60	-3

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
148	5736.35	12.5	-11.3	-63	-60	-3
149	5736.4	12.4	-11.4	-63.1	-60	-3.1
150	5736.45	12.4	-11.4	-63.1	-60	-3.1
151	5736.5	12.4	-11.4	-63.1	-60	-3.1
152	5736.55	12.5	-11.3	-63	-60	-3
153	5736.6	12.5	-11.3	-63	-60	-3
154	5736.65	12.3	-11.5	-63.2	-60	-3.2
155	5736.7	12.1	-11.7	-63.4	-60	-3.4
156	5736.75	12.2	-11.6	-63.3	-60	-3.3
157	5736.8	12.2	-11.6	-63.3	-60	-3.3
158	5736.85	12	-11.8	-63.5	-60	-3.5
159	5736.9	11.9	-11.9	-63.6	-60	-3.6
160	5736.95	11.9	-11.9	-63.6	-60	-3.6
161	5737	12	-11.8	-63.5	-60	-3.5
162	5737.05	12.1	-11.7	-63.4	-60	-3.4
163	5737.1	12	-11.8	-63.5	-60	-3.5
164	5737.15	11.8	-12	-63.7	-60	-3.7
165	5737.2	11.9	-11.9	-63.6	-60	-3.6
166	5737.25	12	-11.8	-63.5	-60	-3.5
167	5737.3	11.9	-11.9	-63.6	-60	-3.6
168	5737.35	11.7	-12.1	-63.8	-60	-3.8
169	5737.4	11.7	-12.1	-63.8	-60	-3.8
170	5737.45	11.7	-12.1	-63.8	-60	-3.8
171	5737.5	11.8	-12	-63.7	-60	-3.7
172	5737.55	11.8	-12	-63.7	-60	-3.7
173	5737.6	11.6	-12.2	-63.9	-60	-3.9
174	5737.65	11.7	-12.1	-63.8	-60	-3.8
175	5737.7	11.8	-12	-63.7	-60	-3.7
176	5737.75	11.9	-11.9	-63.6	-60	-3.6
177	5737.8	11.8	-12	-63.7	-60	-3.7
178	5737.85	11.7	-12.1	-63.8	-60	-3.8
179	5737.9	11.7	-12.1	-63.8	-60	-3.8
180	5737.95	11.8	-12	-63.7	-60	-3.7
181	5738	11.7	-12.1	-63.8	-60	-3.8
182	5738.05	11.6	-12.2	-63.9	-60	-3.9
183	5738.1	11.5	-12.3	-64	-60	-4
184	5738.15	11.6	-12.2	-63.9	-60	-3.9
185	5738.2	11.7	-12.1	-63.8	-60	-3.8
186	5738.25	11.7	-12.1	-63.8	-60	-3.8
187	5738.3	11.6	-12.2	-63.9	-60	-3.9
188	5738.35	11.6	-12.2	-63.9	-60	-3.9
189	5738.4	11.8	-12	-63.7	-60	-3.7
190	5738.45	11.8	-12	-63.7	-60	-3.7
191	5738.5	11.7	-12.1	-63.8	-60	-3.8
192	5738.55	11.6	-12.2	-63.9	-60	-3.9
193	5738.6	11.7	-12.1	-63.8	-60	-3.8
194	5738.65	11.8	-12	-63.7	-60	-3.7
195	5738.7	11.7	-12.1	-63.8	-60	-3.8
196	5738.75	11.6	-12.2	-63.9	-60	-3.9

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
197	5738.8	11.6	-12.2	-63.9	-60	-3.9
198	5738.85	11.7	-12.1	-63.8	-60	-3.8
199	5738.9	11.8	-12	-63.7	-60	-3.7
200	5738.95	11.7	-12.1	-63.8	-60	-3.8
201	5739	11.6	-12.2	-63.9	-60	-3.9
202	5739.05	11.6	-12.2	-63.9	-60	-3.9
203	5739.1	11.7	-12.1	-63.8	-60	-3.8
204	5739.15	11.7	-12.1	-63.8	-60	-3.8
205	5739.2	11.6	-12.2	-63.9	-60	-3.9
206	5739.25	11.5	-12.3	-64	-60	-4
207	5739.3	11.5	-12.3	-64	-60	-4
208	5739.35	11.6	-12.2	-63.9	-60	-3.9
209	5739.4	11.5	-12.3	-64	-60	-4
210	5739.45	11.4	-12.4	-64.1	-60	-4.1
211	5739.5	11.4	-12.4	-64.1	-60	-4.1
212	5739.55	11.6	-12.2	-63.9	-60	-3.9
213	5739.6	11.7	-12.1	-63.8	-60	-3.8
214	5739.65	11.6	-12.2	-63.9	-60	-3.9
215	5739.7	11.5	-12.3	-64	-60	-4
216	5739.75	11.5	-12.3	-64	-60	-4
217	5739.8	11.6	-12.2	-63.9	-60	-3.9
218	5739.85	11.6	-12.2	-63.9	-60	-3.9
219	5739.9	11.4	-12.4	-64.1	-60	-4.1
220	5739.95	11.3	-12.5	-64.2	-60	-4.2
221	5740	11.3	-12.5	-64.2	-60	-4.2
222	5740.05	11.4	-12.4	-64.1	-60	-4.1
223	5740.1	11.4	-12.4	-64.1	-60	-4.1
224	5740.15	11.3	-12.5	-64.2	-60	-4.2
225	5740.2	11.2	-12.6	-64.3	-60	-4.3
226	5740.25	11.4	-12.4	-64.1	-60	-4.1
227	5740.3	11.4	-12.4	-64.1	-60	-4.1
228	5740.35	11.3	-12.5	-64.2	-60	-4.2
229	5740.4	11.1	-12.7	-64.4	-60	-4.4
230	5740.45	11.1	-12.7	-64.4	-60	-4.4
231	5740.5	11.2	-12.6	-64.3	-60	-4.3
232	5740.55	11.1	-12.7	-64.4	-60	-4.4
233	5740.6	11	-12.8	-64.5	-60	-4.5
234	5740.65	10.9	-12.9	-64.6	-60	-4.6
235	5740.7	10.9	-12.9	-64.6	-60	-4.6
236	5740.75	11.1	-12.7	-64.4	-60	-4.4
237	5740.8	11.1	-12.7	-64.4	-60	-4.4
238	5740.85	10.9	-12.9	-64.6	-60	-4.6
239	5740.9	10.9	-12.9	-64.6	-60	-4.6
240	5740.95	11	-12.8	-64.5	-60	-4.5
241	5741	11	-12.8	-64.5	-60	-4.5
242	5741.05	10.9	-12.9	-64.6	-60	-4.6
243	5741.1	10.7	-13.1	-64.8	-60	-4.8
244	5741.15	10.7	-13.1	-64.8	-60	-4.8
245	5741.2	10.7	-13.1	-64.8	-60	-4.8

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
246	5741.25	10.7	-13.1	-64.8	-60	-4.8
247	5741.3	10.5	-13.3	-65	-60	-5
248	5741.35	10.5	-13.3	-65	-60	-5
249	5741.4	10.6	-13.2	-64.9	-60	-4.9
250	5741.45	10.7	-13.1	-64.8	-60	-4.8
251	5741.5	10.7	-13.1	-64.8	-60	-4.8
252	5741.55	10.6	-13.2	-64.9	-60	-4.9
253	5741.6	10.6	-13.2	-64.9	-60	-4.9
254	5741.65	10.7	-13.1	-64.8	-60	-4.8
255	5741.7	10.8	-13	-64.7	-60	-4.7
256	5741.75	10.7	-13.1	-64.8	-60	-4.8
257	5741.8	10.6	-13.2	-64.9	-60	-4.9
258	5741.85	10.8	-13	-64.7	-60	-4.7
259	5741.9	10.9	-12.9	-64.6	-60	-4.6
260	5741.95	10.9	-12.9	-64.6	-60	-4.6
261	5742	11	-12.8	-64.5	-60	-4.5
262	5742.05	11	-12.8	-64.5	-60	-4.5
263	5742.1	11.1	-12.7	-64.4	-60	-4.4
264	5742.15	11.4	-12.4	-64.1	-60	-4.1
265	5742.2	11.4	-12.4	-64.1	-60	-4.1
266	5742.25	11.3	-12.5	-64.2	-60	-4.2
267	5742.3	11.4	-12.4	-64.1	-60	-4.1
268	5742.35	11.5	-12.3	-64	-60	-4
269	5742.4	11.5	-12.3	-64	-60	-4
270	5742.45	11.4	-12.4	-64.1	-60	-4.1
271	5742.5	11.3	-12.5	-64.2	-60	-4.2
272	5742.55	11.4	-12.4	-64.1	-60	-4.1
273	5742.6	11.6	-12.2	-63.9	-60	-3.9
274	5742.65	11.6	-12.2	-63.9	-60	-3.9
275	5742.7	11.5	-12.3	-64	-60	-4
276	5742.75	11.5	-12.3	-64	-60	-4
277	5742.8	11.6	-12.2	-63.9	-60	-3.9
278	5742.85	11.7	-12.1	-63.8	-60	-3.8
279	5742.9	11.6	-12.2	-63.9	-60	-3.9
280	5742.95	11.5	-12.3	-64	-60	-4
281	5743	11.5	-12.3	-64	-60	-4
282	5743.05	11.6	-12.2	-63.9	-60	-3.9
283	5743.1	11.6	-12.2	-63.9	-60	-3.9
284	5743.15	11.6	-12.2	-63.9	-60	-3.9
285	5743.2	11.5	-12.3	-64	-60	-4
286	5743.25	11.6	-12.2	-63.9	-60	-3.9
287	5743.3	11.8	-12	-63.7	-60	-3.7
288	5743.35	11.8	-12	-63.7	-60	-3.7
289	5743.4	11.7	-12.1	-63.8	-60	-3.8
290	5743.45	11.7	-12.1	-63.8	-60	-3.8
291	5743.5	11.8	-12	-63.7	-60	-3.7
292	5743.55	11.9	-11.9	-63.6	-60	-3.6
293	5743.6	11.8	-12	-63.7	-60	-3.7
294	5743.65	11.7	-12.1	-63.8	-60	-3.8

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
295	5743.7	11.7	-12.1	-63.8	-60	-3.8
296	5743.75	11.8	-12	-63.7	-60	-3.7
297	5743.8	11.8	-12	-63.7	-60	-3.7
298	5743.85	11.7	-12.1	-63.8	-60	-3.8
299	5743.9	11.6	-12.2	-63.9	-60	-3.9
300	5743.95	11.7	-12.1	-63.8	-60	-3.8
301	5744	11.9	-11.9	-63.6	-60	-3.6
302	5744.05	11.9	-11.9	-63.6	-60	-3.6
303	5744.1	11.8	-12	-63.7	-60	-3.7
304	5744.15	11.8	-12	-63.7	-60	-3.7
305	5744.2	11.8	-12	-63.7	-60	-3.7
306	5744.25	11.9	-11.9	-63.6	-60	-3.6
307	5744.3	11.9	-11.9	-63.6	-60	-3.6
308	5744.35	11.7	-12.1	-63.8	-60	-3.8
309	5744.4	11.8	-12	-63.7	-60	-3.7
310	5744.45	11.9	-11.9	-63.6	-60	-3.6
311	5744.5	12	-11.8	-63.5	-60	-3.5
312	5744.55	11.9	-11.9	-63.6	-60	-3.6
313	5744.6	11.9	-11.9	-63.6	-60	-3.6
314	5744.65	12	-11.8	-63.5	-60	-3.5
315	5744.7	12.1	-11.7	-63.4	-60	-3.4
316	5744.75	12.1	-11.7	-63.4	-60	-3.4
317	5744.8	11.9	-11.9	-63.6	-60	-3.6
318	5744.85	11.8	-12	-63.7	-60	-3.7
319	5744.9	11.9	-11.9	-63.6	-60	-3.6
320	5744.95	12	-11.8	-63.5	-60	-3.5
321	5745	11.9	-11.9	-63.6	-60	-3.6
322	5745.05	11.7	-12.1	-63.8	-60	-3.8
323	5745.1	11.8	-12	-63.7	-60	-3.7
324	5745.15	11.9	-11.9	-63.6	-60	-3.6
325	5745.2	12	-11.8	-63.5	-60	-3.5
326	5745.25	11.9	-11.9	-63.6	-60	-3.6
327	5745.3	11.8	-12	-63.7	-60	-3.7
328	5745.35	11.9	-11.9	-63.6	-60	-3.6
329	5745.4	12	-11.8	-63.5	-60	-3.5
330	5745.45	12	-11.8	-63.5	-60	-3.5
331	5745.5	11.8	-12	-63.7	-60	-3.7
332	5745.55	11.8	-12	-63.7	-60	-3.7
333	5745.6	11.9	-11.9	-63.6	-60	-3.6
334	5745.65	12	-11.8	-63.5	-60	-3.5
335	5745.7	12	-11.8	-63.5	-60	-3.5
336	5745.75	11.9	-11.9	-63.6	-60	-3.6
337	5745.8	12	-11.8	-63.5	-60	-3.5
338	5745.85	12.2	-11.6	-63.3	-60	-3.3
339	5745.9	12.3	-11.5	-63.2	-60	-3.2
340	5745.95	12.2	-11.6	-63.3	-60	-3.3
341	5746	12.2	-11.6	-63.3	-60	-3.3
342	5746.05	12.2	-11.6	-63.3	-60	-3.3
343	5746.1	12.3	-11.5	-63.2	-60	-3.2

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
344	5746.15	12.3	-11.5	-63.2	-60	-3.2
345	5746.2	12.2	-11.6	-63.3	-60	-3.3
346	5746.25	12.1	-11.7	-63.4	-60	-3.4
347	5746.3	12.3	-11.5	-63.2	-60	-3.2
348	5746.35	12.3	-11.5	-63.2	-60	-3.2
349	5746.4	12.3	-11.5	-63.2	-60	-3.2
350	5746.45	12.2	-11.6	-63.3	-60	-3.3
351	5746.5	12.3	-11.5	-63.2	-60	-3.2
352	5746.55	12.5	-11.3	-63	-60	-3
353	5746.6	12.5	-11.3	-63	-60	-3
354	5746.65	12.4	-11.4	-63.1	-60	-3.1
355	5746.7	12.3	-11.5	-63.2	-60	-3.2
356	5746.75	12.4	-11.4	-63.1	-60	-3.1
357	5746.8	12.5	-11.3	-63	-60	-3
358	5746.85	12.5	-11.3	-63	-60	-3
359	5746.9	12.4	-11.4	-63.1	-60	-3.1
360	5746.95	12.3	-11.5	-63.2	-60	-3.2
361	5747	12.5	-11.3	-63	-60	-3
362	5747.05	12.6	-11.2	-62.9	-60	-2.9
363	5747.1	12.5	-11.3	-63	-60	-3
364	5747.15	12.5	-11.3	-63	-60	-3
365	5747.2	12.5	-11.3	-63	-60	-3
366	5747.25	12.6	-11.2	-62.9	-60	-2.9
367	5747.3	12.6	-11.2	-62.9	-60	-2.9
368	5747.35	12.5	-11.3	-63	-60	-3
369	5747.4	12.4	-11.4	-63.1	-60	-3.1
370	5747.45	12.4	-11.4	-63.1	-60	-3.1
371	5747.5	12.5	-11.3	-63	-60	-3
372	5747.55	12.5	-11.3	-63	-60	-3
373	5747.6	12.4	-11.4	-63.1	-60	-3.1
374	5747.65	12.4	-11.4	-63.1	-60	-3.1
375	5747.7	12.6	-11.2	-62.9	-60	-2.9
376	5747.75	12.7	-11.1	-62.8	-60	-2.8
377	5747.8	12.7	-11.1	-62.8	-60	-2.8
378	5747.85	12.7	-11.1	-62.8	-60	-2.8
379	5747.9	12.7	-11.1	-62.8	-60	-2.8
380	5747.95	12.8	-11	-62.7	-60	-2.7
381	5748	12.9	-10.9	-62.6	-60	-2.6
382	5748.05	12.8	-11	-62.7	-60	-2.7
383	5748.1	12.7	-11.1	-62.8	-60	-2.8
384	5748.15	12.9	-10.9	-62.6	-60	-2.6
385	5748.2	13	-10.8	-62.5	-60	-2.5
386	5748.25	12.9	-10.9	-62.6	-60	-2.6
387	5748.3	12.9	-10.9	-62.6	-60	-2.6
388	5748.35	12.9	-10.9	-62.6	-60	-2.6
389	5748.4	13.1	-10.7	-62.4	-60	-2.4
390	5748.45	13.2	-10.6	-62.3	-60	-2.3
391	5748.5	13.1	-10.7	-62.4	-60	-2.4
392	5748.55	13.1	-10.7	-62.4	-60	-2.4

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
393	5748.6	13.1	-10.7	-62.4	-60	-2.4
394	5748.65	13.2	-10.6	-62.3	-60	-2.3
395	5748.7	13.3	-10.5	-62.2	-60	-2.2
396	5748.75	13.2	-10.6	-62.3	-60	-2.3
397	5748.8	13.1	-10.7	-62.4	-60	-2.4
398	5748.85	13.4	-10.4	-62.1	-60	-2.1
399	5748.9	13.6	-10.2	-61.9	-60	-1.9
400	5748.95	13.5	-10.3	-62	-60	-2
401	5749	13.7	-10.1	-61.8	-60	-1.8
402	5749.05	13.7	-10.1	-61.8	-60	-1.8
403	5749.1	13.9	-9.9	-61.6	-60	-1.6
404	5749.15	14.1	-9.7	-61.4	-60	-1.4
405	5749.2	14	-9.8	-61.5	-60	-1.5
406	5749.25	13.9	-9.9	-61.6	-60	-1.6
407	5749.3	14.1	-9.7	-61.4	-60	-1.4
408	5749.35	14.2	-9.6	-61.3	-60	-1.3
409	5749.4	14.3	-9.5	-61.2	-60	-1.2
410	5749.45	14.3	-9.5	-61.2	-60	-1.2
411	5749.5	14.3	-9.5	-61.2	-60	-1.2
412	5749.55	14.6	-9.2	-60.9	-60	-0.9
413	5749.6	14.7	-9.1	-60.8	-60	-0.8
414	5749.65	14.7	-9.1	-60.8	-60	-0.8
415	5749.7	14.9	-8.9	-60.6	-60	-0.6
416	5749.75	14.9	-8.9	-60.6	-60	-0.6
417	5749.8	15	-8.8	-60.5	-60	-0.5
418	5749.85	15.4	-8.4	-60.1	-60	-0.1
419	5749.9	15.3	-8.5	-60.2	-60	-0.2
420	5749.95	15.1	-8.7	-60.4	-60	-0.4
421	5750	15.6	-8.2	-59.9	-60	0.1
422	5750.05	15.7	-8.1	-59.8	-60	0.2
423	5750.1	15.7	-8.1	-59.8	-60	0.2
424	5750.15	16	-7.8	-59.5	-60	0.5
425	5750.2	16	-7.8	-59.5	-60	0.5
426	5750.25	16.1	-7.7	-59.4	-60	0.6
427	5750.3	16.5	-7.3	-59	-60	1
428	5750.35	16.5	-7.3	-59	-60	1
429	5750.4	16.6	-7.2	-58.9	-60	1.1
430	5750.45	16.8	-7	-58.7	-60	1.3
431	5750.5	16.9	-6.9	-58.6	-60	1.4
432	5750.55	17.3	-6.5	-58.2	-60	1.8
433	5750.6	17.3	-6.5	-58.2	-60	1.8
434	5750.65	17.1	-6.7	-58.4	-60	1.6
435	5750.7	17.8	-6	-57.7	-60	2.3
436	5750.75	17.9	-5.9	-57.6	-60	2.4
437	5750.8	17.9	-5.9	-57.6	-60	2.4
438	5750.85	18.5	-5.3	-57	-60	3
439	5750.9	18.4	-5.4	-57.1	-60	2.9
440	5750.95	18.6	-5.2	-56.9	-60	3.1
441	5751	19.3	-4.5	-56.2	-60	3.8

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
442	5751.05	19.2	-4.6	-56.3	-60	3.7
443	5751.1	19.1	-4.7	-56.4	-60	3.6
444	5751.15	19.8	-4	-55.7	-60	4.3
445	5751.2	19.9	-3.9	-55.6	-60	4.4
446	5751.25	19.9	-3.9	-55.6	-60	4.4
447	5751.3	20.3	-3.5	-55.2	-60	4.8
448	5751.35	20.3	-3.5	-55.2	-60	4.8
449	5751.4	20.6	-3.2	-54.9	-60	5.1
450	5751.45	21.1	-2.7	-54.4	-60	5.6
451	5751.5	21.1	-2.7	-54.4	-60	5.6
452	5751.55	21.5	-2.3	-54	-60	6
453	5751.6	21.7	-2.1	-53.8	-60	6.2
454	5751.65	21.8	-2	-53.7	-60	6.3
455	5751.7	22.6	-1.2	-52.9	-60	7.1
456	5751.75	22.5	-1.3	-53	-60	7
457	5751.8	22.4	-1.4	-53.1	-60	6.9
458	5751.85	23.3	-0.5	-52.2	-60	7.8
459	5751.9	23.4	-0.4	-52.1	-60	7.9
460	5751.95	23.4	-0.4	-52.1	-60	7.9
461	5752	24.1	0.3	-51.4	-60	8.6
462	5752.05	24.1	0.3	-51.4	-60	8.6
463	5752.1	24.2	0.4	-51.3	-60	8.7
464	5752.15	25.2	1.4	-50.3	-60	9.7
465	5752.2	25.2	1.4	-50.3	-60	9.7
466	5752.25	25	1.2	-50.5	-60	9.5
467	5752.3	25.7	1.9	-49.8	-60	10.2
468	5752.35	25.8	2	-49.7	-60	10.3
469	5752.4	26.2	2.4	-49.3	-60	10.7
470	5752.45	26.5	2.7	-49	-60	11
471	5752.5	26.4	2.6	-49.1	-60	10.9
472	5752.55	26.9	3.1	-48.6	-60	11.4
473	5752.6	27.3	3.5	-48.2	-60	11.8
474	5752.65	27.4	3.6	-48.1	-60	11.9
475	5752.7	28.1	4.3	-47.4	-60	12.6
476	5752.75	28.1	4.3	-47.4	-60	12.6
477	5752.8	28.2	4.4	-47.3	-60	12.7
478	5752.85	29.4	5.6	-46.1	-60	13.9
479	5752.9	29.4	5.6	-46.1	-60	13.9
480	5752.95	29.3	5.5	-46.2	-60	13.8
481	5753	30.3	6.5	-45.2	-60	14.8
482	5753.05	30.3	6.5	-45.2	-60	14.8
483	5753.1	30.4	6.6	-45.1	-60	14.9
484	5753.15	31.3	7.5	-44.2	-60	15.8
485	5753.2	31.2	7.4	-44.3	-60	15.7
486	5753.25	31.2	7.4	-44.3	-60	15.7
487	5753.3	32.2	8.4	-43.3	-60	16.7
488	5753.35	32.2	8.4	-43.3	-60	16.7
489	5753.4	32.5	8.7	-43	-60	17
490	5753.45	33	9.2	-42.5	-60	17.5

Tsunami (Model 31145) Processing Gain

9/20/1999

meas #	f MHz	Gp dBm	Pg dBm	Pj dBm	Ps dBm	J/S dB
491	5753.5	33	9.2	-42.5	-60	17.5
492	5753.55	33.8	10	-41.7	-60	18.3
493	5753.6	34	10.2	-41.5	-60	18.5
494	5753.65	33.9	10.1	-41.6	-60	18.4
495	5753.7	34.8	11	-40.7	-60	19.3
496	5753.75	34.9	11.1	-40.6	-60	19.4
497	5753.8	35	11.2	-40.5	-60	19.5
498	5753.85	36.1	12.3	-39.4	-60	20.6
499	5753.9	36	12.2	-39.5	-60	20.5
500	5753.95	36.1	12.3	-39.4	-60	20.6

