

REVISIONS				
ISS	DESCRIPTION	UPDATED	DATE	APPROV
--	PRELIMINARY	LN	05-27-03	

**proxim**

MADE IN XXX

Model No. 40400-  
 FCC ID HZB-S58-B60  
 CANADA 1856-S58B60



Serial No. XXXXXXXXX

The device complies with Part 15 of the FCC Rules  
 IC: RSS-210  
 Operation is subject to the following three conditions:  
 (1.) This device may not cause harmful interference.  
 (2.) This device must accept any interference received,  
 including interference that may cause undesired  
 operation.  
 (3.) This device must be professionally installed.

Electrical Rating: +48 Vdc/1.0 A

XXXX



MAC ID: 00 04 44 12 34 56

ALL CHARACTERS BLACK

4X R .16

7

5

8

5	6
MODEL NO.	DESCRIPTION
25C	TSUNAMI CONNECTORIZED BSU 20
35C	TSUNAMI CONNECTORIZED BSU 30
65C	TSUNAMI CONNECTORIZED BSU 60

6	CPN
63502	
64781	
63515	

CPN XXXXX  
 ISS XX

4

9

3.00

2.50

- 9 MARK MAC ID (ETHERNET ADDRESS). ENCODING FORMAT: CODE 0128.
- 8 SERIAL NUMBER BARCODE. ENCODING FORMAT: CODE 0128.
- 7 PRINT COUNTRY OF ORIGIN IN LOCATION SHOWN (eg MADE IN MALAYSIA)
- 4 MARK REVISION (ISSUE) OF PRODUCT E.G. ISS 1.
- 3 MARK DATE CODE (MONTH/YEAR) E.G. 03/01.

- 2. MATERIAL: WHITE POLYESTER IMPRINTABLE LABEL STOCK, .002 THK, ACRYLIC ADHESIVE, .001 THK. .001 THK CLEAR, MATTE, MYLAR LAMINATION. REMOVE EXTRA MATERIAL AROUND CUT LABELS.
- 1. LABEL MUST BE UL APPROVED AND COMPLIANT WITH UL 969, AND SUITABLE FOR OUTDOOR USE.

**proxim**

UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE:  
 2 PLACE DECIMALS: ±0.015  
 3 PLACE DECIMALS: ±0.005  
 ANGULAR DIMENSIONS: ±1°  
 HOLES UNDER 0.250 DIA: ±0.002

MATERIAL: SEE NOTE 2  
 FINISH:  
 SILKSCREEN:  
 USED ON: POINT TO MULTIPoint | FILE NO.:  
 SCALE: 4:1 | ENGR BY: | CHKD BY:  
 DATE: 0-27-03 | DRWN BY: L. NICOLI | APPVD BY:

**LABEL, PRODUCT ID, CONNECTORIZED WAC**

SIZE C	XXXXX	SHEET 1 OF 1
--------	-------	--------------

**Proxim**

MADE IN XXX

Model No. 40400  
 FCC ID HZB-S58-B60  
 CANADA 1856-S58B60



Serial No. XXXXXXXXX

The device complies with Part 15 of the FCC Rules  
 IC: RSS-210

Operation is subject to the following two conditions:

- (1.) This device may not cause harmful interference.
- (2.) This device must accept any interference received, including interference that may cause undesired operation.

Electrical Rating: +48 Vdc/1.0 A

XXXX



MAC ID: 123456789X12

ALL CHARACTERS BLACK

4X R .16

7

5

8

5 MODEL NO.	DESCRIPTION	6 CPN
25	TSUNAMI BSU 20	58523
25R	TSUNAMI BSU 20 REJECTION	62365
25LT	TSUNAMI BSU 20 LOW TEMP	62527
35	TSUNAMI BSU 30	64776
35R	TSUNAMI BSU 30 REJECTION	64777
35LT	TSUNAMI BSU 30 LOW TEMP	64779
65	TSUNAMI BSU 60	58524
65R	TSUNAMI BSU 60 REJECTION	62366
65LT	TSUNAMI BSU 60 LOW TEMP	62528

CPN XXXXX  
 ISS XX

4

6

9

2.50

3.00

- 9 MARK MAC ID (ETHERNET ADDRESS). ENCODING FORMAT: CODE 0128.
- 8 SERIAL NUMBER BARCODE. ENCODING FORMAT: CODE 0128.
- 7 PRINT COUNTRY OF ORIGIN IN LOCATION SHOWN (eg MADE IN MALAYSIA)
- 4 MARK REVISION (ISSUE) OF PRODUCT E.G. ISS 1.
- 3 MARK DATE CODE (MONTH/YEAR) E.G. 03/01.

2. MATERIAL: WHITE POLYESTER IMPRINTABLE LABEL STOCK, .002 THK, ACRYLIC ADHESIVE, .001 THK. .001 THK CLEAR, MATTE, MYLAR LAMINATION. REMOVE EXTRA MATERIAL AROUND CUT LABELS.
1. LABEL MUST BE UL APPROVED AND COMPLIANT WITH UL 969, AND SUITABLE FOR OUTDOOR USE.

<b>Proxim</b>		UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES AND TOLERANCES ARE: 2 PLACE DECIMALS: ±0.015 3 PLACE DECIMALS: ±0.005 ANGULAR DIMENSIONS: ±1° HOLES UNDER 0.250 DIA: ±0.002
MATERIAL: SEE NOTE 2		
FINISH:		
SILKSCREEN:		
USED ON: POINT TO MULTIPONT   FILE NO.:		
SCALE: 4:1	ENGR BY: C. YU	CHKD BY:
DATE: 08-27-03	DRWN BY: L.NICOLI	APPVD BY:
<b>LABEL, PRODUCT ID, WAC</b>		
SIZE C	XXXXX	SHEET 1 OF 1