



SPORTON International Inc.

No.8, Lane 724, Bo-ai St., Jhubei City, Hsinchu County 302, Taiwan, R.O.C.
Ph: 886-3-656-9065 / FAX: 886-3-656-9085 / www.sporton.com.tw

FCC RADIO TEST REPORT

Applicant's company	Proxim Wireless Corporation
Applicant Address	1561 Buckeye Drive, Milpitas, CA 95035, USA
FCC ID	HZB-XB92WLE
Manufacturer's company	Proxim Wireless Corporation
Manufacturer Address	1561 Buckeye Drive, Milpitas, CA 95035, USA

Product Name	802.11 a/n PCIe Module
Brand Name	Proxim
Model No.	XB92HP
Test Rule Part(s)	47 CFR FCC Part 15 Subpart C § 15.247
Test Freq. Range	5725 ~ 5850MHz
Received Date	Apr. 29, 2013
Final Test Date	Aug. 23, 2013
Submission Type	Original Equipment

Statement

Test result included is only for the IEEE 802.11n and IEEE 802.11a (5725 ~ 5850MHz) of the product.

The test result in this report refers exclusively to the presented test model / sample.

Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.

The measurements and test results shown in this test report were made in accordance with the procedures and found in compliance with the limit given in **ANSI C63.10-2009**,

47 CFR FCC Part 15 Subpart C, KDB 558074 D01 v03r01 and KDB 662911 D01 v02.

The test equipment used to perform the test is calibrated and traceable to NML/ROC.



Table of Contents

1. CERTIFICATE OF COMPLIANCE	1
2. SUMMARY OF THE TEST RESULT	2
3. GENERAL INFORMATION	3
3.1. Product Details	3
3.2. Accessories	4
3.3. Table for Filed Antenna	5
3.4. Table for Carrier Frequencies	6
3.5. Table for Test Modes	6
3.6. Table for Testing Locations.....	7
3.7. Table for Supporting Units	7
3.8. Table for Parameters of Test Software Setting	8
3.9. EUT Operation during Test.....	9
3.10. Duty Cycle.....	10
3.11. Test Configurations.....	12
4. TEST RESULT	13
4.1. AC Power Line Conducted Emissions Measurement	13
4.2. Maximum Conducted Output Power Measurement.....	17
4.3. Power Spectral Density Measurement.....	24
4.4. 6dB Spectrum Bandwidth Measurement	38
4.5. Radiated Emissions Measurement.....	51
4.6. Emissions Measurement.....	82
4.7. Antenna Requirements	111
5. LIST OF MEASURING EQUIPMENTS	112
6. TEST LOCATION	114
7. MEASUREMENT UNCERTAINTY	115
APPENDIX A. TEST PHOTOS	A1 ~ A12
APPENDIX B. MAXIMUM PERMISSIBLE EXPOSURE	B1 ~ B3



History of This Test Report

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FR342910AA	Rev. 01	Initial issue of report	Sep. 02, 2013



1. CERTIFICATE OF COMPLIANCE

Product Name : 802.11 a/n PCIe Module
Brand Name : Proxim
Model No. : XB92HP
Applicant : Proxim Wireless Corporation
Test Rule Part(s) : 47 CFR FCC Part 15 Subpart C § 15.247

Sporton International as requested by the applicant to evaluate the EMC performance of the product sample received on Apr. 29, 2013 would like to declare that the tested sample has been evaluated and found to be in compliance with the tested rule parts. The data recorded as well as the test configuration specified is true and accurate for showing the sample's EMC nature.

A handwritten signature in blue ink that reads 'Sam Chen'.

Sam Chen

SPORTON INTERNATIONAL INC.

2. SUMMARY OF THE TEST RESULT

Applied Standard: 47 CFR FCC Part 15 Subpart C				
Part	Rule Section	Description of Test	Result	Under Limit
4.1	15.207	AC Power Line Conducted Emissions	Complies	14.33 dB
4.2	15.247(b)(3)	Maximum Conducted Output Power	Complies	4.11 dB
4.3	15.247(e)	Power Spectral Density	Complies	9.00 dB
4.4	15.247(a)(2)	6dB Spectrum Bandwidth	Complies	-
4.5	15.247(d)	Radiated Emissions	Complies	0.05 dB
4.6	15.247(d)	Fundamental Emissions	Complies	-
4.7	15.203	Antenna Requirements	Complies	-

3. GENERAL INFORMATION

3.1. Product Details

IEEE 802.11n

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From host system
Modulation	see the below table for IEEE 802.11n
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	see the below table for IEEE 802.11n
Frequency Range	5725 ~ 5850MHz
Channel Number	5 for 20MHz bandwidth ; 2 for 40MHz bandwidth
Channel Band Width (99%)	Mode 1 (Ant. 1): MCS0 (20MHz): 17.84 MHz ; MCS0 (40MHz): 36.32 MHz Mode 2 (Ant. 2): MCS0 (20MHz): 17.84 MHz ; MCS0 (40MHz): 36.48 MHz Mode 3 (Ant. 3): MCS0 (20MHz): 17.92 MHz ; MCS0 (40MHz): 36.80 MHz
Maximum Conducted Output Power	Mode 1 (Ant. 1): MCS0 (20MHz): 15.63 dBm ; MCS0 (40MHz): 14.93 dBm Mode 2 (Ant. 2): MCS0 (20MHz): 21.75 dBm ; MCS0 (40MHz): 22.18 dBm Mode 3 (Ant. 3): MCS0 (20MHz): 22.32 dBm ; MCS0 (40MHz): 23.89 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

802.11a

Items	Description
Product Type	WLAN (2TX, 2RX)
Radio Type	Intentional Transceiver
Power Type	From host system
Modulation	OFDM
Data Modulation	OFDM (BPSK / QPSK / 16QAM / 64QAM)
Data Rate (Mbps)	OFDM (6/9/12/18/24/36/48/54)
Frequency Range	5725 ~ 5850MHz
Channel Number	5
Channel Band Width (99%)	Mode 1 (Ant. 1): 16.64 MHz Mode 2 (Ant. 2): 16.56 MHz Mode 3 (Ant. 3): 16.72 MHz
Maximum Conducted Output Power	Mode 1 (Ant. 1): 15.56 dBm Mode 2 (Ant. 2): 20.89 dBm Mode 3 (Ant. 3): 22.31 dBm
Carrier Frequencies	Please refer to section 3.4
Antenna	Please refer to section 3.3

Antenna and Band width

Antenna	Two (TX)	
Band width Mode	20 MHz	40 MHz
IEEE 802.11a	V	X
IEEE 802.11n	V	V

IEEE 11n Spec.

Protocol	Number of Transmit Chains (NTX)	Data Rate / MCS
802.11n (HT20)	2	MCS 0-15
802.11n (HT40)	2	MCS 0-15
Note 1: IEEE Std. 802.11n modulation consists of HT20 and HT40 (HT: High Throughput). Then EUT support HT20 and HT40. Note 2: Modulation modes consist of below configuration: HT20/HT40: IEEE 802.11n		

3.2. Accessories

N/A

3.3. Table for Filed Antenna

Ant.	Brand	Model No.	Type	Connector	Gain (dBi)	Attenuator (dBi)	Cable Loss	True Gain (dBi)
1	MARS	MA-WA55-30	Panel	N Type	30	12	2	16
2	MARS	MA-WB55-20	Sector	N Type	20	10	2	8
3	MARS	MA-WO55-10NH	Omni	N Type	10	-	2	8
4	Grand-Tek	GTT-AC-05-001	Panel	MMCX type	16	-	-	16

Note: 1. Ant. 1: 12dB attenuator was added in front of antenna port due to simulate the real cable use.

2. Ant. 2: 10dB attenuator was added in front of antenna port due to simulate the real cable use.

Ant.	5150~5250 MHz (Band 1)	5725~5850 MHz (Band 4)
1	X	V(P to P) (P to M)
2	X	V(P to P) (P to M)
3	V	V(P to M)
4	X	V(P to P) (P to M)


Note: The EUT has total antennas amounted to four sets.

There are two modes of Ant. 1, Ant. 2 and Ant. 4, one is P to P, and the other is P to M, after evaluating, P to M has been evaluated to be the worst case, so it was selected to record in this test report.

Because Ant. 1 and Ant. 4 are the same type antennas, only the higher gain antenna "Ant. 1" was tested and recorded in the report.

For IEEE 802.11a/n mode (2TX/2RX)

Chain 1 and Chain 2 could transmit/receive simultaneously.



3.4. Table for Carrier Frequencies

There are two bandwidth systems.

For 20MHz bandwidth systems, use Channel 149, 153, 157, 161, 165.

For 40MHz bandwidth systems, use Channel 151, 159.

Frequency Band	Channel No.	Frequency	Channel No.	Frequency
5725~5850 MHz Band 4	149	5745 MHz	159	5795 MHz
	151	5755 MHz	161	5805 MHz
	153	5765 MHz	165	5825 MHz
	157	5785 MHz	-	-

3.5. Table for Test Modes

Preliminary tests were performed in different data rate to find the worst radiated emission. The data rate shown in the table below is the worst-case rate with respect to the specific test item. Investigation has been done on all the possible configurations for searching the worst cases. The following table is a list of the test modes shown in this test report.

Test Items	Mode	Data Rate	Channel	Chain
AC Power Line Conducted Emissions	CTX	-	-	-
Maximum Conducted Output Power	11n 20MHz	MCS0	149/157/165	1+2
	11n 40MHz	MCS0	151/159	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Power Spectral Density	11n 20MHz	MCS0	149/157/165	1, 2
	11n 40MHz	MCS0	151/159	1, 2
	11a/BPSK	6 Mbps	149/157/165	1, 2
6dB Spectrum Bandwidth	11n 20MHz	MCS0	149/157/165	1+2
	11n 40MHz	MCS0	151/159	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Radiated Emissions Below 1GHz	CTX	-	-	-
Radiated Emissions Above 1GHz	11n 20MHz	MCS0	149/157/165	1+2
	11n 40MHz	MCS0	151/159	1+2
	11a/BPSK	6 Mbps	149/157/165	1+2
Fundamental Emissions	11n 20MHz	MCS0	149/165	1+2
	11n 40MHz	MCS0	151/159	1+2
	11a/BPSK	6 Mbps	149/165	1+2

The following test modes were performed for all tests:

For AC Power Line Conducted Emissions and Radiated Emissions below 1GHz tests:

Mode. EUT + Ant. 1

For others tests:

Mode 1. EUT + Ant. 1

Mode 2. EUT + Ant. 2

Mode 3. EUT + Ant. 3

All test results were recorded in the report.

Note: The antennas are placed by cross-polarization during operating, therefore no array gain issue will be considered.

3.6. Table for Testing Locations

Test Site No.	Site Category	Location	FCC Reg. No.	IC File No.
03CH01-CB	SAC	Hsin Chu	262045	IC 4086D
CO01-CB	Conduction	Hsin Chu	262045	IC 4086D
TH01-CB	OVEN Room	Hsin Chu	-	-

Open Area Test Site (OATS); Semi Anechoic Chamber (SAC).

Please refer section 6 for Test Site Address.

3.7. Table for Supporting Units

For Test Site No: 03CH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6220	D2A62L1989V5
Fixture	Bplus Technology Co., Ltd.	PE3B	N/A
Power Supply	Gwinstek	GPC-6030D	N/A

For Test Site No: CO01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	E6430	QDS-BRCM1049LE
Fixture	Bplus Technology Co., Ltd.	PE3B	N/A
Power Supply	Gwinstek	GPC-6030D	N/A

For Test Site No: TH01-CB

Support Unit	Brand	Model	FCC ID
Notebook	DELL	M1330	E2KWM3945ABG
Fixture	Bplus Technology Co., Ltd.	PE3B	N/A
Power Supply	Gwinstek	GPC-6030D	N/A

3.8. Table for Parameters of Test Software Setting

During testing, Channel and Power Controlling Software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product.

Power Parameters of IEEE 802.11n MCS0 20MHz / Ant. 1 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	10	9	8

Power Parameters of IEEE 802.11n MCS0 40MHz / Ant. 1 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n	
Frequency	5755 MHz	5795 MHz
MCS0 40MHz	8.5	7.5

Power Parameters of IEEE 802.11a / Ant. 1 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	10	9	7.5

Power Parameters of IEEE 802.11n MCS0 20MHz / Ant. 2 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	15.5	15.5	16

Power Parameters of IEEE 802.11n MCS0 40MHz / Ant. 2 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n	
Frequency	5755 MHz	5795 MHz
MCS0 40MHz	14.5	15.5

Power Parameters of IEEE 802.11a / Ant. 2 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	14	14	15

Power Parameters of IEEE 802.11n MCS0 20MHz / Ant. 3 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n		
Frequency	5745 MHz	5785 MHz	5825 MHz
MCS0 20MHz	16.5	16.5	16.5

Power Parameters of IEEE 802.11n MCS0 40MHz / Ant. 3 / Chain 1 + Chain 2

Test Software Version	ART Rev 0.9 BUILD #27 ART_11n	
Frequency	5755 MHz	5795 MHz
MCS0 40MHz	17	17.5

Power Parameters of IEEE 802.11a / Ant. 3 / Chain 1 + Chain 2


Test Software Version	ART Rev 0.9 BUILD #27 ART_11n		
Frequency	5745 MHz	5785 MHz	5825 MHz
IEEE 802.11a	16	16.5	16.5

3.9. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.


3.10. Duty Cycle

IEEE 802.11n MCS0 20MHz / Chain 1 + Chain 2




Date: 23.MAY.2013 04:51:27

IEEE 802.11n MCS0 40MHz / Chain 1 + Chain 2



Date: 23.MAY.2013 04:53:14


IEEE 802.11a / Chain 1 + Chain 2



Date: 23.MAY.2013 04:52:04

3.11. Test Configurations

3.11.1. AC Power Line Conduction Emissions and Radiation Emissions Test Configuration



Item	Connection	Shielded	Length
1	AC Power cable	No	1.8m
2	Ant Cable	No	0.17m
3	Ant Cable	No	1.0m
4	Power supply cable	No	1.1m
5	AC Power cable	No	1.8m

4. TEST RESULT

4.1. AC Power Line Conducted Emissions Measurement

4.1.1. Limit

For this product which is designed to be connected to the AC power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed below limits table.

Frequency (MHz)	QP Limit (dBuV)	AV Limit (dBuV)
0.15~0.5	66~56	56~46
0.5~5	56	46
5~30	60	50

4.1.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the receiver.

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

4.1.3. Test Procedures

1. Configure the EUT according to ANSI C63.10. The EUT or host of EUT has to be placed 0.4 meter far from the conducting wall of the shielding room and at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT or host of EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connected to the other LISNs. The LISN should provide 50uH/50ohms coupling impedance.
4. The frequency range from 150 kHz to 30 MHz was searched.
5. Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. The measurement has to be done between each power line and ground at the power terminal.

4.1.4. Test Setup Layout



LEGEND:

- (1) Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- (2) I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- (3) EUT connected to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω . LISN can be placed on top of, or immediately beneath, reference ground plane.
 - (3.1) All other equipment powered from additional LISN(s).
 - (3.2) Multiple outlet strip can be used for multiple power cords of non-EUT equipment.
 - (3.3) LISN at least 80 cm from nearest part of EUT chassis.
- (4) Cables of hand-operated devices, such as keyboards, mice, etc., shall be placed as for normal use.
- (5) Non-EUT components of EUT system being tested.
- (6) Rear of EUT, including peripherals, shall all be aligned and flush with rear of tabletop.
- (7) Rear of tabletop shall be 40 cm removed from a vertical conducting plane that is bonded to the ground plane.

4.1.5. Test Deviation


There is no deviation with the original standard.

4.1.6. EUT Operation during Test

The EUT was placed on the test table and programmed in normal function.


4.1.7. Results of AC Power Line Conducted Emissions Measurement

Temperature	25°C	Humidity	49%
Test Engineer	Ryo Fan	Phase	Line
Configuration	CTX	Test Mode	EUT + Ant. 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1 av	0.17	38.43	-16.38	54.81	38.16	0.22	0.05	Average
2	0.17	49.48	-15.33	64.81	49.21	0.22	0.05	QP
3	0.23	33.86	-18.58	52.44	33.58	0.21	0.07	Average
4	0.23	43.71	-18.73	62.44	43.43	0.21	0.07	QP
5	0.29	26.65	-23.94	50.59	26.38	0.21	0.06	Average
6	0.29	36.30	-24.29	60.59	36.03	0.21	0.06	QP
7	1.96	26.62	-19.38	46.00	26.29	0.25	0.08	Average
8	1.96	32.49	-23.51	56.00	32.16	0.25	0.08	QP
9	4.08	20.10	-25.90	46.00	19.68	0.29	0.13	Average
10	4.08	28.27	-27.73	56.00	27.85	0.29	0.13	QP
11	13.55	19.93	-30.07	50.00	19.24	0.56	0.13	Average
12	13.55	29.97	-30.03	60.00	29.28	0.56	0.13	QP

Temperature	25°C	Humidity	49%
Test Engineer	Ryo Fan	Phase	Neutral
Configuration	CTX	Test Mode	EUT + Ant. 1



	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark	
	MHz	dBuV	dB	dBuV	dBuV	dB	dB		
1	av	0.17	38.67	-16.14	54.81	38.54	0.08	0.05	Average
2		0.17	50.48	-14.33	64.81	50.35	0.08	0.05	QP
3		0.23	33.62	-18.82	52.44	33.48	0.07	0.07	Average
4		0.23	44.15	-18.29	62.44	44.01	0.07	0.07	QP
5		0.29	28.33	-22.26	50.59	28.19	0.08	0.06	Average
6		0.29	38.71	-21.88	60.59	38.57	0.08	0.06	QP
7		1.90	28.96	-17.04	46.00	28.76	0.12	0.08	Average
8		1.90	32.54	-23.46	56.00	32.34	0.12	0.08	QP
9		4.03	20.86	-25.14	46.00	20.58	0.15	0.13	Average
10		4.03	29.93	-26.07	56.00	29.65	0.15	0.13	QP
11		13.55	20.46	-29.54	50.00	19.95	0.38	0.13	Average
12		13.55	29.29	-30.71	60.00	28.78	0.38	0.13	QP

Note:

Level = Read Level + LISN Factor + Cable Loss

4.2. Maximum Conducted Output Power Measurement

4.2.1. Limit

Systems operating in the 5725-5850 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi without any corresponding reduction in transmitter output power.

4.2.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the power meter.

Power Meter Parameter	Setting
Bandwidth	50MHz bandwidth is greater than the EUT emission bandwidth
Detector	Average

4.2.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 9.2.2 Measurement using a power meter (PM).
2. This procedure provides an alternative for determining the RMS output power using a broadband RF average power meter with a thermocouple detector.

4.2.4. Test Setup Layout



4.2.5. Test Deviation

There is no deviation with the original standard.

4.2.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.2.7. Test Result of Maximum Conducted Output Power

Temperature	23°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11n
Test Date	Aug. 22, 2013	Test Mode	Mode 1. EUT + Ant. 1

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
149	5745 MHz	12.41	12.82	15.63	20.00	Complies
157	5785 MHz	11.60	11.81	14.72	20.00	Complies
165	5825 MHz	10.71	10.65	13.69	20.00	Complies

Note: Antenna true gain = 16dBi > 6dBi, so power limit = $30 - (16 - 6) = 20$ dBm.

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
151	5755 MHz	11.64	12.18	14.93	20.00	Complies
159	5795 MHz	10.73	11.29	14.03	20.00	Complies

Note: Antenna true gain = 16dBi > 6dBi, so power limit = $30 - (16 - 6) = 20$ dBm.

Temperature	23°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11a
Test Date	Aug. 22, 2013	Test Mode	Mode 1. EUT + Ant. 1

Configuration IEEE 802.11a / Ant. 1 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
149	5745 MHz	12.37	12.72	15.56	20.00	Complies
157	5785 MHz	11.48	11.92	14.72	20.00	Complies
165	5825 MHz	10.23	9.72	12.99	20.00	Complies

Note: Antenna true gain = 16dBi > 6dBi, so power limit = $30 - (16 - 6) = 20\text{dBm}$.

Temperature	23°C	Humidity	63%
Test Engineer	David Tseng	Configurations	IEEE 802.11n
Test Date	Aug. 19, 2013	Test Mode	Mode 2. EUT + Ant. 2

Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
149	5745 MHz	17.63	18.84	21.29	28.00	Complies
157	5785 MHz	17.96	18.45	21.22	28.00	Complies
165	5825 MHz	18.80	18.67	21.75	28.00	Complies

Note: Antenna true gain =8dBi >6dBi, so power limit= 30 – (8 – 6) = 28dBm.

Configuration IEEE 802.11n MCS0 40MHz / Ant. 2 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
151	5755 MHz	17.81	18.74	21.31	28.00	Complies
159	5795 MHz	18.89	19.43	22.18	28.00	Complies

Note: Antenna true gain =8dBi >6dBi, so power limit= 30 – (8 – 6) = 28dBm.

Temperature	23°C	Humidity	63%
Test Engineer	David Tseng	Configurations	IEEE 802.11a
Test Date	Aug. 19, 2013	Test Mode	Mode 2. EUT + Ant. 2

Configuration IEEE 802.11a / Ant. 2 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
149	5745 MHz	16.31	16.98	19.67	28.00	Complies
157	5785 MHz	16.45	16.82	19.65	28.00	Complies
165	5825 MHz	17.89	17.86	20.89	28.00	Complies

Note: Antenna true gain = 8dBi > 6dBi, so power limit = $30 - (8 - 6) = 28$ dBm.

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Date	Aug. 20, 2013	Test Mode	Mode 3. EUT + Ant. 3

Configuration IEEE 802.11n MCS0 20MHz / Ant. 3 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
149	5745 MHz	18.52	19.75	22.19	28.00	Complies
157	5785 MHz	19.02	19.59	22.32	28.00	Complies
165	5825 MHz	19.32	19.09	22.22	28.00	Complies

Note: Antenna true gain =8dBi >6dBi, so power limit= 30 – (8 – 6) = 28dBm.

Configuration IEEE 802.11n MCS0 40MHz / Ant. 3 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
151	5755 MHz	19.90	20.68	23.32	28.00	Complies
159	5795 MHz	20.40	21.32	23.89	28.00	Complies

Note: Antenna true gain =8dBi >6dBi, so power limit= 30 – (8 – 6) = 28dBm.

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a
Test Date	Aug. 20, 2013	Test Mode	Mode 3. EUT + Ant. 3

Configuration IEEE 802.11a / Ant. 3 / Chain 1 + Chain 2

Channel	Frequency	Conducted Power (dBm)			Max. Limit (dBm)	Result
		Chain 1	Chain 2	Total		
149	5745 MHz	18.03	19.40	21.78	28.00	Complies
157	5785 MHz	19.01	19.57	22.31	28.00	Complies
165	5825 MHz	19.38	18.99	22.20	28.00	Complies

Note: Antenna true gain = 8dBi > 6dBi, so power limit = $30 - (8 - 6) = 28$ dBm.

4.3. Power Spectral Density Measurement

4.3.1. Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

4.3.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	Set the span to 1.5 times the DTS channel bandwidth.
RBW	$3 \text{ kHz} \leq \text{RBW} \leq 100\text{kHz}$
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto couple

4.3.3. Test Procedures

1. Test procedures refer KDB 558074 D01 v03r01 section 10.2 Method PKPSD (peak PSD) & KDB 662911 D01 v02 section In-Band Power Spectral Density (PSD) Measurements option (2) Measure and add $10 \log(\text{NANT})$ dB.
2. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
3. Ensure that the number of measurement points in the sweep $\geq 2 \times \text{span}/\text{RBW}$ (use of a greater number of measurement points than this minimum requirement is recommended).
4. Use the peak marker function to determine the maximum level in any 3 kHz band segment within the fundamental EBW.
5. The resulting PSD level must be ≤ 8 dBm.

4.3.4. Test Setup Layout



4.3.5. Test Deviation

There is no deviation with the original standard.

4.3.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.3.7. Test Result of Power Spectral Density

Temperature	23°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11n
Test Mode	Mode 1. EUT + Ant. 1		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
149	5745 MHz	-15.33	-15.16	4.99	Complies
157	5785 MHz	-16.13	-15.98	4.99	Complies
165	5825 MHz	-16.27	-16.64	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2)))=4.99dBm/3kHz

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
151	5755 MHz	-18.30	-17.58	4.99	Complies
159	5795 MHz	-19.02	-18.36	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2)))=4.99dBm/3kHz

Temperature	23°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11a
Test Mode	Mode 1. EUT + Ant. 1		

Configuration IEEE 802.11a / Ant. 1 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
149	5745 MHz	-13.86	-13.79	4.99	Complies
157	5785 MHz	-15.41	-15.09	4.99	Complies
165	5825 MHz	-15.31	-16.08	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Temperature	23°C	Humidity	63%
Test Engineer	David Tseng	Configurations	IEEE 802.11n
Test Mode	Mode 2. EUT + Ant. 2		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
149	5745 MHz	-6.53	-6.94	4.99	Complies
157	5785 MHz	-5.33	-5.27	4.99	Complies
165	5825 MHz	-4.05	-4.01	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Configuration IEEE 802.11n MCS0 40MHz / Ant. 2 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
151	5755 MHz	-10.34	-9.58	4.99	Complies
159	5795 MHz	-8.61	-8.93	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Temperature	23°C	Humidity	63%
Test Engineer	David Tseng	Configurations	IEEE 802.11a
Test Mode	Mode 2. EUT + Ant. 2		

Configuration IEEE 802.11a / Ant. 2 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
149	5745 MHz	-7.27	-8.72	4.99	Complies
157	5785 MHz	-7.80	-7.74	4.99	Complies
165	5825 MHz	-6.77	-7.33	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Mode	Mode 3. EUT + Ant. 3		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 3 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
149	5745 MHz	-6.73	-6.43	4.99	Complies
157	5785 MHz	-6.40	-6.01	4.99	Complies
165	5825 MHz	-6.14	-6.77	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Configuration IEEE 802.11n MCS0 40MHz / Ant. 3 / Chain 1, Chain 2

Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
151	5755 MHz	-7.64	-7.37	4.99	Complies
159	5795 MHz	-7.40	-6.92	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a
Test Mode	Mode 3. EUT + Ant. 3		

Configuration IEEE 802.11a / Ant. 3 / Chain 1, Chain 2


Channel	Frequency	Power Density (dBm/3kHz)		Single Port Limit (dBm/3kHz)	Result
		Chain 1	Chain 2		
149	5745 MHz	-6.59	-6.77	4.99	Complies
157	5785 MHz	-5.89	-6.09	4.99	Complies
165	5825 MHz	-4.18	-5.56	4.99	Complies

Note: PSD Limit = (8dBm/3kHz - (10log(2))) = 4.99dBm/3kHz

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / 5745 MHz / Ant. 1 / Chain 2




Date: 23.AUG.2013 01:31:36

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / 5755 MHz / Ant. 1 / Chain 2




Date: 23.AUG.2013 01:39:28

Power Density Plot on Configuration IEEE 802.11a / 5745 MHz / Ant. 1 / Chain 2




Date: 23.AUG.2013 01:20:09

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / 5825 MHz / Ant. 2 / Chain 2




Date: 20.AUG.2013 16:44:08

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / 5795 MHz / Ant. 2 / Chain 1




Date: 20.AUG.2013 16:55:29

Power Density Plot on Configuration IEEE 802.11a / 5825 MHz / Ant. 2 / Chain 1




Date: 20.AUG.2013 16:41:28

Power Density Plot on Configuration IEEE 802.11n MCS0 20MHz / 5785 MHz / Ant. 3 / Chain 2




Date: 20.AUG.2013 14:09:49

Power Density Plot on Configuration IEEE 802.11n MCS0 40MHz / 5795 MHz / Ant. 3 / Chain 2



Date: 20.AUG.2013 14:13:01

Power Density Plot on Configuration IEEE 802.11a / 5825 MHz / Ant. 3 / Chain 1



Date: 20.AUG.2013 13:51:26

4.4. 6dB Spectrum Bandwidth Measurement

4.4.1. Limit

For digital modulation systems, the minimum 6dB bandwidth shall be at least 500 kHz.

4.4.2. Measuring Instruments and Setting


Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> 6dB Bandwidth
RBW	100kHz
VBW	$\geq 3 \times \text{RBW}$
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

4.4.3. Test Procedures

1. The transmitter output (antenna port) was connected to the spectrum analyzer in peak hold mode.
2. Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 8.0 DTS 6-dB signal bandwidth option 1.
3. Multiple antenna system was performed in accordance with KDB 662911 D01 v02 Emissions Testing of Transmitters with Multiple Outputs in the Same Band.
4. Measured the spectrum width with power higher than 6dB below carrier.

4.4.4. Test Setup Layout



4.4.5. Test Deviation

There is no deviation with the original standard.

4.4.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.4.7. Test Result of 6dB Spectrum Bandwidth

Temperature	23°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11n
Test Mode	Mode 1. EUT + Ant. 1		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 1 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.68	17.84	500	Complies
157	5785 MHz	17.68	17.84	500	Complies
165	5825 MHz	17.76	17.84	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 1 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.48	36.32	500	Complies
159	5795 MHz	36.16	36.32	500	Complies

Temperature	23°C	Humidity	63%
Test Engineer	Serway Li	Configurations	IEEE 802.11a
Test Mode	Mode 1. EUT + Ant. 1		

Configuration IEEE 802.11a / Ant. 1 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.40	16.56	500	Complies
157	5785 MHz	16.40	16.64	500	Complies
165	5825 MHz	16.40	16.56	500	Complies

Temperature	23°C	Humidity	63%
Test Engineer	David Tseng	Configurations	IEEE 802.11n
Test Mode	Mode 2. EUT + Ant. 2		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 2 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.52	17.84	500	Complies
157	5785 MHz	17.60	17.84	500	Complies
165	5825 MHz	17.60	17.84	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 2 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	36.32	36.48	500	Complies
159	5795 MHz	35.84	36.48	500	Complies

Temperature	23°C	Humidity	63%
Test Engineer	David Tseng	Configurations	IEEE 802.11a
Test Mode	Mode 2. EUT + Ant. 2		

Configuration IEEE 802.11a / Ant. 2 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.40	16.56	500	Complies
157	5785 MHz	16.32	16.56	500	Complies
165	5825 MHz	16.32	16.56	500	Complies

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11n
Test Mode	Mode 3. EUT + Ant. 3		

Configuration IEEE 802.11n MCS0 20MHz / Ant. 3 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	17.60	17.92	500	Complies
157	5785 MHz	16.96	17.84	500	Complies
165	5825 MHz	17.52	17.92	500	Complies

Configuration IEEE 802.11n MCS0 40MHz / Ant. 3 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
151	5755 MHz	35.68	36.64	500	Complies
159	5795 MHz	33.12	36.80	500	Complies

Temperature	23°C	Humidity	63%
Test Engineer	Benson Peng	Configurations	IEEE 802.11a
Test Mode	Mode 3. EUT + Ant. 3		


Configuration IEEE 802.11a / Ant. 1 / Chain 1 + Chain 2

Channel	Frequency	6dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Min. Limit (kHz)	Test Result
149	5745 MHz	16.40	16.56	500	Complies
157	5785 MHz	16.40	16.64	500	Complies
165	5825 MHz	16.40	16.72	500	Complies

Note: All the test values were listed in the report.


For plots, only the channel with worse result was shown.

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / 5745 MHz / Ant. 1 / Chain 1 + Chain 2




Date: 23.AUG.2013 04:10:32

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / 5795 MHz / Ant. 1 / Chain 1 + Chain 2




Date: 23.AUG.2013 04:16:10

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5785 MHz / Ant. 1 / Chain 1 + Chain 2




Date: 23.AUG.2013 04:02:13

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / 5745 MHz / Ant. 2 / Chain 1 + Chain 2




Date: 20.AUG.2013 17:02:20

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / 5795 MHz / Ant. 2 / Chain 1 + Chain 2




Date: 20.AUG.2013 16:58:38

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5785 MHz / Ant. 2 / Chain 1 + Chain 2




Date: 20.AUG.2013 17:06:18

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 20MHz / 5785 MHz / Ant. 3 / Chain 1 + Chain 2




Date: 20.AUG.2013 13:45:46

6 dB Bandwidth Plot on Configuration IEEE 802.11n MCS0 40MHz / 5795 MHz / Ant. 3 / Chain 1 + Chain 2



Date: 20.AUG.2013 13:42:16

6 dB Bandwidth Plot on Configuration IEEE 802.11a / 5785 MHz / Ant. 3 / Chain 1 + Chain 2



Date: 20.AUG.2013 13:43:44

4.5. Radiated Emissions Measurement

4.5.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micровolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.5.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100kHz / 300kHz for peak


Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RBW 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RBW 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RBW 120kHz for QP

4.5.3. Test Procedures


1. Configure the EUT according to ANSI C63.10. The EUT was placed on the top of the turntable 0.8 meter above ground. The phase center of the receiving antenna mounted on the top of a height-variable antenna tower was placed 3 meters far away from the turntable.
2. Power on the EUT and all the supporting units. The turntable was rotated by 360 degrees to determine the position of the highest radiation.
3. The height of the broadband receiving antenna was varied between one meter and four meters above ground to find the maximum emissions field strength of both horizontal and vertical polarization.
4. For each suspected emissions, the antenna tower was scan (from 1 M to 4 M) and then the turntable was rotated (from 0 degree to 360 degrees) to find the maximum reading.
5. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function with specified bandwidth under Maximum Hold Mode.
6. For emissions above 1GHz, use 1MHz VBW and 3MHz RBW for peak reading. Then 1MHz RBW and 10Hz VBW for average reading in spectrum analyzer.
7. When the radiated emissions limits are expressed in terms of the average value of the emissions, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 seconds. As an alternative (provided the transmitter operates for longer than 0.1 seconds) or in cases where the pulse train exceeds 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.
8. If the emissions level of the EUT in peak mode was 3 dB lower than the average limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method for below 1GHz.
9. For testing above 1GHz, the emissions level of the EUT in peak mode was lower than average limit (that means the emissions level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.
10. In case the emission is lower than 30MHz, loop antenna has to be used for measurement and the recorded data should be QP measured by receiver. High – Low scan is not required in this case.

4.5.4. Test Setup Layout


For Radiated Emissions: 9kHz ~30MHz



For Radiated Emissions: 30MHz~1GHz



For Radiated Emissions: Above 1GHz



4.5.5. Test Deviation

There is no deviation with the original standard.

4.5.6. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

4.5.7. Results of Radiated Emissions (9kHz~30MHz)

Temperature	25°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	CTX
Test Date	May 22, 2013		

Freq. (MHz)	Level (dBuV)	Over Limit (dB)	Limit Line (dBuV)	Remark
-	-	-	-	See Note

Note:

The amplitude of spurious emissions that are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor = $40 \log(\text{specific distance} / \text{test distance})$ (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

4.5.8. Results of Radiated Emissions (30MHz~1GHz)


Temperature	25°C	Humidity	56%
Test Engineer	Jim Huang	Configurations	CTX
Test Mode	EUT + Ant. 1		

Horizontal



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		deg	cm	
1 !	232.73	41.70	46.00	-4.30	54.88	2.29	27.01	11.54	Peak	0	100	HORIZONTAL
2 !	299.66	42.48	46.00	-3.52	53.00	2.51	26.83	13.80	Peak	0	100	HORIZONTAL
3 !	365.62	37.90	46.00	-8.10	46.55	2.86	27.19	15.68	Peak	0	100	HORIZONTAL
4 !	498.51	38.67	46.00	-7.33	45.45	3.38	27.93	17.77	Peak	0	100	HORIZONTAL
5 !	698.33	42.45	46.00	-3.55	45.42	4.15	27.10	19.98	Peak	0	100	HORIZONTAL
6 p	897.18	42.88	46.00	-3.12	43.65	4.58	26.83	21.48	Peak	0	100	HORIZONTAL

Vertical



	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	232.73	35.07	46.00	-10.93	48.25	2.29	27.01	11.54	Peak	0	400	VERTICAL
2	298.69	39.53	46.00	-6.47	50.05	2.51	26.83	13.80	Peak	0	400	VERTICAL
3	432.55	35.08	46.00	-10.92	42.81	3.15	27.71	16.83	Peak	0	400	VERTICAL
4	498.51	37.86	46.00	-8.14	44.64	3.38	27.93	17.77	Peak	0	400	VERTICAL
5	698.33	41.15	46.00	-4.85	44.12	4.15	27.10	19.98	Peak	0	400	VERTICAL
6	896.21	38.86	46.00	-7.14	39.64	4.58	26.84	21.48	Peak	0	400	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.5.9. Results for Radiated Emissions (1GHz~10th Harmonic)

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 149 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4839.94	46.52	54.00	-7.48	45.14	3.32	33.09	35.03	Average	113	168	HORIZONTAL
2	4840.17	60.61	74.00	-13.39	59.23	3.32	33.09	35.03	Peak	113	168	HORIZONTAL
3	11485.45	61.26	74.00	-12.74	52.65	5.11	38.78	35.28	Peak	123	58	HORIZONTAL
4	11486.09	44.57	54.00	-9.43	35.96	5.11	38.78	35.28	Average	123	58	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4879.81	53.93	54.00	-0.07	52.47	3.33	33.16	35.03	Average	114	182	VERTICAL
2	4879.81	64.52	74.00	-9.48	63.06	3.33	33.16	35.03	Peak	114	182	VERTICAL
3	11489.68	48.09	54.00	-5.91	39.48	5.11	38.78	35.28	Average	115	284	VERTICAL
4	11490.29	63.74	74.00	-10.26	55.13	5.11	38.78	35.28	Peak	115	284	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 157 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4919.86	62.27	74.00	-11.73	60.70	3.35	33.23	35.01	Peak	111	168	HORIZONTAL
2	4919.98	49.04	54.00	-4.96	47.47	3.35	33.23	35.01	Average	111	168	HORIZONTAL
3	11570.38	56.79	74.00	-17.21	48.12	5.14	38.83	35.30	Peak	106	45	HORIZONTAL
4	11572.76	41.95	54.00	-12.05	33.28	5.14	38.83	35.30	Average	106	45	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4879.98	53.93	54.00	-0.07	52.47	3.33	33.16	35.03	Average	116	183	VERTICAL
2	4880.06	67.88	74.00	-6.12	66.42	3.33	33.16	35.03	Peak	116	183	VERTICAL
3	11569.81	45.90	54.00	-8.10	37.23	5.14	38.83	35.30	Average	115	284	VERTICAL
4	11570.38	60.93	74.00	-13.07	52.26	5.14	38.83	35.30	Peak	115	284	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 20MHz CH 165 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoL/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4839.74	59.01	74.00	-14.99	57.63	3.32	33.09	35.03	Peak	105	170	HORIZONTAL
2	4839.97	45.76	54.00	-8.24	44.38	3.32	33.09	35.03	Average	105	170	HORIZONTAL
3	11646.99	55.27	74.00	-18.73	46.55	5.16	38.86	35.30	Peak	100	280	HORIZONTAL
4	11648.37	40.38	54.00	-13.62	31.66	5.16	38.86	35.30	Average	100	280	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoL/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4878.32	68.24	74.00	-5.76	66.78	3.33	33.16	35.03	Peak	117	181	VERTICAL
2	4879.92	53.85	54.00	-0.15	52.39	3.33	33.16	35.03	Average	117	181	VERTICAL
3	11647.05	59.25	74.00	-14.75	50.53	5.16	38.86	35.30	Peak	111	295	VERTICAL
4	11648.01	43.74	54.00	-10.26	35.02	5.16	38.86	35.30	Average	111	295	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 151 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4800.23	45.18	54.00	-8.82	43.94	3.29	32.99	35.04	Average	100	168 HORIZONTAL
2	4800.43	59.80	74.00	-14.20	58.56	3.29	32.99	35.04	Peak	100	168 HORIZONTAL
3	11509.94	42.33	54.00	-11.67	33.70	5.12	38.79	35.28	Average	118	45 HORIZONTAL
4	11510.77	57.42	74.00	-16.58	48.79	5.12	38.79	35.28	Peak	118	45 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4800.00	53.94	54.00	-0.06	52.70	3.29	32.99	35.04	Average	120	185 VERTICAL
2	4800.32	65.75	74.00	-8.25	64.51	3.29	32.99	35.04	Peak	120	185 VERTICAL
3	11508.21	58.43	74.00	-15.57	49.80	5.12	38.79	35.28	Peak	163	283 VERTICAL
4	11509.71	44.22	54.00	-9.78	35.59	5.12	38.79	35.28	Average	163	283 VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11n MCS0 40MHz CH 159 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4839.96	47.24	54.00	-6.76	45.86	3.32	33.09	35.03	Average	100	170 HORIZONTAL
2	4840.45	60.88	74.00	-13.12	59.50	3.32	33.09	35.03	Peak	100	170 HORIZONTAL
3	11589.90	39.92	54.00	-14.08	31.25	5.14	38.83	35.30	Average	119	46 HORIZONTAL
4	11590.42	55.47	74.00	-18.53	46.80	5.14	38.83	35.30	Peak	119	46 HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg	
1	4839.54	66.97	74.00	-7.03	65.59	3.32	33.09	35.03	Peak	114	185 VERTICAL
2	4839.99	53.83	54.00	-0.17	52.45	3.32	33.09	35.03	Average	114	185 VERTICAL
3	11589.62	42.52	54.00	-11.48	33.85	5.14	38.83	35.30	Average	100	293 VERTICAL
4	11590.74	56.54	74.00	-17.46	47.87	5.14	38.83	35.30	Peak	100	293 VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11a CH 149 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4839.99	46.84	54.00	-7.16	45.46	3.32	33.09	35.03	Average	108	170	HORIZONTAL
2	4840.12	60.83	74.00	-13.17	59.45	3.32	33.09	35.03	Peak	108	170	HORIZONTAL
3	11486.15	61.61	74.00	-12.39	53.00	5.11	38.78	35.28	Peak	112	45	HORIZONTAL
4	11489.94	46.66	54.00	-7.34	38.05	5.11	38.78	35.28	Average	112	45	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor		cm	deg	
1	4879.72	67.01	74.00	-6.99	65.55	3.33	33.16	35.03	Peak	116	182	VERTICAL
2	4879.98	53.86	54.00	-0.14	52.40	3.33	33.16	35.03	Average	116	182	VERTICAL
3	11489.42	61.74	74.00	-12.26	53.13	5.11	38.78	35.28	Peak	108	283	VERTICAL
4	11489.74	47.97	54.00	-6.03	39.36	5.11	38.78	35.28	Average	108	283	VERTICAL



Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11a CH 157 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4839.79	61.24	74.00	-12.76	59.86	3.32	33.09	35.03	Peak	114	170	HORIZONTAL
2	4839.99	47.89	54.00	-6.11	46.51	3.32	33.09	35.03	Average	114	170	HORIZONTAL
3	11569.90	42.54	54.00	-11.46	33.87	5.14	38.83	35.30	Average	115	45	HORIZONTAL
4	11570.51	56.87	74.00	-17.13	48.20	5.14	38.83	35.30	Peak	115	45	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Antenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4839.89	66.47	74.00	-7.53	65.09	3.32	33.09	35.03	Peak	112	183	VERTICAL
2	4839.97	53.95	54.00	-0.05	52.57	3.32	33.09	35.03	Average	112	183	VERTICAL
3	11569.04	59.66	74.00	-14.34	51.00	5.13	38.83	35.30	Peak	117	283	VERTICAL
4	11569.65	45.91	54.00	-8.09	37.25	5.13	38.83	35.30	Average	117	283	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Kenneth Huang	Configurations	IEEE 802.11a CH 165 / Chain 1 + Chain 2
Test Date	Aug. 16, 2013	Test Mode	Mode 1. EUT + Ant. 1

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4839.34	60.16	74.00	-13.84	58.78	3.32	33.09	35.03	Peak	111	171	HORIZONTAL
2	4839.93	47.07	54.00	-6.93	45.69	3.32	33.09	35.03	Average	111	171	HORIZONTAL
3	11649.65	39.13	54.00	-14.87	30.41	5.16	38.86	35.30	Average	100	47	HORIZONTAL
4	11649.81	53.45	74.00	-20.55	44.73	5.16	38.86	35.30	Peak	100	47	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	PoI/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	4879.96	53.92	54.00	-0.08	52.46	3.33	33.16	35.03	Average	115	183	VERTICAL
2	4879.96	69.06	74.00	-4.94	67.60	3.33	33.16	35.03	Peak	115	183	VERTICAL
3	11648.33	56.82	74.00	-17.18	48.10	5.16	38.86	35.30	Peak	117	296	VERTICAL
4	11649.04	42.67	54.00	-11.33	33.95	5.16	38.86	35.30	Average	117	296	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25°C	Humidity	56%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 20MHz CH 149 / Chain 1 + Chain 2
Test Date	Jul. 25, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11486.90	52.99	54.00	-1.01	39.33	9.24	39.50	35.08	Average	129	343	HORIZONTAL
2	11487.30	68.10	74.00	-5.90	54.44	9.24	39.50	35.08	Peak	129	343	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11488.80	53.57	54.00	-0.43	39.91	9.24	39.50	35.08	Average	129	321	VERTICAL
2	11490.50	67.66	74.00	-6.34	54.00	9.24	39.50	35.08	Peak	129	321	VERTICAL



Temperature	25°C	Humidity	56%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 20MHz CH 157 / Chain 1 + Chain 2
Test Date	Jul. 25, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11573.00	50.34	54.00	-3.66	36.69	9.26	39.47	35.08	Average	153	208	HORIZONTAL
2	11575.10	63.32	74.00	-10.68	49.67	9.26	39.47	35.08	Peak	153	208	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11569.50	53.41	54.00	-0.59	39.77	9.26	39.47	35.09	Average	133	193	VERTICAL
2	11569.50	67.28	74.00	-6.72	53.64	9.26	39.47	35.09	Peak	133	193	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 20MHz CH 165 / Chain 1 + Chain 2
Test Date	Jul. 25, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11649.50	63.49	74.00	-10.51	49.84	9.28	39.44	35.07	Peak	101	172	HORIZONTAL
2	11651.20	50.76	54.00	-3.24	37.11	9.28	39.44	35.07	Average	101	172	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11649.00	68.06	74.00	-5.94	54.41	9.28	39.44	35.07	Peak	125	192	VERTICAL
2	11649.30	53.66	54.00	-0.34	40.01	9.28	39.44	35.07	Average	125	192	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 40MHz CH 151 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11511.10	59.21	74.00	-14.79	48.78	6.75	34.82	38.50	Peak	175	146	HORIZONTAL
2	11512.50	47.16	54.00	-6.84	36.73	6.75	34.82	38.50	Average	175	146	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11506.50	66.10	74.00	-7.90	55.67	6.75	34.82	38.50	Peak	293	115	VERTICAL
2	11509.00	51.69	54.00	-2.31	41.26	6.75	34.82	38.50	Average	293	115	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Nick Peng	Configurations	IEEE 802.11n MCS0 40MHz CH 159 / Chain 1 + Chain 2
Test Date	Jul. 25, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	
1	11588.80	48.11	54.00	-5.89	34.45	9.27	39.47	35.08	Average	127	171	HORIZONTAL
2	11589.00	62.21	74.00	-11.79	48.55	9.27	39.47	35.08	Peak	127	171	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp		A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	Loss	Factor	Factor	Remark	cm	deg	
1	11588.70	53.70	54.00	-0.30	40.04	9.27	39.47	35.08	Average	126	329	VERTICAL
2	11589.50	67.71	74.00	-6.29	54.05	9.27	39.47	35.08	Peak	126	329	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Nick Peng	Configurations	IEEE 802.11a CH 149 / Chain 1 + Chain 2
Test Date	Jul. 25, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11489.30	59.67	74.00	-14.33	46.01	9.24	39.50	35.08	Peak	100	191	HORIZONTAL
2	11489.50	46.94	54.00	-7.06	33.28	9.24	39.50	35.08	Average	100	191	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11489.60	53.45	54.00	-0.55	39.79	9.24	39.50	35.08	Average	133	196	VERTICAL
2	11490.20	67.65	74.00	-6.35	53.99	9.24	39.50	35.08	Peak	133	196	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Nick Peng	Configurations	IEEE 802.11a CH 157 / Chain 1 + Chain 2
Test Date	Jul. 25, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11568.70	47.28	54.00	-6.72	33.64	9.26	39.47	35.09	Average	133	168	HORIZONTAL
2	11569.10	60.71	74.00	-13.29	47.07	9.26	39.47	35.09	Peak	133	168	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	CableAntenna Loss	Antenna Factor	Preamp Factor	Remark	A/Pos	T/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB		cm	deg	
1	11569.50	53.38	54.00	-0.62	39.74	9.26	39.47	35.09	Average	133	195	VERTICAL
2	11570.10	67.42	74.00	-6.58	53.78	9.26	39.47	35.09	Peak	133	195	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Nick Peng	Configurations	IEEE 802.11a CH 165 / Chain 1 + Chain 2
Test Date	Jul. 25, 2013	Test Mode	Mode 2. EUT + Ant. 2

Horizontal

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11649.00	48.14	54.00	-5.86	34.49	9.28	39.44	35.07	Average	113	172	HORIZONTAL
2	11649.30	62.45	74.00	-11.55	48.80	9.28	39.44	35.07	Peak	113	172	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	CableAntenna	Preamp	Remark	A/Pos	T/Pos	Pol/Phase	
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB/m	dB	cm	deg		
1	11648.20	66.30	74.00	-7.70	52.65	9.28	39.44	35.07	Peak	125	330	VERTICAL
2	11649.00	53.32	54.00	-0.68	39.67	9.28	39.44	35.07	Average	125	330	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 20MHz CH 149 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11490.60	48.40	54.00	-5.60	37.98	6.74	34.82	38.50	Average	43	168	HORIZONTAL
2	11492.20	62.02	74.00	-11.98	51.60	6.74	34.82	38.50	Peak	43	168	HORIZONTAL

Vertical

	Freq	Level	Limit	Over	Read	Cable	Preamp	Antenna	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11488.30	68.17	74.00	-5.83	57.75	6.74	34.82	38.50	Peak	291	132	VERTICAL
2	11488.50	53.19	54.00	-0.81	42.77	6.74	34.82	38.50	Average	291	132	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 20MHz CH 157 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11568.90	49.52	54.00	-4.48	39.09	6.77	34.84	38.50	Average	40	140	HORIZONTAL
2	11569.20	62.27	74.00	-11.73	51.84	6.77	34.84	38.50	Peak	40	140	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11567.10	53.69	54.00	-0.31	43.26	6.77	34.84	38.50	Average	288	126	VERTICAL
2	11568.90	66.99	74.00	-7.01	56.56	6.77	34.84	38.50	Peak	288	126	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 20MHz CH 165 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11649.40	48.76	54.00	-5.24	38.33	6.80	34.87	38.50	Average	168	173	HORIZONTAL
2	11650.70	61.15	74.00	-12.85	50.72	6.80	34.87	38.50	Peak	168	173	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11649.20	53.06	54.00	-0.94	42.63	6.80	34.87	38.50	Average	292	120	VERTICAL
2	11654.20	66.10	74.00	-7.90	55.67	6.80	34.87	38.50	Peak	292	120	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 40MHz CH 151 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11510.50	50.89	54.00	-3.11	40.46	6.75	34.82	38.50	Average	167	140	HORIZONTAL
2	11511.40	63.27	74.00	-10.73	52.84	6.75	34.82	38.50	Peak	167	140	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11508.50	52.63	54.00	-1.37	42.20	6.75	34.82	38.50	Average	291	132	VERTICAL
2	11509.60	67.32	74.00	-6.68	56.89	6.75	34.82	38.50	Peak	291	132	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11n MCS0 40MHz CH 159 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11589.60	47.85	54.00	-6.15	37.42	6.78	34.85	38.50	Average	169	154	HORIZONTAL
2	11592.70	59.82	74.00	-14.18	49.39	6.78	34.85	38.50	Peak	169	154	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11588.90	65.67	74.00	-8.33	55.24	6.78	34.85	38.50	Peak	288	108	VERTICAL
2	11588.90	53.23	54.00	-0.77	42.80	6.78	34.85	38.50	Average	288	108	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 149 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11490.20	47.33	54.00	-6.67	36.91	6.74	34.82	38.50	Average	45	167	HORIZONTAL
2	11490.30	61.82	74.00	-12.18	51.40	6.74	34.82	38.50	Peak	45	167	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11487.90	67.20	74.00	-6.80	56.78	6.74	34.82	38.50	Peak	292	128	VERTICAL
2	11488.70	53.33	54.00	-0.67	42.91	6.74	34.82	38.50	Average	292	128	VERTICAL

Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 157 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11569.60	48.21	54.00	-5.79	37.78	6.77	34.84	38.50	Average	41	140	HORIZONTAL
2	11570.60	63.37	74.00	-10.63	52.95	6.77	34.85	38.50	Peak	41	140	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11565.00	67.10	74.00	-6.90	56.67	6.77	34.84	38.50	Peak	290	122	VERTICAL
2	11568.80	53.18	54.00	-0.82	42.75	6.77	34.84	38.50	Average	290	122	VERTICAL



Temperature	25°C	Humidity	56%
Test Engineer	Serway Li	Configurations	IEEE 802.11a CH 165 / Chain 1 + Chain 2
Test Date	Aug. 02, 2013	Test Mode	Mode 3. EUT + Ant. 3

Horizontal

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11647.70	60.10	74.00	-13.90	49.67	6.80	34.87	38.50	Peak	138	136	HORIZONTAL
2	11652.30	48.95	54.00	-5.05	38.52	6.80	34.87	38.50	Average	138	136	HORIZONTAL

Vertical

	Freq	Level	Limit Line	Over Limit	Read Level	Cable Loss	Preamp Factor	Antenna Factor	Remark	T/Pos	A/Pos	Pol/Phase
	MHz	dBuV/m	dBuV/m	dB	dBuV	dB	dB	dB/m		deg	cm	
1	11650.30	67.76	74.00	-6.24	57.33	6.80	34.87	38.50	Peak	291	129	VERTICAL
2	11651.40	53.05	54.00	-0.95	42.62	6.80	34.87	38.50	Average	291	129	VERTICAL

Note:

The amplitude of spurious emissions that are attenuated by more than 20dB below the permissible value has no need to be reported.

Emission level (dBuV/m) = 20 log Emission level (uV/m).

Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level.

4.6. Emissions Measurement

4.6.1. Limit

30dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

4.6.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of the spectrum analyzer.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	100 MHz
RBW / VBW (Emission in restricted band)	1MHz / 3MHz for Peak, 1MHz / 10Hz for Average
RBW / VBW (Emission in non-restricted band)	100 kHz / 300 kHz for Peak

4.6.3. Test Procedures

- Test was performed in accordance with KDB 558074 D01 v03r01 for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under §15.247 section 10.1 Unwanted Emissions into Non-Restricted Frequency Bands Measurement Procedure
- The radiated emission test is performed on each TX port of operating mode without summing or adding 10log (N) since the limit is relative emission limit.
Only worst data of each operating mode is presented.

4.6.4. Test Setup Layout

This test setup layout is the same as that shown in section 4.5.4.

4.6.5. Test Deviation


There is no deviation with the original standard.

4.6.6. EUT Operation during Test


The EUT was programmed to be in continuously transmitting mode.

4.6.7. Test Result of Fundamental Emissions


Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level / Ant. 1 / Chain 1 + Chain 2




Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2



Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 5850MHz~40000MHz (down 30dBc) /
Ant. 1 / Chain 1 + Chain 2




Date: 16.AUG.2013 21:43:49


Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level / Ant. 1 / Chain 1 + Chain 2



Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Date: 16.AUG.2013 21:37:38

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Date: 16.AUG.2013 21:39:34

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Date: 16.AUG.2013 21:39:08


Plot on Configuration IEEE 802.11a / Reference Level / Ant. 1 / Chain 1 + Chain 2




Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2



Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc) / Ant. 1 / Chain 1 + Chain 2




Date: 16.AUG.2013 21:47:48

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:06:45

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:09:39

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:10:22

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:07:33

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 5850MHz~40000MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:08:21

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 00:56:57

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:02:54

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:03:32

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 00:57:55

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 00:59:26

Plot on Configuration IEEE 802.11a / Reference Level / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:12:55

Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:15:43

Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:16:23

Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:13:43

Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc) / Ant. 2 / Chain 1 + Chain 2




Date: 3.AUG.2013 01:14:31

Plot on Configuration IEEE 802.11n MCS0 20MHz / Reference Level / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:26:34

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 30MHz~5725MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:29:06

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 149 / 5850MHz~40000MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:29:44

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 30MHz~5725MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:27:24

Plot on Configuration IEEE 802.11n MCS0 20MHz / CH 165 / 5850MHz~40000MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:28:07

Plot on Configuration IEEE 802.11n MCS0 40MHz / Reference Level / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:19:56

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 30MHz~5725MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:22:52

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 151 / 5850MHz~40000MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:20:33

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 30MHz~5725MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:20:33

Plot on Configuration IEEE 802.11n MCS0 40MHz / CH 159 / 5850MHz~40000MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:21:20

Plot on Configuration IEEE 802.11a / Reference Level / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:32:07

Plot on Configuration IEEE 802.11a / CH 149 / 30MHz~5725MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:34:43

Plot on Configuration IEEE 802.11a / CH 149 / 5850MHz~40000MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2




Date: 2.AUG.2013 23:35:41

Plot on Configuration IEEE 802.11a / CH 165 / 30MHz~5725MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2



Date: 2.AUG.2013 23:32:56

Plot on Configuration IEEE 802.11a / CH 165 / 5850MHz~40000MHz (down 30dBc) / Ant. 3 / Chain 1 + Chain 2



Date: 2.AUG.2013 23:33:36

4.7. Antenna Requirements

4.7.1. Limit

Except for special regulations, the Low-power Radio-frequency Devices must not be equipped with any jacket for installing an antenna with extension cable. An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that the user can replace a broken antenna, but the use of a standard antenna jack or electrical connector is prohibited. Further, this requirement does not apply to intentional radiators that must be professionally installed.

4.7.2. Antenna Connector Construction

Please refer to section 3.3 in this test report; antenna connector complied with the requirements.

5. LIST OF MEASURING EQUIPMENTS

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
EMI Test Receiver	R&S	ESCS 30	100377	9kHz ~ 2.75GHz	Oct. 23, 2012	Conduction (CO01-CB)
LISN	F.C.C.	FCC-LISN-50-16-2	04083	150kHz ~ 100MHz	Nov. 26, 2012	Conduction (CO01-CB)
V- LISN	Schwarzbeck	NSLK 8127	8127478	9kHz ~ 30MHz	Jun. 22, 2012	Conduction (CO01-CB)
Impulsbegrenzer Pulse Limiter	Rohde&Schwarz	ESH3-Z2	100430	9kHz-30MHz	Feb. 21, 2013	Conduction (CO01-CB)
COND Cable	Woken	Cable	01	0.15MHz-30MHz	Dec. 04, 2012	Conduction (CO01-CB)
Software	Audix	E3	5.410e	-	-	Conduction (CO01-CB)
BILOG ANTENNA	Schaffner	CBL6112D	22021	20MHz ~ 2GHz	Apr. 16, 2013	Radiation (03CH01-CB)
Loop Antenna	Teseq	HLA 6120	24155	9 kHz - 30 MHz	Nov. 05, 2012*	Radiation (03CH01-CB)
Horn Antenna	EMCO	3115	00075790	750MHz-18GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Horn Antenna	SCHWARZBEAK	BBHA 9170	BBHA9170252	15GHz ~ 40GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8447D	2944A10991	0.1MHz ~ 1.3GHz	Nov. 27, 2012	Radiation (03CH01-CB)
Pre-Amplifier	Agilent	8449B	3008A02310	1GHz ~ 26.5GHz	Nov. 23, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 31, 2012	Radiation (03CH01-CB)
Pre-Amplifier	WM	TF-130N-R1	923365	26.5GHz ~ 40GHz	Jul. 30, 2013	Radiation (03CH01-CB)
Spectrum analyzer	R&S	FSP40	100056	9kHz-40GHz	Nov. 16, 2012	Radiation (03CH01-CB)
EMI Test Receiver	R&S	ESCS 30	100355	9kHz ~ 2.75GHz	Apr. 12, 2013	Radiation (03CH01-CB)
Turn Table	INN CO	CO 2000	N/A	0 ~ 360 degree	N.C.R	Radiation (03CH01-CB)
Antenna Mast	INN CO	CO2000	N/A	1 m - 4 m	N.C.R	Radiation (03CH01-CB)
RF Cable-low	Woken	Low Cable-1	N/A	30 MHz - 1 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-1	N/A	1 GHz ~ 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-2	N/A	1 GHz ~ 26.5 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-3	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
RF Cable-high	Woken	High Cable-4	N/A	1 GHz - 40 GHz	Nov. 18, 2012	Radiation (03CH01-CB)
Signal analyzer	R&S	FSV40	100979	9kHz-40GHz	Oct. 08, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	2 Way	0120A02056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	3 Way	MDC2366	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Power Divider	Woken	4 Way	0120A04056002D	2GHz ~ 18GHz	Nov. 18, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-7	-	1 GHz ~ 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-8	-	1 GHz ~ 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-9	-	1 GHz ~ 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
RF Cable-high	Woken	High Cable-10	-	1 GHz ~ 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)



Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
RF Cable-high	Woken	High Cable-11	-	1 GHz – 26.5 GHz	Nov. 19, 2012	Conducted (TH01-CB)
Power Sensor	Anritsu	MA2411B	0917223	300MHz-40GHz	Nov. 28, 2012	Conducted (TH01-CB)
Power Meter	Anritsu	ML2495A	1035008	300MHz-40GHz	Nov. 27, 2012	Conducted (TH01-CB)

Note: Calibration Interval of instruments listed above is one year.

*** Calibration Interval of instruments listed above is two years.

N.C.R. means Non-Calibration required.

6. TEST LOCATION

SHIJR	ADD : 6Fl., No. 106, Sec. 1, Shintai 5th Rd., Shijr City, Taipei, Taiwan 221, R.O.C. TEL : 886-2-2696-2468 FAX : 886-2-2696-2255
HWA YA	ADD : No. 52, Hwa Ya 1st Rd., Kwei-Shan Hsiang, Tao Yuan Hsien, Taiwan, R.O.C. TEL : 886-3-327-3456 FAX : 886-3-318-0055
LINKOU	ADD : No. 30-2, Dingfu Tsuen, Linkou Shiang, Taipei, Taiwan 244, R.O.C TEL : 886-2-2601-1640 FAX : 886-2-2601-1695
DUNGHU	ADD : No. 3, Lane 238, Kangle St., Neihu Chiu, Taipei, Taiwan 114, R.O.C. TEL : 886-2-2631-4739 FAX : 886-2-2631-9740
JUNGHE	ADD : 7Fl., No. 758, Jungjeng Rd., Junghe City, Taipei, Taiwan 235, R.O.C. TEL : 886-2-8227-2020 FAX : 886-2-8227-2626
NEIHU	ADD : 4Fl., No. 339, Hsin Hu 2 nd Rd., Taipei 114, Taiwan, R.O.C. TEL : 886-2-2794-8886 FAX : 886-2-2794-9777
JHUBEI	ADD : No.8, Lane 724, Bo-ai St., Jhubei City, HsinChu County 302, Taiwan, R.O.C. TEL : 886-3-656-9065 FAX : 886-3-656-9085

7. MEASUREMENT UNCERTAINTY

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	0.026	dB	normal(k=2)	0.013
Cable loss	0.002	dB	normal(k=2)	0.001
AMN/LISN specification	1.200	dB	normal(k=2)	0.600
Mismatch Receiver VSWR 1= AMN/LISN VSWR 2=	-0.080	dB	U-shaped	0.060
Combined standard uncertainty $U_c(y)$				1.2
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				2.4

Uncertainty of Radiated Emission Measurement (30MHz ~ 1,000MHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	± 0.173	dB	K=1	0.086
Cable loss	± 0.174	dB	K=2	0.087
Antenna gain	± 0.169	dB	K=2	0.084
Site imperfection	± 0.433	dB	Triangular	0.214
Pre-amplifier gain	± 0.366	dB	K=2	0.183
Transmitter antenna	± 1.200	dB	Rectangular	0.600
Signal generator	± 0.461	dB	Rectangular	0.231
Mismatch	± 0.080	dB	U-shape	0.040
Spectrum analyzer	± 0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.778
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.555

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.191	dB	K=1	0.095
Cable loss	±0.169	dB	K=2	0.084
Antenna gain	±0.191	dB	K=2	0.096
Site imperfection	±0.582	dB	Triangular	0.291
Pre-amplifier gain	±0.304	dB	K=2	0.152
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.839
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.678

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Receiver reading	±0.186	dB	K=1	0.093
Cable loss	±0.167	dB	K=2	0.083
Antenna gain	±0.190	dB	K=2	0.095
Site imperfection	±0.488	dB	Triangular	0.244
Pre-amplifier gain	±0.269	dB	K=2	0.134
Transmitter antenna	±1.200	dB	Rectangular	0.600
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				1.771
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				3.541

Uncertainty of Conducted Emission Measurement

Contribution	Uncertainty of x_i			$u(x_i)$
	Value	Unit	Probability Distribution k	
Cable loss	±0.038	dB	K=2	0.019
Attenuator	±0.047	dB	K=2	0.024
Power Meter specification	±0.300	dB	Triangular	0.150
Power Sensor specification	±0.300	dB	Rectangular	0.150
Signal generator	±0.461	dB	Rectangular	0.231
Mismatch	±0.080	dB	U-shape	0.040
Spectrum analyzer	±0.500	dB	Rectangular	0.250
Combined standard uncertainty $U_c(y)$				0.863
Measuring uncertainty for a level of confidence of 95% $U=2U_c(y)$				1.726