

**MPE CALCULATION**  
**FCC ID: I28MD-ZBRBLE**

<b>RF Exposure Requirements:</b>	47 CFR §1.1307(b)
<b>RF Radiation Exposure Limits:</b>	47 CFR §1.1310
<b>RF Radiation Exposure Guidelines:</b>	FCC OST/OET Bulletin Number 65
<b>EUT Frequency Band:</b>	2402 - 2480 MHz
<b>Limits for General Population/Uncontrolled Exposure in the band of:</b>	1500 - 100,000 MHz
<b>Power Density Limit:</b>	1 mW / cm <sup>2</sup>

**Equation:**  $S = PG / 4\pi R^2$  or  $R = \sqrt{PG / 4\pi S}$   
Where, S = Power Density  
P = Power Input to Antenna  
G = Antenna Gain  
R = distance to the center of radiated antenna

---

Prediction distance 20cm

**EUT: Bluetooth Low Energy Module**

(2.4GHz Band): Power = -1.85dBm, Antenna Gain = 1dBi, Power density = 0.000164mW/ cm<sup>2</sup>

The Above Result had shown that the Device complied with MPE requirement.

Completed By: Gary Zhou

*Gary Zhou*

SIEMIC, Inc.

775 Montague Expressway, Milpitas, CA 95035

Date: 11/02/ 2015