

# ZEBRA TECHNOLOGIES CORP

WRISTBAND PRINTER WITH RADIO 802.11B/G

Model: HC100

20 May 2008

Report No.: SL08021101-ZBR-011 (15.247)(HC100)  
(This report supersedes NONE)



Modifications made to the product : None

This Test Report is Issued Under the Authority of:

	
<b>Dan Corona</b> Test Engineer	<b>Leslie Bai</b> Engineering Reviewer

This test report may be reproduced in full only.  
Test result presented in this test report is applicable to the representative sample only.

# EMC Test Report

To: FCC Part 15.247 & IC RSS210

SIEMIC, INC.  
Accessing global markets



**SIEMIC ACREDITATION DETAILS: NVLAP Lab Code: 200729-0**

United States Department of Commerce  
National Institute of Standards and Technology

**NVLAP<sup>®</sup>**

---

**Certificate of Accreditation to ISO/IEC 17025:2005**

---

**NVLAP LAB CODE: 200729-0**

**SIEMIC Laboratories**  
San Jose, CA

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,  
listed on the Scope of Accreditation, for:*

**ELECTROMAGNETIC COMPATIBILITY AND TELECOMMUNICATIONS**

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005.  
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality  
management system (refer to joint ISO-ILAC-IAF Communique dated 18 June 2005).*

2008-01-01 through 2008-12-31  
*Effective dates*



*Sally J. Bruce*  
For the National Institute of Standards and Technology

**SIEMIC ACREDITATION DETAILS: FCC Registration No. 783147**

**FEDERAL COMMUNICATIONS COMMISSION**

**Laboratory Division  
7435 Oakland Mills Road  
Columbia, MD 21046**

December 20, 2007

Registration Number: 783147

SIEMIC Laboratories  
2206 Ringwood Avenue,  
San Jose, CA 95131

Attention: Leslie Bai

Re: Measurement facility located at San Jose  
3 & 10 meter site  
Date of Renewal: December 20, 2007

Dear Sir or Madam:

Your request for renewal of the registration of the subject measurement facility has been received. The information submitted has been placed in your file and the registration has been renewed. The name of your organization will remain on the list of facilities whose measurement data will be accepted in conjunction with applications for Certification under Parts 15 or 18 of the Commission's Rules. Please note that the file must be updated for any changes made to the facility and the registration must be renewed at least every three years.

Measurement facilities that have indicated that they are available to the public to perform measurement services on a fee basis may be found on the FCC website [www.fcc.gov](http://www.fcc.gov) under E-Filing, OET Equipment Authorization Electronic Filing, Test Firms.

Sincerely,

Phyllis Parrish  
Industry Analyst



**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Zebra Technologies Corp ,Model : HC100  
To: FCC 15.247 2007, RSS 210 Issue 7: 2007

Serial# SL08021101-ZBR-011 (15.247)(HC100)  
Issue Date 20 May 2008  
Page 4 of 50  
www.siemic.com

**SIEMIC ACREDITATION DETAILS: Industry of Canada Registration No. 4842-1**



April 28, 2006

OUR FILE: 46405-4842  
Submission No: 114591

Siemic Inc.  
2206 Ringwood Ave.,  
San Jose, CA 95131

Dear Sir/Madame:

The Bureau has received your application for the Alternate Test Site and the filing is satisfactory to Industry Canada.

Please reference to the file number (4842-1 ) in the body of all test reports containing measurements performed on the site.

Renewal of the filing is required every two years.

If you have any questions, you may contact the Bureau at the telephone number below or by e-mail at [certification.bureau@ic.gc.ca](mailto:certification.bureau@ic.gc.ca) Please reference our file number above for all correspondence.

Yours sincerely,

Robert Corey  
Manager Certification  
Certification and Engineering Bureau  
3701 Carling Ave., Building 94  
Ottawa, Ontario  
K2H 8S2  
Tel. No. (613) 990-3869



**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Zebra Technologies Corp ,Model : HC100  
To: FCC 15.247 2007, RSS 210 Issue 7: 2007

Serial# SL08021101-ZBR-011 (15.247)(HC100)  
Issue Date 20 May 2008  
Page 5 of 50  
www.siemec.com

**SIEMIC ACREDITATION DETAILS: Japan VCCI Registration No. 2195**



Voluntary Control Council for Interference  
by Information Technology Equipment  
7F NDA Bldg. 2-3-5, Azabudai,  
Minato-Ku, Tokyo, Japan, 106-0041  
Tel:+81-3-5575-3138  
Fax:+81-3-5575-3137  
<http://www.vccior.jp>

February 12, 2004

**TO: SIEMIC, INC.**

**Membership NO: 2195**

We confirmed your payment for annual membership fee and admission fee. Thank you very much for your remitting.

Please find enclosed VCCI documents. As admission fee and annual membership fee were confirmed, your company registered as VCCI official member.

From now on, it is possible for your company to submit conformity verification report or/and application for registration of measurement facilities.

Please find necessary forms for your submission from VCCI web-site.  
[www.vccior.jp](http://www.vccior.jp)

When you submit conformity verification report, please submit to Ms. Yoko Inagaki / [inagaki@vccior.jp](mailto:inagaki@vccior.jp) and application for registration of measurement facilities, please submit to Mr. Masaru Denda / [denda@vccior.jp](mailto:denda@vccior.jp)

Their address, phone and fax number are absolutely same as I. Please refer address indicated on top right-hand corner of this page.

If you have any other questions regarding membership, feel free to contact me. Thank you very much.

Best Regards,

Naoko Hori (Ms.)  
VCCI  
[hori@vccior.jp](mailto:hori@vccior.jp)

Enclosure

**SIEMIC ACREDITATION DETAILS: Japan RF Technologies Accreditation No. MRF050927**

**RFT**

## Certificate

This is to certify that the  
Quality Management System  
of

**SIEMIC , Inc.**  
2206 Ringwood Avenue  
San Jose, California 95131 U.S.A

has been authorized to carry out Japan Specified Radio Equipment test by  
order and under supervision of RF Technologies Co., Ltd. according to  
Notification No.88 of Radio Law.

An assessment of the laboratory was conducted according to the "Procedure and  
Conditions for Appointments of 2.4GHz Band Low power data communications system  
that Bluetooth and Wireless LAN test with reference to ISO/IEC 17025  
by an RF Technologies Co., Ltd. auditor.

**Audit Report No. MRF050927**

 Kazuyuki Sarashina Auditor RF Technologies Co., Ltd.	 Toshihiro Heganami President RF Technologies Co., Ltd.
Audit Date September 27th, 2005	Issued Date October 5th, 2005

This Certificate is valid until **September 26<sup>th</sup> 2006 or next schedule audit.**

No:006 Registered Certification Body  
RF Technologies Co., Ltd.  
472, Nippa-cho,Kohoku-ku, Yokohama, 223-0057, Japan





**SIEMIC ACREDITATION DETAILS: Korea MIC Lab Code: KR0032**

# 시험기관지정서

## Certificate

of Designated Testing Laboratory

지정번호(No.) : KR0032

시험기관명 : (주)현대고정인증기술원  
(Name of Lab.) (Hyundai Calibration & Certification Technologies Co., Ltd)

주 소 : 경기도 이천시 부발읍 아미리 산136-1  
(Address) (136-1, Ami-ri, Bubal-eup, Icheon-si, Kyunggi-Do, Korea)  
2206 Ringwood Avenue San Jose, CA, USA.

시험분야 및 범위 : 유선(Telecommunication Part)  
(Area & Category) 무선(Radio Communication Part)  
전자파장해(EMD) : 미국지사 포함  
전자파내성(EMS) : 미국지사 포함  
전기안전(Safety)  
전자파흡수율(SAR)

위 기관을 정보통신기기시험기관지정및관리등에관한규칙에 의해 정보통신기기시험기관으로 지정합니다.

*This is to certify that the above mentioned laboratory is designated as the testing laboratory in accordance with the Regulations on Designation of Testing Laboratory for Information and Communication Equipment.*

2005년(Year) 7월(Month) 5일(Date)

**전 파 연구 소 장**  
Director General of Radio Research Laboratory  
Ministry of Information and Communication  
Republic of Korea







**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Zebra Technologies Corp ,Model : HC100  
To: FCC 15.247 2007, RSS 210 Issue 7: 2007

Serial# SL08021101-ZBR-011 (15.247)(HC100)  
Issue Date 20 May 2008  
Page 8 of 50  
www.siemic.com

**SIEMIC ACREDITATION DETAILS: Korea CAB ID: US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
National Institute of Standards and Technology  
Gaithersburg, Maryland 20899

April 17, 2006

Mr. Leslie Bai  
SIEMIC Laboratories  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Ministry of Information and Communication's Radio Research Laboratory (RRL) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. The pertinent information about your laboratory's designation is as follows:

CAB Name: **SIEMIC Laboratories**  
Identification No.: **US0160**  
Scope:

Coverage	Standards	Date of Recognition
Electro Magnetic Interference	1. RRL Notice No. 2005-82: Technical Requirements for Electromagnetic Interference 2. Annex 8(KN-22), RRL Notice No. 2005-131: Conformity Assessment Procedure for Electromagnetic Interference	April 13, 2006
Electro Magnetic Susceptibility	1. RRL Notice No. 2005-130: Technical Requirements for Electromagnetic Susceptibility 2. Annex 1-7(KN-61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11), RRL Notice No. 2005-132: Conformity Assessment Procedure for Electromagnetic Susceptibility	April 13, 2006

You may submit test data to RRL to verify that the equipment to be imported into Korea satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements.

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions please contact Mr. Jogindar (Joe) Dhillon at (301) 975-5521. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon

**NIST**





**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Zebra Technologies Corp ,Model : HC100  
To: FCC 15.247 2007, RSS 210 Issue 7: 2007

Serial# SL08021101-ZBR-011 (15.247)(HC100)  
Issue Date 20 May 2008  
Page 9 of 50  
www.siemic.com

**SIEMIC ACREDITATION DETAILS: Taiwan BSMI Accreditation No. SL2-IN-E-1130R**



**UNITED STATES DEPARTMENT OF COMMERCE**  
National Institute of Standards and Technology  
Gaithersburg, Maryland 20885

May 3, 2006

Mr. Leslie Bai  
SIEMIC Laboratories  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that your laboratory has been recognized by the Chinese Taipei's Bureau of Standards, Metrology, and Inspection (BSMI) under the Asia Pacific Economic Cooperation (APEC) Mutual Recognition Arrangement (MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA. You may submit test data to BSMI to verify that the equipment to be imported into Chinese Taipei satisfies the applicable requirements. The designation of your organization will remain in force as long as its accreditation for the designated scope remains valid and comply with the designation requirements. The pertinent designation information is as follows:

- BSMI number: **SL2-IN-E-1130R** (Must be applied to the test reports)
- U.S. Identification No: **US0160**
- Scope of Designation: **CNS 13438**
- Authorized signatory: **Mr. Leslie Bai**

The names of all recognized CABs will be posted on the NIST website at <http://ts.nist.gov/mra>. If you have any questions, please contact Mr. Dhillon at 301-975-5321. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon

**NIST**



**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Zebra Technologies Corp ,Model : HC100  
To: FCC 15.247 2007, RSS 210 Issue 7: 2007

Serial# SL08021101-ZBR-011 (15.247)(HC100)  
Issue Date 20 May 2008  
Page 10 of 50  
www.siemic.com

**SIEMIC ACREDITATION DETAILS: Taiwan NCC CAB ID: US0160**



**UNITED STATES DEPARTMENT OF COMMERCE**  
**National Institute of Standards and Technology**  
Gaithersburg, Maryland 20899

August 8, 2006

Mr. Leslie Bai  
SIEMIC Laboratories  
2206 Ringwood Avenue  
San Jose, CA 95131

Dear Mr. Bai:

I am pleased to inform you that SIEMIC Laboratories has been recognized by the Chinese Taipei's National Communications Commission (NCC) under the Asia Pacific Economic Cooperation for Telecommunications and Information, Mutual Recognition Arrangement (APEC Tel MRA). Your laboratory is now designated to act as a Conformity Assessment Body (CAB) under Appendix B, **Phase I** Procedures, of the APEC Tel MRA.

You may submit test data to NCC to verify that the equipment to be imported into Chinese Taipei satisfies their applicable requirements using the following guidelines:

- Your laboratory's assigned 6-digit U.S. identification number is **US0160**. You should reference this number in your correspondence.
- The scope of designation is limited to **LP0002**. Your designation will remain in force as long as your accreditation remains valid for the scope of designation.

If you have any questions please contact Mr. Jogindar Dhillon via email at [dhillon@nist.gov](mailto:dhillon@nist.gov) or via fax at 301-975-5414. The names of all recognized laboratories will be posted on the NIST website at <http://ts.nist.gov/mra>. We appreciate your continued interest in our international conformity assessment activities.

Sincerely,

David F. Alderman  
Group Leader, Standards Coordination and Conformity Group

cc: Jogindar Dhillon

**NIST**



**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Zebra Technologies Corp ,Model : HC100  
To: FCC 15.247 2007, RSS 210 Issue 7: 2007

Serial# SL08021101-ZBR-011 (15.247)(HC100)  
Issue Date 20 May 2008  
Page 11 of 50  
www.siemic.com

## SIEMIC ACREDITATION DETAILS: Mexico NOM Recognition



CAN I E T I  
CAMARA NACIONAL  
DE LA INDUSTRIA  
ELECTRONICA, DE  
TELECOMUNICACIONES  
E INFORMATICA

### Laboratorio Valentín V. Rivero

México D.F. a 16 de octubre de 2006.

**LESLIE BAI  
DIRECTOR OF CERTIFICATION  
SIEMIC LABORATORIES, INC.  
ACCESSING GLOBAL MARKETS  
P R E S E N T E**

En contestación a su escrito de fecha 5 de septiembre del año en curso, le comento que estamos muy interesados en su intención de firmar un Acuerdo de Reconocimiento Mutuo, para lo cual adjunto a este escrito encontrara el Acuerdo en idioma inglés y español prefrenado de los cuales le pido sea revisado y en su caso corregido, para que si esta de acuerdo poder firmarlo para mandarlo con las autoridades Mexicanas para su visto bueno y así poder ejercer dicho acuerdo.

Aprovecho este escrito para mencionarle que nuestro intermediario gestor será la empresa Isabel de México, S. A. de C. V., empresa que ha colaborado durante mucho tiempo con nosotros en lo relacionado a la evaluación de la conformidad y que cuenta con amplia experiencia en la gestoría de la certificación de cumplimiento con Normas Oficiales Mexicanas de producto en México.

Me despido de usted enviándole un cordial saludo y esperando sus comentarios al Acuerdo que nos ocupa.

Atentamente:



**Ing. Faustino Sotelo González  
Gerente Técnico del Laboratorio de  
CANIETI.**

Callejón 77  
Hidráulica Condésa  
06100 México, D.F.  
Tel. 5264-0908 con 12 líneas  
Fax 5264-0488  
www.canieti.org



**SIEMIC, Inc.**  
Accessing global markets

Title: RF Test Report Zebra Technologies Corp ,Model : HC100  
To: FCC 15.247 2007, RSS 210 Issue 7: 2007

Serial# SL08021101-ZBR-011 (15.247)(HC100)  
Issue Date 20 May 2008  
Page 12 of 50  
www.siemic.com

**SIEMIC ACREDITATION DETAILS: Hong Kong OFTA Recognition No. D23/16V**



Your Ref 來函編號 : D23/16 V  
Our Ref 本局編號 :

Telephone 電話 : (852) 2961 6320  
Fax No 圖文傳真 : (852) 2838 5004  
E-mail 電郵地址 : 20 July 2005

Mr. Leslie Bai  
Director of Certification,  
SIEMIC Laboratories  
2206 Ringwood Avenue  
San Jose, California 95131  
USA

Dear Mr. Bai,

**Application of Recognised Testing Agency (RTA)**

Referring your submission of 28 June 2005 in relation to the application of RTA, I am pleased to inform you that OFTA has appointed SIEMIC Laboratories (SIEMIC) as a Recognised Testing Agency (RTA) :

Please note that, under the Hong Kong Telecommunications Equipment Evaluation and Certification (HKTEC) Scheme, SIEMIC is authorized to conduct evaluation tests on telecommunications equipment against the following HKTA specifications :

Scope of recognition (HKTA Specifications) :

1001, 1002, 1004, 1006, 1007, 1008  
1010, 1015, 1016  
1022, 1026, 1027, 1029  
1030, 1031, 1032, 1033, 1034, 1035, 1039  
1041, 1042, 1043, 1045, 1047, 1048  
2001

You are requested to refer to and comply with the code of practice and guidelines for RTA as given in the Information Note OFTA I 411 "Recognised Testing Agency (RTA) for Conducting Evaluation Test of Telecommunications Equipment", which can be downloaded from OFTA's homepage at <http://www.ofta.gov.hk/tec/information-notes.html>.

If you have any queries, please do not hesitate to contact me.

Yours sincerely,

(K K Sin)  
for Director-General  
of Telecommunications

Office of the Telecommunications Authority  
29/F Wu Chung House 213 Queen's Road East Wan Chai Hong Kong  
電訊管理局  
香港灣仔皇后大道東 213 號胡忠大廈 29 字樓

<http://www.ofta.gov.hk>

This page has been left blank intentionally.

# CONTENTS

1	EXECUTIVE SUMMARY & EUT INFORMATION .....	16
2	TECHNICAL DETAILS.....	17
3	MODIFICATION.....	18
4	TEST SUMMARY.....	19
5	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS .....	20
	ANNEX A. TEST INSTRUMENT & METHOD .....	42
	ANNEX B EUT AND TEST SETUP PHOTOGRAPHS.....	46
	ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	46
	ANNEX D USER MANUAL, BLOCK & CIRCUIT DIAGRAM .....	50



---

This page has been left blank intentionally.

# 1 Executive Summary & EUT information

The purpose of this test programme was PCII application and to demonstrate compliance of the Zebra Technologies Corp , WristBand Printer with Radio 802.11b/g Model: HC100 against the current Stipulated Standards. The WristBand Printer with Radio 802.11b/g have demonstrated compliance with the FCC 15.247 2007 and RSS 210 Issue 7 2007.

## EUT Information

<b>EUT Description</b>	: The HC100 is a Zebra product that integrates a Printer/Media Cartridge solution for printing on-demand patient identification wristbands. The value to the end user is significantly improved easy-of-use and high reliability in correctly identifying patients through high quality barcodes. The HC100 is a Direct Spread Spectrum device that is operation within the band of 2400-2483.5MHz.
<b>Model No</b>	: HC100
<b>Serial No</b>	: 0010-00-75
<b>Input Power</b>	: 100~240 VAC, 50~60Hz 24 VDC , 2.92A Power Supply → Model : FSP070-RDBM
<b>Classification Per Stipulated Test Standard</b>	: Spread Spectrum System / Device

## 2 TECHNICAL DETAILS

Purpose	Compliance testing of Wristband Printer 802.11b/g with stipulated standard
Applicant / Client	Zebra Technologies Corp
Manufacturer	Zebra Technologies Corp 333 Corporate Woods Parkway. Vernon Hills, IL 60061
Laboratory performing the tests	SIEMIC Laboratories
Test report reference number	SL08021101-ZBR-011 (15.247)(HC100)
Date EUT received	21 March 2008
Standard applied	47 CFR §15.247 (2007) and RSS 210 Issue 7: 2007
Dates of test (from – to)	22 March 2008 - 25 March 2008
No of Units:	1
Equipment Category:	DTS
Trade Name:	Zebra Technologies Corp
Model :	HC100
RF Operating Frequency (ies)	2412 to 2462 MHz
Number of Channels :	11
Modulation :	CCK & OFDM
FCC ID :	I28MD-ZLAN11G
IC ID :	3798A- ZLAN11G

### 3 MODIFICATION

**NONE**

## 4 TEST SUMMARY

The product was tested in accordance with the following specifications. All Testing has been performed according to below product classification:

### Spread Spectrum System / Device

#### Test Results Summary

Test Standard		Description	Pass / Fail
CFR 47 Part 15.247: 2007	RSS 210 Issue 7: 2007		
15.203		Antenna Requirement	Pass
15.205	RSS210(A8.5)	Restricted Band of Operation	Pass
15.207(a)	RSSGen(7.2.2)	Conducted Emissions Voltage	Pass
15.247(a)(1)	RSS210(A8.1)	Channel Separation	N/A
15.247(a)(1)	RSS210(A8.1)	Occupied Bandwidth	Pass - Refer to RTL report no.: 2006029
15.247(a)(2)	RSS210 (A8.2)	Bandwidth	Pass - Refer to RTL report no.: 2006029
15.247(a)(1)	RSS210(A8.1)	Number of Hopping Channels	N/A
15.247(a)(1)	RSS210(A8.1)	Time of Occupancy	N/A
15.247(b)	RSS210(A8.4)	Output Power	Pass - Refer to RTL report no.: 2006029
15.247(c)	RSS210(A8.4)	Antenna Gain > 6 dBi	Pass
15.247(d)	RSS210(A8.5)	Conducted Spurious Emissions	Pass - Refer to RTL report no.: 2006029
15.209; 15.247(d)	RSS210(A8.5)	Radiated Spurious Emissions	Pass
15.247(e)	RSS210(A8.3)	Power Spectral Density	Pass - Refer to RTL report no.: 2006029
15.247(f)	RSS210(A8.3)	Hybrid System Requirement	N/A
15.247(g)	RSS210(A8.1)	Hopping Capability	N/A
15.247(h)	RSS210(A8.1)	Hopping Coordination Requirement	N/A
15.247(i)	RSSGen(5.5)	RF Exposure requirement	Pass
	RSSGen(4.8)	Receiver Spurious Emissions	Pass

ANSI C63.4: 2003/ RSS-Gen Issue 2: 2007

PS: All measurement uncertainties are not taken into consideration for all presented test result.

## 5 MEASUREMENTS, EXAMINATION AND DERIVED RESULTS

### 5.1 Antenna Requirement

**Requirement(s):** 47 CFR §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.


Antenna requirement must meet at least one of the following:

- a) Antenna must be permanently attached to the device.
- b) Antenna must use a unique type of connector to attach to the device.
- c) Device must be professionally installed. Installer shall be responsible for ensuring that the correct antenna is employed with the device.

The antenna connector is SMA Reverse SMA connector type. Antenna maximum gain is -9.49dBi for 2.412–2.462 GHz band.








Quasi-Peak Limit

Average Limit

120V, 60Hz, Neutral Line

Frequency (MHz)	QP Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
1.25	45.63	56.00	PASS	-10.37	22.99	46.00	PASS	-23.01	Neutral
0.96	45.34	56.00	PASS	-10.66	23.80	46.00	PASS	-22.20	Neutral
0.69	45.79	56.00	PASS	-10.21	26.01	46.00	PASS	-19.99	Neutral
1.20	44.03	56.00	PASS	-11.97	20.54	46.00	PASS	-25.46	Neutral
1.51	44.37	56.00	PASS	-11.63	20.54	46.00	PASS	-25.46	Neutral
1.48	43.66	56.00	PASS	-12.34	18.92	46.00	PASS	-27.08	Neutral



Quasi-Peak Limit

Average Limit

120V, 60Hz, Phase Line

Frequency (MHz)	QP Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Avg Value (dB $\mu$ V)	Class B Limit (dB)	Pass / Fail	Margin (dB)	Line
1.24	45.92	56.00	PASS	-10.08	23.56	46.00	PASS	-22.44	Phase
2.05	44.14	56.00	PASS	-11.86	21.01	46.00	PASS	-24.99	Phase
2.07	43.91	56.00	PASS	-12.09	20.92	46.00	PASS	-25.08	Phase
0.96	45.75	56.00	PASS	-10.25	23.92	46.00	PASS	-22.08	Phase
0.69	46.08	56.00	PASS	-9.92	26.39	46.00	PASS	-19.61	Phase
1.50	44.88	56.00	PASS	-11.12	21.30	46.00	PASS	-24.70	Phase



## 5.4 Peak Spectral Density

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5$ dB.
3. Environmental Conditions

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : March 22-25 2008  
Tested By :Dan Corona

**Standard Requirement :** 47 CFR §15.247(e)

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission

**Procedures:** The Peak Spectral density measurement was taken conducted using a spectrum analyzer.

RBW=3KHz, VBW > RBW , Sweep time to SPAN/RBW (sec)

### **Test Result:**

Refer to RTL report no.: 2006026.

## 5.10 Peak Output Power

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is  $\pm 1.5$ dB.
3. Environmental Conditions  
Temperature 25°C  
Relative Humidity 50%  
Atmospheric Pressure 1019mbar
4. Test Date : March 22-25 2008  
Tested By :Dan Corona

Standard Requirement : 47 CFR §15.247(b)

**Procedures:** The peak output power was measured conducted using a spectrum analyzer at low, mid, and hi channels. Peak detector was set to measure the power output. The power is converted from watt to dBm, therefore, 1 watt = 30 dBm. The highest antenna gain that will be used is -9.49 dBi.

### **Test Result:**

Refer to RTL report no.: 2006026.



## 5.10 Antenna Port Emission

1. Conducted Measurement  
EUT was set for low , mid, high channel with modulated mode and highest RF output power.  
The spectrum analyzer was connected to the antenna terminal.
2. Conducted Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 40GHz is ±1.2dB.
3. Environmental Conditions
 

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar
4. Test Date : March 22-25 2008  
Tested By :Dan Corona

Standard Requirement : 47 CFR §15.247(d)

**Procedures:** The conducted spurious emissions were measured conducted using a spectrum analyzer at low, mid, and hi channels. The limit was determined by attenuating 20 dB of the RF peak power output

**Test Result:**

Refer to RTL report no.: 2006026.

## 5.10 Radiated Spurious Emission < 1GHz

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 30MHz – 1GHz (QP only @ 3m) is +6.0dB (for EUTs < 0.5m X 0.5m X 0.5m).
4. Environmental Conditions
 

Temperature	25°C
Relative Humidity	50%
Atmospheric Pressure	1019mbar

Test Date : March 22-25 2008  
Tested By :Dan Corona

Standard Requirement: 47 CFR §15.247(d)

**Procedures:** Radiated emissions were measured according to ANSI C63.4. The EUT was set to transmit at the highest output power. The EUT was set to transmit at mid channel. Note that setting the channel other than mid, the spurious emissions are the same.


The limit is converted from microvolts/meter to decibel microvolts/meter.

Sample Calculation: Corrected Amplitude = Raw Amplitude (dBμV/m) + ACF(dB) + Cable Loss(dB)

**Test Result:**

### Radiated Emission Plot (Transmit Mode)

#### Test Data




Limit

#### Test Data

Frequency (MHz)	Quasi-Peak (dBµV/m) @ 3m	Antenna height (cm)	Turntable position (deg)	Polarity	Distance Factor (dB)	Corrected Amplitude @ 3m	Limit (dBµV/m)	Margin (dB)
30.03	31.42	205.00	38.00	V	0	29.02	40.00	-8.58
288.01	43.56	107.00	139.00	H	0	30.37	46.00	-2.44
40.92	27.56	190.00	36.00	V	0	27.59	40.00	-12.44
56.30	23.24	181.00	103.00	V	0	37.04	40.00	-16.76
81.85	32.47	128.00	293.00	V	0	38.68	40.00	-7.53
59.17	26.31	212.00	32.00	V	0	35.52	40.00	-13.69

### Radiated Emission Plot (Receive Mode)

#### Test Data



Limit

#### Test Data

Frequency (MHz)	Quasi-Peak (dBµV/m) @ 3m	Antenna height (cm)	Turntable position (deg)	Polarity	Distance Factor (dB)	Corrected Amplitude @ 3m	Limit (dBµV/m)	Margin (dB)
37.79	29.02	104	48	V	0	29.02	40	-10.98
33.74	30.37	114	138	V	0	30.37	40	-9.63
39.76	27.59	111	35	V	0	27.59	40	-12.41
192.0	37.04	126	264	H	0	37.04	43.5	-6.46
287.98	38.68	104	118	H	0	38.68	46	-7.32
188.61	35.52	121	248	H	0	35.52	43.5	-7.98

## **5.10 Radiated Spurious Emissions > 1GHz & Band Edge**

1. All possible modes of operation were investigated. Only the 6 worst case emissions measured, using the correct CISPR detectors, are reported. All other emissions were relatively insignificant.
2. A "-ve" margin indicates a PASS as it refers to the margin present below the limit line at the particular frequency.
3. Radiated Emissions Measurement Uncertainty  
All test measurements carried out are traceable to national standards. The uncertainty of the measurement at a confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2, in the range 1GHz – 40GH is +6.0dB (for EUTs < 0.5m X 0.5m).
4.

Environmental Conditions	Temperature	25°C
	Relative Humidity	50%
	Atmospheric Pressure	1019mbar

Test Date : March 22-25 2008  
Tested By : Dan Corona

Standard Requirement: 47 CFR §15.247(d)

**Procedures:** Equipment was setup in a semi-anechoic chamber. For measurements above 1 GHz an average measurement was taken with a 10Hz video bandwidth. The EUT was tested at low, mid and high with the highest output power. Investigated up to 10<sup>th</sup> harmonic of the operating frequency.

Sample Calculation:

EUT Field Strength = Raw Amplitude(dBµV/m) – Amplifier Gain(dB) + Antenna Factor(dB) + Cable Loss(dB) + Filter Attenuation(dB, if used)

**Test Result:**

**802.11b @ 2412MHz @ 3 Meter**

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant .Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
4.824	148	V	1.6	50.60	32.49	33	4.125	55.235	74	-18.765	Peak
4.824	281	H	1.3	52.93	32.49	33	4.125	57.565	74	-16.435	Peak
4.824	148	V	1.6	32.90	32.49	33	4.125	37.535	54	-16.465	Ave
4.824	281	H	1.3	40.33	32.49	33	4.125	44.965	54	-9.035	Ave

Emission was scanned up to 25GHz.

**802.11b @ 2437MHz @ 3 Meter**

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant .Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
4.874	218	V	1.0	50.12	32.49	33	4.125	54.755	74	-19.245	Peak
4.874	272	H	1.3	49.65	32.49	33	4.125	54.285	74	-19.715	Peak
4.874	218	V	1.0	43.84	32.49	33	4.125	48.475	54	-5.525	Ave
4.874	272	H	1.3	46.61	32.49	33	4.125	51.245	54	-2.755	Ave

Emission was scanned up to 25GHz.

**802.11b @ 2462MHz @ 3 Meter**

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant .Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
4.924	221	V	1.3	50.23	32.49	33	4.125	54.865	74	-19.135	Peak
4.924	262	H	1.2	49.75	32.49	33	4.125	54.385	74	-19.615	Peak
4.924	221	V	1.3	46.49	32.49	33	4.125	51.125	54	-2.875	Ave
4.924	262	H	1.2	47.11	32.49	33	4.125	51.745	54	-2.255	Ave

Emission was scanned up to 25GHz.

Note: No more emissions were found for the succeeding harmonics only noise floor.



**802.11g @ 2412MHz @ 3 Meter**

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant .Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
4.824	248	V	1.3	43.79	32.49	33	4.125	48.425	74	-25.575	Peak
4.824	258	H	1.2	50.70	32.49	33	4.125	55.335	74	-18.665	Peak
4.824	248	V	1.3	31.19	32.49	33	4.125	35.825	54	-18.175	Ave
4.824	258	H	1.2	37.86	32.49	33	4.125	42.495	54	-11.505	Ave

Emission was scanned up to 25GHz.

**802.11g @ 2437MHz @ 3 Meter**

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant .Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
4.874	213	V	1.3	45.61	32.49	33	4.125	50.245	74	-23.755	Peak
4.874	257	H	1.2	51.27	32.49	33	4.125	55.905	74	-18.095	Peak
4.874	213	V	1.3	37.76	32.49	33	4.125	42.395	54	-11.605	Ave
4.874	257	H	1.2	38.34	32.49	33	4.125	42.975	54	-11.025	Ave

Emission was scanned up to 25GHz.


**802.11g @ 2462MHz @ 3 Meter**

Frequency (GHz)	Azimuth (Degrees)	Antenna Polarity (H/V)	Height (m)	Raw Amp. @ 1m (dBuV)	Pre Amp. (dB)	Ant .Corr. Factor (dB)	Cable Loss (dB)	EUT Final Field Strength (dBuV/m)	Limit @ 3m (dBuV/m)	Delta (dBuV/m)	Detector (pk/avg)
4.924	164	V	1.3	51.84	32.49	33	4.125	56.475	74	-17.525	Peak
4.924	243	H	1.3	53.15	32.49	33	4.125	57.785	74	-16.215	Peak
4.924	164	V	1.3	38.83	32.49	33	4.125	43.465	54	-10.535	Ave
4.924	243	H	1.3	40.13	32.49	33	4.125	44.765	54	-9.235	Ave


Emission was scanned up to 25GHz.

Note: No more emissions were found for the succeeding harmonics only noise floor.


### Band Edge Plots




**802.11b Low Channel-Vertical Polarity -Peak**




**802.11b Low Channel-Vertical Polarity -Average**




802.11b Low Channel-Horizontal Polarity -Peak




802.11b Low Channel-Horizontal Polarity -Average




802.11b High Channel-Vertical Polarity –Peak




802.11b High Channel-Vertical Polarity –Average




802.11b High Channel-Horizontal Polarity –Peak




802.11b High Channel-Horizontal Polarity –Average




802.11g Low Channel-Vertical Polarity –Peak




802.11g Low Channel-Vertical Polarity –Average




802.11g Low Channel-Horizontal Polarity -Peak



802.11g Low Channel-Horizontal Polarity -Average




802.11g High Channel-Vertical Polarity –Peak




802.11g High Channel-Vertical Polarity –average





802.11g High Channel-Horizontal Polarity –Peak



802.11g High Channel-Horizontal Polarity –Average

**Annex A. TEST INSTRUMENT & METHOD**

**Annex A.i. TEST INSTRUMENTATION & GENERAL PROCEDURES**

Instrument	Manufacturer	Model	CAL Due Date
Spectrum Analyzer	HP	8564E	04/26/2009
EMI Receiver	Rohde & Schwarz	ESIB 40	04/25/2009
R&S LISN	R&S	ESH2-Z5	04/24/2009
CHASE LISN	Chase	MN2050B	04/24/2009
Antenna(1 ~18GHz)	Emco	3115	10/04/2008
Antenna (30MHz~2GHz)	Sunol Sciences	JB1	10/04/2008
Chamber	Lingren	3m	04/18/2009
Pre-Amplifier(1 ~ 26GHz)	HP	8449	04/24/2009
DMM	Fluke	73III	04/25/2009
Variac	KRM	AEEC-2090	See Note
DMM	Fluke	51II	See Note
Horn Antenna (18~40GHz)	Com Power	AH-840	03/19/2010
Microwave Pre-Amp (18~40GHz)	Com Power	PA-840	5/21/2010

Note: No calibration required.

## Annex A.ii. CONDUCTED EMISSIONS TEST DESCRIPTION

### Test Set-up

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table, as shown in Annex B.
2. The power supply for the EUT was fed through a 50Ω/50μH EUT LISN, connected to filtered mains.
3. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss coaxial cable.
4. All other supporting equipments were powered separately from another main supply.

### Test Method

1. The EUT was switched on and allowed to warm up to its normal operating condition.
2. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver.
3. High peaks, relative to the limit line, were then selected.
4. The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 KHz. For FCC tests, only Quasi-peak measurements were made; while for CISPR/EN tests, both Quasi-peak and Average measurements were made.
5. Steps 2 to 4 were then repeated for the LIVE line (for AC mains) or DC line (for DC power).

### Sample Calculation Example

At 20 MHz	limit = 250 μV = 47.96 dBμV
Transducer factor of LISN, pulse limiter & cable loss at 20 MHz = 11.20 dB	
Q-P reading obtained directly from EMI Receiver = 40.00 dBμV (Calibrated for system losses)	
Therefore, Q-P margin = 47.96 – 40.00 = 7.96	i.e. <b>7.96 dB below limit</b>

**Annex A. iii RADIATED EMISSIONS TEST DESCRIPTION**


**EUT Characterisation**

EUT characterisation, over the frequency range from 30MHz to 10<sup>th</sup> Harmonic , was done in order to minimise radiated emissions testing time while still maintaining high confidence in the test results.

The EUT was placed in the chamber, at a height of about 0.8m on a turntable. Its radiated emissions frequency profile was observed, using a spectrum analyzer /receiver with the appropriate broadband antenna placed 3m away from the EUT. Radiated emissions from the EUT were maximised by rotating the turntable manually, changing the antenna polarisation and manipulating the EUT cables while observing the frequency profile on the spectrum analyzer / receiver. Frequency points at which maximum emissions occurred, clock frequencies and operating frequencies were then noted for the formal radiated emissions test at the Open Area Test Site (OATS).

**Test Set-up**

1. The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m X 1.0m X 0.8m high, non-metallic table.
2. The filtered power supply for the EUT and supporting equipment were tapped from the appropriate power sockets located on the turntable.
3. The relevant broadband antenna was set at the required test distance away from the EUT and supporting equipment boundary.



**Test Method**

The following procedure was performed to determine the maximum emission axis of EUT:

1. With the receiving antenna is H polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
2. With the receiving antenna is V polarization, rotate the EUT in turns with three orthogonal axes to determine the axis of maximum emission.
3. Compare the results derived from above two steps. So, the axis of maximum emission from EUT was determined and the configuration was used to perform the final measurement.

**Final Radiated Emission Measurement**

1. Setup the configuration according to figure 1. Turn on EUT and make sure that it is in normal function.
2. For emission frequencies measured below 1 GHz, a pre-scan is performed in a shielded chamber to determine the accurate frequencies of higher emissions will be checked on a open test site. As the same purpose, for emission frequencies measured above 1 GHz, a pre-scan also be performed with a 1 meter measuring distance before final test.
3. For emission frequencies measured below and above 1 GHz, set the spectrum analyzer on a 100 kHz and 1 MHz resolution bandwidth respectively for each frequency measured in step 2.
4. The search antenna is to be raised and lowered over a range from 1 to 4 meters in horizontally polarized orientation. Position the highness when the highest value is indicated on spectrum analyzer, then change the orientation of EUT on test table over a range from 0 ° to 360 ° with a speed as slow as possible, and keep the azimuth that highest emission is indicated on the spectrum analyzer. Vary the antenna position again and record the highest value as a final reading.
5. Repeat step 4 until all frequencies need to be measured were complete.
6. Repeat step 5 with search antenna in vertical polarized orientations.

During the radiated emission test, the Spectrum Analyzer was set with the following configurations:

Frequency Band (MHz)	Function	Resolution bandwidth	Video Bandwidth
30 to 1000	Peak	100 kHz	100 kHz
Above 1000	Peak	1 MHz	1 MHz
	Average	1 MHz	10 Hz

**Sample Calculation Example**

The field strength is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain (if any) from the measured reading. For the limit is employed average value, therefore the peak value can be transferred to average value by subtracting the duty factor. The basic equation with a sample calculation is as follows:

$$\text{Peak} = \text{Reading} + \text{Corrected Factor}$$

where

$$\text{Corr. Factor} = \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain (if any)}$$

And the average value is

$$\text{Average} = \text{Peak Value} + \text{Duty Factor or}$$

$$\text{Set RBW} = 1\text{MHz, VBW} = 10\text{Hz.}$$

Note :

If the measured frequencies are fall in the restricted frequency band, the limit employed must be quasi peak value when frequencies are below or equal to 1 GHz. And the measuring instrument is set to quasi peak detector function.

## **Annex B EUT AND TEST SETUP PHOTOGRAPHS**

**Please see the attachment**

## **Annex C. TEST SETUP AND SUPPORTING EQUIPMENT**


### **EUT TEST CONDITIONS**

#### **Annex C. i. SUPPORTING EQUIPMENT DESCRIPTION**


The following is a description of supporting equipment and details of cables used with the EUT.

<b>Equipment Description (Including Brand Name)</b>	<b>Model &amp; Serial Number</b>	<b>Cable Description (List Length, Type &amp; Purpose)</b>
PC Laptop / DELL	Latitude DS520	USB & Serial Cable , 1meter From PC Laptop to EUT

### Block Configuration Diagram for Radiated Emission



### Block Configuration Diagram for Conducted Emission





**Annex C.ii. EUT OPERATING CONDITIONS**

The following is the description of how the EUT was exercised during testing.

Test	Description Of Operation
<p><b>Emissions Testing</b></p>	<p>The EUT was connected to PC and configured using manufacturer's program for continuous printing to simulate the worst case.</p>
<p><b>Others Testing</b></p>	<p>The EUT was connected to PC and configured using manufacturer's program for TX mode with full power to simulate the worst case.</p>

## **Annex D USER MANUAL, BLOCK & CIRCUIT DIAGRAM**

**Please see attachment**