

RF TEST REPORT



Report No.: FCC_IC_RF_SL18032902-ZBR-011_DSS
Supersede Report No.:

Applicant	:	Zebra Technologies Corporation
Host Product Name	:	Mobile Thermal Printer
Host Model No.	:	ZQ610 and ZQ620
Module Model No.	:	WYSBHVXGXG
Test Standard	:	47 CFR 15.247 RSS247 Issue 2, 2017
Test Method	:	ANSI C63.10: 2013 RSS-Gen Issue 4, Nov 2014 FCC Public Notice DA 00-705
FCC ID	:	I28MD-FXLAN11AC
IC ID	:	3798B-FXLAN11AC
Dates of test	:	04/19/2018 – 04/24/2018
Issue Date	:	04/30/2018
Test Result	:	☒ Pass ☐ Fail
Equipment complied with the specification ☒		
Equipment did not comply with the specification ☐		

This Test Report is Issued Under the Authority of:

Rachana Khanduri	Chen Ge
Test Engineer	Engineer Reviewer

Issued By:
SIEMIC Laboratories
775 Montague Expressway, Milpitas, 95035 CA



775 Montague Expressway, Milpitas, CA 95035, USA • Phone: (+1) 408 526 1188 • Facsimile (+1) 408 526 1088

Visit us at: www.siemmic.com; Follow us at:



Laboratory Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Accreditation Body	Scope
USA	FCC, A2LA	EMC, RF/Wireless, Telecom
Canada	IC, A2LA, NIST	EMC, RF/Wireless, Telecom
Taiwan	BSMI, NCC, NIST	EMC, RF, Telecom, Safety
Hong Kong	OFTA, NIST	RF/Wireless, Telecom
Australia	NATA, NIST	EMC, RF, Telecom, Safety
Korea	KCC/RRR, NIST	EMI, EMS, RF, Telecom, Safety
Japan	VCCI, JATE, TELEC, RFT	EMI, RF/Wireless, Telecom
Mexico	NOM, COFETEL, Caniety	Safety, EMC, RF/Wireless, Telecom
Europe	A2LA, NIST	EMC, RF, Telecom, Safety
Israel	MOC, NIST	EMC, RF, Telecom, Safety

Accreditations for Product Certifications

Country	Accreditation Body	Scope
USA	FCC TCB, NIST	EMC, RF, Telecom
Canada	IC FCB, NIST	EMC, RF, Telecom
Singapore	iDA, NIST	EMC, RF, Telecom
EU	NB	EMC & Radio Equipment Directive (RED)
Japan	MIC (RCB 208)	RF, Telecom
Hong Kong	OFTA (US002)	RF, Telecom

CONTENTS

1	REPORT REVISION HISTORY	4
2	EXECUTIVE SUMMARY	5
3	CUSTOMER INFORMATION	5
4	TEST SITE INFORMATION	5
5	MODIFICATION	5
6	EUT INFORMATION	6
6.1	EUT Description	6
6.2	Spec for BT Radio	6
6.3	EUT test modes/configuration Description.....	6
7	SUPPORTING EQUIPMENT/SOFTWARE AND CABLING DESCRIPTION.....	7
7.1	Supporting Equipment	7
7.2	Cabling Description	7
7.3	Test Software Description	7
8	TEST SUMMARY	8
9	MEASUREMENT UNCERTAINTY	9
9.1	Conducted Emissions	9
9.2	Radiated Emissions (30MHz to 1GHz).....	9
9.3	Radiated Emissions (1GHz to 40GHz).....	10
9.4	RF conducted measurement.....	10
10	MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	11
10.1	Antenna Requirement	11
10.2	Transmitter Radiated Spurious Emissions Below 1GHz.....	12
10.3	Transmitter Radiated Spurious Emissions > 1GHz & Restricted band & non-restricted band emission	14
	ANNEX A. TEST INSTRUMENT	19
	ANNEX B. SIEMIC ACCREDITATION	20

1 Report Revision History

Report No.	Report Version	Description	Issue Date
FCC_IC_RF_SL18032902-ZBR-011_DSS	None	Original	04/30/2018

2 Executive Summary

The purpose of this test program was to demonstrate compliance of following product

Company: Zebra Technologies Corporation
Host Product Name: Mobile Thermal Printer
Host Model No.: ZQ610 and ZQ620
Module Model No. WYSBHVXGX

against the current Stipulated Standards. The specified model product stated above has demonstrated compliance with the Stipulated Standard listed on 1st page.

3 Customer information

Applicant Name	Zebra Technologies Corp.
Applicant Address	3 Overlook Point, Lincolnshire, IL 60069
Manufacturer Name	Zebra Technologies Corp.
Manufacturer Address	3 Overlook Point, Lincolnshire, IL 60069

4 Test site information

Lab performing tests	SIEMIC Laboratories
Lab Address	775 Montague Expressway, Milpitas, CA 95035
FCC Test Site No.	881796
IC Test Site No.	4842D-2
VCCI Test Site No.	A0133

5 Modification

Index	Item	Description	Note
-	-	-	-

6 EUT Information

6.1 EUT Description

Host Product Name	Mobile Thermal Printer
Host Model No.	ZQ610 and ZQ620
Module Model No.	WYSBHVXG
Trade Name	Zebra
Serial No.	XXZJJ181101055
Input Power	100-240VAC,50/60Hz
Power Adapter Manu/Model	FSP025-DYAA3
Power Adapter SN	N/A
Product Hardware version	N/A
Product Software version	39869
Radio Hardware version	N/A
Radio Software version	15.68.07.p62
Date of EUT received	04/19/2018
Equipment Class/ Category	FHSS
Port/Connectors	USB
Remark	NONE

6.2 Spec for BT Radio

Radio Type	Bluetooth (Ver4.0+EDR)
Operating Frequency	2402MHz-2480MHz
Modulation	FHSS (BDR, EDR)
Channel Spacing	1MHz (BDR, EDR)
Antenna Type	Patch Antenna
Antenna Gain	3.66 dBi
Antenna Connector Type	U.FL connector

6.3 EUT test modes/configuration Description

Mode	Note
Bluetooth	BDR (GFSK)
Bluetooth	EDR (8-DPSK)

7 Supporting Equipment/Software and cabling Description

7.1 Supporting Equipment

Item	Supporting Equipment Description	Model	Serial Number	Manufacturer	Note
1	Laptop	ThinkPad T420s	N/A	Lenovo	-

7.2 Cabling Description

Name	Connection Start		Connection Stop		Length / shielding Info		Note
	From	I/O Port	To	I/O Port	Length (m)	Shielding	
USB	EUT	I/O Port	Laptop	USB	2	Unshielded	-

7.3 Test Software Description

Test Item	Software	Description
RF Testing	Zebra Toolbox	Set the EUT to transmit continuously in diferent test mode

8 Test Summary

Test Item	Test standard		Test Method/Procedure		Pass / Fail
Antenna Requirement	FCC	15.203	FCC	ANSI C63.10 – 2013 558074 D01 DTS Meas. Guidance v03r02	☒ Pass
	IC	-	IC		☐ N/A
Restricted Band of Operation	FCC	15.205	FCC	ANSI C63.10: 2013 Public Notice DA 00-705	☒ Pass
	IC	RSS Gen 8.10	IC	RSS Gen Issue 4: 2014	☐ N/A
AC Conducted Emissions Voltage	FCC	15.207(a)	FCC	ANSI C63.10: 2013	☒ Pass*
	IC	RSS Gen 8.8	IC	RSS Gen Issue 4: 2014	☐ N/A

DSS Band Requirement

Test Item	Test standard		Test Method/Procedure		Pass / Fail
Channel Separation	FCC	15.247 (a)(1)	FCC	Public Notice DA 00-705	☒ Pass*
	IC	RSS247 (5.1.5)	IC	-	☐ N/A
20dB Occupied Bandwidth	FCC	15.247(a)(1)	FCC	Public Notice DA 00-705	☒ Pass*
	IC	RSS247 (5.1.2)	IC	-	☐ N/A
99% Occupied Bandwidth	FCC	15.247(a)(2)	FCC		☒ Pass*
	IC	RSS Gen 6.6	IC	RSS Gen Issue 4: 2014 -	☐ N/A
Number of Hopping Channels	FCC	15.247(a)(1)	FCC	Public Notice DA 00-705	☒ Pass*
	IC	RSS247 (5.1.5)	IC	-	☐ N/A
Band Edge and Radiated Spurious Emissions	FCC	15.247(d)	FCC	Public Notice DA 00-705	☒ Pass
	IC	RSS247(5.5)	IC	-	☐ N/A
Time of Occupancy	FCC	15.247(a)(1)	FCC	Public Notice DA 00-705	☒ Pass*
	IC	RSS247 (5.1.5)	IC	-	☐ N/A
Output Power	FCC	15.247(b)	FCC	Public Notice DA 00-705	☒ Pass*
	IC	RSS247 (5.4.2)	IC	-	☐ N/A
Receiver Spurious Emissions	FCC	15.247(d)	FCC	-	☐ Pass
	IC	RSS Gen (7.1)	IC	RSS Gen (7.1)	☒ N/A
Antenna Gain > 6 dBi	FCC	15.247(e)	FCC	Public Notice DA 00-705	☐ Pass
	IC	RSS247 (5.4.6)	IC	-	☒ N/A
Power Spectral Density	FCC	15.247(e)	FCC	Public Notice DA 00-705	☐ Pass
	IC	RSS247 (5.2.2)	IC	-	☒ N/A
Hybrid System Requirement	FCC	15.247(f)	FCC	Public Notice DA 00-705	☐ Pass
	IC	RSS247 (5.3)	IC	-	☒ N/A
Hopping Capability	FCC	15.247(g)	FCC	Public Notice DA 00-705	☒ Pass*
	IC	RSS247 (5.1.5)	IC	-	☐ N/A
RF Exposure requirement	FCC	15.247(i)	FCC	Public Notice DA 00-705	☐ Pass
	IC	RSS Gen(3.2)	IC	-	☒ N/A

Remark

- All measurement uncertainties are not taken into consideration for all presented test result.
- The applicant shall ensure frequency stability by showing that an emission is maintained within the band of operation under all normal operating conditions as specified in the user's manual.
- Pass* : Please refer to FCC ID: I28MD-FXLAN11A test report.
- ZQ610 host printer was used for testing. The only difference between ZQ610 and ZQ620 is the print head size. The size of enclosures is slightly different in the neighborhood of 2" vs. 3".

9 Measurement Uncertainty

9.1 Conducted Emissions

The test is to measure the conducted emissions to the mains port of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the LISN
- Uncertainty of cables
- Uncertainty due to the mismatches
- Etc, see the below table for details

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Receiver Reading	0.12	Rectangular	1.732	1	0.069284
Cable Insertion Loss	0.21	Normal	2	1	0.105
Filter Insertion Loss	0.25	Normal	2	1	0.125
LISN Insertion Loss	0.40	Normal	2	1	0.20
Receiver CW accuracy	0.5	Rectangular	1.732	1	0.2886836
Pulse Amplitude Response	1.5	Rectangular	1.732	1	0.86605081
PRF Response	1.5	Rectangular	1.732	1	0.86605081
Mismatch LISN - Receiver	0.25	U-Shape	1.414	1	0.1768033
LISN Impedance	2.5	Triangular	2.449	1	1.0208248
Combined Standard Uncertainty					1.928133
Expanded Uncertainty (K=2)					3.856266

The total derived measurement uncertainty is +/- 3.86 dB.

9.2 Radiated Emissions (30MHz to 1GHz)

The test is to measure the radiated emissions of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the antenna
- Uncertainty of cables
- Uncertainty due to the mismatches
- NSA Calibration
- Etc., details see the below table

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Receiver Reading	0.12	Rectangular	1.732	1	0.069284
Cable Insertion Loss	0.21	Normal	2	1	0.105
Filter Insertion Loss	0.25	Normal	2	1	0.125
Antenna Factor	0.65	Normal	2	1	0.325
Receiver CW accuracy	0.5	Rectangular	1.732	1	0.2886836
Pulse Amplitude Response	1.5	Rectangular	1.732	1	0.86605081
PRF Response	1.5	Rectangular	1.732	1	0.86605081
Mismatch Filter - Receiver	0.25	U-Shape	1.414	1	0.1768033
NSA Calibration	4.0	U-Shape	1.414	1	2.8288543
Combined Standard Uncertainty					3.0059131
Expanded Uncertainty (K=2)					6.0118262

The total derived measurement uncertainty is +/- 6.00 dB.

9.3 Radiated Emissions (1GHz to 40GHz)

The test is to measure the radiated emissions of the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the receiver
- Uncertainty of the antenna
- Uncertainty of cables
- Uncertainty due to the mismatches
- VSWR Calibration
- Etc., details see the below table

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Receiver Reading	0.12	Rectangular	1.732	1	0.0692840
Cable Insertion Loss	0.21	Normal	2	1	0.1050000
Filter Insertion Loss	0.25	Normal	2	1	0.1250000
Antenna Factor	0.65	Normal	2	1	0.3250000
Receiver CW accuracy	0.5	Rectangular	1.732	1	0.2886836
Pulse Amplitude Response	1.5	Rectangular	1.732	1	0.8660508
PRF Response	1.5	Rectangular	1.732	1	0.8660508
Mismatch Filter - Receiver	0.25	U-Shape	1.414	1	0.1768033
VSWR Calibration	2.0	U-Shape	1.414	1	1.4144272
Combined Standard Uncertainty					4.2363
Expanded Uncertainty (K=2)					8.4726

The total derived measurement uncertainty is +/- 8.47 dB.

9.4 RF conducted measurement

The test is to measure the RF output power from the EUT.

Some error sources that can contribute to the total uncertainty:

- Uncertainty of the Reference Level Uncertainty
- Uncertainty of variable attenuators
- Uncertainty of cables
- Uncertainty due to the mismatches

Source of Uncertainty	Value (dB)	Probability Distribution	Division	Sensitivity Coefficient	Expanded Uncertainty
Reference Level	0.12	Rectangular	1.732	1	0.069284
Cable Insertion Loss	0.21	Normal	2	1	0.105
Attenuator	0.25	Normal	2	1	0.125
Mismatch	0.25	U-Shape	1.414	1	0.1768033
Combined Standard Uncertainty					0.476087
Expanded Uncertainty (K=2)					0.952174

The total derived measurement uncertainty is +/- 0.95 dB.


10 Measurements, Examination and Derived Results

10.1 Antenna Requirement

Spec	Requirement	Applicable
§15.203	An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. Antenna requirement must meet at least one of the following: a) Antenna must be permanently attached to the device. b) The antenna must use a unique type of connector to attach to the device. c) Device must be professionally installed. The installer shall be responsible for ensuring that the correct antenna is employed by the device.	☒
Remark	The EUT uses a u.fl connector for antenna connection which meet the requirement.	
Result	☒ PASS ☐ FAIL	

10.2 Transmitter Radiated Spurious Emissions Below 1GHz

Requirement(s):

Spec	Item	Requirement	Applicable							
47CFR§15.247(d), RSS247(5.5)	a)	Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges	☒							
		<table><thead><tr><th>Frequency range (MHz)</th><th>Field Strength (uV/m)</th></tr></thead><tbody><tr><td>30 – 88</td><td>100</td></tr><tr><td>88 – 216</td><td>150</td></tr><tr><td>216 960</td><td>200</td></tr><tr><td>Above 960</td><td>500</td></tr></tbody></table>		Frequency range (MHz)	Field Strength (uV/m)	30 – 88	100	88 – 216	150	216 960
Frequency range (MHz)	Field Strength (uV/m)									
30 – 88	100									
88 – 216	150									
216 960	200									
Above 960	500									
Test Setup										
Procedure	1. 2. 3. 4. The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: a. b. c. Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. The EUT was then rotated to the direction that gave the maximum emission. Finally, the antenna height was adjusted to the height that gave the maximum emission. A Quasi-peak measurement was then made for that frequency point. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.									
Remark	The EUT was scanned up to 1GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.									
Result	☒ Pass ☐ Fail									


Test Data ☒ Yes (See below) ☐ N/A

Test Plot ☒ Yes (See below) ☐ N/A

Test was done by *Rachana Khanduri* **at** *10m Chamber*.

Radiated Emission Test Results (Below 1GHz)

Test specification:	Radiated Spurious Emissions (30MHz – 1000MHz)			
Environmental Conditions:	Temp(°C):	22	Result :	☒ Pass ☐ Fail
	Humidity (%):	37		
	Atmospheric(mbar):	1021		
Mains Power:	120VAC, 60Hz			
Tested by:	Rachana Khanduri			
Test Date:	04/19/2018			
Remarks:	BDR 2441MHz			




Quasi Max Measurement

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
35.48	20.84	11.21	-17.78	14.27	Quasi Max	V	239	213	40	-25.73	Pass
41.70	33.54	11.34	-22.34	22.54	Quasi Max	V	123	288	40	-17.46	Pass
72.04	50.88	11.60	-27.69	34.79	Quasi Max	V	108	188	40	-5.21	Pass
84.01	50.50	11.72	-28.02	34.20	Quasi Max	V	141	157	40	-5.80	Pass
119.97	44.11	12.07	-22.87	33.31	Quasi Max	V	118	228	43.5	-10.20	Pass
864.61	30.44	15.60	-14.09	31.95	Quasi Max	H	100	244	46	-14.05	Pass

Note: Both horizontal and vertical polarities were investigated. The results above show only the worst case.

10.3 Transmitter Radiated Spurious Emissions > 1GHz & Restricted band & non-restricted band emission

Requirement(s):

Spec	Item	Requirement	Applicable
47CFR§15.247(d), RSS247(5.5)	a)	For non-restricted band, In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB or 30dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, determined by the measurement method on output power to be used. Attenuation below the general limits specified in § 15.209(a) is not required ☒ 20 dB down ☐ 30 dB down	☒
	b)	or restricted band, emission must also comply with the radiated emission limits specified in 15.209	☒
Test Setup			
Procedure	- The EUT was switched on and allowed to warm up to its normal operating condition. - The test was carried out at the selected frequency points obtained from the EUT characterisation. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: - Vertical or horizontal polarisation (whichever gave the higher emission level over a full rotation of the EUT) was chosen. - The EUT was then rotated to the direction that gave the maximum emission. - Finally, the antenna height was adjusted to the height that gave the maximum emission. - An average measurement was then made for that frequency point. - Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.		
Remark	The EUT was scanned up to 26GHz. Both horizontal and vertical polarities were investigated. The results show only the worst case.		
Result	☒ Pass ☐ Fail		

Test Data ☒ Yes (See below) ☐ N/A

Test Plot ☐ Yes (See below) ☒ N/A

Test was done by **Rachana Khanduri** at **3m Chamber**.

Radiated Emission Test Results

Bluetooth BDR – 2402MHz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
3312.03	49.67	3.49	-1.60	51.56	Peak Max	V	151	312	74	-22.44	Pass
7205.70	39.20	5.14	-0.57	43.78	Peak Max	V	245	123	74	-30.22	Pass
4804.19	39.12	4.06	-0.92	42.26	Peak Max	V	173	247	74	-31.74	Pass
3312.03	46.87	3.49	-1.60	48.77	Average Max	V	151	312	54	-5.23	Pass
7205.70	25.92	5.14	-0.57	30.50	Average Max	V	245	123	54	-23.50	Pass
4804.19	26.83	4.06	-0.92	29.96	Average Max	V	173	247	54	-24.04	Pass

Bluetooth BDR – 2441MHz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
9930.78	39.63	5.81	1.19	46.63	Peak Max	V	101	250	74	-27.37	Pass
1871.88	40.78	2.66	-2.96	40.48	Peak Max	H	214	157	74	-33.53	Pass
4882.10	39.46	4.08	-0.92	42.62	Peak Max	V	184	95	74	-31.38	Pass
9930.78	26.98	5.81	1.19	33.98	Average Max	V	101	250	54	-20.02	Pass
1871.88	29.16	2.66	-2.96	28.85	Average Max	H	214	157	54	-25.15	Pass
4882.10	26.57	4.08	-0.92	29.73	Average Max	V	184	95	54	-24.27	Pass

Bluetooth BDR – 2480MHz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
9429.00	38.67	5.72	0.35	44.73	Peak Max	V	104	4	74	-29.27	Pass
7440.43	38.02	4.91	-0.26	42.67	Peak Max	V	285	29	74	-31.33	Pass
4960.91	38.62	3.93	-0.90	41.65	Peak Max	V	201	346	74	-32.35	Pass
9429.00	26.76	5.72	0.35	32.82	Average Max	V	104	4	54	-21.18	Pass
7440.43	25.98	4.91	-0.26	30.64	Average Max	V	285	29	54	-23.37	Pass
4960.91	26.22	3.93	-0.90	29.25	Average Max	V	201	346	54	-24.75	Pass

Bluetooth EDR – 2402MHz

Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
1912.01	46.37	2.68	-2.61	46.44	Peak Max	V	195	115	74	-27.56	Pass
9917.10	38.71	5.78	1.18	45.68	Peak Max	H	274	185	74	-28.32	Pass
4803.67	39.09	4.10	-0.93	42.27	Peak Max	V	142	154	74	-31.73	Pass
1912.01	41.62	3.49	-2.61	42.50	Average Max	V	195	115	54	-11.50	Pass
9917.10	26.76	5.78	1.18	33.72	Average Max	H	274	185	54	-20.28	Pass
4803.67	26.36	4.10	-0.93	29.54	Average Max	V	142	154	54	-24.46	Pass

Bluetooth EDR – 2441MHz


Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
9397.62	38.61	5.73	0.35	44.69	Peak Max	V	323	15	74	-29.31	Pass
4668.38	39.24	4.11	-0.91	42.44	Peak Max	V	141	203	74	-31.56	Pass
2003.23	40.46	2.74	-2.39	40.81	Peak Max	V	299	196	74	-33.20	Pass
9397.62	26.44	5.73	0.35	32.52	Average Max	V	323	15	54	-21.48	Pass
4668.38	26.65	4.11	-0.91	29.85	Average Max	V	141	203	54	-24.15	Pass
2003.23	28.21	2.74	-2.39	28.56	Average Max	V	299	196	54	-25.45	Pass

Bluetooth EDR – 2480MHz


Frequency (MHz)	Raw (dBuV)	Cable Loss (dB)	AF (dB)	Level (dBuV/m)	Measurement Type	Pol (V/H)	Hgt (cm)	Azt (Deg)	Limit (dBuV/m)	Margin (dB)	Pass /Fail
9414.24	38.88	5.72	0.33	44.93	Peak Max	V	145	288	74	-29.07	Pass
4960.23	38.78	3.93	-0.90	41.81	Peak Max	V	168	311	74	-32.19	Pass
7439.54	38.31	4.91	-0.26	42.96	Peak Max	V	210	174	74	-31.04	Pass
9414.24	26.82	5.72	0.33	32.87	Average Max	V	145	288	54	-21.13	Pass
4960.23	26.18	3.93	-0.90	29.21	Average Max	V	168	311	54	-24.79	Pass
7439.54	25.62	4.91	-0.26	30.27	Average Max	V	210	174	54	-23.73	Pass

Note: Both horizontal and vertical polarities were investigated. The results above show only the worst case.


Restricted Band Test plot (Bluetooth BDR/EDR)




Restricted Band BDR 2402MHz



Restricted Band BDR 2480MHz



Restricted Band EDR 2402MHz



Restricted Band EDR 2480MHz

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Cycle	Cal Due	In use
Radiated Emissions						
Keysight EXA 44GHz Spectrum Analyzer	N9030B(PXA)	MY57140374	09/06/2017	1 Year	09/06/2018	☒
Bi-Log antenna (30MHz~2GHz)	JB1	A030702	03/09/2018	2 Year	03/09/2020	☒
Horn Antenna (1GHz~26GHz)	3115	100059	11/09/2017	1 Year	11/09/2018	☒
Horn Antenna (18GHz~40GHz)	PA-840	181251	06/23/2017	1 Year	06/23/2018	☒
Preamplifier (100KHz~7GHz)	LPA-6-30	11170602	05/09/2017	1 Year	05/09/2018	☒
Pre-Amplifier (1-26.5GHz)	8449B	3008A00715	08/16/2017	1 Year	08/16/2018	☒

Annex B. SIEMIC Accreditation

Accreditations	Document	Scope / Remark
ISO 17025 (A2LA)		Please see the documents for the detailed scope
ISO Guide 65 (A2LA)		Please see the documents for the detailed scope
TCB Designation		A1 , A2 , A3 , A4 , B1 , B2 , B3 , B4 , C
FCC DoC Accreditation		FCC Declaration of Conformity Accreditation
FCC Site Registration		3 meter site
FCC Site Registration		10 meter site
IC Site Registration		3 meter site
IC Site Registration		10 meter site
EU NB		Radio & Telecommunications Terminal Equipment: EN45001 – EN ISO/IEC 17025
		Electromagnetic Compatibility: EN45001 – EN ISO/IEC 17025
Singapore iDA CB(Certification Body)	 	Phase I , Phase II
Vietnam MIC CAB Accreditation		Please see the document for the detailed scope
Hong Kong OFCA		(Phase II) OFCA Foreign Certification Body for Radio and Telecom
		(Phase I) Conformity Assessment Body for Radio and Telecom
Industry Canada CAB		Radio: Scope A – All Radio Standard Specification in Category I
		Telecom: CS-03 Part I, II, V, VI, VII, VIII

Japan Recognized Certification Body Designation		Radio: A1. Terminal equipment for purpose of calling Telecom: B1. Specified radio equipment specified in Article 38-2, Paragraph 1, Item 1 of the Radio Law
Korea CAB Accreditation		EMI: KCC Notice 2008-39, RRL Notice 2008-3: CA Procedures for EMI KN22: Test Method for EMI EMS: KCC Notice 2008-38, RRL Notice 2008-4: CA Procedures for EMS KN24, KN61000-4-2, -4-3, -4-4, -4-5, -4-6, -4-8, -4-11: Test Method for EMS Radio: RRL Notice 2008-26, RRL Notice 2008-2, RRL Notice 2008-10, RRL Notice 2007-49, RRL Notice 2007-20, RRL Notice 2007-21, RRL Notice 2007-80, RRL Notice 2004-68 Telecom: President Notice 20664, RRL Notice 2007-30, RRL Notice 2008-7 with attachments 1, 3, 5, 6; President Notice 20664, RRL Notice 2008-7 with attachment 4
Taiwan NCC CAB Recognition		LP0002, PSTN01, ADSL01, ID0002, IS6100, CNS14336, PLMN07, PLMN01, PLMN08
Taiwan BSMI CAB Recognition		CNS 13438
Japan VCCI		R-3083: Radiation 3 meter site C-3421: Main Ports Conducted Interference Measurement T-1597: Telecommunication Ports Conducted Interference Measurement
Australia CAB Recognition		EMC: AS/NZS CISPR 11, AS/NZS CISPR 14.1, AS/NZS CISPR22, AS/NZS 61000.6.3, AS/NZS 61000.6.4 Radio communications: AS/NZS 4281, AS/NZS 4268, AS/NZS 4280.1, AS/NZS 4280.2, AS/NZS 4295, AS/NZS 4582, AS/NZS 4583, AS/NZS 4769.1, AS/NZS 4769.2, AS/NZS 4770, AS/NZS 4771 Telecommunications: AS/ACIF S002:05, AS/ACIF S003:06, AS/ACIF S004:06 AS/ACIF S006:01, AS/ACIF S016:01, AS/ACIF S031:01, AS/ACIF S038:01, AS/ACIF S040:01, AS/ACIF S041:05, AS/ACIF S043.2:06, AS/ACIF S60950.1
Australia NATA Recognition		AS/ACIF S002, AS/ACIF S003, AS/ACIF S004, AS/ACIF S006, AS/ACIF S016, AS/ACIF S031, AS/ACIF S038, AS/ACIF S040, AS/ACIF S041, AS/ACIF S043.2