

Contents

Introduction
Hello!
What's in the Box?
Inspecting the Printer
Opening the printer
Closing the printer
Reporting Damage. 6 FCC STATEMENTS. 6
Getting Started 6
Modes of Printing
Attaching Power Supply
Loading Roll Media
Placing the Roll in the Media Compartment
Adjusting the Guides
Loading Ribbon
Install the Ribbon Supply Roll
Install the Take-Up Core
Attach and Tighten the Ribbon
Auto Calibration
Operator Controls
Power Switch
Feed Button
Status Light
Printing a Test Label
Hooking Up the Printer and Computer
Parallel Interface Requirements
Interface Cable Requirements
Communicating with the Printer
Adjusting the Print Width
Adjusting the Print Darkness
Adjusting the Print Speed
Operation & Options
Thermal Printing
Replacing Supplies
Adding a New Transfer Ribbon
Zebra R402 User's Guide iii









Reporting Damage

If you discover damage or missing parts:

- Immediately notify and file a damage report with the shipping company. Zebra Technologies Corporation is not responsible for any damage incurred during shipment of the printer and will not cover the repair of this damage under its warranty policy.
- Keep the carton and all packing material for inspection.
- Notify the authorized reseller

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will no occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- -Reorient or relocate the receiving antenna.
- -Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- -Consult the dealer or an experienced radio/TV technician for help.

The user is caution that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.





