



# FCC RF Test Report

**APPLICANT** : Leadtek Research Inc.  
**EQUIPMENT** : amor H100 cloud gateway  
**BRAND NAME** : LEADTEK  
**MODEL NAME** : 8Z61  
**FCC ID** : I2I8Z61  
**STANDARD** : FCC 47 CFR Part 2, 22(H), 24(E)  
**CLASSIFICATION** : PCS Licensed Transmitter (PCB)

The product was received on Apr. 28, 2015 and testing was completed on Oct. 31, 2015. We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Reviewed by: Joseph Lin / Supervisor

Approved by: Jones Tsai / Manager



**SPORTON INTERNATIONAL INC.**  
No. 52, Hwa Ya 1<sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C.



## TABLE OF CONTENTS

<b>REVISION HISTORY.....</b>	<b>3</b>
<b>SUMMARY OF TEST RESULT .....</b>	<b>4</b>
<b>1 GENERAL DESCRIPTION .....</b>	<b>5</b>
1.1 Applicant.....	5
1.2 Manufacturer .....	5
1.3 Product Feature of Equipment Under Test .....	5
1.4 Product Specification subjective to this standard.....	6
1.5 Modification of EUT .....	6
1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator .....	7
1.7 Testing Location .....	8
1.8 Applicable Standards .....	8
<b>2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST .....</b>	<b>9</b>
2.1 Test Mode.....	9
2.2 Connection Diagram of Test System .....	10
2.3 Support Unit used in test configuration .....	10
2.4 Measurement Results Explanation Example .....	10
<b>3 CONDUCTED TEST RESULT.....</b>	<b>11</b>
3.1 Measuring Instruments.....	11
3.2 Test Setup .....	11
3.3 Test Result of Conducted Test.....	11
3.4 Conducted Output Power .....	12
3.5 Peak-to-Average Ratio .....	13
3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement.....	14
3.7 Conducted Band Edge .....	15
3.8 Conducted Spurious Emission .....	16
3.9 Frequency Stability .....	17
<b>4 RADIATED TEST ITEMS .....</b>	<b>18</b>
4.1 Measuring Instruments.....	18
4.2 Test Setup .....	18
4.3 Test Result of Radiated Test.....	18
4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement .....	19
4.5 Field Strength of Spurious Radiation Measurement .....	21
<b>5 LIST OF MEASURING EQUIPMENT .....</b>	<b>22</b>
<b>6 UNCERTAINTY OF EVALUATION.....</b>	<b>23</b>

### APPENDIX A. TEST RESULTS OF CONDUCTED TEST

### APPENDIX B. TEST RESULTS OF RADIATED TEST

### APPENDIX C. TEST SETUP PHOTOGRAPHS



## REVISION HISTORY



## SUMMARY OF TEST RESULT

Report Section	FCC Rule	IC Rule	Description	Limit	Result	Remark
3.4	§2.1046	RSS-132 (5.4) RSS-133 (6.4)	Conducted Output Power	Reporting Only	PASS	-
3.4	§90.635	N/A	Conducted Output Power	<100W	PASS	-
3.5	§24.232(d)	RSS-132 (5.4) RSS-133 (6.4) RSS-139 (6.5)	Peak-to-Average Ratio	< 13 dB	PASS	-
3.6	§2.1049 §22.917(b) §24.238(b)	RSS-GEN(6.6) RSS-132(3.1) RSS-133(3.1)	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Band Edge Measurement	< 43+10log10(P[Watts])	PASS	-
3.8	§2.1051 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Conducted Emission	< 43+10log10(P[Watts])	PASS	-
3.9	§2.1055 §22.355	RSS-GEN(6.11) RSS-132 (5.3)	Frequency Stability for Temperature & Voltage	< 2.5 ppm for Part 22	PASS	-
	§2.1055 §24.235	RSS-GEN(6.11) RSS-133 (6.3)		Within Authorized Band		
4.4	§22.913(a)(2)	RSS-132(5.4) SRSP-503(5.1.3)	Effective Radiated Power	< 7 Watts	PASS	-
	§24.232(c)	RSS-133 (6.4) SRSP-510(5.1.2)	Equivalent Isotropic Radiated Power	< 2 Watts	PASS	-
4.5	§2.1053 §22.917(a) §24.238(a)	RSS-132 (5.5) RSS-133 (6.5)	Field Strength of Spurious Radiation	< 43+10log10(P[Watts])	PASS	Under limit 8.63 dB at 2472.000 MHz



## 1 General Description

### 1.1 Applicant

**Leadtek Research Inc.**

18F., No. 166, Jian-Yi Rd., Chung-Ho Dist., New Taipei City 23511, Taiwan, R.O.C.

### 1.2 Manufacturer

**Leadtek Research Inc.**

5F, No. 4, Alley 11, Lane 327, Sec. 2, Chung Shan Rd., Chung-Ho Dist., New Taipei City 23511, Taiwan, R.O.C.

### 1.3 Product Feature of Equipment Under Test

Product Feature	
<b>Equipment</b>	amor H100 cloud gateway
<b>Brand Name</b>	LEADTEK
<b>Model Name</b>	8Z61
<b>FCC ID</b>	I2I8Z61
<b>EUT supports Radios application</b>	GSM/EGPRS/WCDMA/HSPA/SDR WLAN 11b/g/n HT20 Bluetooth v4.0 LE
<b>HW Version</b>	V1.0
<b>SW Version</b>	V1.0 KOT 49H test Keys
<b>EUT Stage</b>	Production Unit

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.



## 1.4 Product Specification subjective to this standard

Product Specification subjective to this standard	
<b>Tx Frequency</b>	<b>GSM/GPRS/EDGE:</b> 850: 824.2 MHz ~ 848.8 MHz 1900: 1850.2 MHz ~ 1909.8MHz <b>WCDMA:</b> Band V: 826.4 MHz ~ 846.6 MHz
<b>Rx Frequency</b>	<b>GSM/GPRS/EDGE:</b> 850: 869.2 MHz ~ 893.8 MHz 1900: 1930.2 MHz ~ 1989.8 MHz <b>WCDMA:</b> Band V: 871.4 MHz ~ 891.6 MHz
<b>Maximum Output Power to Antenna</b>	<b>GSM/GPRS/EDGE:</b> 850: 32.71 dBm 1900: 29.61 dBm <b>WCDMA:</b> Band V: 22.16 dBm
<b>Antenna Type</b>	PIFA Antenna
<b>Antenna Gain</b>	Cellular Band: 1.60 dBi PCS Band: 1.60 dBi
<b>Type of Modulation</b>	GSM: GMSK GPRS: GMSK EDGE: GMSK / 8PSK WCDMA: QPSK (Uplink) HSDPA: QPSK (Uplink) HSUPA: QPSK (Uplink)

## 1.5 Modification of EUT

No modifications are made to the EUT during all test items.



## 1.6 Maximum ERP/EIRP Power, Frequency Tolerance, and Emission Designator

FCC Rule	System	Type of Modulation	Maximum ERP/EIRP (W)	Frequency Tolerance (ppm)	Emission Designator
Part 22	GSM850 GPRS class 8	GMSK	0.4826	0.0084 ppm	248KGXW
Part 22	GSM850 EDGE class 8	8PSK	0.2572	0.0108 ppm	262KG7W
Part 22	WCDMA Band V RMC 12.2Kbps	QPSK	0.0495	0.0084 ppm	4M11F9W
Part 24	GSM1900 GPRS class 8	GMSK	0.3677	0.0255 ppm	248KGXW
Part 24	GSM1900 EDGE class 8	8PSK	0.1130	0.0239 ppm	243KG7W



## 1.7 Testing Location

Sportun Lab is accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code : 1190) and the FCC designation No. TW1022 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC Test.

<b>Test Site</b>	SPORTON INTERNATIONAL INC.	
<b>Test Site Location</b>	No. 52, Hwa Ya 1 <sup>st</sup> Rd., Hwa Ya Technology Park, Kwei-Shan District, Tao Yuan City, Taiwan, R.O.C. TEL: +886-3-327-3456 FAX: +886-3-328-4978	
<b>Test Site No.</b>	<b>Sportun Site No.</b>	
	TH03-HY	03CH07-HY

## 1.8 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 22(H), 24(E)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

### Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



## 2 Test Configuration of Equipment Under Test

### 2.1 Test Mode

Antenna port conducted and radiated test items were performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated emissions were investigated as following frequency range:


1. 30 MHz to 9000 MHz for GSM850 and WCDMA Band V.
2. 30 MHz to 19000 MHz for GSM1900.

All modes and data rates and positions were investigated.

Test modes are chosen to be reported as the worst case configuration below:

Test Modes		
Band	Radiated TCs	Conducted TCs
GSM 850	<ul style="list-style-type: none"><li>■ GPRS class 8 Link</li><li>■ EDGE class 8 Link</li></ul>	<ul style="list-style-type: none"><li>■ GPRS class 8 Link</li><li>■ EDGE class 8 Link</li></ul>
GSM 1900	<ul style="list-style-type: none"><li>■ GPRS class 8 Link</li><li>■ EDGE class 8 Link</li></ul>	<ul style="list-style-type: none"><li>■ GPRS class 8 Link</li><li>■ EDGE class 8 Link</li></ul>
WCDMA Band V	<ul style="list-style-type: none"><li>■ RMC 12.2Kbps Link</li></ul>	<ul style="list-style-type: none"><li>■ RMC 12.2Kbps Link</li></ul>

## 2.2 Connection Diagram of Test System



## 2.3 Support Unit used in test configuration

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m

## 2.4 Measurement Results Explanation Example

### For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between RF conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level will be exactly the RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

*Offset = RF cable loss + attenuator factor.*

The following shows an offset computation example with RF cable loss 4.2 dB and a 10dB attenuator.

Example :

$$\begin{aligned} \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)} \\ &= 4.2 + 10 = 14.2 \text{ (dB)} \end{aligned}$$

### 3 Conducted Test Result

#### 3.1 Measuring Instruments


See list of measuring instruments of this test report.

#### 3.2 Test Setup


##### 3.2.1 Conducted Output Power



##### 3.2.2 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge and Conducted Spurious Emission



##### 3.2.3 Frequency Stability



#### 3.3 Test Result of Conducted Test

Please refer to Appendix A.



## 3.4 Conducted Output Power

### 3.4.1 Description of the Conducted Output Power

A system simulator was used to establish communication with the EUT. Its parameters were set to enforce EUT transmitting at the maximum power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

### 3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure the maximum burst average power for GSM and maximum average power for other modulation signal.



## 3.5 Peak-to-Average Ratio

### 3.5.1 Description of the PAR Measurement

The peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. Set EUT to transmit at maximum output power.
4. When the duty cycle is less than 98%, then signal gating will be implemented on the spectrum analyzer by triggering from the system simulator.
5. Set the CCDF (Complementary Cumulative Distribution Function) option of the spectrum analyzer.

Record the maximum PAPR level associated with a probability of 0.1%.



## 3.6 99% Occupied Bandwidth and 26dB Bandwidth Measurement

### 3.6.1 Description of 99% Occupied Bandwidth and 26dB Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace. (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.



## 3.7 Conducted Band Edge

### 3.7.1 Description of Conducted Band Edge Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

### 3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The band edges of low and high channels for the highest RF powers were measured.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.



## 3.8 Conducted Spurious Emission

### 3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10<sup>th</sup> harmonic.

### 3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 6.0.
2. The EUT was connected to the spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by an RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
7. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
 $= P(W) - [43 + 10\log(P)]$  (dB)  
 $= [30 + 10\log(P)]$  (dBm) -  $[43 + 10\log(P)]$  (dB)  
 $= -13$  dBm.



## 3.9 Frequency Stability

### 3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within  $\pm 0.00025\%$  ( $\pm 2.5\text{ppm}$ ) of the center frequency.

### 3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to  $-30^\circ\text{C}$  and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in  $10^\circ\text{C}$  steps up to  $50^\circ\text{C}$ . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 D01 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at  $25\pm 5^\circ\text{C}$  and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


## 4 Radiated Test Items

### 4.1 Measuring Instruments


See list of measuring instruments of this test report.

### 4.2 Test Setup

#### 4.2.1 For radiated test from 30MHz to 1GHz



#### 4.2.2 For radiated test above 1GHz



### 4.3 Test Result of Radiated Test

Please refer to Appendix B.



## 4.4 Effective Radiated Power and Effective Isotropic Radiated Power Measurement

### 4.4.1 Description of the ERP/EIRP Measurement

The substitution method, in ANSI / TIA / EIA-603-D-2010, was used for ERP/EIRP measurement, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. The ERP of mobile transmitters must not exceed 7 Watts (Cellular Band) and the EIRP of mobile transmitters are limited to 2 Watts (PCS Band).

### 4.4.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.2.1. (for CDMA/WCDMA), Section 5.2.2.2 (for GSM/GPRS/EDGE) and ANSI / TIA-603-D-2010 Section 2.2.17.
2. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
3. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
4. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor,  $EIRP = LVL + \text{Correction factor}$  and  $ERP = EIRP - 2.15$ . Take the record of the output power at substitution antenna.



	GSM/GPRS/EDGE	WCDMA/HSPA
SPAN	500kHz	10MHz
RBW	10kHz	100kHz
VBW	30kHz	300kHz
Detector	RMS	RMS
Trace	Average	Average
Average Type	Power	Power
Sweep Count	100	100



## 4.5 Field Strength of Spurious Radiation Measurement

### 4.5.1 Description of Field Strength of Spurious Radiated Measurement

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least  $43 + 10 \log (P)$  dB. The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

### 4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 D01 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table 0.8 meters above the ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search for the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11.  $EIRP \text{ (dBm)} = S.G. \text{ Power} - Tx \text{ Cable Loss} + Tx \text{ Antenna Gain}$
12.  $ERP \text{ (dBm)} = EIRP - 2.15$
13. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
14. The limit line is derived from  $43 + 10\log(P)$  dB below the transmitter power P(Watts)  
$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$
$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)}$$
$$= -13 \text{ dBm.}$$



## 5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	Rohde & Schwarz	FSP30	101329	9kHz~30GHz	Jun. 24, 2015	Oct. 29, 2015	Jun. 23, 2016	Conducted (TH03-HY)
Base Station (Measure)	Rohde & Schwarz	CMU200	117995	GSM / GPRS / WCDMA / CDMA	Jul. 26, 2015	Oct. 29, 2015	Jul. 25, 2016	Conducted (TH03-HY)
Programmable Power Supply	GW Instek	PSS-2005	EL883644	Voltage:0~20V; Current:0~5A	Dec. 01, 2014	Oct. 29, 2015	Nov. 30, 2015	Conducted (TH03-HY)
Temperature Chamber	ESPEC	SU-641	92013721	-30°C~70°C	Dec. 01, 2014	Oct. 29, 2015	Nov. 30, 2015	Conducted (TH03-HY)
Bilog Antenna	Teseq GmbH	CBL6112D	35379	30MHz~2GHz	Oct. 15, 2015	Oct. 31, 2015	Oct. 14, 2016	Radiation (03CH07-HY)
Double Ridge Horn Antenna	ESCO	3117	00075962	1GHz ~ 18GHz	Aug. 21, 2015	Oct. 31, 2015	Aug. 20, 2016	Radiation (03CH07-HY)
EMI Test Receiver	Rohde & Schwarz	ESCI 7	100724	9kHz~7GHz	Aug. 25, 2015	Oct. 31, 2015	Aug. 24, 2016	Radiation (03CH07-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120D	9120D-1328	1GHz ~ 18GHz	Nov. 05, 2014	Oct. 31, 2015	Nov. 04, 2015	Radiation (03CH07-HY)
Horn Antenna	SCHWARZBECK	BBHA 9170	BBHA917058 4	18GHz- 40GHz	Nov. 03, 2014	Oct. 31, 2015	Nov. 02, 2015	Radiation (03CH07-HY)
Preamplifier	COM-POWER	PA-103A	161241	10MHz-1000MHz	Mar. 12, 2015	Oct. 31, 2015	Mar. 11, 2016	Radiation (03CH07-HY)
Preamplifier	Agilent	8449B	3008A02362	1GHz~ 26.5GHz	Oct. 19, 2015	Oct. 31, 2015	Oct. 18, 2016	Radiation (03CH07-HY)
Signal Analyzer	Rohde & Schwarz	FSV 30	101749	10Hz~30GHz	Mar. 10, 2015	Oct. 31, 2015	Mar. 09, 2016	Radiation (03CH07-HY)
Signal Generator	Rohde & Schwarz	SMF100A	101107	100kHz~40GHz	May. 22, 2015	Oct. 31, 2015	May. 21, 2016	Radiation (03CH07-HY)
Controller	ChainTek	Chaintek 3000	N/A	Control Turn table	N/A	Oct. 31, 2015	N/A	Radiation (03CH07-HY)
Controller	Max-Full	MF7802	MF78020836 8	Control Ant Mast	N/A	Oct. 31, 2015	N/A	Radiation (03CH07-HY)
Antenna Mast	Max-Full	MFA520BS	N/A	1m~4m	N/A	Oct. 31, 2015	N/A	Radiation (03CH07-HY)
Turn Table	ChainTek	Chaintek 3000	N/A	0~360 degree	N/A	Oct. 31, 2015	N/A	Radiation (03CH07-HY)



## 6 Uncertainty of Evaluation

### Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y))	4.50
---	------



## Appendix A. Test Results of Conducted Test

### Conducted Output Power(Average power)

Conducted Power (*Unit: dBm)						
Band	GSM850			GSM1900		
Channel	128	189	251	512	661	810
Frequency	824.2	836.4	848.8	1850.2	1880.0	1909.8
GRPS class 8	32.71	32.64	32.59	29.47	29.50	29.61
GRPS class 10	30.43	30.49	30.50	27.14	27.17	27.35
GRPS class 11	28.66	28.68	28.66	25.59	25.63	25.83
GRPS class 12	26.67	26.68	26.66	23.60	23.62	23.82
EGPRS class 8	30.50	30.17	29.72	25.50	25.12	24.23
EGPRS class 10	30.33	30.06	29.54	24.99	24.65	23.82
EGPRS class 11	29.36	28.97	28.41	23.19	22.75	21.88
EGPRS class 12	27.25	26.93	26.39	20.79	20.30	19.41

Conducted Power (*Unit: dBm)			
Band	WCDMA Band V		
Channel	4132	4182	4233
Frequency	826.4	836.4	846.6
RMC 12.2K	21.94	22.16	22.00
HSDPA Subtest-1	20.57	20.50	20.72
HSDPA Subtest-2	20.61	20.57	20.55
HSDPA Subtest-3	20.55	20.50	20.44
HSDPA Subtest-4	20.52	20.50	20.46
HSUPA Subtest-1	17.54	17.71	17.50
HSUPA Subtest-2	17.11	17.15	17.05
HSUPA Subtest-3	17.71	17.85	17.65
HSUPA Subtest-4	17.18	17.28	17.20
HSUPA Subtest-5	18.55	18.57	18.50



## Appendix B. Test Results of Radiated Test

### ERP/EIRP

Channel	Mode	Horizontal		Vertical	
		ERP(dBm)	ERP(W)	ERP(dBm)	ERP(W)
Lowest	GSM850 GPRS class 8	25.21	0.3317	26.84	0.4826
Middle		24.83	0.3043	26.65	0.4627
Highest		24.96	0.3132	26.65	0.4619
Lowest	GSM850 EDGE class 8	22.29	0.1696	23.85	0.2424
Middle		22.10	0.1622	23.63	0.2308
Highest		22.18	0.1651	24.10	0.2572
Lowest	WCDMA Band V RMC 12.2Kbps	14.72	0.0296	16.33	0.0429
Middle		15.08	0.0322	16.60	0.0457
Highest		15.32	0.0341	16.95	0.0495
Limit	ERP < 7W	Result		PASS	

Channel	Mode	Horizontal		Vertical	
		EIRP(dBm)	EIRP(W)	EIRP(dBm)	EIRP(W)
Lowest	GSM1900 GPRS class 8	25.66	0.3677	24.33	0.2710
Middle		24.85	0.3058	23.63	0.2305
Highest		24.43	0.2776	22.77	0.1892
Lowest	GSM1900 EDGE class 8	20.53	0.1130	19.12	0.0817
Middle		19.49	0.0890	18.27	0.0672
Highest		18.59	0.0722	16.62	0.0459
Limit	EIRP < 2W	Result		PASS	



## Radiated Spurious Emission

GSM850 (GPRS class 8)									
Channel	Frequency ( MHz )	ERP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-30.83	-13	-17.83	-41.78	-32.59	0.98	4.89	H
	2472	-21.74	-13	-8.74	38.06	-23.62	1.28	5.32	H
	3296	-38.98	-13	-25.98	-56.34	-42.39	1.54	7.10	H
	4120	-45.98	-13	-32.98	-67.54	-50.62	1.83	8.62	H
	4944	-42.29	-13	-29.29	-65.85	-47.42	2.30	9.59	H
	5768	-50.98	-13	-37.98	-75.84	-55.86	2.78	9.81	H
	1648	-29.53	-13	-16.53	-41.39	-31.29	0.98	4.89	V
	2472	-21.63	-13	-8.63	-39.28	-23.51	1.28	5.32	V
	3296	-44.71	-13	-31.71	-63.65	-48.12	1.54	7.10	V
	4120	-47.38	-13	-34.38	-69.36	-52.02	1.83	8.62	V
	4944	-45.09	-13	-32.09	-69.66	-50.22	2.30	9.59	V
	5768	-49.81	-13	-36.81	-75.47	-54.69	2.78	9.81	V
	6592	-50.37	-13	-37.37	-77.09	-55.81	2.72	10.31	V
Middle	1672	-29.34	-13	-16.34	-40.4	-31.02	0.99	4.82	H
	2512	-24.64	-13	-11.64	-41.29	-26.61	1.29	5.41	H
	3344	-50.72	-13	-37.72	-68.24	-54.33	1.56	7.31	H
	4184	-47.44	-13	-34.44	-68.95	-52.06	1.87	8.64	H
	5016	-46.12	-13	-33.12	-69.66	-51.32	2.35	9.70	H
	5856	-52.47	-13	-39.47	-77.35	-57.33	2.83	9.84	H
	1672	-29.01	-13	-16.01	-41.02	-30.69	0.99	4.82	V
	2512	-22.36	-13	-9.36	-40.36	-24.33	1.29	5.41	V
	3344	-48.94	-13	-35.94	-67.94	-52.55	1.56	7.31	V
	4184	-45.41	-13	-32.41	-67.52	-50.03	1.87	8.64	V
	5016	-48.31	-13	-35.31	-72.61	-53.51	2.35	9.70	V
	5856	-48.36	-13	-35.36	-73.92	-53.22	2.83	9.84	V
Highest	1696	-25.95	-13	-12.95	-37.66	-27.55	1.00	4.75	H
	2544	-25.01	-13	-12.01	-41.65	-26.99	1.30	5.44	H
	3392	-48.08	-13	-35.08	-65.45	-51.88	1.57	7.52	H
	4240	-45.92	-13	-32.92	-67.51	-50.52	1.90	8.65	H
	5096	-50.61	-13	-37.61	-74.03	-55.77	2.39	9.70	H
	5944	-50.77	-13	-37.77	-75.6	-55.62	2.88	9.88	H
	1696	-30.99	-13	-17.99	-43.47	-32.59	1.00	4.75	V
	2544	-26.71	-13	-13.71	44.84	-28.69	1.30	5.44	V
	3392	-48.53	-13	-35.53	67.5	-52.33	1.57	7.52	V
	4240	-45.95	-13	-32.95	68.35	-50.55	1.90	8.65	V
	5096	-47.41	-13	-34.41	71.79	-52.57	2.39	9.70	V
	5944	-51.17	-13	-38.17	77.07	-56.02	2.88	9.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM850 (EDGE class 8)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-30.26	-13	-17.26	-41.28	-32.02	0.98	4.89	H
	2472	-21.81	-13	-8.81	-38.09	-23.69	1.28	5.32	H
	3296	-39.27	-13	-26.27	-56.67	-42.68	1.54	7.10	H
	4120	-49.05	-13	-36.05	-70.61	-53.69	1.83	8.62	H
	4944	-43.69	-13	-30.69	-67.09	-48.82	2.30	9.59	H
	5768	-49.23	-13	-36.23	-74.12	-54.11	2.78	9.81	H
	1648	-30.01	-13	-17.01	-41.81	-31.77	0.98	4.89	V
	2472	-22.48	-13	-9.48	-40.18	-24.36	1.28	5.32	V
	3296	-44.03	-13	-31.03	-62.97	-47.44	1.54	7.10	V
	4120	-48.58	-13	-35.58	-70.77	-53.22	1.83	8.62	V
	4944	-40.89	-13	-27.89	-65.39	-46.02	2.30	9.59	V
	5768	-50.18	-13	-37.18	-75.81	-55.06	2.78	9.81	V
Middle	1672	-28.98	-13	-15.98	-40.07	-30.66	0.99	4.82	H
	2512	-23.76	-13	-10.76	-40.23	-25.73	1.29	5.41	H
	3344	-51.45	-13	-38.45	-68.84	-55.06	1.56	7.31	H
	4184	-47.89	-13	-34.89	-69.33	-52.51	1.87	8.64	H
	5016	-50.24	-13	-37.24	-73.63	-55.44	2.35	9.70	H
	5856	-51.92	-13	-38.92	-76.82	-56.78	2.83	9.84	H
	1672	-30.38	-13	-17.38	-42.25	-32.06	0.99	4.82	V
	2512	-22.84	-13	-9.84	-40.79	-24.81	1.29	5.41	V
	3344	-50.08	-13	-37.08	-69.03	-53.69	1.56	7.31	V
	4184	-45.49	-13	-32.49	-67.74	-50.11	1.87	8.64	V
	5016	-47.56	-13	-34.56	-72.01	-52.76	2.35	9.70	V
	5856	-48.16	-13	-35.16	-73.79	-53.02	2.83	9.84	V
Highest	1696	-26.42	-13	-13.42	-37.79	-28.02	1.00	4.75	H
	2544	-25.24	-13	-12.24	-41.91	-27.22	1.30	5.44	H
	3392	-47.29	-13	-34.29	-64.97	-51.09	1.57	7.52	H
	4240	-46.32	-13	-33.32	-67.96	-50.92	1.90	8.65	H
	5096	-48.43	-13	-35.43	-71.84	-53.59	2.39	9.70	H
	5944	-50.81	-13	-37.81	-75.67	-55.66	2.88	9.88	H
	1696	-31.09	-13	-18.09	-43.5	-32.69	1.00	4.75	V
	2544	-26.54	-13	-13.54	44.78	-28.52	1.30	5.44	V
	3392	-47.41	-13	-34.41	-66.33	-51.21	1.57	7.52	V
	4240	-45.92	-13	-32.92	-68.34	-50.52	1.90	8.65	V
	5096	-46.57	-13	-33.57	-70.91	-53.88	2.39	9.70	V
	5944	-51.07	-13	-38.07	-76.87	-55.92	2.88	9.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (GPRS class 8)									
Channel	Frequency (MHz)	EIRP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-39.95	-13	-26.95	-59.06	-46.52	1.67	8.24	H
	5548	-37.95	-13	-24.95	-62.62	-45.02	2.65	9.72	H
	7403	-42.51	-13	-29.51	-68.84	-51.66	2.46	11.61	H
	9251	-50.82	-13	-37.82	-77.75	-60.88	2.54	12.60	H
	3700	-42.02	-13	-29.02	-62.14	-48.59	1.67	8.24	V
	5548	-27.95	-13	-14.95	-53.74	-35.02	2.65	9.72	V
	7403	-39.88	-13	-26.88	-68.05	-49.03	2.46	11.61	V
	9251	-47.96	-13	-34.96	-77.59	-58.02	2.54	12.60	V
	3756	-39.40	-13	-26.40	-58.51	-46.02	1.68	8.31	H
Middle	5639	-40.16	-13	-27.16	-64.69	-47.21	2.71	9.76	H
	7522	-40.38	-13	-27.38	-67.38	-49.77	2.42	11.81	H
	9398	-49.02	-13	-36.02	-76.22	-58.99	2.57	12.54	H
	3756	-48.69	-13	-35.69	-68.86	-55.31	1.68	8.31	V
	5639	-44.83	-13	-31.83	-70.31	-51.88	2.71	9.76	V
	7522	-40.38	-13	-27.38	-68.99	-49.77	2.42	11.81	V
	9398	-50.14	-13	-37.14	-80.1	-60.11	2.57	12.54	V
	3819	-34.38	-13	-21.38	-55.22	-41.06	1.70	8.38	H
Highest	5730	-41.19	-13	-28.19	-66.03	-48.22	2.76	9.79	H
	7641	-39.95	-13	-26.95	-67.44	-49.45	2.38	11.88	H
	9552	-50.79	-13	-37.79	-78.16	-60.66	2.60	12.47	H
	3819	-37.34	-13	-24.34	-58.42	-44.02	1.70	8.38	V
	5730	-34.52	-13	-21.52	-60.18	-41.55	2.76	9.79	V
	7641	-37.02	-13	-24.02	-66.22	-46.52	2.38	11.88	V
	9552	-48.57	-13	-35.57	-78.56	-58.44	2.60	12.47	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



GSM1900 (EDGE class 8)									
Channel	Frequency ( MHz )	EIRP ( dBm )	Limit ( dBm )	Over Limit ( dB )	SPA Reading (dBm)	S.G. Power ( dBm )	TX Cable loss ( dB )	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	3700	-38.09	-13	-25.09	-57.17	-44.66	1.67	8.24	H
	5548	-37.81	-13	-24.81	-62.38	-44.88	2.65	9.72	H
	7403	-41.91	-13	-28.91	-68.42	-51.06	2.46	11.61	H
	3700	-41.95	-13	-28.95	-62.02	-48.52	1.67	8.24	V
	5551	-28.04	-13	-15.04	-53.85	-35.11	2.65	9.72	V
	7401	-38.88	-13	-25.88	-67.15	-48.02	2.46	11.60	V
Middle	3756	-36.89	-13	-23.89	-56.3	-43.51	1.68	8.31	H
	5639	-39.62	-13	-26.62	-64.24	-46.67	2.71	9.76	H
	7522	-41.63	-13	-28.63	-68.54	-51.02	2.42	11.81	H
	3756	-39.44	-13	-26.44	-59.59	-46.06	1.68	8.31	V
	5639	-34.41	-13	-21.41	-60.25	-41.46	2.71	9.76	V
	7522	-38.63	-13	-25.63	-67.32	-48.02	2.42	11.81	V
Highest	3819	-34.34	-13	-21.34	-54.92	-41.02	1.70	8.38	H
	5730	-42.19	-13	-29.19	-66.96	-49.22	2.76	9.79	H
	7641	-36.89	-13	-23.89	-64.48	-46.39	2.38	11.88	H
	3819	-38.34	-13	-25.34	-59.48	-45.02	1.70	8.38	V
	5730	-34.33	-13	-21.33	59.97	-41.36	2.76	9.79	V
	7641	-37.02	-13	-24.02	-66.23	-46.52	2.38	11.88	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



WCDMA Band V(RMC 12.2Kbps)									
Channel	Frequency (MHz)	ERP (dBm)	Limit (dBm)	Over Limit (dB)	SPA Reading (dBm)	S.G. Power (dBm)	TX Cable loss (dB)	TX Antenna Gain (dBi)	Polarization (H/V)
Lowest	1648	-49.46	-13	-36.46	-60.46	-51.22	0.98	4.89	H
	2472	-46.61	-13	-33.61	-62.98	-48.49	1.28	5.32	H
	3296	-59.98	-13	-46.98	-77.42	-63.39	1.54	7.10	H
	1648	-50.03	-13	-37.03	-61.87	-51.79	0.98	4.89	V
	2472	-48.11	-13	-35.11	-65.85	-49.99	1.28	5.32	V
	3296	-58.62	-13	-45.62	-77.49	-62.03	1.54	7.10	V
Middle	1672	-43.34	-13	-30.34	-54.32	-45.02	0.99	4.82	H
	2512	-46.25	-13	-33.25	-62.89	-48.22	1.29	5.41	H
	3344	-59.92	-13	-46.92	-77.23	-63.53	1.56	7.31	H
	1672	-43.01	-13	-30.01	-54.96	-44.69	0.99	4.82	V
	2512	-49.06	-13	-36.06	-67	-51.03	1.29	5.41	V
	3344	-58.61	-13	-45.61	-77.56	-62.22	1.56	7.31	V
Highest	1688	-45.59	-13	-32.59	-56.91	-47.22	1.00	4.77	H
	2536	-45.68	-13	-32.68	-62.25	-47.66	1.30	5.43	H
	3384	-60.02	-13	-47.02	-77.73	-63.79	1.57	7.49	H
	1696	-46.62	-13	-33.62	-59.02	-48.22	1.00	4.75	V
	2536	-47.94	-13	-34.94	-65.91	-49.92	1.30	5.43	V
	3384	-58.92	-13	-45.92	-77.86	-62.69	1.57	7.49	V

Remark: Spurious emissions within 30-1000MHz were found more than 20dB below limit line.



## **Appendix C. Test Setup Photographs**